New Constructions for Query-Efficient Locally Decodable Codes of Subexponential Length

TOSHIYA ITOH titoh@dac.gsic.titech.ac.jp Global Scientific and Computing Center Tokyo Institute of Technology Meguro-ku, Tokyo 152-8550, Japan

YASUHIRO SUZUKI suzuki@dac.gsic.titech.ac.jp Department of Computer Science Tokyo Institute of Technology Meguro-ku, Tokyo 152-8550, Japan

Abstract: A (k, δ, ε) -locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ is an error-correcting code that encodes each message $\vec{x} = (x_1, x_2, \ldots, x_n) \in \mathbf{F}_q^n$ to a codeword $C(\vec{x}) \in \mathbf{F}_q^N$ and has the following property: For any $\vec{y} \in \mathbf{F}_q^N$ such that $d(\vec{y}, C(\vec{x})) \leq \delta N$ and each $1 \leq i \leq n$, the symbol x_i of \vec{x} can be recovered with probability at least $1 - \varepsilon$ by a randomized decoding algorithm looking only at k coordinates of \vec{y} . The efficiency of a (k, δ, ε) -locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ is measured by the code length N and the number k of queries. For any k-query locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$, the code length N is conjectured to be exponential of n, i.e., $N = \exp(n^{\Omega(1)})$, however, this was disproved. Yekhanin [In Proc. of STOC, 2007] showed that there exists a 3-query locally decodable code $C : \mathbf{F}_2^n \to \mathbf{F}_2^N$ such that $N = \exp(n^{(1/\log \log n)})$ assuming that the number of Mersenne primes is infinite. For a 3-query locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$, Efferemenko [ECCC Report No.69, 2008] reduced the code length further to $N = \exp(n^{O((\log \log n/\log n)^{1/2})})$, and also showed that for any integer r > 1, there exists a k-query locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ such that $k \leq 2^r$ and $N = \exp(n^{O((\log \log n/\log n)^{1-1/r})})$. In this paper, we present a query-efficient locally decodable code by introducing a technique of "composition of locally decodable codes," and show that for any integer r > 1, there exists a k-query locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ such that $k \leq 3 \cdot 2^{r-2}$ and $N = \exp(n^{O((\log \log n/\log n)^{1-1/r})})$.

Keywords: Locally Decodable Codes, S-Matching Vectors, S-Decoding Polynomials, Composition of Locally Decodable Codes, Perfectly Smooth Decoders, Private Information Retrieval.

1 Introduction

Conventional error-correcting codes $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ allow one to encode any $\vec{x} = (x_1, x_2, \dots, x_n) \in \mathbf{F}_q^n$ to $C(\vec{x}) \in \mathbf{F}_q^N$ and have the following property: For any $\vec{y} \in \mathbf{F}_q^N$ such that $d(\vec{y}, C(\vec{x})) \leq \delta N$, the original message \vec{x} can be recovered by looking at entire coordinates of \vec{y} . If one is interested in recovering a single symbol x_i of \vec{x} , more efficient schemes are possible. Such schemes are known as *locally decodable codes* $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ that allow recovery of any single symbol x_i of $\vec{x} \in \mathbf{F}_q^n$ by looking only at k randomly chosen coordinates of $\vec{y} \in \mathbf{F}_q^N$ such that $d(\vec{y}, C(\vec{x})) \leq \delta N$. Informally, a (k, δ, ε) -locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ is an error-correcting code that encodes each message $\vec{x} = (x_1, x_2, \dots, x_n) \in$ \mathbf{F}_q^n to a codeword $C(\vec{x}) \in \mathbf{F}_q^N$ and has the following property: For any $\vec{y} \in \mathbf{F}_q^N$ such that $d(\vec{y}, C(\vec{x})) \leq$ δN and each $1 \leq i \leq n$, the symbol x_i of \vec{x} can be recovered with probability at least $1 - \varepsilon$ by a randomized decoding algorithm looking only at k coordinates of \vec{y} .

1.1 Known Results

From theoretical and practical point of view, we are interested in designing a (k, δ, ε) -locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ as shorter N as possible and as smaller k as possible. The notion of locally de-

codable codes was considered in several contexts [2, 20, 18], and Katz and Trevisan [16] were the first to provide a formal definition of locally decodable codes and prove lower bounds for the code length. Gasarch [8] and Goldreich [10] conjectured that for a k-query locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ with k > 1, the code length N is unavoidable to be the exponential of n, i.e., $N = \exp(n^{\Omega(1)})$. In Table 1, we summarize the known results on the code length for k-query locally decodable codes.

	Upper Bound		Lower Bound		
2-Query	$\exp\left(O(n) ight)$	[15]	$\exp\left(\Omega(n)\right)$	[15]	
3-Query	$\exp\left(n^{1/2} ight)$	[4]	$\tilde{\Omega}\left(n^{2} ight)$	[15, 23]	
k-Query	$\exp\left(n^{O(\log\log k)/k\log k}\right)$	[5]	$\tilde{\Omega}\left(n^{1+1(\lceil k/2\rceil-1)}\right)$	[15, 23]	

Table 1: Known Results on the Code Length

Yekhanin [25, 26] improved the upper bound for the code length of 3-query locally decodable codes to $N = \exp(n^{1/32582657})$ and disproved the conjecture [8, 10] on the code length of 3-query locally decodable codes, i.e., if there exist infinitely many Mersenne primes, then $N = \exp(n^{O(1/\log \log n)})$ for infinitely many *n*'s. Very recently, Efremenko [7, Theorem 3.8] improved much further the upper bound for the code length of 3-query locally decodable codes to

$$N = \exp\left(\exp\left(O\left(\sqrt{\log n \cdot \log \log n}\right)\right)\right) = \exp\left(n^{O((\log \log n / \log n)^{1/2})}\right)$$

by introducing the notions of S-matching vectors [7, Definition 3.1] and S-decoding polynomials [7, Definition 3.4] — this reduces the code length of 3-query locally decodable codes and removes the unproven assumption that infinitely many Mersenne primes exist. For any k > 2, Efremenko [7, Theorem 3.6] also disproved the conjecture [8, 10] on the code length of k-query locally decodable codes, and showed that for any r > 1, there exists a k-query locally decodable code such that $k \leq 2^r$ and

$$N = \exp\left(\exp\left(O\left(\sqrt[r]{\log n \cdot (\log \log n)^{r-1}}\right)\right)\right) = \exp\left(n^{O((\log \log n/\log n)^{1-1/r})}\right).$$

1.2 Main Result

In this paper, we present an improved construction of a k-query locally decodable code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$, and show that for any r > 1, there exists a k-query locally decodable code such that $k \leq 3 \cdot 2^{r-2}$ and

$$N = \exp\left(\exp\left(O\left(\sqrt[r]{\log n \cdot (\log \log n)^{r-1}}\right)\right)\right) = \exp\left(n^{O((\log \log n/\log n)^{1-1/r})}\right)$$

Our construction of the $3 \cdot 2^{r-2}$ -query locally decodable codes is partially based on the construction by Efremenko [7]. To reduce the number of queries, we introduce a technique of "composition of locally decodable codes." In fact, we show that for a k_1 -query locally decodable code and a k_2 -query locally decodable code, there exists a k_1k_2 -query locally decodable code. Applying our technique of "composition of locally decodable codes" to the 3-query locally decodable code [7, Theorem 3.8] and the 2^{r-2} -query locally decodable code [7, Theorem 3.6], a $3 \cdot 2^{r-2}$ -query locally decodable code is achieved.

1.3 Application of Locally Decodable Codes

Locally decodable codes have many applications in complexity theory and cryptography (see, e.g., [21, 8]). In particular, locally decodable codes are closely related to designing efficient private information retrieval. Informally, a k-server private information retrieval is a protocol that consists of a user \mathcal{U} and k databases $\mathcal{DB}_1, \mathcal{DB}_2, \ldots, \mathcal{DB}_k$ with identical data $\vec{x} = (x_1, x_2, \ldots, x_n)$, where each database \mathcal{DB}_j does not communicate to any other database \mathcal{DB}_h , and allows the user \mathcal{U} to retrieve x_i of \vec{x} while any of the k databases $\mathcal{DB}_1, \mathcal{DB}_2, \ldots, \mathcal{DB}_k$ learns nothing about i. Private information retrieval is measured by Chor et al. [6], and the efficiency of a k-server private information retrieval is measured by its communication complexity $C_k(n)$, i.e., the total amount of bits exchanged between the user \mathcal{U} and each of the k databases $\mathcal{D}_1, \mathcal{D}_2, \ldots, \mathcal{D}_k$. For further details on k-server private information retrieval information retrieval, see, e.g., [1, 17, 13, 14, 11, 15, 4, 3, 19, 24].

	Upper Bound	Lower Bound		
1-Server	n+1	[6]	n	[6]
2-Server	$n^{1/3}$	[6, 12]	$5\log n$	[22]
3-Server	$n^{O((\log\log n/\log n)^{1/2})}$	[7]		
4-Server	$n^{1/7.87}$	[5]		
k-Server	$n^{O(\log \log k/k \log k)}$	[5]		

Table 2: Known Results on the Communication Complexity

In Table 2, we summarize the known results on the communication complexity $C_k(n)$ for k-server private information retrieval. In particular, Efremenko [7, Theorem 3.6] showed that a communication-efficient k-server private information retrieval exists for a specific k > 1, i.e., for any r > 1, there exists a k-server private information retrieval such that $k \leq 2^r$ and $C_k(n) = n^{O((\log \log n / \log n)^{(r-1)/r})}$.

2 Preliminaries

2.1 Locally Decodable Codes

We use \mathbf{F}_q to denote a finite field of q elements and $d(\vec{x}, \vec{y})$ to denote the Hamming distance of vectors $\vec{x} = (x_1, x_2, \ldots, x_n) \in \mathbf{F}_q^n$ and $\vec{y} = (y_1, y_2, \ldots, y_n) \in \mathbf{F}_q^n$, i.e., the number of indices such that $x_i \neq y_i$. For any integer a < b, we use [a, b] to denote the set $\{a, a+1, \ldots, b\}$. For any integer m > 1, let $\mathbf{Z}_m = \{0, 1, \ldots, m-1\}$ and $\mathbf{Z}_m^* = \{z \in \mathbf{Z}_m : \gcd(z, m) = 1\}$.

Definition 2.1 ([16]) We say that $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ is a (k, δ, ε) -locally decodable code if for each $i \in [1, n]$, there exists a randomized decoding algorithm $D_i : \mathbf{F}_q^N \to \mathbf{F}_q$ such that (1) for any message $\vec{x} = (x_1, x_2, \ldots, x_n) \in \mathbf{F}_q^n$ and any $\vec{y} \in \mathbf{F}_q^N$ such that $d(C(\vec{x}), \vec{y}) \leq \delta N$, $\Pr[D_i(\vec{y}) = x_i] \geq 1 - \epsilon$; (2) the algorithm D_i makes at most k queries to \vec{y} .

We say that a (k, δ, ϵ) -locally decodable code C is *linear* if C is linear over \mathbf{F}_q and is *nonadaptive* if for each $i \in [1, n]$, the decoding algorithm D_i makes all its queries simultaneously. In this paper, we deal with only linear and nonadaptive (k, δ, ϵ) -locally decodable codes.

Definition 2.2 ([21]) We say that $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$ has a perfectly smooth decoder $\mathcal{D} = \{D_i\}_{i \in [1,n]}$ if for each $\vec{x} \in \mathbf{F}_q^n$ and each $i \in [1, n]$, $\Pr[D_i(C(\vec{x})) = x_i] = 1$, and each query made by the randomized decoding algorithm D_i is uniformly distributed over [1, N].

Trevisan [21] observed that for a code $C : \mathbf{F}_q^n \to \mathbf{F}_q^N$, if C has a perfectly smooth decoder and makes at most k queries, then C is a $(k, \delta, k\delta)$ -locally decodable code. Thus in the rest of this paper, we use k-query locally decodable codes instead of (k, δ, ε) -locally decodable codes.

2.2 S-Matching Vectors

Let m > 1 and h > 0 be integers DFor any $\vec{x} = (x_1, x_2, \dots, x_h) \in \mathbf{Z}_m^h$ and $\vec{y} = (y_1, y_2, \dots, y_h) \in \mathbf{Z}_m^h$, we use $\langle \vec{x}, \vec{y} \rangle_m$ to denote the *inner product* of \vec{x} and \vec{y} modulo m, i.e.,

$$\langle \vec{x}, \vec{y} \rangle_m \equiv \sum_{j=1}^h x_j y_j \pmod{m}$$

Definition 2.3 ([7]) Let $S \subseteq \mathbb{Z}_m \setminus \{0\}$ and $\mathcal{U} = \{\vec{u}_1, \vec{u}_2, \ldots, \vec{u}_n\}$ be a family of vectors, where $\vec{u}_i \in \mathbb{Z}_m^h$ for each $i \in [1, n]$. We say that a family $\mathcal{U} = \{\vec{u}_1, \vec{u}_2, \ldots, \vec{u}_n\}$ of vectors is S-matching if (1) for each $i \in [1, n]$, $\langle \vec{u}_i, \vec{u}_i \rangle_m = 0$; (2) for each $i, j \in [1, n]$ such that $i \neq j$, $\langle \vec{u}_i, \vec{u}_j \rangle_m \in S$.

Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct primes. Define $S_m \subseteq \mathbb{Z}_m \setminus \{0\}$ as follows: For each $s \in \mathbb{Z}_m \setminus \{0\}$, if either $s \equiv 0 \pmod{p_i^{e_i}}$ or $s \equiv 1 \pmod{p_i^{e_i}}$ for each $i \in [r]$, then $s \in S_m$. We refer to S_m as the *canonical* set of the integer $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$.

For each integer $t \in [0, 2^r - 1]$, we use $bin(t) = (t_{r-1}, t_{r-2}, \ldots, t_0) \in \{0, 1\}^r$ to denote the binary representation of t, i.e., $t = t_{r-1} \cdot 2^{r-1} + t_{r-2} \cdot 2^{r-2} + \cdots + t_0 \cdot 2^0$, and let $s_t \in [0, m-1]$ be an integer such that $s_t \equiv t_{i-1} \pmod{p_i^{e_i}}$ for each $i \in [1, r]$. Thus from the definition of $S_m \subseteq Z_m \setminus \{0\}$, it follows that $S_m = \{s_1, s_2, \ldots, s_{2^r-1}\}$, where $s_0 = 0$ and $s_{2^r-1} = 1$.

Lemma 2.1 ([9, Theorems 1.2 and 1.3]) Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct primes. Then there exists a constant c = c(m) > 0 such that for every integer h > 0, there exists an explicitly constructible uniform set-system \mathcal{H} over the universe [1, h] that satisfies the following:

- (1) $|\mathcal{H}| \ge \exp\left(c \frac{(\log h)^r}{(\log \log h)^{r-1}}\right);$
- (2) for each $H \in \mathcal{H}$, $|H| \equiv 0 \pmod{m}$;
- (3) for any $G, H \in \mathcal{H}$ such that $G \neq H$, there exists $i \in [1, 2^r 1]$ such that $|G \cap H| \equiv s_i \pmod{m}$, where $S_m = \{s_1, s_2, \dots, s_{2^r-1}\}$ is the canonical set of m.

For each $H_i \in \mathcal{H}$, let $\vec{u}_i = (u_{i1}, u_{i2}, \dots, u_{ih}) \in \{0, 1\}^h$ be the incidence vector of H_i , i.e., for each $j \in [1, h]$, $u_{ij} = 1$ iff $j \in H_i$. By Lemma 2.1, Efremenko [7] showed the following results:

Lemma 2.2 ([7, Corollary 3.3]) Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct primes and S_m be the canonical set of m. Then for any integer h > 0, there exists a family $\mathcal{U} = \{\vec{u}_1, \vec{u}_2, \ldots, \vec{u}_n\}$ of S_m -matching vectors such that $\vec{u}_i \in \{0, 1\}^h \subseteq \mathbf{Z}_m^h$ for each $i \in [n]$ and $n \ge \exp\left(c\frac{(\log h)^r}{(\log \log h)^{r-1}}\right)$.

2.3 S-Decoding Polynomials

To construct a (k, δ, ϵ) -locally decodable codes of short length, the following lemma is useful.

Lemma 2.3 ([7, Fact 2.4]) For any odd integer m > 1, there exist a finite field \mathbf{F}_{2^t} with $t \in [1, m-1]$ and an element $\gamma \in \mathbf{F}_{2^t}$ of order m, i.e., $\gamma^m = 1$ and $\gamma^i \neq 1$ for each $i \in [1, m-1]$.

Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct odd primes and $\gamma \in \mathbf{F}_{2^t}$ be an element given by Lemma 2.3. Effemenko [7] introduced a notion of S-decoding polynomials, which plays a crucial role to construct a query-efficient locally decodable code.

Definition 2.4 ([7, Definition 3.4]) For any $S \subseteq \mathbb{Z}_m \setminus \{0\}$, we say that $P(x) \in \mathbb{F}_{2^t}[x]$ is an S-decoding polynomial if (1) $P(\gamma^s) = 0$ for each $s \in S$; (2) $P(\gamma^0) = P(1) = 1$.

Efremenko [7] showed that there exists an S-decoding polynomial with a few monomials.

Lemma 2.4 ([7, Claim 3.1]) For any odd integer $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{r_r}$ with r > 1 and any $S \subseteq \mathbb{Z}_m \setminus \{0\}$, there exists an S-decoding polynomial P(x) with at most |S| + 1 monomials.

Remark 2.1 The number of monomials of an S-decoding polynomial is closely related to the number of queries of the corresponding locally decodable code. In fact, the number of monomials of an S-decoding polynomial is k iff the number of queries of the corresponding locally decodable code is k.

Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct odd primes. It is immediate that $|S_m| = 2^r - 1$ from the definition of the canonical set S_m of m. Thus from Lemma 2.4, we have the following lemma:

Lemma 2.5 ([7]) Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct odd primes. Then there exists an S_m -decoding polynomial P(x) with at most 2^r monomials.

3 Known Construction for *k*-Locally Decodable Codes

We describe the construction of (k, δ, ε) -locally decodable codes given by Efremenko [7].

3.1 Encoding

Let $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct odd primes, $\gamma \in \mathbf{F}_{2^t}$ be an element determined by Lemma 2.3, and $P(x) = a_0 + a_1 x^{b_1} + \cdots + a_{k-1} x^{b_{k-1}} \in \mathbf{F}_{2^t}[x]$ be an S_m -decoding polynomial, where S_m is the canonical set of m. For each $i \in [1, n]$, let $\vec{e_i} \in \mathbf{F}_{2^t}^n$ be the *i*th unit vector and $N = m^h$, where

$$h = \exp\left(O\left(\sqrt[r]{(\log n) \cdot (\log \log n)^{r-1}}\right)\right) = n^{O((\log \log n / \log n)^{1-1/r})}.$$
(1)

Let $\mathcal{U} = \{\vec{u}_1, \vec{u}_2, \dots, \vec{u}_n\}$ be a family of S_m -matching vectors, where $\vec{u}_i \in \mathbf{Z}_m^h$ for each $i \in [1, n]$. We define a code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ as follows: For any $\vec{x} = (x_1, x_2, \dots, x_n) \in \mathbf{F}_{2^t}^n$, let $C(\vec{x}) = x_1 C(\vec{e}_1) + x_2 C(\vec{e}_2) + \dots + x_n C(\vec{e}_n)$, where for each $i \in [1, n]$,

$$C(\vec{e}_i) = \left(\gamma^{\langle \vec{u}_i, \vec{z} \rangle_m}\right)_{\vec{z} \in \mathbf{Z}_m^h}.$$
(2)

Input: A vector $\vec{y} \in \mathbf{F}_{2^t}^N$.

- Step 1: Choose $\vec{v} \in \mathbf{Z}_m^h$ uniformly at random.
- Step 2: Query $\vec{y}(\vec{v}), \vec{y}(\vec{v}+b_1\vec{u}_i), \dots, \vec{y}(\vec{v}+b_{k-1}\vec{u}_i) \in \mathbf{F}_{2^t}$, where $\vec{y}(\vec{z})$ denotes the symbol of $\vec{y} \in \mathbf{F}_{2^t}^N$ indexed by $\vec{z} \in \mathbf{Z}_m^h$.

Step 3: Output $x_i = \gamma^{-\langle \vec{u}_i, \vec{v} \rangle_m} \{ a_0 \cdot \vec{y}(\vec{v}) + a_1 \cdot \vec{y}(\vec{v} + b_1 \vec{u}_i) + \dots + a_{k-1} \cdot \vec{y}(\vec{v} + b_{k-1} \vec{u}_i) \}.$

Figure 1: Decoding Algorithm D_i

3.2 Decoding

For each $i \in [1, n]$, a randomized decoding algorithm $D_i : \mathbf{F}_{2^t}^N \to \mathbf{F}_{2^t}$ is defined as in Figure 1.

Lemma 3.1 ([7, Lemma 3.5]) The decoding algorithm $\mathcal{D} = \{D_i\}_{i \in [1,n]}$ is a perfectly smooth decoder.

To be self-contained, we show the proof of Lemma 3.1 in Appendix A. Thus from Lemmas 2.2 and 2.5, we have the following result:

Theorem 3.1 ([7, Theorem 3.6]) For any integer n > 1 and any integer r > 1, there exists a k-query locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ such that $k \leq 2^r$ and

$$N = \exp\left(\exp\left(O\left(\sqrt[r]{\log n \cdot (\log \log n)^{r-1}}\right)\right)\right) = \exp\left(n^{O((\log \log n/\log n)^{1-1/r})}\right).$$

4 Query-Efficient Locally Decodable Codes

4.1 How to Reduce the Number of Queries

By setting r = 2 in Theorem 3.1, it is immediate to see that for any integer n > 1, there exists a 4query locally decodable code $C : \mathbf{F}_{2t}^n \to \mathbf{F}_{2t}^N$ such that

$$N = \exp\left(\exp\left(O\left(\sqrt{\log n \cdot \log \log n}\right)\right)\right) = \exp\left(n^{O((\log \log n / \log n)^{1/2})}\right).$$
(3)

On the other hand, Efremenko [7, Example 3.7] found a surprising example: Let $m = 511 = 2^9 - 1 = 7 \cdot 73$ and $S_{511} = \{1, 365, 147\}$. For the integer m = 511, determine a finite field \mathbf{F}_{2^t} and an element $\gamma \in \mathbf{F}_{2^t}$ of order m = 511 by Lemma 2.3. Indeed, the finite field \mathbf{F}_{2^t} is $\mathbf{F}_{2^9} = \mathbf{F}_2[\gamma]/(\gamma^9 + \gamma^4 + 1)$ and $\gamma \in \mathbf{F}_{2^9}$ is an element of order 511. For the integer m = 511, there exists an S_{511} -decoding polynomial $P(x) = \gamma^{423} \cdot x^{65} + \gamma^{257} \cdot x^{12} + \gamma^{342}$ with 3 monomials, which implies that for any n > 1, there exists a 3-query locally decodable code $C : \mathbf{F}_{2^9}^n \to \mathbf{F}_{2^9}^N$, where N is given by (3).

The result above for the integer m = 511 is special. For an integer $m = 15 = 2^4 - 1 = 3 \cdot 5$, let $S_{15} = \{1, 10, 6\}$ and by Lemma 2.3, we take the finite field \mathbf{F}_{2^t} to be $\mathbf{F}_{2^4} = \mathbf{F}_2[\gamma]/(\gamma^4 + \gamma + 1)$ and the element $\gamma \in \mathbf{F}_{2^4}$ of order 15. By an exhaustive search, we can verify that for the integer m = 15, there does not exist an S_{15} -decoding polynomial with less than 4 monomials. From these observations, we see that it is impossible for every odd integer $m = p_1^{e_1} p_2^{e_2}$ to have an S_m -decoding polynomial with less than 4 monomials. Thus for an odd integer $m = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$, we need to find structural properties of S_m -decoding polynomials to reduce the number of queries to less than 2^r .

4.2 Building Blocks for Query-Efficient Locally Decodable Codes

In this section, we present a new construction for query-efficient locally decodable codes of subexponential length. A key idea of our construction is to generate a k_1k_2 -locally decodable code by composing a k_1 -locally decodable code and a k_2 -locally decodable code.

Let $m_1 = p_1^{e_1} p_2^{e_2} \cdots p_r^{e_r}$ be a product of r > 1 distinct odd primes and $m_2 = q_1^{e_1} q_2^{e_2} \cdots q_\ell^{e_\ell}$ be a product of $\ell > 1$ distinct odd primes. Assume that $gcd(m_1, m_2) = 1$ in the rest of this paper and let $m = m_1 m_2$ be a product of $r + \ell > 2$ distinct odd primes. From Lemma 2.3, we know that (1) for the odd integer m_1 , there exist a finite field $\mathbf{F}_{2^{t_1}}$ with $t_1 \in [1, m_1 - 1]$ and an element $\gamma_1 \in \mathbf{F}_{2^{t_1}}$ of order m_1 ; (2) for the odd integer m_2 , there exist a finite field $\mathbf{F}_{2^{t_2}}$ with $t_2 \in [1, m_2 - 1]$ and an element $\gamma_2 \in \mathbf{F}_{2^{t_2}}$ of order m_2 ; (3) for the odd integer $m = m_1 m_2$, there exist a finite field \mathbf{F}_{2^t} with $t \in [1, m - 1]$ and an element $\gamma \in \mathbf{F}_{2^t}$ of order m. The following lemmas are crucial for our construction.

Lemma 4.1 For the finite fields $\mathbf{F}_{2^{t_1}}$, $\mathbf{F}_{2^{t_2}}$, and \mathbf{F}_{2^t} , the following holds: (1) $\mathbf{F}_{2^{t_1}}$ is a subfield of \mathbf{F}_{2^t} ; (2) $\mathbf{F}_{2^{t_2}}$ is a subfield of \mathbf{F}_{2^t} ; (3) $t = \operatorname{lcm}(t_1, t_2)$.

Proof: For the statement (1), it is immediate that $\mathbf{F}_{2^{t_1}}$ is a subfield of \mathbf{F}_{2^t} iff t is divisible by t_1 . Note that $t_1 \in [1, m_1-1]$ is a minimum integer such that $2^{t_1} \equiv 1 \pmod{m_1}$ and $t \in [1, m-1]$ is a minimum integer such that $2^t \equiv 1 \pmod{m_1}$. Assume that t is not divisible by t_1 , i.e., there exist $q \ge 1$ and $0 < r < t_1$ such that $t = qt_1 + r$. Since $m = m_1m_2$, we have that $2^t \equiv 1 \pmod{m_1}$. So from the fact that $2^{t_1} \equiv 1 \pmod{m_1}$, it follows that $1 \equiv 2^t \equiv 2^{qt_1+r} \equiv (2^{t_1})^q \cdot 2^r \equiv 2^r \pmod{m_1}$. This contradicts the fact that $t_1 \in [1, m_1 - 1]$ is a minimum integer such that $2^{t_1} \equiv 1 \pmod{m_1}$. Thus t is divisible by t_1 , which completes the proof of the statement (1). The proof of the statement (2) is analogous to that of the statement (1). The statement (3) follows from the statements (1) and (2) and the fact that $t \in [1, m - 1]$ is a minimum integer such that $2^t \equiv 1 \pmod{m}$.

For the finite field $\mathbf{F}_{2^{t_1}}$ and the element $\gamma \in \mathbf{F}_{2^t}$ given by Lemma 4.1, the following claims hold:

Claim 4.1 For every $h \in \mathbf{Z}_{m_1}^*$, $\gamma^{hm_2} \in \mathbf{F}_{2^{t_1}}$ is an element of order m_1 .

Proof: Since $2^{t_1} \equiv 1 \pmod{m_1}$, there exists $q \ge 1$ such that $2^{t_1} - 1 = qm_1$. From the fact that $\gamma \in \mathbf{F}_2^t$ is an element of order $m = m_1 m_2$, we have that for every $h \in \mathbf{Z}_{m_1}^*$,

$$(\gamma^{hm_2})^{2^{t_1}-1} = (\gamma^{hm_2})^{qm_1} = (\gamma^{m_1m_2})^h = (\gamma^m)^h = 1,$$

which implies that $\gamma^{hm_2} \in \mathbf{F}_{2^{t_1}}$. It is immediate that $(\gamma^{hm_2})^{m_1} = (\gamma^{m_1m_2})^h = (\gamma^m)^h = 1$. By contradiction, we show that for every $h \in \mathbf{Z}_{m_1}^*$, the order of $\gamma^{hm_2} \in \mathbf{F}_{2^{t_1}}$ is m_1 Assume that there exists an $h \in \mathbf{Z}_{m_1}^*$ such that the order of γ^{hm_2} is $0 < \ell < m_1$, i.e., $(\gamma^{hm_2})^\ell = \gamma^{h\ell m_2} = 1$. Since the order of $\gamma \in \mathbf{F}_{2^t}$ is m, we have that $h\ell m_2$ is divisible by $m = m_1m_2$, i.e., $h\ell$ is divisible by m_1 . From the fact that $h \in \mathbf{Z}_{m_1}^*$, it follows that ℓ is divisible by m_1 , which contradicts the assumption that $0 < \ell < m_1$.

Claim 4.2 In the finite field $\mathbf{F}_{2^{t_1}}$, there exist exactly $|\mathbf{Z}_{m_1}^*|$ elements of order m_1 .

Proof: For an element $g \in \mathbf{F}_{2^{t_1}}$ of order $2^{t_1} - 1$, we have that $\alpha = g^{(2^{t_1}-1)/m_1} \in \mathbf{F}_{2^{t_1}}$ is an element of order m_1 . So the m_1 elements $\alpha^0, \alpha^1, \ldots, \alpha^{m_1-1}$ are the set of all elements that satisfies $x^{m_1} = 1$. It is immediate that for each $j \in \mathbf{Z}_m$, the order of α^j is $m_1/\gcd(j, m_1)$. This implies that in the finite field $\mathbf{F}_{2^{t_1}}$, there exist exactly $|\mathbf{Z}_{m_1}^*|$ elements of order m_1 .

In a way similar to the proofs of Claims 4.1 and 4.2, we can also show the following claims for the finite field $\mathbf{F}_{2^{t_2}}$ and the element $\gamma \in \mathbf{F}_{2^t}$ determined by Lemma 4.1.

Claim 4.3 For every $h \in \mathbf{Z}_{m_2}^*$, $\gamma^{hm_1} \in \mathbf{F}_{2^{t_2}}$ is an element of order m_2 .

Claim 4.4 In the finite field $\mathbf{F}_{2^{t_2}}$, there exist $|\mathbf{Z}_{m_2}^*|$ elements of order m_2 .

From Claims 4.1, 4.2, 4.3, and 4.4, we can show the following lemma:

Lemma 4.2 For the elements $\gamma_1 \in \mathbf{F}_{2^{t_1}}$, $\gamma_2 \in \mathbf{F}_{2^{t_2}}$, and $\gamma \in \mathbf{F}_{2^t}$, the following holds: (1) there exists $h_1 \in \mathbf{Z}_{m_1}^*$ such that $\gamma_1 = \gamma^{h_1 m_2}$; (2) there exists $h_2 \in \mathbf{Z}_{m_2}^*$ such that $\gamma_2 = \gamma^{h_2 m_1}$.

Proof: The statement (1) immediately follows from Claims 4.1 and 4.2 and the statement (2) immediately follows from Claims 4.3 and 4.4.

Let $S_{m_1} = \{s_1^1, s_2^1, \dots, s_{2^r-1}^1\}$, $S_{m_2} = \{s_1^2, s_2^2, \dots, s_{2^\ell-1}^2\}$, and $S_m = \{s_1, s_2, \dots, s_{2^r+\ell-1}\}$ be the canonical sets of the integers m_1, m_2 , and m, respectively, and let $s_0^1 = s_0^2 = s_0 = 0$.

Lemma 4.3 For the sets S_{m_1} , S_{m_2} , and S_m , the following holds: For any $s \in S_m \cup \{0\}$, (1) $s \in S_m$ iff there exist $s_{i_1}^1 \in S_{m_1} \cup \{0\}$ and $s_{i_2}^2 \in S_{m_2} \cup \{0\}$ such that $s \equiv s_{i_1}^1 \pmod{m_1}$, $s \equiv s_{i_2}^2 \pmod{m_2}$, and either $s_{i_1}^1 \neq 0$ or $s_{i_2}^2 \neq 0$; (2) s = 0 iff $s \equiv 0 \pmod{m_1}$ and $s \equiv 0 \pmod{m_2}$.

Proof: It follows from the definitions of S_{m_1} , S_{m_2} , and S_m and the Chinese Remainder Theorem.

4.3 Constructions for Query-Efficient Locally Decodable Codes

For the integers m_1 , m_2 , and m and the integer h > 0 given by (1), let $N_1 = m_1^h$, $N_2 = m_2^h$, and $N = m^h$, respectively. The following is essential to construct query-efficient locally decodable codes.

Theorem 4.1 ((Composition Theorem)) Let $C_1 : \mathbf{F}_{2^{t_1}}^n \to \mathbf{F}_{2^{t_1}}^{N_1}$ be a k_1 -query locally decodable code that has an S_{m_1} -decoding polynomial $P_1(x) \in \mathbf{F}_{2^{t_1}}[x] \subseteq \mathbf{F}_{2^t}[x]$ with k_1 monomials and $C_2 : \mathbf{F}_{2^{t_2}}^n \to \mathbf{F}_{2^{t_2}}^{N_2}$ be a k_2 -query locally decodable code that has an S_{m_2} -decoding polynomial $P_2(x) \in \mathbf{F}_{2^{t_2}}[x] \subseteq \mathbf{F}_{2^t}[x]$ with k_2 monomials. Then we can construct a k-query locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ that has an S_m -decoding polynomial $P(x) \in \mathbf{F}_{2^t}[x]$ with k monomials, where $k \leq k_1 k_2$.

Proof: For $m = m_1m_2$ and h given by (1), we define $C : \mathbf{F}_{2t}^n \to \mathbf{F}_{2t}^N$ as follows: For any vector $\vec{x} = (x_1, x_2, \ldots, x_n) \in \mathbf{F}_{2t}$, let $C(\vec{x}) = x_1 C(\vec{e_1}) + x_2 C(\vec{e_2}) + \cdots + x_n C(\vec{e_n})$, where for each $i \in [1, n]$, $C(\vec{e_i})$ is given by (2). For the integer $h_1 \in \mathbf{Z}_{m_1}^*$ determined by Lemma 4.2-(1) and the integer $h_2 \in \mathbf{Z}_{m_2}^*$ determined by Lemma 4.2-(2), let $P(x) = P_1(x^{h_1m_2}) \cdot P_2(x^{h_2m_1})$. It is obvious that P(x) is a polynomial with $k \leq k_1k_2$ monomials. Let $P(x) = a_0 + a_1x^{b_1} + \cdots + a_{k-1}x^{k-1}$. For each $i \in [1, n]$, a randomized decoding algorithm D_i is defined exactly the same as Figure 1. For each $i \in [1, n]$, we have that

$$D_i(C(\vec{x})) = D_i(x_1C(\vec{e}_1) + x_2C(\vec{e}_2) + \dots + x_nC(\vec{e}_n))$$

= $x_1D_i(C(\vec{e}_1)) + x_2D_i(C(\vec{e}_2)) + \dots + x_nD_i(C(\vec{e}_n)).$

Thus it suffices to show that $\Pr[D_i(C(\vec{e_i})) = 1] = 1$ for each $i \in [1, n]$ and $\Pr[D_i(C(\vec{e_j})) = 0] = 1$ for each $j \in [1, n] \setminus \{i\}$. From (2), it follows that for queries $\vec{v}, \vec{v} + b_1 \vec{u_i}, \ldots, \vec{v} + b_{k-1} \vec{u_i} \in Z_m^h$,

$$D_{i}(C(\vec{e}_{i})) = \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0}\gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}} + a_{1}\gamma^{\langle \vec{u}_{i}, \vec{v} + b_{1}\vec{u}_{i} \rangle_{m}} + \dots + a_{k-1}\gamma^{\langle \vec{u}_{i}, \vec{v} + b_{k-1}\vec{u}_{i} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0}\gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}} + a_{1}\gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}}\gamma^{b_{1}\langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}} + \dots + a_{k-1}\gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}}\gamma^{b_{k-1}\langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}}\right)$$

$$= a_{0} + a_{1}\gamma^{b_{1}\langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}} + \dots + a_{k-1}\gamma^{b_{k-1}\langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}}$$

$$= P\left(\gamma^{\langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}}\right) = P(1) = P_{1}(1) \cdot P_{2}(1) = 1;$$

$$D_{i}(C(\vec{e}_{j})) = \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0}\gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} + a_{1}\gamma^{\langle \vec{u}_{j}, \vec{v} + b_{1}\vec{u}_{i} \rangle_{m}} + \cdots + a_{k-1}\gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}}\gamma^{b_{k-1}\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0}\gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} + a_{1}\gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}}\gamma^{b_{1}\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}} + \cdots + a_{k-1}\gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}}\gamma^{b_{k-1}\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \cdot \left(a_{0} + a_{1}\gamma^{b_{1}\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}} + \cdots + a_{k-1}\gamma^{b_{k-1}\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \cdot P\left(\gamma^{\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right) \cdot P_{2}\left(\gamma^{b_{2}m_{1}\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \cdot P_{1}\left(\gamma^{\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right) \cdot P_{2}\left(\gamma^{\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right), \qquad (4)$$

where (4) follows from Lemma 4.2. Since $\mathcal{U} = \{\vec{u}_1, \vec{u}_2, \ldots, \vec{u}_n\}$ is a family of S_m -matching vectors, we have that $\langle \vec{u}_i, \vec{u}_j \rangle_m \in S_m$. Thus from Lemma 4.3, it follows that there exist $s_{i_1}^1 \in S_{m_1} \cup \{0\}$ and $s_{i_2}^2 \in S_{m_2} \cup \{0\}$ such that $\langle \vec{u}_i, \vec{u}_j \rangle_m \equiv s_{i_1}^1 \pmod{m_1}, \langle \vec{u}_i, \vec{u}_j \rangle_m \equiv s_{i_2}^2 \pmod{m_2}$, and either $s_{i_1}^1 \neq 0$ or $s_{i_2}^2 \neq 0$. Recall that $\gamma_1 \in \mathbf{F}_{2^{t_1}}$ is an element of order $m_1; \gamma_2 \in \mathbf{F}_{2^{t_2}}$ is an element of order $m_2; P_1(x)$ is an S_{m_1} -decoding polynomial; $P_2(x)$ is an S_{m_2} -decoding polynomial. Then from (4), we have that

$$P_1\left(\gamma_1^{\langle \vec{u}_i, \vec{u}_j \rangle_m}\right) = P_1\left(\gamma_1^{s_{i_1}^1}\right) = 0 \quad \bigvee \quad P_2\left(\gamma_2^{\langle \vec{u}_i, \vec{u}_j \rangle_m}\right) = P_2\left(\gamma_1^{s_{i_2}^2}\right) = 0.$$

Thus it follows that $D_i(C(\vec{e_i})) = 1$ for each $i \in [1, n]$ and $D_i(C(\vec{e_j})) = 0$ for each $j \in [1, n] \setminus \{i\}$.

Corollary 4.1 ((to Theorem 4.1)) For any integer n > 1 and any integer r > 1, there exists a k-query locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ such that $k \leq 3 \cdot 2^{r-2}$ and

$$N = \exp\left(\exp\left(O\left(\sqrt[r]{\log n \cdot (\log \log n)^{r-1}}\right)\right)\right) = \exp\left(n^{O((\log \log n/\log n)^{1-1/r})}\right)$$

Proof: Efremenko [7, Example 3.7] showed that for an odd integer $m_1 = 511 = 7.73$, there exists a 3query locally decodable code $C_1 : \mathbf{F}_{2^{t_1}}^n \to \mathbf{F}_{2^{t_1}}^{N_1}$ that has an S_{m_1} -decoding polynomial $P_1(x) \in \mathbf{F}_{2^{t_1}}[x]$ with 3 monomials. For any integer r > 1, we take $m_2 = p_1^{e_1} p_2^{e_2} \cdots p_{r-2}^{e_{r-2}}$ that is a product of r-2 distinct odd primes such that $gcd(m_1, m_2) = 1$, and let $m = m_1 m_2$. Efremenko [7, Theorem 3.6] also derived that for any integer r > 1, there exists a k_2 -query locally decodable code $C_1 : \mathbf{F}_{2^{t_1}}^n \to \mathbf{F}_{2^{t_1}}^{N_1}$ that has an S_{m_2} -decoding polynomial $P_2(x) \in \mathbf{F}_{2^{t_2}}[x]$ with k_2 monomials, where $k_2 \leq 2^r$. So from Theorem 4.1, we can construct a k-query locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ that has an S_m -decoding polynomial $P(x) \in \mathbf{F}_{2^t}[x]$ with k monomials, where $k \leq 3 \cdot 2^{r-2}$.

5 Concluding Remarks

In this paper, we have shown the Composition Theorem that constructs a k_1k_2 -query locally decodable code ble code by composing a k_1 -query locally decodable code and a k_2 -query locally decodable code (see Theorem 4.1) and in Corollary 4.1, we have also shown that for any integer r > 1, there exists a kquery locally decodable code $C : \mathbf{F}_{2t}^n \to \mathbf{F}_{2t}^N$ such that $k \leq 3 \cdot 2^{r-2}$ and

$$N = \exp\left(\exp\left(O\left(\sqrt[r]{\log n \cdot (\log \log n)^{r-1}}\right)\right)\right) = \exp\left(n^{O((\log \log n / \log n)^{1-1/r})}\right).$$

For perfectly smooth decoders, we can immediately modify Theorem 4.1 as follows:

Theorem 5.1 Let $C_1 : \mathbf{F}_{2^{t_1}}^n \to \mathbf{F}_{2^{t_1}}^{N_1}$ be a k_1 -query locally decodable code with a perfectly smooth decoder \mathcal{D}_1 that has an S_{m_1} -decoding polynomial $P_1(x) \in \mathbf{F}_{2^{t_1}}[x] \subseteq \mathbf{F}_{2^t}[x]$ with k_1 monomials and $C_2 : \mathbf{F}_{2^{t_2}}^n \to \mathbf{F}_{2^{t_1}}^{N_2}$ be a k_2 -query locally decodable code with a perfectly smooth decoder \mathcal{D}_2 that has an S_{m_2} -decoding polynomial $P_2(x) \in \mathbf{F}_{2^{t_2}}[x] \subseteq \mathbf{F}_{2^t}[x]$ with k_2 monomials. Then we can construct a kquery locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ with a perfectly smooth decoder \mathcal{D} that has an S_m -decoding polynomial $P(x) \in \mathbf{F}_{2^t}[x]$ with k monomials, where $k \leq k_1 k_2$.

From Theorem 5.1 and the transformation [21] from a k-query locally decodable codes with a perfectly smooth decoder to k-server private information retrieval, we can show the following theorem:

Theorem 5.2 For any integer n > 1 and any integer r > 1, there exists a k-server private information retrieval such that $k \leq 3 \cdot 2^{r-2}$ and $C_k(n) = n^{O((\log \log n / \log n)^{(r-1)/r})}$.

At present, we know only a 3-query locally decodable code $\mathbf{F}_{2^9}^n \to \mathbf{F}_{2^9}^N$ such that

$$N = \exp\left(\exp\left(O\left(\sqrt{\log n \cdot \log \log n}\right)\right)\right) = \exp\left(n^{O((\log \log n / \log n)^{1/2})}\right),$$

for an add integer $m = 511 = 2^9 = 7 \cdot 73$ [7, Example 3.7]. Let \mathcal{M}_r be a set of integers, each of which is a product of r > 1 distinct odd primes. From the Composition Theorem (see Theorem 4.1), it follows that if there exist $m_1, m_2, \ldots, m_\ell \in \mathcal{M}_2$ such that $gcd(m_i, m_j) = 1$ for each $1 \leq i < j \leq \ell$ and each $m_i \in \mathcal{M}_2$ generates a 3-query locally decodable code $C_i : \mathbf{F}_{2^{t_i}}^n \to \mathbf{F}_{2^{t_i}}^N$ that has an S_{m_i} -decoding polynomial $P_i(x) \in \mathbf{F}_{2^{t_i}}[x]$ with less than 4 monomials, where

$$N = \exp\left(\exp\left(O\left(\sqrt{\log n \cdot \log \log n}\right)\right)\right) = \exp\left(n^{O((\log \log n / \log n)^{1/2})}\right),$$

then for the integer $m = m_1 m_2 \cdots m_\ell$, we can construct a k-query locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ that has an S_m -decoding polynomial $P(x) \in \mathbf{F}_{2^t}[x]$ with k monomials, where $k \leq 3^\ell$ and

$$N = \exp\left(\exp\left(O\left(\sqrt[2\ell]{\log n \cdot \log \log n}\right)\right)\right) = \exp\left(n^{O((\log \log n / \log n)^{1-1/2\ell})}\right),$$

however, we do not know such integers $m_1, m_2, \ldots, m_\ell \in \mathcal{M}_2$ exist other than $m = 511 \in \mathcal{M}_2$. Thus the following problems are both of theoretical interest and of practical importance.

- (1) Find integers $m \in \mathcal{M}_2 \setminus \{511\}$ that generate a 3-query locally decodable code $C : \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$, i.e., the code C has an S_m -decoding polynomial $P(x) \in \mathbf{F}_{2^t}[x]$ with less than 4 monomials.
- (2) For any integer r > 2, find an integer $m \in \mathcal{M}_r$ that generate a k-query locally decodable code $C: \mathbf{F}_{2^t}^n \to \mathbf{F}_{2^t}^N$ that has an S_m -decoding polynomial $P(x) \in \mathbf{F}_{2^t}[x]$ with $k < 3 \cdot 2^{r-2}$ monomials.

Acknowledgments

The authors would like to thank Osamu Watanabe for his insightful discussions and valuable comments for the earlier version of the paper.

References

- A. Ambainis. Upper Bound on the Communication Complexity of Private Information Retrieval. In Proc. of the 24th International Colloquium on Automata, Languages, and Programming, Lecture Notes in Computer Science 1256, pp.401-407 (1997).
- [2] L. Babai, L. Fortnow, L. Levin, and M. Szegedy. Checking Computation in Polylogarithmic Time. In Proc. of the 23rd Annual ACM Symposium on Theory of Computing, pp.21-31 (1991).
- [3] A. Beimel, L. Fortnow, and W. Gasarch. A Tight Lower Bound for Restricted PIR Protocols. Comoutat. Comlex., 15, pp.82-91 (2006).
- [4] A. Beimel, Y. Ishai, and E. Kushilevitz. General Constructions for Information-Theoretic Private Information Retrieval. J. of Computer and System Sciences, 71(2), pp.213-247 (2005).
- [5] A. Beimel, Y. Ishai, E. Kushilevitz, and F. Raymond. Breaking the $O(n^{\frac{1}{2k-1}})$ Barrier for Information-Theoretic Private Information Retrieval. In *Proc. of the 43rd IEEE Annual Symposium* on Foundations of Computer Science, pp.261-270 (2002).
- [6] B. Chor, O. Goldreich, E. Kushilevitz, and M. Sudan. Private Information Retrieval. In *Proc.* of the 36th IEEE Annual Symposium on Foundations of Computer Science, pp.41-51 (1995).
- [7] K. Efremenko. 3-Query Locally Decodable Codes of Subexponential Length. *Electronic Colloquium on Computational Complexity*, Report No.69 (2008).
- [8] W. Gasarch. A Survey on Private Information Retrieval. Bull. EATCS 82, pp.72-107 (2004).
- [9] V. Grolmusz. Superpolynomial Size Set-Systems with Restricted Intersections Mod 6 and Explicit Ramsey Graphs. *Combinatorica*, 20(1), pp.71-85 (2000).
- [10] O. Goldreich. Short Locally Testable Codes and Proofs. Electronic Colloquium on Computational Complexity, Report No.14 (2005).
- [11] O. Goldreich, H. Karloff, L.J. Schulman, and L. Trevisan. Lower Bounds for Linear Locally Decodable Codes and Private Information Retrieval. In Proc. of the 17th IEEE Annual Conference on Computational Complexity, pp.175-183 (2002).
- [12] Y. Ishai and E. Kushilevitz. Improved Upper Bounds on Information-Theoretic Private Information Retrieval. In Proc. of the 31st Annual ACM Symposium on Theory of Computing, pp.79-88 (1999).
- [13] T. Itoh. Efficient Private Information Retrieval. IEICE Trans. Fund. Electron. Commun. Comput. Sci., E82-A(1), pp.11-20 (1999).
- [14] T. Itoh. On Lower Bound for the Communication Complexity of Private Information Retrieval. IEICE Trans. Fund. Electron. Commun. Comput. Sci., E84-A(1), pp.157-164 (2001).
- [15] I. Kerenidis and R. de Wolf. Exponential Lower Bound for 2-Query Locally Decodable Code via a Quantum Argument. In Proc. of the 35th Annual ACM Symposium on Theory of Computing, pp.106-115 (2003).

- [16] J. Katz and L. Trevisan. On the Efficiency of Locally Decoding Procedures for Error-Correcting Codes. In Proc. of the 32nd Annual ACM Symposium on Theory of Computing, pp.80-86 (2000).
- [17] E. Mann. Private Access to Distributed Information. Master's Thesis, Technion Israel Institute of Technology, Haifa, Israel (1998).
- [18] A. Polisgchuk and D. Spielman. Nearly-Linear Size Holographic Proofs. In Proc. of the 26th Annual ACM Symposium on Theory of Computing, pp.194-203 (1994).
- [19] A. Razborov and S. Yekhanin. An $\Omega(n^{1/3})$ Lower Bounds for Bilinear Group Based Private Information Retrieval. In Proc. of the 47th Annual IEEE Symposium on Foundations of Computer Science, pp.739-748 (2006).
- [20] M. Sudan. Efficient Checking of Polynomials and Proofs and the Hardness of Approximation Problems. Ph.D Thesis, University of California at Berkeley (1992).
- [21] R. Trevisan. Some Applications of Coding Theory in Computational Complexity. Quad. Matemat. 13, pp.347-424 (2004). Electronic Colloquium on Computational Complexity, Report No.43 (2004).
- [22] S. Wehner and R. de Wolf. Improved Lower Bound for Locally Decodable Codes and Private Information Retrieval. In Proc. of the 32nd International Colloquium on Automata, Languages, and Programming, Lecture Notes in Computer Science 3580, pp.1424-1436 (1997).
- [23] D. Woodruff. New Lower Bounds for General Locally Decodable Codes. *Electronic Colloquium* on Computational Complexity, Report No.6 (2007).
- [24] D. Woodruff and S. Yekhanin. A Geometric Approach to Information Theoretic Private Information Retrieval. SIAM J. Comput., 37(4), pp.1046-1056 (2007).
- [25] S. Yekhanin. Towards 3-Query Locally Decodable Codes of Subexponential Length. In Proc. of the 39th Annual ACM Symposium on Theory of Computing, pp.266-274 (2007).
- [26] S. Yekhanin. Towards 3-Query Locally Decodable Codes of Subexponential Length. J. of the ACM, 55(1), pp.1-16 (2008).

A Proof of Lemma 3.1

For each $i \in [1, n]$, it is obvious that each of queries $\vec{v}, \vec{v} + b_1 \vec{u}_i, \ldots, \vec{v} + b_{k-1} \vec{u}_i \in Z_m^h$ is uniformly distributed over [1, N]. So for any vector $\vec{x} = (x_1, x_2, \ldots, x_n) \in \mathbf{F}_{2^t}^n$, we show that $\Pr[D_i(C(\vec{x})) = x_i] = 1$ for each $i \in [1, n]$. Since $C(\vec{x}) = x_1 C(\vec{e}_1) + x_2 C(\vec{e}_2) + \cdots + x_n C(\vec{e}_n)$, we have that for each $i \in [1, n]$,

$$D_i(C(\vec{x})) = D_i(x_1C(\vec{e}_1) + x_2C(\vec{e}_2) + \dots + x_nC(\vec{e}_n))$$

= $x_1D_i(C(\vec{e}_1)) + x_2D_i(C(\vec{e}_2)) + \dots + x_nD_i(C(\vec{e}_n)).$

Thus it suffices to show that $\Pr[D_i(C(\vec{e_i})) = 1] = 1$ for each $i \in [1, n]$ and $\Pr[D_i(C(\vec{e_j})) = 0] = 1$ for each $j \in [1, n] \setminus \{i\}$. From (2), it follows that for queries $\vec{v}, \vec{v} + b_1 \vec{u_i}, \ldots, \vec{v} + b_{k-1} \vec{u_i} \in Z_m^h$,

$$D_i(C(\vec{e}_i)) = \gamma^{-\langle \vec{u}_i, \vec{v} \rangle_m} \cdot \left(a_0 \gamma^{\langle \vec{u}_i, \vec{v} \rangle_m} + a_1 \gamma^{\langle \vec{u}_i, \vec{v} + b_1 \vec{u}_i \rangle_m} + \dots + a_{k-1} \gamma^{\langle \vec{u}_i, \vec{v} + b_{k-1} \vec{u}_i \rangle_m} \right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0} \gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}} + a_{1} \gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \gamma^{b_{1} \langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}} + \dots + a_{k-1} \gamma^{\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \gamma^{b_{k-1} \langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}} \right)$$

$$= a_{0} + a_{1} \gamma^{b_{1} \langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}} + \dots + a_{k-1} \gamma^{b_{k-1} \langle \vec{u}_{i}, \vec{u}_{i} \rangle_{m}}$$

$$= P\left(\gamma^{\langle \vec{u}_{i}, \vec{u} \rangle_{m}}\right); \qquad (5)$$

$$D_{i}(C(\vec{e}_{j})) = \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0} \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} + a_{1} \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \gamma^{b_{1} \langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}} + \dots + a_{k-1} \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \gamma^{b_{k-1} \langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \left(a_{0} \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} + a_{1} \gamma^{\langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}} + \dots + a_{k-1} \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \gamma^{b_{k-1} \langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right)$$

$$= \gamma^{-\langle \vec{u}_{i}, \vec{v} \rangle_{m}} \cdot \gamma^{\langle \vec{u}_{j}, \vec{v} \rangle_{m}} \cdot \left(a_{0} + a_{1} \gamma^{b_{1} \langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}} + \dots + a_{k-1} \gamma^{b_{k-1} \langle \vec{u}_{i}, \vec{u}_{j} \rangle_{m}}\right). \qquad (6)$$

Since $\mathcal{U} = \{\vec{u}_1, \vec{u}_2, \dots, \vec{u}_n\}$ is a family of S_m -matching vectors, we have that $\langle \vec{u}_i, \vec{u}_i \rangle_m = 0$ for each $i \in [1, n]$ and $\langle \vec{u}_i, \vec{u}_j \rangle_m = s_{ij} \in S_m \subseteq Z_m \setminus \{0\}$ for each $i, j \in [1, n]$ such that $i \neq j$, and from the definition of S_m -decoding polynomial $P(x) = a_0 + a_1 x^{b_1} + \dots + a_{k-1} x^{b_{k-1}}$, we have that $P(\gamma^{\langle \vec{u}_i, \vec{u}_i \rangle_m}) = P(1) = 1$ for each $i \in [1, n]$ and $P(\gamma^{\langle \vec{u}_i, \vec{u}_j \rangle_m}) = P(\gamma^{s_{ij}}) = 0$ for each $i, j \in [1, n]$ such that $i \neq j$.

Thus it follows from (5) that $D_i(C(\vec{e}_i)) = P(\gamma^{\langle \vec{u}_i, \vec{u}_i \rangle_m}) = P(1) = 1$ for each $i \in [1, n]$, and it follows from (6) that $D_i(C(\vec{e}_j)) = \gamma^{-\langle \vec{u}_i, \vec{v} \rangle_m} \cdot \gamma^{\langle \vec{u}_j, \vec{v} \rangle_m} \cdot P(\gamma^{s_{ij}}) = 0$ for each $i, j \in [1, n]$ such that $i \neq j$.