On Pole Placement and Invariant Subspaces

Naim Bajcinca

Max Planck Institute for Dynamics of Complex Technical Systems Sandtorstr. 1, 39106, Magdeburg, Germany Email: bajcinca@mpi-magdeburg.mpg.de

Abstract—The classical eigenvalue assignment problem is revisited in this note. We derive an analytic expression for pole placement which represents a slight generalization of the celebrated Bass-Gura and Ackermann formulae, and also is closely related to the modal procedure of Simon and Mitter.

I. INTRODUCTION

For a single-input linear time-invariant system $\dot{x} = Ax + bu$ with $x \in \mathbb{R}^n$, $A \in \mathbb{R}^{n \times n}$, $b \in \mathbb{R}^{n \times 1}$, the solution to the pole placement problem provides the feedback gain $k \in \mathbb{R}^n$ in $u = k^T x$, such that the open-loop eigenvalues $\Lambda(A)$ are shifted to some prespecified values $\Lambda(\bar{A})$ where $\bar{A} := A + bk^T$, [5], [1], [7], etc. In this note, we utilize a left eigenvector assignment procedure for a controllable pair (A, b) to derive the following pole placement analytic expression:

$$k^T = \omega_{n-r}^T q_r(A), \tag{1}$$

where $1 \leq r \leq n$, $\omega_{n-r} \in \mathbb{R}^n$ and $q_r(A) \in \mathbb{R}^{n \times n}$ represent the design parameters that independently assign (n - r) and r eigenvalues, respectively, and are defined as follows: Let $q_n(\lambda) = q_{n-r}(\lambda)q_r(\lambda)$ be the specified closed-loop characteristic polynomial, where $q_{n-r}(\lambda)$ and $q_r(\lambda)$ are real polynomials in λ with leading coefficients equal to one, and let them host the desired (n-r) and r eigenvalues, respectively. Then, $\omega_{n-r}^T = \gamma_{n-r}^T T^{-1}$, where $q_{n-r}(\lambda) = [1, \lambda, \dots, \lambda^{n-1}]\gamma_{n-r}$, $\gamma_{n-r} \in \mathbb{R}^n$, and T represents the controller canonical statespace transformation matrix [5], while $q_r(A)$ is the matrix polynomial corresponding to $q_r(\lambda)$. To the best author's knowledge, (1) has not appeared in that form previously in the control literature and could be of interest in the sense that it includes both the Ackermann and Bass-Gura formulae as special cases. Indeed, it will be shown later in the paper that for r = n we obtain the Ackermann formula, and for r = 0we can link (1) to the Bass-Gura formula. We also stress its close relationship to the procedure of Simon and Mitter.

Preliminaries & Notation: \mathbb{C}_{-} stands for the open left-hand complex half-plane. By $\Lambda(A)$ we denote the multiset of the eigenvalues of the matrix A. (λ, ω) is an eigenpair of A (i.e. $\omega^{H}A = \lambda \omega^{H}$) if and only if $(\lambda, Q^{-1}\omega)$ is an eigenpair of the similar matrix of $Q^{-1}AQ$. A real matrix A can be factorized into a product $Q^{T}TQ$, where Q is an orthogonal matrix and Tis lower quasitriangular (i.e., block lower triangular with 1×1 or/and 2×2 blocks along the diagonal), representing the real Schur decomposition [4]. $\mathcal{V} \subseteq \mathbb{C}^{n}$ is said to be A-invariant if there exists a matrix Y such that AV = VY, where $\mathcal{V} = Range(V)$. The controllability matrix $[b, Ab, \ldots, A^{n-1}b]$ of the pair (A, b) is denoted by Con(A, b). Finally, we use the shorthand: $\mathbf{r} := \{1, \dots, r\}$ for $r \in \mathbb{N}$ in $i \in \mathbf{r}$ to indicate $i \in \{1, \dots, r\}$; $i \in \mathbf{r_0}$ allows i to take also the value 0.

II. SPECTRUM ASSIGNMENT

Consider the state space representation of a finitedimensional controllable single-input linear time invariant system: $\dot{x} = Ax + bu$. It is well-known that for any arbitrary multiset of self-conjugate eigenvalues $\{\lambda_i\}_{i \in \mathbf{n}}$ in \mathbb{C}_- , there exists always a unique state feedback gain $k \in \mathbb{R}^n$ which solves the pole assignment problem [5]. In the sequel, we provide an original method for computation of k.

Let $\omega_{n-1} \in \mathbb{C}^n$ be a left eigenvector of the closed-loop system matrix $\bar{A} := A + bk^T$ corresponding to an arbitrary eigenvalue $\lambda_1 \in \mathbb{C}_-$. Then, with $\omega_{n-1}^H(A + bk^T) = \lambda_1 \omega_{n-1}^H$, we claim:

$$k^T = \omega_{n-1}^H (\lambda_1 I - A) \quad \text{and} \quad \omega_{n-1}^H b = 1, \tag{2}$$

whereby in light of implementation, care has to be taken in selecting a pair ω_{n-1} and λ_1 that guarantee a real outcome $k \in \mathbb{R}^n$. Observe, that the right-hand side statement in (2) results from the fact that $\omega_{n-1}/\omega_{n-1}^H b$ is a left eigenvector of \overline{A} , as well, and the condition $\omega_{n-1}^H b \neq 0$, which is guaranteed by the controllability of the pair (A, b). Indeed, if the opposite would hold true, i.e. if $\omega_{n-1}^H b = 0$, we would have: $\omega_{n-1}^H (A + bk^T) = \omega_{n-1}^H A = \lambda_1 \omega_{n-1}^H$ for all k, indicating that λ_1 is an eigenvalue of A and \overline{A} simultaneously, i.e. it cannot be shifted by any k, which contradicts the controllability of (A, b).

Furthermore, equation (2) reveals that the remainder eigenvalues in the multiset $\{\lambda_i\}_{i=2}^n$ are uniquely specified by the left eigenvector ω_{n-1} . Hence, it is natural to pose the spectrum assignment in terms of computing the eigenvector ω_{n-1} such that a prespecified multiset of self-conjugate (not necessarily distinct) eigenvalues $\{\lambda_j\}_{i=2}^n$ are assigned to

$$\bar{A} = \left(I - b\omega_{n-1}^{H}\right)A + \lambda_1 b\omega_{n-1}^{H}.$$
(3)

To this end, we start with the characteristic polynomial of the closed loop matrix \overline{A} , which (with a little of technical effort) is shown to be given by:

$$\det(\lambda I - \bar{A}) = (\lambda - \lambda_1)\omega_{n-1}^H \operatorname{adj}(\lambda I - A^T)b.$$
(4)

Next, consider the controller canonical form $\dot{\xi} = A_c \xi + b_c u$, with $TA_c = AT$, $Tb_c = b$, and

$$A_{c} = \begin{pmatrix} 0 & 1 & \cdots & 0 \\ \vdots & & & \\ 0 & 0 & \cdots & 1 \\ -a_{n} & -a_{n-1} & \cdots & -a_{1} \end{pmatrix}, b_{c} = \begin{pmatrix} 0 \\ \vdots \\ 0 \\ 1 \end{pmatrix}.$$

Here, $T := CC_c^{-1}$ [5] indicates the transformation $x = T\xi$, where, for convenience, we denote by C := Con(A, b) and $C_c := Con(A_c, b_c)$ the open-loop and closed-loop controllability matrix [5], respectively. The characteristic polynomial of A then reads:

$$p(\lambda) = \det(\lambda I - A) = \lambda^n + a_1 \lambda^{n-1} + \ldots + a_n.$$
 (5)

Following the discussion related to equation (2), if we let

$$\gamma_{n-1}^{H} := [\gamma_{n-1,n-1}, \dots, \gamma_{n-1,1}, 1]$$
(6)

represent the desired left eigenvector, and λ_1 the corresponding eigenvalue of the closed loop $\bar{A}_c := A_c + b_c k_c^T = T^{-1} \bar{A} T$ in the ξ -coordinates, then from (4) we get

$$\det(\lambda I - \bar{A}_c) = (\lambda - \lambda_1)\gamma_{n-1}^H \Upsilon(\lambda), \tag{7}$$

where we introduce: $\Upsilon(\lambda) := [1 \ \lambda \ \dots \ \lambda^{n-1}]^T = \operatorname{adj}(\lambda I - A_c^T)b_c$. From (7) it is obvious that the eigenvalues $\{\lambda_j\}_{j=2}^n$ of the closed-loop matrix \overline{A}_c (that is, of \overline{A} , as well) are independent of the parameters a_1, \ldots, a_n , and they are entirely determined by the left eigenvector γ_{n-1} . On the other hand, let (7) be specified by a desired closed-loop characteristic polynomial of the form:

$$q_n(\lambda) = \lambda^n + \alpha_1 \lambda^{n-1} \dots + \alpha_n.$$
(8)

Equation (7) says that γ_{n-1} hosts the parameters of the polynomial $q_{n-1}(\lambda)$, where $q_n(\lambda) = (\lambda - \lambda_1)q_{n-1}(\lambda)$. Explicitly, it can be checked that γ_{n-1} , as defined in (6), is given by the recursive algorithm: $\gamma_{n-1,i} = \alpha_i + \gamma_{n-1,i-1}\lambda_1$ for $i \in n - 1$, where, in accordance with our adoption in (6): $\gamma_{n-1,0} = 1$. Moreover, with \overline{A} and \overline{A}_c being similar, we have

$$\omega_{n-1}^{H} = \gamma_{n-1}^{H} \mathcal{C}_c \mathcal{C}^{-1}, \quad k^T = \omega_{n-1}^{H} (\lambda_1 I - A).$$
(9)

This represents our initial pole assignment formula. Next, we generalize it and demonstrate its relationship to the Bass-Gura and Ackermann formulae. First, it is readily verified that $\gamma_{n-1}^{H}(\lambda_{1}I - A_{c}) = [\alpha_{1} - a_{1}, \dots, \alpha_{n} - a_{n}] := \gamma_{n}^{H}$, (10)

indicating that all the closed-loop eigenvalues in $\{\lambda_j\}_{j \in n}$ are "encoded" in the (real) vector γ_n , whereas γ_{n-1} carries the information about $\{\lambda_j\}_{j=2}^n$. Then, the Bass-Gura formula:

$$k^T = \gamma_n^H \mathcal{C}_c \mathcal{C}^{-1} \tag{11}$$

results immediately, if we rewrite (9) as: $k^T = \gamma_{n-1}^H (\lambda_1 I - A_c) C_c C^{-1}$, with the term $T^{-1} = C_c C^{-1}$ shifted right most.

Equation (10) can be interpreted as "pulling out" or "carrying over" the eigenvalue λ_1 from γ_n via the factor $\lambda_1 I - A_c$, this necessarily introducing γ_{n-1} . By proceeding in the same way, one can pullout the eigenvalue λ_2 from γ_{n-1} by means of $\lambda_2 I - A_c$, λ_3 from γ_{n-2} via $\lambda_3 I - A_c$, and so on. Hence, we can introduce

$$\gamma_{n-r}^{H} := [\gamma_{n-r,n-1}, \dots, \gamma_{n-r,r}, 1, 0, \dots, 0], \quad r \in \mathbf{n}$$
 (12)

using:

$$\gamma_n^H = \gamma_{n-r}^H \prod_{i=1}^r (\lambda_i I - A_c), \qquad (13)$$

where the (r-1) zeros (for $r \ge 2$) result due to the "absence" of the eigenvalues $\lambda_2, \ldots, \lambda_r$ in γ_{n-r} , while the n-r nonzero terms carry the information about $\lambda_{r+1}, \ldots, \lambda_n$. In this sense, by substituting (13) into (11), our spectrum assignment formula (9) can be set in the general form:

$$k^{T} = \gamma_{n-r}^{H} \mathcal{C}_{c} \mathcal{C}^{-1} \prod_{i=1}^{r} (\lambda_{i} I - A), \quad r \in \boldsymbol{n},$$
(14)

which can be slightly generalized to

$$k^T = \omega_{n-r}^H q_r(A), \quad r \in \boldsymbol{n_0}, \tag{15}$$

with $q_0(A) := I_n$ and otherwise:

$$\omega_{n-r}^{H} := \gamma_{n-r}^{H} \mathcal{C}_{c} \mathcal{C}^{-1}, \quad q_{r}(A) := \prod_{i=1}^{r} (\lambda_{i} I - A).$$
(16)

Clearly, equation (15) represents the generalized form of our initial expression in (9). For $r \ge 1$ the vector γ_{n-r} is simply defined by the coefficients of the polynomial $q_{n-r}(\lambda)$, where

$$q_n(\lambda) = q_{n-r}(\lambda) q_r(\lambda).$$
(17)

The definition of γ_n (i.e. reflecting the Bass-Gura formula with r = 0, c.f. (10)) represents an exception to this rule.

Now, consider the special case with r = n and let $q_n(A)$ denote the real matrix polynomial corresponding to the desired characteristic polynomial $q_n(\lambda)$ from (8). Then, using $\gamma_0^H = [1, 0, \dots, 0]$ from (12), and: $[1, 0, \dots, 0] \cdot C_c = [0, \dots, 0, 1]$, we obtain the Ackermann formula directly from (14):

$$k^{T} = [0, \dots, 0, 1] \mathcal{C}^{-1} q_{n}(A).$$
 (18)

A. Comments

(*i*) Expressions (14) and (15) provide a direct link of the Bass-Gura and Ackermann formulae. Moreover, it represents a generalization thereof: the former one results with r = 0 (leading to the definition (10) for γ_n), while the latter one for r = n in (14). Notice that from (18) we immediately obtain

$$\omega_0^T = [0, \dots, 0, 1] \mathcal{C}^{-1}.$$

(*ii*) The desired conjugate eigenpairs should be "encoded" jointly in (14), either in the real vector ω_{n-r} or in the real matrix polynomial $q_r(A)$ to benefit from the numerical computation with real numbers. Therefore, without loss of generality we may consider

$$k^T = \omega_{n-r}^T q_r(A), \quad r \in \mathbf{n_0}, \tag{19}$$

as the general form of our spectrum assignment formula. In this sense, it is also convenient to use a real λ_1 in (2).

(*iii*) If ω_{n-1} in (2) is selected to be the left eigenvector of the open-loop matrix A corresponding to a real eigenvalue, say μ_1 , then from (3) we have $\bar{A} = A + \Delta_1 b \omega_{n-1}^T$, with $\Delta_1 := \lambda_1 - \mu_1$ referring to a real shift. The remainder open-loop eigenvalues $\{\mu_i\}_{i=2}^n$ are thereby unaltered, as for any right eigenvector ν_{n-i} of A corresponding to the eigenvalue μ_i , we have $\bar{A}\nu_{n-i} = A\nu_{n-i} = \mu_i\nu_{n-i}$, $i \in \{2, ..., n\}$ (as a consequence of $\omega_{n-1}^T \nu_{n-i} = 0$). In this case we retain:

$$k^T = \Delta_1 \omega_{n-1}^T,$$

which represents the well-known result of Simon and Mitter [7] (cf. pp. 338). It is important to observe in this case the geometric interpretation of the vector term ω_{n-1} in (2): it is orthogonal to the invariant subspace corresponding to the eigenvalues that remain unchanged. We discuss this more generally in the next section.

(*iv*) Finally, due to the presence of the factor C^{-1} , which for large *n* is typically ill-conditioned, related well-known numerical robustness problems are inherent in the expression (14). In the sequel, we discuss the avoidance of such difficulties.

B. Partial spectrum assignment

Next, we consider the usability of the vector $\omega_{n-r} \in \mathbb{R}^n$ in the context of the partial spectrum assignment and a sequential spectrum assignment based thereon, which consists in shifting a submultiset of open-loop self-conjugate eigenpairs, say $M_r = {\mu_i}_{i=1}^r$, to some prescribed self-conjugate $L_r = {\lambda_i}_{i=1}^r$, while keeping the remainder (n-r)-ones of $M_{n-r} = {\mu_i}_{i=r+1}^n$ unaltered $(r \in \mathbf{n})$.

To this end, consider the operator description of A:

$$A = \begin{bmatrix} X & 0 \\ * & Y \end{bmatrix} : \bigoplus_{\mathcal{V}} \to \bigoplus_{\mathcal{V}}, \qquad (20)$$

corresponding to the real Schur decomposition:

$$A(U,V) = (U,V) \begin{pmatrix} X & 0\\ * & Y \end{pmatrix},$$
(21)

where $\mathcal{U} \oplus \mathcal{V} = \mathbb{R}^n$ (i.e. \mathcal{U} and \mathcal{V} are complementary subspaces), $\mathcal{U} = Range(U) \subseteq \mathbb{R}^r$, $\mathcal{V} = Range(V) \subseteq \mathbb{R}^{n-r}$ is the A-invariant subspace (i.e. AV = VY) corresponding to the eigenvalues in M_{n-r} , and $[U, V] \in \mathbb{R}^{n \times n}$ is orthogonal (i.e., \mathcal{U} and \mathcal{V} are mutually orthogonal subspaces). Next, introducing

$$\omega_{n-r} = U\eta \tag{22}$$

in terms of $\eta \in \mathbb{R}^r$ in (19), it can be readily checked that the block-triangular form is preserved under feedback [6]:

$$\begin{pmatrix} U^T \\ V^T \end{pmatrix} \bar{A} (U, V) = \begin{pmatrix} X + U^T b \eta^T q_r(X) & 0 \\ * & Y \end{pmatrix}.$$
(23)

Note that due to the re-appearance of Y in the diagonal, the eigenvalues in M_{n-r} remain unaltered in \overline{A} , while those from M_r change subject to the parameter η in the term $X + U^T b \eta^T q_r(X)$. The latter expression suggests using the Ackermann formula for computation of η in shifting the eigenvalues M_r of X to L_r :

$$\omega_{n-r}^{T} = \eta^{T} U^{T}, \quad \eta^{T} = [0, \dots, 1] \mathcal{C}^{-1}(X, U^{T} b).$$
(24)

In words, if ω_{n-r} is fixed perpendicularly to the invariant subspace \mathcal{V} , then the corresponding open-loop eigenvalues remain unchanged if we apply the feedback of the form (19) with (22) and (24). This fact provides a geometric interpretation for the term ω_{n-r} in the expression (19).

With reference to (27), it is easily seen that the invertibiliy of the controllability matrix $C^{-1}(X, U^T b)$ in (24) requires

$$rank\left(U^{T}\left[b,Ab,\ldots,A^{r-1}b\right]\right)=r,$$

which refers to the projected subsystem $(U^T A U, U^T b)$ onto the subspace $\mathcal{U} \subseteq \mathbb{R}^r$ [6].

C. Sequential spectrum assignment

Comment (iv) indicates the difficulties with the invertibility of the underlying controllability matrix, while in the previous section we saw that the latter is reduced due to the projection of the system matrix onto a subspace of a lower dimension. This idea can now be utilized sequentially as suggested by the following algorithm. Let

$$\Lambda(A) = \bigcup_{\ell=1}^{m} M_{\ell}, \quad \Lambda(\bar{A}) = \bigcup_{\ell=1}^{m} L_{\ell}, \tag{25}$$

where M_{ℓ} includes a submultiset of self-conjugate open-loop eigenvalues, and L_{ℓ} the corresponding desired self-conjugate closed-loop eigenvalues. In other words, the eigenvalues in M_{ℓ} are to be shifted to L_{ℓ} for all $\ell \in \mathbf{m}$. Then, introduce:

$$u_{\ell} = \omega_{\ell}^{T} q_{\ell}(\bar{A}_{\ell}) x + u_{\ell+1}, \quad \ell \in \boldsymbol{m}$$
(26)

with $u = u_1$, $u_{m+1} = 0$, $\bar{A}_1 = A$, $\bar{A}_{\ell+l} = \bar{A}_{\ell} + b\omega_{\ell}^T q_{\ell}(\bar{A}_{\ell})$,

$$\bar{A}_{\ell} = \begin{bmatrix} X_{\ell} & 0 \\ * & Y_{\ell} \end{bmatrix} : \underset{\mathcal{V}_{\ell}}{\overset{\mathcal{U}_{\ell}}{\mapsto} \rightarrow \bigoplus},$$
(27)

where $\mathcal{V}_{\ell} = Range(V_{\ell})$ represents the \bar{A}_{ℓ} -invariant subspace corresponding to the eigenvalues $\Lambda(\bar{A}_{\ell}) \setminus M_{\ell}, \mathcal{U}_{\ell} = Range(U_{\ell})$ is orthogonal to \mathcal{V}_{ℓ} in \mathbb{R}^n ,

$$\omega_{\ell}^{T} = \eta_{\ell}^{T} U_{\ell}^{T}, \quad \eta_{\ell}^{T} = [0, \dots, 1] \mathcal{C}^{-1}(X_{\ell}, U_{\ell}^{T} b)$$
(28)

and $q_{\ell}(\cdot)$ is the characteristic polynomial corresponding to the desired eigenvalues in L_{ℓ} . Effectively, we obtain:

$$k^T = \sum_{\ell=1}^m \omega_\ell^T q_\ell(\bar{A}_\ell).$$
⁽²⁹⁾

In words, the vector ω_{ℓ} is set perpendiculary to the invariant subspaces \mathcal{V}_{ℓ} corresponding to the unaltered eigenvalues at the ℓ^{th} iteration, while the Ackermann formula is used to design the feedback gain η_{ℓ} for the assignment of the eigenvalues Λ_{ℓ} in the projected subspace. This procedure is repeated sequentially. Thereby, \bar{A}_{ℓ} represents the closed-loop system matrix up to the ℓ^{th} iteration. Finally, if M_{ℓ} includes a pair of conjugated poles only, then this algorithm reduces to the Ackermann's method of invariant planes [2].

III. CONCLUSION

This short note introduces a slightly generalized version of pole placement formulae and discusses its relationships to Ackermann, Bass-Gura and Simon & Mitter algorithms. It extends and completes initial ideas of [3]. The author thanks Dietrich Flockerzi for useful discussions.

REFERENCES

- [1] J. Ackermann. Der Entwurf linearer Regelungssyst. im Zustandsr., 1972.
- [2] J. Ackermann. Robust control. Springer Verlag, 1993.
- [3] N. Bajcinca, D. Flockerzi, and Y. Kouhi. Geometric underdetermined state-feedback control with applications to continuous and switched linear systems. In *sub. Asian Journal of Control*, 2013.
- [4] R. A. Horn and C. R. Johnson. Matrix Analysis. Cam.Univ.Press, 1990.
- [5] T. Kailath. Linear Systems. Prentice Hall, Englewood Cliffs, NJ, 1980.
- [6] Y. Saad. A projection method for partial pole assignment in linear state feedback. Technical report, 1986.
- [7] J. D. Simon and S. K. Mitter. A theory of modal control. *Information and Control*, 13:316–353, 1968.