# POLYNOMIAL DELAY ALGORITHM FOR LISTING MINIMAL EDGE DOMINATING SETS IN GRAPHS

MAMADOU MOUSTAPHA KANTÉ, VINCENT LIMOUZY, ARNAUD MARY, LHOUARI NOURINE, AND TAKEAKI UNO

ABSTRACT. A hypergraph is a pair  $(V, \mathcal{E})$  where V is a finite set and  $\mathcal{E} \subseteq 2^V$  is called the set of hyper-edges. An output-polynomial algorithm for  $\mathcal{C} \subseteq 2^V$  is an algorithm that lists without repetitions all the elements of  $\mathcal{C}$  in time polynomial in the sum of the size of  $\mathcal{H}$  and the accumulated size of all the elements in  $\mathcal{C}$ . Whether there exists an output-polynomial algorithm to list all the inclusion-wise minimal hitting sets of hyper-edges of a given hypergraph (the Trans-Enum problem) is a fifty years old open problem, and up to now there are few tractable examples of hypergraph classes. An inclusion-wise minimal hitting set of the closed neighborhoods of a graph is called a minimal dominating set. A closed neighborhood of a vertex is the set composed of the vertex itself with all its neighbors. It is known that there exists an output-polynomial algorithm for the set of minimal dominating sets in graphs if and only if there is one for the minimal hitting sets in hypergraphs. Hoping this equivalence can help to get new insights in the Trans-Enum problem, it is natural to look at graph classes. It was proved independently and with different techniques in [Golovach et al. - ICALP 2013] and [Kanté et al. - ISAAC 2012] that there exists an incremental output-polynomial algorithm for the set of minimal edge dominating sets in graphs (i.e. minimal dominating sets in line graphs). We provide the first polynomial delay and polynomial space algorithm that lists all the minimal edge dominating sets in graphs, answering an open problem of [Golovach et al. -ICALP 2013]. Besides the result, we hope the used techniques that are a mix of a modification of the well-known Berge's algorithm and a strong use of the structure of line graphs, are of great interest and could be used to get new output-polynomial algorithms.

#### 1. Introduction

The MINIMUM DOMINATING SET problem is a classic and well-studied graph optimization problem. A dominating set in a graph G is a subset D of its set of vertices such that each vertex is either in D or has a neighbor in D. Computing a minimum dominating set has numerous applications in many areas, e.g., networks, graph theory (see for instance the book [10]). The MINIMUM EDGE DOMINATING SET problem is a classic well-studied variant of the MINIMUM DOMINATING SET problem [10]. An edge dominating set is a subset F of the edge set such that each edge is in F or is adjacent to an edge in F. In this paper, we are interested in an output-polynomial algorithm for listing without duplications the (inclusion-wise) minimal edge dominating sets of a graph. An output-polynomial algorithm is an algorithm whose running time is bounded by a polynomial depending on the sum of the sizes of the input and output. The enumeration of minimal or maximal subsets of vertices satisfying some property in a (hyper)graph is a central area in graph algorithms and for several properties output-polynomial algorithms have been proposed e.g. [2, 4, 6, 7, 20, 24, 28], while for others it was proven that no output-polynomial time algorithm exists unless P=NP [16, 17, 19, 20, 26].

The existence of an output-polynomial algorithm for the enumeration of minimal dominating sets of graphs (Dom-Enum problem) is a widely open question and is closely related to the well-known Trans-Enum problem in hypergraphs which asks for an output-polynomial algorithm for the enumeration of all minimal transversals in hypergraphs. A transversal (or a hitting-set) in a hypergraph is a subset of its vertex set that intersects every of its hyper-edges. This is a long-standing open problem (see for instance [5]) and is well-studied due to its applications in several areas [5, 6, 9, 18, 23]. Up to now only few tractable cases are known (see [11] for some examples). It is easy to see that the minimal dominating sets of a graph are the minimal

transversals of its closed neighbourhoods<sup>1</sup>, and then, as a particular case, it seems that the DOM-ENUM problem is more tractable than the TRANS-ENUM problem, but some of the authors have very recently proved in [12] that there exists an output-polynomial algorithm for DOM-ENUM if and only if there exists one for TRANS-ENUM. It is therefore interesting to look at the TRANS-ENUM problem in the perspective of graph theory and to investigate graph classes where the DOM-ENUM problem is tractable. Indeed, the authors have exhibited several new tractable cases split graphs [11], undirected path graphs [13], permutation graphs [14] and chordal P6-free graphs [11]. It is proved in [13] (and independently in [8]) that the enumeration of minimal edge dominating sets can be done in (incremental) output-polynomial. In this paper we improve drastically these two algorithms and give the first algorithm with polynomial delay (the time between two consecutive outputs is bounded by a polynomial on the input size) and that uses polynomial space.

The strategy of our algorithm is based on a modified version of Berge's algorithm [3] for enumerating minimal transversals. Berge's algorithm consists in ordering the hyper-edges  $E_1, \ldots, E_m$ of a given hypergraph  $\mathcal{H}$  and for each i computes the minimal transversals of the hypergraph  $\mathcal{H}_i$ with set of hyper-edges  $\{E_1, \ldots, E_i\}$  from the minimal transversals of  $\mathcal{H}_{i-1}$ . The main drawback of Berge's algorithm is that a minimal transversal of  $\mathcal{H}_i$  is not necessarily a subset of a minimal transversal of  $\mathcal{H}$ , and therefore Berge's algorithm does not guarantee an output-polynomial algorithm. Indeed, it is proved in [27] that there exist hypergraphs for which Berge's algorithm is not output-polynomial for any ordering. We will propose a new version of Berge's algorithm that consists in grouping the hyper-edges of a given hypergraph with respect to the hyper-edges of a maximal matching<sup>2</sup>. This overcomes the inconvenient of Berge's algorithm, but the counterpart is the difficulty in the extension of the already computed sub-transversals (which was trivial in Berge's algorithm). We will show how to solve this extension part in the case of minimal edge dominating sets. It is worth noticing that a strategy similar to the Berge's algorithm exists for enumerating maximal subsets satisfying a certain property [20]. It consists in ordering the vertices  $x_1, \ldots, x_n$  of a hypergraph and for each i computes the maximal sets that are maximal within  $\{1, \ldots, i\}$ . But contrary to Berge's algorithm every sub-solution computed at step i is a subset of a solution, and therefore as in our version of Berge's algorithm if one can compute the maximal sets that are maximal within  $\{1, \ldots, i\}$  from those that are maximal within  $\{1, \ldots, i-1\}$ one gets an output-polynomial algorithm. This strategy has been used by Lawler et al. in [20] to give output-polynomial algorithms for enumerating maximal set packings, maximal complete k-partite subgraphs, the bases of the intersection of m matroids for fixed  $m, \ldots$ 

The remainder of the text is as follows. In Section 2 we give some necessary definitions. Section 3 explains the strategy for the enumeration and give an informal description of the algorithm. Section 4 is devoted to the technical parts of the paper. We sum up all the details of the algorithm in Section 5, and conclude with some open questions in Section 6.

### 2. Preliminaries

If A and B are two sets,  $A \setminus B$  denotes the set  $\{x \in A \mid x \notin B\}$ . The power-set of a set V is denoted by  $2^V$ . For three sets A, B and C, we write  $A = B \sqcup C$  if  $A = B \cup C$  and  $B \cap C = \emptyset$ . The size of a set A is denoted by |A|. We refer to [1] for graph terminology. A graph G = (V, E) is a pair of vertex set V and edge set  $E \subseteq V \times V$ . We only deal with finite and simple graphs. An edge between x and y in a graph is denoted by xy (equivalently yx) and sometimes it will be convenient to see an edge xy as the set  $\{x,y\}$ , but this will be clear from the context.

Let G := (V, E) be a graph. For a vertex x, we denote by  $\widetilde{N}(x)$  the set of edges incident to x, and N(x) denotes the set of vertices adjacent to x. For every edge e := xy, we denote by N[e] the set of edges adjacent to e, i.e.  $N[e] := \widetilde{N}(x) \cup \widetilde{N}(y)$ . A subset D of E is called an edge dominating set if for every edge e of G, we have  $N[e] \cap D \neq \emptyset$ , and D is minimal if no proper subset of it is an edge dominating set.

<sup>&</sup>lt;sup>1</sup>The closed neighborhood of a vertex v in a graph is the set containing v and all its neighbors.

<sup>&</sup>lt;sup>2</sup>A maximal matching in a hypergraph is a set of disjoint edges maximal with respect to inclusion.

If V is a finite set and  $\mathcal{C} \subseteq 2^V$ , then the size of  $\mathcal{C}$ , denoted by  $\|\mathcal{C}\|$  is  $\sum_{C \in \mathcal{C}} |C|$ . A hypergraph  $\mathcal{H}$  is a pair  $(V, \mathcal{F})$  with a vertex set V and a hyper-edge set  $\mathcal{F} \subseteq 2^V$ . It is worth noticing that graphs are special cases of hypergraphs. The size of a hypergraph  $\mathcal{H}$ , denoted by  $\|\mathcal{H}\|$ , is defined as  $|V| + \|\mathcal{F}\|$ .

Let  $\mathcal{H}$  be a hypergraph and let  $\mathcal{C}$  be a subset of  $2^V$ . An output-polynomial algorithm for  $\mathcal{C}$  is an algorithm that lists the elements of  $\mathcal{C}$  without repetitions in time  $\mathcal{O}\left(p\left(\|\mathcal{H}\|,\|\mathcal{C}\|\right)\right)$  for some polynomial p. We say that an algorithm enumerates  $\mathcal{C}$  with polynomial delay if, after a pre-processing that runs in time  $\mathcal{O}(p(\|\mathcal{H}\|))$  for some polynomial p, the algorithm outputs the elements of  $\mathcal{C}$  without repetitions, the delay between two consecutive outputs being bounded by  $\mathcal{O}(q(\|\mathcal{H}\|))$  for some polynomial q (we also require that the time between the last output and the termination of the algorithm is bounded by  $\mathcal{O}(q(\|\mathcal{H}\|))$ . It is worth noticing that an algorithm which enumerates a subset  $\mathcal{C}$  of  $2^V$  in polynomial delay outputs the set  $\mathcal{C}$  in time  $\mathcal{O}\left(p(\|\mathcal{H}\|) + q(\|\mathcal{H}\|) \cdot |\mathcal{C}| + \|\mathcal{C}\|\right)$  where p and q are respectively the polynomials bounding the pre-processing time and the delay between two consecutive outputs. Notice that any polynomial delay algorithm is obviously an output-polynomial one, but not all output-polynomial algorithms are polynomial delay [26]. We say that an output-polynomial algorithm uses polynomial space if there exists a polynomial q such that the space used by the algorithm is bounded by  $q(\|\mathcal{G}\|)$ . The output polynomiality is one of a criteria of efficiency for enumeration algorithms, and polynomial delay is that of more efficiency. This paper addresses the following question.

**Question**: Is there a polynomial delay polynomial space algorithm to enumerate all minimal edge dominating sets of a given graph?

Let  $\mathcal{H} := (V, \mathcal{F})$  be a hypergraph. A private neighbor of a vertex x with respect to  $T \subseteq V$  is a hyper-edge that intersect T only on x, and the set of private neighbors of x is denoted by  $P_{\mathcal{H}}(x,T)$ , i.e.  $P_{\mathcal{H}}(x,T) := \{F \in \mathcal{F} \mid F \cap T = \{x\}\}$ . A subset T of  $V(\mathcal{H})$  is called an irredundant set if  $P_{\mathcal{H}}(x,T) \neq \emptyset$  for all  $x \in T$ . We denote by  $IR(\mathcal{H})$  the set of irredundant sets of  $\mathcal{H}$ .

A transversal (or hitting set) of  $\mathcal{H}$  is a subset of V that has a non-empty intersection with every hyper-edge of  $\mathcal{F}$ ; it is minimal if it does not contain any other transversal as a proper subset. It is known that T is a minimal transversal if and only if T is a transversal and  $P_{\mathcal{H}}(x,T) \neq \emptyset$  for all  $x \in T$ . The set of all minimal transversals of  $\mathcal{H}$  is denoted by  $tr(\mathcal{H})$ . The edge neighborhood hypergraph  $\mathcal{H}(G)$  of G is the hypergraph  $(E, \{N[e] \mid e \in E\})$ . The following proposition is easy to obtain.

**Proposition 1.** For any graph G := (V, E),  $T \subseteq E$  is an edge dominating set of G if and only if T is a transversal of  $\mathcal{H}(G)$ . Therefore,  $T \subseteq E(G)$  is a minimal edge dominating set of G if and only if T is a minimal transversal of  $\mathcal{H}(G)$ .

Our algorithm is based on algorithms developed for enumerating minimal transversals. Thus, we introduce the dominating set version of the above notions. For an edge set  $T \subseteq E$ , a private neighbor of an edge e with respect to T is an edge f that is adjacent to e but not to any edge in  $T\setminus\{e\}$ . The set of private neighbors of e is denoted by  $P_E(e,T)$ . For an edge subset E' of E, an edge set T is called transversal (or hitting set) of E', if for any edge e of E', E' includes at least one edge e of E' that is adjacent to the edge e. A transversal of E' is minimal if it does not contain any other transversal of E' as a proper subset. Again E' is a minimal transversal of E' and E' if and only if E' is a transversal of E' and E' and E' if and only if E' is also denoted by E'.

#### 3. Berge's Algorithm and Basic Strategy

Hereafter, we explain our approach to enumerate all minimal edge dominating sets. Our strategy for the enumeration is based on Berge's algorithm [3]. For a given hypergraph with hyper-edges enumerated as  $F_1, \ldots, F_m$ , let  $\mathcal{F}_j$  be  $\{F_1, \ldots, F_j\}$  for each  $1 \leq j \leq m$ . Roughly, Berge's algorithm computes, for each  $1 < j \leq m$ ,  $tr(\mathcal{F}_j)$  from  $tr(\mathcal{F}_{j-1})$ . Although the algorithm is not polynomial space, there is a way to reduce the space complexity to polynomial. For  $j \geq 1$ 

and  $T \in tr(\mathcal{F}_i)$ , we define the parent Q'(T,j) of T as follows

$$Q'(T,j) := \begin{cases} T & \text{if } T \in tr(\mathcal{F}_{j-1}), \\ T \setminus \{v\} & \text{if } v \text{ is such that } P_{\mathcal{F}_j}(v,T) = \{F_j\}. \end{cases}$$

We can observe that  $T \notin tr(\mathcal{F}_{j-1})$  if and only if  $P_{\mathcal{F}_j}(v,T) = \{F_j\}$  holds for some  $v \in T$ , thus the parent is well defined and always in  $tr(\mathcal{F}_{j-1})$  [15, 22]. One can moreover compute the parent of any  $T \in tr(\mathcal{F}_j)$  in time polynomial in  $\|\mathcal{H}\|$ . This parent-child relation induces a tree, rooted at  $\emptyset$ , spanning all members of  $\bigcup_{1 \leq j \leq m} tr(\mathcal{F}_j)$ . We can traverse this tree in a depth-first search

manner from the root by recursively generating the children of the current visiting minimal hitting set. Any child is obtained by adding at most one vertex, then the children can be listed in polynomial time. In this way, we can enumerate all the minimal hitting sets of a hypergraph with polynomial space.

Formally and generally, we consider the problem of enumerating all elements of a set  $\mathcal{Z}$  that is a subset of an implicitly given set  $\mathcal{X}$ . Assume that we have a polynomial time computable parent function  $P: \mathcal{X} \to \mathcal{X} \cup \{nil\}$ . For each  $X \in \mathcal{X}$ , P(X) is called the *parent* of X, and the elements Y such that P(Y) = X are called *children* of X. The parent-child relation of P is *acyclic* if any  $X \in \mathcal{X}$  is not a proper ancestor of itself, that is, it always holds that  $X \neq P(P(\cdots P(X)) \cdots)$ . We say that an acyclic parent-child relation is *irredundant* when any  $X \in \mathcal{X}$  has a descendant in  $\mathcal{Z}$ , in the parent-child relation. The following statements are well-known in the literature [2, 25, 21, 15, 22].

**Proposition 2.** All elements in  $\mathcal{Z}$  can be enumerated with polynomial space if there is an acyclic parent-child relation  $P: \mathcal{X} \to \mathcal{X} \cup \{nil\}$  such that there is a polynomial space algorithm for enumerating all the children of each  $X \in \mathcal{X} \cup \{nil\}$ .

**Proposition 3.** All elements in  $\mathcal{Z}$  can be enumerated with polynomial delay and polynomial space if there is an irredundant parent-child relation  $P: \mathcal{X} \to \mathcal{X} \cup \{nil\}$  such that there is a polynomial delay polynomial space algorithm for enumerating all the children of each  $X \in \mathcal{X} \cup \{nil\}$ .

With acyclic (resp., irredundant) parent-child relation  $P: \mathcal{X} \to \mathcal{X} \cup \{nil\}$ , the following algorithm enumerates all elements in  $\mathcal{Z}$ , with polynomial space (resp., with polynomial delay and polynomial space).

**Algorithm** ReverseSearch(X)

- 1. if  $X \in \mathcal{Z}$  then output X
- 2. for each Y satisfying X = P(Y) do
- 3. call ReverseSearch(Y)
- 4. end for

The call ReverseSearch(nil) enumerates all elements in  $\mathcal{Z}$ . Since the above parent-child relation for transversals Q' is acyclic, the algorithms proposed in [15, 22] use polynomial space. However, the parent-child relation Q' is not irredundant and hence ReverseSearch(nil) does not guarantee a polynomial delay neither an output-polynomiality. Indeed, we can expect that the size of  $tr(\mathcal{F}_j)$  increases as the increase of j, and it can be observed in practice. However,  $tr(\mathcal{F}_j)$  can be exponentially larger than  $tr(\mathcal{F}_m)$ , thus Berge's algorithm is not output polynomial [27]. Examples of irredundant parent-child relations can be found in the literature [2, 25, 21].

One idea to avoid the lack of irredundancy is to certificate the existence of minimal transversals in the descendants. Suppose that we choose some levels  $1 = l_1, \ldots, l_k = m$  of Berge's algorithm, and state that for any  $T \in tr(\mathcal{F}_{l_j})$ , we have at least one descendant in  $tr(\mathcal{F}_{l_{j+1}})$ . This implies that any transversal in  $tr(\mathcal{F}_{l_j})$  has a descendant in  $tr(\mathcal{F}_m)$ , thus we can have an irredundant parent-child relation by looking only at these levels, and the enumeration can be polynomial delay and polynomial space.

We will use this idea to obtain a polynomial delay polynomial space algorithm to enumerate the minimal edge dominating sets, the levels are determined with respect to a maximal matching. From now one we assume that we have a fixed graph G := (V, E) and we will show how to enumerate all its minimal edge dominating sets. A subset of E is a matching if every two of

its edges e and f are not adjacent. A matching is maximal if it is not included in any other matching. Let  $\{b_1,\ldots,b_k\}$  be a maximal matching of G, and let  $b_i=x_iy_i$ . For each  $0 \le i \le k$ , let  $V_i:=V\setminus \left(\bigcup_{i'>i}b_{i'}\right)$ , and let  $E_i:=\{e\mid e\subseteq V_i\}$ ). Let  $B_i:=E_i\setminus E_{i-1}$  for i>1. Note that any edge in  $E_1$  is adjacent to  $b_1$  and by definition  $B_i$  never includes an edge  $b_j\neq b_i$ . Without loss of generality, we here assume that we have taken a linear ordering  $\le$  on the edges of G so that: (1) for each  $e\in B_i$  and each  $f\in E_{i-1}$  we have e< f, (2) for each  $e\in \widetilde{N}(x_i)\cap B_i$ , each  $f\in \widetilde{N}(y_i)\cap B_i$  we have  $b_i< e< f$ . Observe that with that ordering we have e< f whenever  $e\in B_i$  and  $f\in B_j$  with i< j. We consider that Berge's algorithm on  $\mathcal{H}(G)$  follows that ordering. In fact we will prove using Berge's algorithm that we can define an irredundant parent-child relation to enumerate  $tr(E_i)$  from  $tr(E_{i-1})$ .

**Lemma 4.** Let  $1 \le i < k$ . Any  $T \in tr(E_{i-1})$  has at least one descendant in  $tr(E_i)$ .

Proof. If  $T' \in tr(E_i)$  satisfies T' = T, then T' is a descendant of T since the parent is never greater than the child. If  $T \notin tr(E_i)$ , some edges X of  $B_i$  are not dominated by T, and consider  $T' := T \cup \{b_i\}$ . We observe that  $b_i$  is adjacent to all edges of  $B_i$  and the edges in X are private neighbors of  $b_i$  in T', thus T' is included in  $tr(E_i)$ . Let us compute the ancestor of T' in  $E_{i-1}$  as follows: set T'' := T' and repeatedly compute the parent of T'' and set T'' to its parent, until reaching a minimal transversal in  $tr(E_{i-1})$ . In this process no vertex of T is removed since each vertex in T has a private neighbor in  $E_{i-1}$ . But, at some point  $b_i$  is removed from T' since it is the only one in T' which has a private neighbor in  $B_i$ . This means that T is an ancestor of T', and thus T always has a descendant in  $tr(E_i)$ .

For conciseness, we introduce a new parent-child relation for edge dominating set enumeration. For  $T \in tr(E_i)$ , let  $Q'_j(T,|E_i|)$  be the ancestor of T located on the j-th level of Berge's algorithm, i.e.,  $Q'_j(T,|E_i|) = Q'(Q'(\cdots(T,|E_i|),|E_i|-1),\cdots,j+1)$ . Then, we define the *skip parent* Q(T,i) of T by  $Q'_{|E_i-1|}(T,|E_i|)$ . T' is a *skip-child* of  $T \in tr(E_{i-1})$  if and only if  $T' \in tr(E_i)$  and Q(T',i) = T. The set of skip-children of  $T \in tr(E_i)$  is denoted by C(T,i). From Propositions 2 and 3, and Lemma 4 we have the following proposition.

**Proposition 5.** If we can list all skip-children of  $T \in tr(E_i)$ , for each  $1 \le i \le k$ , with polynomial delay and polynomial space, then we can enumerate all minimal edge dominating sets with polynomial delay and polynomial space.

But, as we will show in the next section, for a transversal T in  $tr(E_{i-1})$ , the problem of finding a transversal of  $tr(E_i)$  including T is NP-complete in general. In order to overcome this difficulty, we will identify a pattern, that we call an H-pattern, that makes the problem difficult. We will first show that one can enumerate with polynomial delay and polynomial space all the skip-children that include no edges from H-patterns, and then define a new parent-child relation that will allow to enumerate also with polynomial delay and polynomial space the other skip-children in a different way. In the following sections, we explain the methods for the enumeration.

## 4. Computing Skip-Children

Let T be in  $tr(E_{i-1})$  and  $T' \in tr(E_i)$  a skip-child of T. First notice that every edge in  $T' \setminus T$  can have a private neighbor only in  $B_i$ . Indeed every edge in  $E_{i-1}$  is already dominated by T and an edge in  $T' \setminus T$  is only used to dominate an edge in  $B_i$ . Moreover, an edge  $e \neq b_i$  in  $\widetilde{N}(x_i) \cap (T' \setminus T)$  (resp. in  $\widetilde{N}(y_i) \cap (T' \setminus T)$ ) can have private neighbors only in  $\widetilde{N}(x_i) \cap B_i$  (resp.  $\widetilde{N}(x_i) \cap B_i$ ). And from the proof of Lemma 4 if  $b_i \in T' \setminus T$  then  $T' \setminus T = \{b_i\}$ .

Let us first consider the case that every edge in  $T'\backslash T$  is adjacent to  $b_i$ . From our discussion above, when two edges in  $T'\backslash T$  are incident to  $x_i$  (resp.  $y_i$ ), they cannot have both private neighbors. Thus  $T'\backslash T$  can include at most two such edges. Therefore, by choosing all combinations of one or two edges adjacent to  $b_i$ , adding them to T and then checking if the skip-parent of the resulting set is T, we can enumerate all the skip-children T' of T such that  $T'\backslash T\subseteq B_i$  with polynomial delay and polynomial space.

We now consider the remaining case that an edge in  $T'\backslash T$  is not adjacent to  $b_i$ . We call such a skip-child extra. We can see that at least one edge  $f \neq b_i$  adjacent to  $b_i$  has to be included in T' to dominate  $b_i$ . Actually, since  $b_i < e$  for any  $e \in B_i\backslash \{b_i\}$ , any extra skip-child of T is a descendant of some  $T \cup \{f\}$  with  $f \neq b_i$  incident to  $x_i$  or  $y_i$  in the original parent-child relation. So, without loss of generality, we will assume that such an edge  $f \neq b_i$  is incident to  $x_i$  and is included in T. Hereafter, we suppose that  $N(y_i) := \{z_1, \ldots, z_k\}$  and assume T' is an extra skip-child of T.

A vertex  $z_h \in N(y_i) \cap V_i$  is free if it is not incident to an edge in T, and is non-free otherwise. A free vertex is said to be *isolated* if it is not incident to an edge in  $E_{i-1}$ . Clearly, if there is an isolated free vertex, then T has no extra skip-child. Thus, we assume that there is no isolated free vertex. Edges in  $E_i \setminus B_i$  that are incident to some free vertices are called border edges. Observe that any border edge  $vz_h$  incident to a free vertex  $z_h$  is adjacent to an edge  $vw \in T$  if  $v \in V_{i-1}$ . The set of border edges is denoted by Bd(T,i). Note that no edge in Bd(T,i) is incident to two free vertices, otherwise the edge is in  $E_{i-1}$  but not dominated by T, and then any border edge is incident to exactly one free vertex. We can see that an edge of  $B_i$  incident to  $y_i$  is not dominated by T if and only if it is incident to a free vertex, and any edge in  $T' \setminus T$  that is not incident to  $x_i$  is a border edge. Then, for any border edge set  $Z \subseteq Bd(T,i)$ ,  $T \cup Z \in tr(E_i)$  only if each free vertex has a border edge  $e \in Z$  incident to it. Since any border edge is incident to exactly one free vertex, for any  $Z \subseteq Bd(T,i)$  such that  $T \cup Z$  is irredundant and for any edge  $vz_h \in Z$  with free vertex  $z_h$ ,  $P_{E_i}(e, T \cup Z)$  is always  $\{vz_h\}$ . This implies that  $T \cup Z$  is in  $tr(E_i)$ only if  $Z \subseteq Bd(T,i)$  includes exactly one edge incident to each free vertex. We call such an edge set Z a selection. We observe that all border edges are dominated by Z. We have the following lemma which is straightforward to prove.

**Lemma 6.** For any edge subset Z with  $Z \cap T = \emptyset$ , there holds  $T \cup Z \in tr(E_i)$  only if Z is a selection.

An edge  $e \in T$  is called *redundant* if all edges in  $P_{E_{i-1}}(e,T)$  are border edges and no edge  $y_i z_h$  is in  $P_{E_i}(e,T)$ .

**Lemma 7.** If T has a redundant edge, then any selection Z does not satisfy  $T \cup Z \in tr(E_i)$ .

Proof. Let e be a redundant edge of T. Since any border edge f is incident to a free vertex  $z_h$ , any selection Z should contain one edge incident to  $z_h$  and then if f is incident to e, we have  $f \notin P_{E_i}(e, T \cup Z)$ . Since no edge  $y_i z_h$  is in  $P_{E_i}(e, T)$ , there holds that  $P_{E_i}(e, T \cup Z) = \emptyset$  for any selection Z.

Let  $X_T := \{e \in Bd(T,i) \mid \exists e' \in T \text{ and } P_{E_i}(e',T \cup \{e\}) \subseteq Bd(T,i)\}$ . The addition of any edge  $e \in X_T$  to T transforms an edge e' of T into a redundant one with respect to  $T \cup \{e\}$ , and thus by Lemma 7 for any  $Z \subseteq Bd(T,i)$ ,  $T \cup Z \in tr(E_i)$  holds only if  $Z \cap X_T = \emptyset$ . Therefore, the following follows.

**Lemma 8.** If a free vertex is not incident to an edge in  $Bd(T,i)\backslash X_T$ , then any  $Z\subseteq Bd(T,i)$  does not satisfy  $T\cup Z\in tr(E_i)$ .

One can hope that we can characterize the selections Z not intersecting  $X_T$  such that  $T \cup Z \in tr(E_i)$  and be able to use it for listing the extra skip-children. Unfortunately, checking whether there is such a selection Z is NP-complete.

IRREDUNDANT MINIMAL TRANSVERSAL (IMT).


**Input.** A minimal transversal T of  $tr(E_{i-1})$ .

**Output.** Is there a selection  $Z, Z \cap X_T = \emptyset$ , such that  $T \cup Z \in tr(E_i)$ ?

**Theorem 9.** *IMT is NP-complete.* 

*Proof.* We reduce the 3SAT problem to IMT. Let  $C = C_1, C_2, \dots, C_m$  be the sets of clauses of a 3SAT instance over variables  $x_1, \dots, x_n$ . We create an instance of IMT as follows:

- $\begin{array}{l} \bullet \ \ V_{i-1} := \{x_j \mid j \leqslant n\} \sqcup \{\overline{x_j} \mid j \leqslant n\} \sqcup \{C_h \mid h \leqslant m\} \sqcup \{z_j \mid j \leqslant n\} \sqcup \{y_j \mid j \leqslant n\} \sqcup \{w\} \\ \bullet \ E_{i-1} := \{x_j C_h \mid x_j \in C_h\} \sqcup \{\overline{x_j} C_h \mid \overline{x_j} \in C_h\} \sqcup \{x_j z_j\} \mid j \leqslant n\} \sqcup \{\overline{x_j} y_j \mid j \leqslant n\} \sqcup \{x_j \overline{x_j} \mid j \leqslant n\} \sqcup \{x_j \overline{x_j} \mid j \leqslant n\} \end{array}$  $j \leq n$
- $V_i := V_{i-1} \sqcup \{x, y\}$
- $E_i := E_{i-1} \sqcup \{yC_h \mid h \leq m\} \sqcup \{xy, xw\}$
- $T := \{x_j \overline{x_j} \mid j \leq n\} \sqcup \{xw\}$



Notice that  $X_T = \emptyset$ , and then any selection Z is such that  $Z \cap X_T = \emptyset$ . Now we claim that the 3SAT instance is satisfiable if and only if there is an edge set  $Z \subset Bd(T,i)$  with  $Z \cap T = \emptyset$ such that  $T \cup Z$  is included in  $tr(E_i)$ .

Note that here we have  $Bd(T,i) = \{x_j C_h \mid x_j \in C_h\} \cup \{\overline{x_j} C_h \mid \overline{x_j} \in C_h\}$ . Notice now that a subset Z of Bd(T,i) is such that  $T \cup Z \notin tr(E_i)$  if and only if Z contains an edge of  $N(x_i)$  and an edge of  $N(\overline{x_i})$  for some  $i \leq n$ .

Let  $f: \{x_1, \dots, x_n\} \to \{0, 1\}$  be an assignment to the variables which satisfies the 3SAT formula. Then consider the following subset Z of Bd(T,i),

$$Z := \left( \bigcup_{x_j \mid f(x_j) = 1} \widetilde{N}(x_j) \cap Bd(T, i) \right) \cup \left( \bigcup_{x_j \mid f(x_j) = 0} \widetilde{N}(\overline{x_j}) \cap Bd(T, i) \right).$$

Clearly, since f satisfies the formula, Z is a selection in Bd(T,i) since otherwise a clause would not be satisfied by f. Notice now that by construction, either  $N(x_i) \cap Z = \emptyset$  or  $N(\overline{x_i}) \cap Z = \emptyset$ for every  $j \leq n$ , and then there exists  $Z' \subseteq Z$  such that  $T \cup Z'$  is in  $tr(E_i)$ .

Assume now that there exists a selection Z such that  $T \cup Z \in tr(E_i)$ . Let  $f: \{x_1, \dots, x_n\} \to x$  $\{0,1\}$  be such that:

$$f(x_j) := \begin{cases} 1 & \text{if } \widetilde{N}(x_j) \cap Z \neq \emptyset \\ 0 & \text{if } \widetilde{N}(\overline{x_j}) \cap Z \neq \emptyset. \end{cases}$$

Notice first that f is well-defined. Indeed, assume that for some  $x_j$ , we have  $\widetilde{N}(x_j) \cap Z \neq \emptyset$ and  $\widetilde{N}(\overline{x_i}) \cap Z \neq \emptyset$ . Then the private neighbor of the edge  $x_i \overline{x_i}$  with respect to  $T \cup Z$  would be empty, contradicting the fact that  $T \cup Z \in tr(E_i)$ . Now since Z is a selection of Bd(T,i), for every  $h \leq m, Z \cap \widetilde{N}(C_h) \neq \emptyset$  and then there exists either  $x_j \in C_h$  with  $f(x_j) = 1$  or  $\overline{x_j} \in C_h$ with  $f(x_i) = 0$ . Thus f satisfies all clauses.

In order to overcome this difficulty, we identify a pattern, that we call an H-pattern, that makes the problem difficult.

**Definition 10** (H-Pattern). A vertex set  $\{z_{\ell}, v_{\ell}, z_{j}, v_{j}\}$  is an H-pattern if  $z_{\ell}$  and  $z_{j}$  are free vertices,  $v_{\ell}v_{j}$  is in T, and  $v_{\ell}v_{j}$  has two non-border private neighbors in  $E_{i-1}\backslash T$ : one is adjacent to  $v_{\ell}$  and the other to  $v_{j}$ . We also say that the edges  $z_{\ell}v_{\ell}$ ,  $z_{j}v_{j}$  and  $v_{\ell}v_{j}$  induces an H-pattern.




FIGURE 1. Examples of *H*-patterns:  $u_l$  and  $u_j$  are the free vertices and  $v_lv_j$  is the edge in T

We will see that the difficulty of IMT comes from the presence of H-patterns. Indeed, for an H-pattern  $\{z_\ell, v_\ell, z_j, v_j\}$ , any private neighbor of  $v_\ell v_j$  is adjacent to either  $z_\ell v_\ell$  or to  $z_j v_j$ , thus we cannot add both to a selection Z since in that case  $P_{E_i}(v_\ell v_j, T \cup Z)$  will be empty. Let  $H_T$  be the set of border edges included in an H-pattern. In the next two subsections we will see how to list selections including no edge from  $H_T$ , and those that do.

**Lemma 11.** If T has no redundant edge, then  $T \cup Z \in tr(E_i)$  holds for any selection  $Z \subseteq Bd(T,i) \setminus (X_T \cup H_T)$ .

Proof. From the definition,  $T \cup Z$  dominates all the edges in  $E_i$  and for each  $e \in Z$  it holds that  $P_{E_i}(e, T \cup Z) \neq \emptyset$ . Since Z includes no edge from  $H_T \cup X_T$ , and T has no redundant edge, one easily checks from Lemmas 6, 7 and 8 by case analysis that any edge  $e \in T$  has a private neighbor f that is adjacent to no border edge, or an edge  $y_i z_h$  is adjacent to e and not to edges in  $T \setminus \{e\}$ . Thus, either  $f \in P_{E_i}(e, T \cup Z)$  or  $y_i z_h \in P_{E_i}(e, T \cup Z)$ . These imply that  $T \cup Z$  is in  $tr(E_i)$ .

4.1. **Dealing with Redundancies.** The lemmas above demonstrate how to construct transversals  $T' \in tr(E_i)$  from T, but some generated transversals may not be extra skip-children of T. This is because such T' can be also generated from another transversals in  $tr(E_{i-1})$ . Such redundancies happen for example when two edges  $f_1$  and  $f_2$  in T' have private neighbors only in  $B_i$ , but after the removal of either one from T', the other will have a private neighbor outside  $B_i$ . Assuming in this case that  $f_1 \in T$  and  $f_2 \in T' \setminus T$ , it holds that T' can be generated from T or from  $(T \setminus \{f_1\}) \cup \{f_2\}$ . And since the number of selections Z such that  $T \cup Z \in tr(E_i)$  can be arbitrarily large, we need to avoid such redundancies.

To address this issue, we state the following lemmas to characterize the edges not to be added to selections Z such that  $T \cup Z$  is an extra skip-child of T. We say that a border edge  $vz_{\ell}$  is preceding if there is an edge  $vz_h$  in T satisfying  $P_{E_{i-1}}(vz_h,T) \subseteq N[vz_{\ell}]$  and  $y_iz_{\ell} < y_iz_h$ , and denote the set of preceding edges by  $X'_T$ . We also say that an edge  $vz_h \in T$  is fail if  $P_{E_{i-1}}(vz_h,T) \subseteq Bd(T,i)$ ,  $y_iz_h$  is in  $P_{E_i}(vz_h,T)$ , and no edge  $wz_{\ell} \in P_{E_{i-1}}(vz_h,T)$  satisfies  $y_iz_h < y_iz_{\ell}$ .

**Lemma 12.** For any selection Z including a preceding edge,  $T \cup Z$  is not an extra skip-child of T.

Proof. We can assume without loss of generality that  $T \cup Z \in tr(E_i)$ , otherwise the statement holds. Suppose that there are several edges  $v_1z_{h_1}, \cdots, v_1z_{h_p}$  in T that are adjacent to preceding edges included in Z, and among them let  $v_jz_{h_j}$  be such that  $y_iz_{h_j}$  is greater than any  $y_iz_{h_\ell}$  for  $1 \leq \ell \leq p$  and  $\ell \neq j$ , and let  $v_jz_{\ell_j}$  be the preceding edge included in Z such that  $P_{E_{i-1}}(vz_{h_j}, T) \subseteq N[v_jz_{\ell_j}]$ . Let t be the index of  $y_iz_{h_j}$  in our ordering of the edges of E and let  $\mathcal{F}_t$  be the first t edges of E in our ordering (which includes of course  $y_iz_{h_j}$ ). Since  $P_{E_{i-1}}(vz_{h_j}, T) \subseteq N[v_jz_{\ell_j}]$  no edge of E but E

empty, and then  $P_{E_i}(v_jz_{h_j}, T \cup Z) = \{y_iz_{h_j}\}$ . From the choice of  $v_jz_{h_j}$  it follows that for any edge  $e \in T$  that is adjacent to a neighbor  $z_h$  of  $y_i$  and such that  $y_iz_h > y_iz_{h_j}$  there exists an edge  $f \in E_{i-1} \cap P_{E_i}(e, Q_t'(T \cup Z, |E_i|))$ . Thus, every edge in T has a private neighbor in  $\mathcal{F}_t$  and hence  $Q_t'(T \cup Z, |E_i|)$  includes all edges of T. But since  $y_iz_{h_j}$  has index t and  $P_{\mathcal{F}_t}(v_jz_{h_j}, T \cup Z) = P_{E_i}(v_jz_{h_j}, T \cup Z) = \{y_iz_{h_j}\}$ , we can conclude that  $Q_{t-1}'(T \cup Z, |E_i|)$  does not contain  $v_jz_{h_j}$ , and then the skip-parent of  $T \cup Z$  does not include  $v_jz_{h_j}$ . Therefore,  $T \cup Z$  is not an extra skip-child of T.

**Lemma 13.** If T has a fail edge, then  $T \cup Z$  is not an extra skip-child of T for any selection Z.

Proof. Let  $vz_h$  be a fail edge of T and let Z be a selection. Suppose without loss of generality that  $T \cup Z \in tr(E_i)$ . Since  $P_{E_{i-1}}(vz_h, T) \subseteq Bd(T, i)$  and each free vertex should be incident to an edge in Z we can conclude that  $P_{E_i}(vz_h, T \cup Z) = \{y_iz_h\}$ . Now let t be the index of  $y_iz_h$  in the ordering of E and let  $\mathcal{F}_t$  be the first t edges in this ordering. Assume also that  $Q'_t(T \cup Z, |E_i|)$  contains all edges of T, otherwise  $T \cup Z$  is not an extra skip-child of T. But, since  $P_{\mathcal{F}_t}(v_jz_{h_j}, T \cup Z) = P_{E_i}(v_jz_{h_j}, T \cup Z) = \{y_iz_h\}$ , we can conclude that  $Q'_{t-1}(T \cup Z, |E_i|)$  does not contain  $v_jz_h$ , and then the skip-parent of  $T \cup Z$  does not include  $v_jz_{h_j}$ . Thus,  $T \cup Z$  is not an extra skip-child of T.

We are now able to characterize exactly those selections Z not intersecting  $H_T$  and such that  $T \cup Z$  is an extra skip-child of T.

**Lemma 14.** Suppose that T has neither redundant edge nor fail edge and any free vertex is incident to an edge in Bd(T,i). Then,  $T \cup Z$  with  $T \cap Z = \emptyset$  is an extra skip-child of T including no edge of  $H_T$  if and only if Z is a selection including no edge of  $X_T \cup X_T' \cup H_T$ .

*Proof.* The only if part is clear from lemmas 6, 11, 12 and 13. Let us now prove the if part. Suppose that we have a selection Z including no edge in  $X_T \cup X_T' \cup H_T$ . By Lemmas 8 and 11 it holds that  $T \cup Z \in tr(E_i)$ . Suppose now that  $Q(T \cup Z, i) \neq T$ . Then, let us consider the computation of  $Q(T \cup Z, i)$  in  $E_i$ : we compute  $Q'(T \cup Z, |E_i|), Q'(Q'(T \cup Z, |E_i|), |E_i| - 1),$ and so on. Let F be the set of edges not in  $B_i$  incident to the neighbors of  $y_i$  in  $V_i$ , i.e.  $F := N(N(y_i)) \setminus N(y_i)$ . First notice that  $T \setminus F = Q(T \cup Z, i) \setminus F$ . So, T and  $Q(T \cup Z, i)$  can differ only on edges in F. So, let  $vz_h$  be the first edge removed among  $T \setminus Q(T \cup Z, i)$  in this operation sequence, i.e.,  $Q'_{i+1}(T \cup Z, |E_i|)$  includes all edges in  $T \setminus Q(T \cup Z, i)$ , but  $Q'_i(T \cup Z, |E_i|)$  does not include  $vz_h$ . Let  $\mathcal{F}_j$  be the first j edges in our ordering. Notice that all edges in  $E_{i-1}$  are in  $\mathcal{F}_j$ . Then, we can see that  $P_{E_i}(vz_h, T \cup Z) = \{y_iz_h\}$ . This implies that any private neighbor in  $P_{E_{i-1}}(vz_h,T)$  is dominated by some edges in Z, and no edge in  $(T\setminus\{vz_h\})\cup Z$  is adjacent to  $z_h$ . We further see that if there is a private neighbor  $uv \in P_{E_{i-1}}(vz_h, T)$  that is not a border edge, then no border edge is incident to u. Indeed, u is not a free vertex and is necessarily in  $V_{i-1}$ and if there is a border edge  $uz_{\ell}$  this edge should be in  $E_{i-1}$  and since it should be dominated by T and  $vu \in P_{E_{i-1}}(vz_h, T)$ , there would exist an edge in T incident to  $z_\ell$  contradicting that  $uz_{\ell}$  is a border edge. Similarly if there is a non border  $uz_h \in P_{E_{i-1}}(vz_h, T)$ , then no border edge is incident to u.

Suppose that all edges in  $P_{E_{i-1}}(vz_h,T)$  are border edges. Since  $vz_h$  is not a fail edge, there exists an edge  $wz_\ell \in P_{E_{i-1}}(vz_h,T)$  satisfying  $y_iz_h < y_iz_\ell$ . This implies that the edge  $wz_\ell \in P_{\mathcal{F}_j}(vz_h,Q'_{j+1}(T \cup Z,|E_i|))$ , and then  $vz_h$  should be in  $Q'_j(T \cup Z,|E_i|)$ , otherwise  $wz_\ell$  would not be dominated by  $Q'_j(T \cup Z,|E_i|)$ , thus yielding a contradiction.

Suppose now that there is a non-border edge vu in  $P_{E_{i-1}}(vz_h,T)$ . We note that u can be  $z_h$  so that  $vu = vz_h$ . Since  $vz_h$  is not in  $Q'_j(T \cup Z, |E_i|)$ , there should be a border edge in Z adjacent to  $vz_h$ . We can observe that u is incident to no edge in  $T \setminus \{vz_h\}$ , thus any border edge adjacent to uv is incident to v. If  $P_{E_{i-1}}(vz_h,T) \subseteq \tilde{N}(v)$ , then since T has no preceding edge any border edge  $vz_\ell \in Z$  satisfies that  $y_iz_h < y_iz_\ell$ . This implies that  $Q'_{j+1}(T \cup Z, |E_i|)$  includes no such border edge, and uv is a private neighbor of  $vz_h$  in  $P_{\mathcal{F}_j}(vz_h, Q'_{j+1}(T \cup Z, |E_i|))$ . This implies that  $vz_h$  is included in  $Q'_j(T \cup Z, |E_i|)$ , yielding a contradiction. So, there is a non border edge  $z_hw \in P_{E_{i-1}}(vz_h,T)$ . Let  $z_s$  and  $z_p$  be free vertices adjacent respectively to  $z_h$  and v and such that  $z_hz_s$  and  $vz_p$  are in z. If  $z_s \neq z_p$ , then  $\{z_s, z_h, z_p, v\}$  would form an  $z_p$ . So there is

at most one free vertex  $z_s$  such that  $vz_s$  and  $z_hz_s$  are in Z. If such a  $z_s$  exists, then one of  $z_hz_s$  and  $vz_s$  is not in Z. And then in this case either  $wz_h$  or vu is in  $P_{\mathcal{F}_j}(vz_h,Q'_{j+1}(T\cup Z,|E_i|))$ , contradicting that  $vz_h$  is not in  $Q'_j(T\cup Z,|E_i|)$ . If  $z_h$  is not adjacent to a border edge, then  $wz_h \in P_{\mathcal{F}_j}(vz_h,Q'_{j+1}(T\cup Z,|E_i|))$ , and then again  $vz_h$  would be in  $Q'_j(T\cup Z,|E_i|)$ .

From the discussion, we have that  $T \setminus Q(T \cup Z, i) = \emptyset$ . Since  $Q(T \cup Z, i)$  and T are both minimal in  $tr(E_{i-1})$ , we have  $Q(T \cup Z, i) = T$ .

As a corollary we have the following.

**Proposition 15.** One can enumerate with polynomial delay and space all the extra skip-children of T that do not contain edges of  $H_T$ .

Proof. If T has redundant edges or fail edges or has a free vertex not incident to an edge in  $Bd(T,i)\backslash X_T$ , then by Lemmas 7, 8 and 13 we can conclude that T has no extra skip-child. Since we can compute  $X_T$  in polynomial time and check in polynomial time whether an edge is redundant or is a fail edge, this step can be done in polynomial time. So, assume T has no redundant edge nor fail edges and every free vertex is incident to an edge in  $Bd(T,i)\backslash X_T$ . By Lemma 14 by removing all edges in  $H_T \cup X_T \cup X_T'$ , any selection Z is such that  $T \cup Z$  is a skip-child of T. One easily checks that the enumeration of these selections can be reduced to the enumeration of the minimal transversals of a hypergraph of degree at most 2, and in these hypergraphs minimal transversals can be enumerated with polynomial delay and polynomial space [6].

4.2. **Dealing with the Presence of** H**-Patterns.** As we saw in Theorem 9, it is hard to enumerate all extra skip-children having some edges in H-patterns from a given transversal  $T \in tr(E_{i-1})$ . Let us call these children H-children. We approach this difficulty by introducing a new parent-child relation among H-children, and enumerate them by traversing the forest induced by the new relation. In this way, we now do not follow the skip-parent skip-child relation for H-children. However, the root of each tree in the induced forest is a transversal obtained with the skip-child skip-parent relation. Let us be more precise now. For two sets S and S' of edges we write  $S <_{lex} S'$  if  $\min(S \Delta S') \in S$ , called lexicographical ordering.

Hereafter, we consider an extra skip-child  $T' = T \cup Z$  of  $T \in tr(E_{i-1})$  such that  $T' \cap H_T \neq \emptyset$ . Let  $H^*(T') := \{v_h z_h, v_\ell z_\ell, v_h v_\ell\}$  be the lexicographically minimum H-pattern among all H-patterns of T that includes an edge of Z. Without loss of generality, we assume that  $v_\ell z_\ell$  is in Z. Let  $uz_h$  be the edge in Z incident to  $z_h$ . Notice that such an edge exists because  $z_h$  is a free vertex. Then, we define the  $slide-parent Q^*(T',i)$  of T' by  $T' \cup \{v_h z_h\} \setminus \{uz_h, v_h v_\ell\}$ .

**Lemma 16.** The slide-parent of T' is well-defined and is a member of  $tr(E_i)$ .

*Proof.* Since  $z_h$  is a free vertex for T, Z includes exactly one edge in Z, thus  $uz_h$  is uniquely determined, and thus the slide-parent is uniquely defined. Since  $uz_h$  is a border edge, either  $u \notin V_{i-1}$  or u is incident to an edge of T. This together with that  $v_h z_h$  and  $v_\ell z_\ell$  dominate all edges in  $N[v_h v_\ell]$  leads that  $Q^*(T', i)$  dominates all edges in  $E_i$ .

By the addition of  $v_h z_h$  to T', no edge in  $T' \setminus \{u z_h, v_h v_\ell\}$  loses its private neighbor. The edge  $v_h z_h$  is adjacent to no edge in  $T' \setminus \{u z_h, v_h v_\ell\}$ , and then  $v_h z_h \in P_{E_i}(v_h z_h, Q^*(T', i))$ . These imply that  $Q^*(T', i)$  is a member of  $tr(E_i)$ .

The slide-parent of T has less edges than T, thus the (slide-parent)-(slide-child) relationship is acyclic, and for each  $T' \in tr(E_i)$ , there is an ancestor  $T'' \in tr(E_i)$  in the (slide-parent)-(slide-child) relation such that the skip-parent of T'' has no H-pattern. Similar to the depth-first search versions of Berge's algorithm [15, 22], we will traverse the (slide-parent)-(slide-child) relation to enumerate all transversals including H-pattern edges. The following follows from the definition of slide-parent.

**Proposition 17.** Any slide-child T' of T'' is obtained from T'' by adding two edges and remove one edge.

The computation of the slide-parent of any  $T' \in tr(E_i)$  including edges of H-patterns can be easily done in polynomial time: compute its skip-parent T in polynomial time, choose  $H^*(T)$  and then compute its slide-parent in polynomial time as described above. Proposition 17 shows that there are at most  $m^3$  candidates for slide-children, thus the enumeration of slide-children can be done with polynomial delay and polynomial space.

**Lemma 18.** For any  $T' \in tr(E_i)$ , all its slide-children can be enumerated with polynomial delay and polynomial space.

#### 5. Summary

We can now summarize the steps of the algorithm.

- all transversals in  $tr(E_1)$  can be enumerated with polynomial delay and polynomial space, since they include at most two edges from  $N[b_1]$ .
- In Section 4 (second paragraph), we have explained how to enumerate all non-extra skip-children with polynomial delay and polynomial space
- By Proposition 15 all the extra skip-children not including any edges of *H*-patterns can be enumerated with polynomial delay and polynomial space.
- Let  $\mathcal{T}$  be the set of all extra skip-children including some edges from H-patterns of their skip-parent. We proved in Section 4.2 how to enumerate all the members of  $\mathcal{T}$  with polynomial delay and polynomial space, by traversing the (slide-parent)-(slide-child) relation, *i.e.*, recursively listing all the slide-children of the current visiting transversal.
- Therefore, by executing these three enumeration algorithms for each transversal in  $T \in tr(E_{i-1})$ , we can generate all the members in  $tr(E_i)$  with polynomial delay and polynomial space.

All these show that the conditions of Proposition 5 are satisfied. And thus we can state our main result.

**Theorem 19.** All edge minimal dominating sets in a graph G can be enumerated with polynomial delay and polynomial space.

# 6. Conclusion

In this paper, we propose a polynomial delay polynomial space algorithm for listing all minimal edge dominating sets in a given graph. This improves drastically the previously known algorithms which were incremental output-polynomial and use exponential space. We state furthermore that usual approaches with Berge's algorithm involves an NP-complete problem, and thus it is difficult with usual approaches of Berge's algorithm to produce an efficient algorithm. To cope with this difficulty, we introduce a new idea of "changing the traversal routes in the area of difficult solutions" (the notion of skip-children and the removal of edges involved in H-patterns). Based on this idea, we give a new traversal route on these difficult solutions, that is totally independent from Berge's traversal route (the (slide-parent)-(slide-child) relation). As a result, we are able to construct a polynomial delay polynomial space algorithm.

The idea of changing the traversal routes seems to be new and to be able to apply to many other kind of algorithms in enumeration area. Interesting future works are applications of this idea to other kind of enumeration algorithms, e.g. the one used by Lawler et al. for enumerating maximal subsets [20] or other algorithms for enumerating minimal transversals (see for instance [6]).

## References

- [1] Bondy A. and Murty U.S.R. Graph Theory. Graduate Texts in Mathematics. Springer, 2008.
- [2] David Avis and Komei Fukuda. Reverse search for enumeration. Discrete Applied Mathematics, 65(1-3):21–46, 1996.
- [3] Claude Berge. Hypergraphs: Combinatorics of Finite Sets. North-Holland, 1989.
- [4] Endre Boros, Khaled M. Elbassioni, and Vladimir Gurvich. Transversal hypergraphs to perfect matchings in bipartite graphs: Characterization and generation algorithms. *Journal of Graph Theory*, 53(3):209–232, 2006.

- [5] Thomas Eiter and Georg Gottlob. Identifying the minimal transversals of a hypergraph and related problems. SIAM J. Comput., 24(6):1278–1304, 1995.
- [6] Thomas Eiter, Georg Gottlob, and Kazuhisa Makino. New results on monotone dualization and generating hypergraph transversals. SIAM J. Comput., 32(2):514–537, 2003.
- [7] Fedor V. Fomin, Pinar Heggernes, Dieter Kratsch, Charis Papadopoulos, and Yngve Villanger. Enumerating minimal subset feedback vertex sets. *Algorithmica*, 69(1):216–231, 2014.
- [8] Petr A. Golovach, Pinar Heggernes, Dieter Kratsch, and Yngve Villanger. An incremental polynomial time algorithm to enumerate all minimal edge dominating sets. In Fedor V. Fomin, Rusins Freivalds, Marta Z. Kwiatkowska, and David Peleg, editors, *ICALP* (1), volume 7965 of *Lecture Notes in Computer Science*, pages 485–496. Springer, 2013.
- [9] Dimitrios Gunopulos, Roni Khardon, Heikki Mannila, and Hannu Toivonen. Data mining, hypergraph transversals, and machine learning. In *PODS*, pages 209–216, 1997.
- [10] Teresa W. Haynes, Stephen T. Hedetniemi, and Peter J. Slater. Fundamentals of Domination in Graphs, volume 208 of Pure and Applied Mathematics. Marcel Dekker, 1998.
- [11] Mamadou Moustapha Kanté, Vincent Limouzy, Arnaud Mary, and Lhouari Nourine. Enumeration of minimal dominating sets and variants. In Olaf Owe, Martin Steffen, and Jan Arne Telle, editors, FCT, volume 6914 of Lecture Notes in Computer Science, pages 298–309. Springer, 2011.
- [12] Mamadou Moustapha Kanté, Vincent Limouzy, Arnaud Mary, and Lhouari Nourine. On the enumeration of minimal dominating sets and related notions. In Submitted, 2012.
- [13] Mamadou Moustapha Kanté, Vincent Limouzy, Arnaud Mary, and Lhouari Nourine. On the neighbourhood helly of some graph classes and applications to the enumeration of minimal dominating sets. In ISAAC, pages 289–298, 2012.
- [14] Mamadou Moustapha Kanté, Vincent Limouzy, Arnaud Mary, Lhouari Nourine, and Takeaki Uno. On the enumeration and counting of minimal dominating sets in interval and permutation graphs. In Leizhen Cai, Siu-Wing Cheng, and Tak Wah Lam, editors, ISAAC, volume 8283 of Lecture Notes in Computer Science, pages 339–349. Springer, 2013.
- [15] Dimitris J. Kavvadias and Elias C. Stavropoulos. An efficient algorithm for the transversal hypergraph generation. J. Graph Algorithms Appl., 9(2):239–264, 2005.
- [16] Leonid Khachiyan, Endre Boros, Konrad Borys, Khaled M. Elbassioni, and Vladimir Gurvich. Generating all vertices of a polyhedron is hard. Discrete & Computational Geometry, 39(1-3):174–190, 2008.
- [17] Leonid Khachiyan, Endre Boros, Konrad Borys, Khaled M. Elbassioni, Vladimir Gurvich, and Kazuhisa Makino. Generating cut conjunctions in graphs and related problems. Algorithmica, 51(3):239–263, 2008.
- [18] Leonid Khachiyan, Endre Boros, Khaled M. Elbassioni, and Vladimir Gurvich. An efficient implementation of a quasi-polynomial algorithm for generating hypergraph transversals and its application in joint generation. *Discrete Applied Mathematics*, 154(16):2350–2372, 2006.
- [19] Leonid Khachiyan, Endre Boros, Khaled M. Elbassioni, and Vladimir Gurvich. On enumerating minimal dicuts and strongly connected subgraphs. *Algorithmica*, 50(1):159–172, 2008.
- [20] Eugene L. Lawler, Jan Karel Lenstra, and A. H. G. Rinnooy Kan. Generating all maximal independent sets: Np-hardness and polynomial-time algorithms. SIAM J. Comput., 9(3):558–565, 1980.
- [21] Kazuhisa Makino and Takeaki Uno. New algorithms for enumerating all maximal cliques. In Torben Hagerup and Jyrki Katajainen, editors, SWAT, volume 3111 of Lecture Notes in Computer Science, pages 260–272. Springer, 2004.
- [22] Keisuke Murakami and Takeaki Uno. Efficient algorithms for dualizing large-scale hypergraphs. Discrete Applied Mathematics, 170(0):83-94, 2014.
- [23] Lhouari Nourine and Jean-Marc Petit. Extending set-based dualization: Application to pattern mining. In *ECAI*, pages IOS Press ed, Montpellier, France, 2012.
- [24] Benno Schwikowski and Ewald Speckenmeyer. On enumerating all minimal solutions of feedback problems. Discrete Applied Mathematics, 117(1-3):253–265, 2002.
- [25] Akiyoshi Shioura, Akihisa Tamura, and Takeaki Uno. An optimal algorithm for scanning all spanning trees of undirected graphs. SIAM J. Comput., 26(3):678–692, 1997.
- [26] Yann Strozecki. Enumeration Complexity and Matroid Decomposition. PhD thesis, Université Paris Diderot - Paris 7, 2010.
- [27] Ken Takata. A worst-case analysis of the sequential method to list the minimal hitting sets of a hypergraph. SIAM J. Discrete Math., 21(4):936–946, 2007.
- [28] Robert Endre Tarjan. Enumeration of the elementary circuits of a directed graph. SIAM J. Comput., 2(3):211–216, 1973.

CLERMONT-UNIVERSITÉ, UNIVERSITÉ BLAISE PASCAL, LIMOS, CNRS, FRANCE E-mail address: {mamadou.kante,limouzy,mary,nourine}@isima.fr

NATIONAL INSTITUTE OF INFORMATICS, JAPAN

E-mail address: uno@nii.jp