

SciRecSys: a Recommendation System for Scientific Publication by Discovering Keyword Relationships

Vu Le Anh^{1,2}, Hai Vo Hoang^{3*}, Hung Nghiep Tran⁴, and Jason J. Jung⁵

¹ Nguyen Tat Thanh University, Ho Chi Minh city, Vietnam

² Big IoT BK Project Team, Yeungnam University, Gyeongsan, Korea

³ Information Technology College, Ho Chi Minh city, Vietnam

⁴ University of Information Technology, Ho Chi Minh city, Vietnam

⁵ Chung-Ang University, Seoul, Korea

lavu@ntt.edu.vn, vohoanghai2@gmail.com, nghiepth@uit.edu.vn,
j2jung@gmail.com

Abstract. In this work, we propose a new approach for discovering various relationships among keywords over the scientific publications based on a Markov Chain model. It is an important problem since keywords are the basic elements for representing abstract objects such as documents, user profiles, topics and many things else. Our model is very effective since it combines four important factors in scientific publications: content, publicity, impact and randomness. Particularly, a recommendation system (called SciRecSys) has been presented to support users to efficiently find out relevant articles.

Keywords: Keyword ranking, Keyword similarity, Keyword inference, Scientific Recommendation System, Bibliographical corpus

1 Introduction

Keyword-based search engines (Google, Bing Search, and Yahoo) have emerged and dominated the Internet. The success of these search engines are based on the study of keyword relationships and keyword indexes. The task of measuring keywords' relationships is the basic operation for building the related network of abstract objects which are applied in many problems and applications, such as document clustering, synonym extraction, plagiarism detection problem, taxonomy, search engine optimization, recommendation system, etc. In this work, we focus on two problems. First, we study the rank, inference and similarity of keywords over scientific publications on assuming that the keywords belong to a *virtual ontology of keywords*. The inference relationship will help us find *parents*, *children*, the similarity relationship will help us find *siblings* of a given keyword and the rank of keywords will determine how important they are. Second, we apply these relationship in our scientific recommendation system, SciRecSys. The first problem is not easy since we have to consider four main factors:

- i- *Content factor*. The meaning of the keyword should be considered in the context of its paper. The paper itself is determined by its keywords;

* Corresponding Author: Hai Vo Hoang, Information Technology College, Ho Chi Minh, Vietnam. Phone/Fax: +84 938 642 717. Email: vohoanghai2@gmail.com.

- ii- *Publicity factor*. The hotness of a topic (or keyword) depends on how popular it is. People always find the hot topic for reading.
- iii- *Impact factor*. In the world of scientific publications the citation is a very important factor. People often follow the citations of a scientific paper for finding the necessary information;
- iv- *Randomness factor*. Randomness is very important factor in many real complex systems. Readers sometimes find something for reading quite randomly.

SciRecSys recommendation system is designed to be a search engine for scientific publications. We want to apply the rank, inference and similarity of keywords to solve three following problems: (i) Ranking papers matched to the given keyword; (ii) Recommending additional keywords related to a given keyword to help the reader navigating the corpus effectively; (iii) Suggesting papers for “*Reading more*” function in the context the reader is reading a given topic.

2 Related works

The similarity of keywords is often used as a crucial feature to reveal the relation between objects and many methods to measure it have been proposed. One baseline for similarity measures is using distance functions such as squared Euclidean distance, cosine similarity, Jaccard coefficient, Pearsons correlation coefficient, and relative entropy. Anna Huang et al. [6] has compared and analyzed the effectiveness of these measures in text clustering problem. She represent a document as an m-dimensional vector of the frequency of terms and uses a weighting scheme to reflect their importance through frequencies tf/idf . Singthongchai et al. [12] make keywords search more practical by calculating keyword similarity by combining Jaccard’s, N-Gram and Vector Space. Probabilistic models for similarity measure has been studied in language speech [4,3]. Ido Dagan et al. have proposed a bigram similarity model and used the relative entropy to compute the similarity of keywords [4]. Sung-Hyuk Cha has conducted a comprehensive survey on probability density functions for similarity measures [3]. Ontology-based methods are also exploited to measure the similarity of keywords [2,11,10]. Bollegala et al. [2] use the Wordnet database - ontology of words to measure keywords’ relatedness by extracting lexico-syntactic patterns that indicate various aspects of semantic similarity and modifying four popular co-occurrence measures, including Jaccard, Overlap (Simpson), Dice, and Pointwise mutual information (PMI). Vincent Schickel-Zuber and Boi Falting [11] present a novel similarity measure for hierarchical ontologies called Ontology Structure based Similarity (OSS) that allows similarities to be asymmetric. Snchez et al. [10] presents an ontology-based method relying on the exploitation of taxonomic features available in an ontology.

Markov Chain model which properties are studied in [7,8] is used for computing the similarity and ranking [5,1]. Fouss et al.[5] use a stochastic random-walk model to compute similarities between nodes of a graph for recommendation. Vu et al. [1] introduce an N-star model, and demonstrate it in ranking conference and journal problems. Finally, Lops et al. [9] do a thorough review on state-of-the-art and trends of content-based recommender systems.

3 Backgrounds

3.1 Basic definitions

Suppose \mathcal{K} , \mathcal{P} are the sets of keywords and papers respectively. $p \in \mathcal{P}$ is a paper and $A \in \mathcal{K}$ is a keyword. $K(p) \subseteq \mathcal{K}$ is the set of keywords belonging to p . $P(A) = \{q \in \mathcal{P} | A \in K(q)\}$ is the set of papers containing A . We assume that $K(p) \neq \emptyset \wedge P(A) \neq \emptyset$. Finally, $C(p) \subseteq \mathcal{P}$ is the set of papers cited by p . In the case p has no citing, we assume that $C(p) = \mathcal{P}$. It guarantees that $C(p) \neq \emptyset$.

A couple (\mathcal{A}, R) is called a *ranking system* if: (i) $\mathcal{A} = \{a_1, \dots, a_n\}$ is a finite set, and (ii) R is a non-negative function on \mathcal{A} (i.e., $R : \mathcal{A} \rightarrow [0, +\infty)$). A *ranking score* on \mathcal{A} can be represented as $R = (R(a_1), \dots, R(a_n))^T$. Furthermore, (\mathcal{A}, R) is *normalized* if R^T is normalized ($\|R^T\| = 1$).

Suppose A and B are two events. The *inference* and *similarity* of two events A and B are denoted by $I(A, B)$ and $S(A, B)$, respectively. They can be computed as follows:

$$I(A, B) = \frac{Pr(A \text{ and } B)}{Pr(A)} \quad S(A, B) = \frac{Pr(A \text{ and } B)}{Pr(A \text{ or } B)} \quad (1)$$

We have $S(A, B) \leq 1$, $I(A, B) \leq 1$. $S(A, B)$ is symmetric. $I(A, B) = Pr(B|A)$.

3.2 Relationships of keywords based on the occurrences

Let us introduce two normalized ranking scores R^c , R^p on set of keywords, \mathcal{K} , based on the occurrences. R^c (c stands for *counting*) is based on counting the documents containing the given keyword.

$$R^c(A) = \frac{|P(A)|}{\sum_{B \in \mathcal{K}} |P(B)|} \quad (A \in \mathcal{K}) \quad (2)$$

R^p (p stands for *probability*) is based on the probability of the occurrence of the given keyword in the papers.

$$R^p(A) = \frac{1}{|\mathcal{P}|} \sum_{p \in P(A)} \frac{1}{|K(p)|} \quad (A \in \mathcal{K}) \quad (3)$$

$\frac{1}{|\mathcal{P}|}$ is the probability of choosing a paper from the corpus. $\frac{1}{|K(p)|}$ is the probability of choosing keyword A from the paper p containing $|K(p)|$ keywords.

We propose following formulas for measuring the inference and similarity of two keywords A , B based on the occurrences:

$$I^c(A, B) = \frac{|P(A) \cap P(B)|}{|P(A)|} \quad S^c(A, B) = \frac{|P(A) \cap P(B)|}{|P(A) \cup P(B)|} \quad (A, B \in \mathcal{K}) \quad (4)$$

$P(A) \cap P(B)$ is the set of papers containing both keywords A and B . $P(A) \cup P(B)$ is the set of papers containing keywords A or B .

4 Relationships of keywords based on graph of keywords

4.1 Markov Chain model of the reading process

We propose a Markov Chain model to simulate the reading process which can combine four factors: content, publicity, impact and randomness. We assume that the reader reads

a topic (keyword) A in some paper p at any time ($A \in K(p)$). $S = \{(A, p) \in \mathcal{K} \times \mathcal{P} | A \in K(p)\}$ is the set of states. From current state $\theta = (A, p)$, the reader will move to new state $\xi = (B, q) \in S$ with the conditional probability $Pr(\theta \rightarrow \xi)$ by applying 4 following actions:

- A_1 . *Same paper - some topic*. The reader is interested in current paper, and choose randomly a topic in the same paper with the probability equal to α_1 . Thus, $p = q$.

$$Pr(\theta \rightarrow_{A_1} \xi) = if(p = q, \frac{\alpha_1}{|K(p)|}, 0) \quad (5)$$

- A_2 . *Same topic - some paper*. The reader is interested in current topic, and choose randomly another paper which have the same topic with the probability equal to α_2 . Thus, $A = B$.

$$Pr(\theta \rightarrow_{A_2} \xi) = if(A = B, \frac{\alpha_2}{|P(A)|}, 0) \quad (6)$$

- A_3 . *Some topic - cited paper*. The reader is interested in some cited paper with the probability equal to α_3 . First, he choose randomly a cited paper and then choose randomly a new topic belonging to the chosen paper. Thus, $q \in C(p)$.

$$Pr(\theta \rightarrow_{A_3} \xi) = if(q \in C(p), \frac{\alpha_3}{|C(p)||K(q)|}, 0) \quad (7)$$

- A_4 . *Some paper - some topic*. The reader stop reading the current paper and choose randomly a new paper with the probability equal to α_4 .

$$Pr(\theta \rightarrow_{A_4} \xi) = \frac{\alpha_4}{|\mathcal{P}||K(q)|} \quad (8)$$

$\alpha_i > 0$ are constants and $\sum_{i=1}^4 \alpha_i = 1$. From the assumptions, we have:

$$Pr(\theta \rightarrow \xi) = \sum_{i=1}^4 Pr(\theta \rightarrow_{A_i} \xi)$$

The necessary condition of the Markov Chain model is that total of the output conditional probability from any state is equal to 1. Here is the formula of the conditions:

$$O(\theta) = \sum_{\xi} Pr(\theta \rightarrow \xi) = 1$$

Our readers can check it by apply the formula 5, 6, 7 and 8. The probability of a reader in state $\theta = (A, p)$ is denoted by $Pr(\theta)$. We have:

$$Pr(\theta) = \sum_{\xi \in S} Pr(\xi) \times Pr(\xi \rightarrow \theta) \quad (9)$$

Proposition 1. *There exists a unique stationary score $\{Pr(\theta)\}_{\theta \in S}$ satisfying (9).*

Proof. Since a state θ can jump to any state (and itself too) by apply action A_4 , the Markov Chain is irreducible and aperiodic (see more [7,8]). The Perron-Frobenius theorem [7] states that there exists a unique stationary score $\{Pr(\theta)\}_{\theta \in S}$.

$\{Pr(\theta)\}_{\theta \in S}$ is determined by following algorithm:

Algorithm : Computing Stationary probability $\{Pr(\theta)\}_{\theta \in S}$

1. **begin**

```

2.  $k = 0$ 
3. Foreach  $\theta \in \mathcal{S}$  do  $Pr(\theta)^{(0)} = \frac{1}{|\mathcal{S}|}$ 
4. repeat
5.    $k = k + 1$   $stop = true$ 
6.   Foreach  $\theta \in \mathcal{S}$  do
7.      $Pr(\theta)^{(k)} = 0$ 
8.     Foreach  $\xi \in \mathcal{S}$  do  $Pr(\theta)^{(k)} += Pr(\xi)^{(k-1)} Pr(\xi \rightarrow \theta)$ 
9.     if  $|Pr(\theta)^{(k)} - Pr(\theta)^{(k-1)}| > \epsilon$  then  $stop = false$ 
10.  until  $stop$ 
11. Foreach  $\theta \in \mathcal{S}$  do  $Pr(\theta) = Pr^{(k)}(\theta)$ 
12. end

```

4.2 Ranking, Inference and Similarity of keywords

The rank score of keyword A based on the transition graph, $R^g(A)$ (g stands for *graph*), is equal to the probability of user reads keyword A . We have:

$$R^g(A) = \sum_{p \in K(A)} Pr(\theta) \quad (\theta = (A, p) \in S) \quad (10)$$

Let n_0 be a positive integer. For each sequence $s = \theta_1 \theta_2 \dots \theta_{n_0} \in \mathcal{S}^{n_0}$, let $Pr(s)$ is the probability of s occurs in \mathcal{S}^{n_0} generated by the Markov Chain model. $F \subseteq \mathcal{S}^{n_0}$, we denote $Pr(F) = \sum_{s \in F} Pr(s)$. For each keyword A , let

$$P^g(A) = \{s = \theta_1 \theta_2 \dots \theta_{n_0} \in \mathcal{S}^{n_0} | \exists i \in \{1, 2, \dots, n_0\}, p \in \mathcal{P} : \theta_i = (A, p)\}$$

The formulas for measuring the inference and similarity of two keywords A, B based on the Markov Chain model:

$$I^g(A, B) = \frac{Pr(P^g(A) \cap P^g(B))}{Pr(P^g(A))} \quad S^g(A, B) = \frac{Pr(P^g(A) \cap P^g(B))}{Pr(P^g(A) \cup P^g(B))} \quad (11)$$

We will apply Monte Carlo method for Markov Chain to compute the formulas (11). First, we generate a large enough number of n_0 -length sequences of states by our Markov Chain model. Then we apply counting techniques for approximating the probabilities and computing the formulas.

5 SciRecSys - Recommendation System

In this paper, we want to present three scenarios by using SciRecSys.

Universal ranking vs. keyword based ranking The reader chooses a keyword A to find some related papers belonging to $P(A)$. Question is ‘‘What is the order for sorting $P(A)$?’’. There are two ways for ranking: (i) All results are sorted by only one *universal ranking*, $\{R_u^g(p)\}_{p \in \mathcal{P}}$ or (ii) The order of the results depend on A with the *keyword based ranking*, $\{R_A^g(p)\}_{p \in P(A)}$. We propose $R_u^g(p)$ is equal to the probability of user reads p . Hence,

$$R_u^g(p) = \sum_{A \in K(p), \theta = (A, p)} Pr(\theta) \quad (12)$$

We propose $R_A^g(p)$ is equal to the probability of state (A, p) . Hence,

$$R_A^g(p) = Pr(\theta) \quad (\theta = (A, p), p \in P(A)) \quad (13)$$

Recommending keywords The user is in keyword (topic) A . What are the next recommended topics for following situations: (i) similar topics, $Sibling(A)$? (ii) more detail topics, $Child(A)$? (iii) more general topics, $Parent(A)$? Let m_c , m_p , m_s be the parameters of the system. We denote: $Child(A) = \{B \in \mathcal{K} | I^g(B, A) > m_c\}$; $Parent(A) = \{B \in \mathcal{K} | I^g(A, B) > m_f\}$; $Sibling(A) = \{B \in \mathcal{K} | S^g(A, B) > m_b\}$. We remind our readers that keyword A may have many parents or his parent can be his sibling or his child.

Recommending papers The user is in paper p . The user can choose the most interesting keyword $A \in K(p)$ to read more. What are the next recommended papers for him? The system will request the user to refine recommended papers by choosing a keyword A and then give the recommendation based on the conditional probability change from state $\theta = (A, p)$ to the papers by applying actions A_2 and A_3 . Suppose:

$$R_\theta^g(q) = \sum_{B \in K(q), \xi = (B, q)} (Pr(\theta \rightarrow_{A_2} \xi) + Pr(\theta \rightarrow_{A_3} \xi)) \quad (14)$$

Finally, the recommended papers are chosen based on R_θ^g ranking function.

6 Experiments

We collect data from DBLP⁶ and Microsoft Academic Search⁷ (MAS) to conduct experiments. We choose three datasets for experiments from three different domains: (i) D_1 is the publications of ICRA - International Conference on Robotics and Automation; (ii) D_2 is the publications of ICDE - International Conference on Data Engineering (iii) D_3 is the publications of GI-Jahrestagung - Germany Conference in Computer Science. ICRA and ICDE conferences are one of the most famous and biggest ones in their area. They are chosen for rich publications and citations. GI-Jahrestagung is a smaller conference but its topic is quite various.

Table 1: Experiment datasets

Datasets	Paper No.	Keyword No.	Citation No.	State No.
ICRA	9291	4676	125610	28736
ICDE	3254	2755	99492	12365
GI-Jahrestagung	1335	1640	5	2932

6.1 Experiments for rank scores

We do the experiments for three different ranking scores R^c , R^p and R^g . The values on $\{\alpha_i\}_{i=1}^4$ are chosen for testing different contexts. The rank scores are scaled with the same rate for the convenience. For each two ranking scores i and j , we do examine: (i) the Spearman's rank correlation coefficient (denote ρ_{ij}) for monotone checking; (ii) the differences of values: $\Delta_{ij}(A) = R^i(A) - R^j(A)$, $\% \Delta_{ij}(A) = \frac{\Delta_{ij}(A)}{R^j(A)}$. Here are some interesting observations:

⁶ <http://dblp.uni-trier.de> accessed on December 2013

⁷ <http://academic.research.microsoft.com/> accessed on December 2013

- *The rank scores are monotone but quite different to each others.* It comes from that ρ_{ij} are close to 1 and the average values of $\% \Delta_{ij}$ are very high. For instance with dataset D_1 , we have: $\rho_{cg} = 0.97$, $\rho_{pg} = 0.99$, $\rho_{cp} = 0.97$. The average of $|\% \Delta_{cg}|$, $|\% \Delta_{pg}|$, $|\% \Delta_{cp}|$ are 47.13%, 30.06% and 51.76% respectively.

 Table 2: Top 5 keywords most different using R^g vs. R^c on D_1 .

Keyword	R^c	R^p	R^g	Δ_{cg}	$\Delta_{cg}\%$
Mobile Robot	924	1082	1221	297	32.16
Robot Hand	140	230	276	136	97.40
Path Planning	313	389	442	129	41.19
Motion Planning	393	483	511	118	29.96
Visual servoing	248	316	350	102	41.02

(a) Top 5 increasing values

Keyword	R^c	R^p	R^g	Δ_{cg}	$\Delta_{cg}\%$
Indexing Terms	419	228	251	-168	40.19
Satisfiability	109	66	83	-26	23.77
Real Time	422	366	397	-25	6.02
Extended Kalman Filter	70	37	45	-25	35.04
Computer Vision	58	37	35	-23	39.11

(b) Top 5 decreasing values

- R^g reflects how hot a keyword is. Let us see the result shown in Tab. 2. All *increasing* keywords are hot topics now and all *decreasing* keywords seem not being currently hot topics for conferences on robotics and automation. Let us see the example of two keywords *Robot Hand* and *Satisfiability*. They have quite the same R^c values but R^g values are four times difference. The explanation is that the hot topics have rich citations which increase the R^g values.
- R^p is more acceptable to R^g than R^c . Let us see Tab. 2 again. For top 5 *increasing* keywords, $R^c < R^p < R^g$. For top 5 *decrease* keywords, $R^p < R^g < R^c$. The explanation is that the probability occurrences reflect the world more exactly than the counting but they still neglect the latent information like the citation graphs in the data corpus.

6.2 Experiments for Inference and Similarity

We do experiments to compare (I^c, S^c) vs. (I^g, S^g) . For both inference and similarity, we find out some amazing results:

- I^g & S^g exploits the citation network and the results are domain dependent. Our approach seems to give “hot” results. Let us see Tab. 3(a), which shows similar keywords to *Real Time* over dataset D_1 . S^g generates “hot” keyword *Humanoid Robot* instead of *Indexing Terms*. This phenomenon also occurs in dataset D_2 . We assume the cause is I^g & S^g exploit citation network and the paper–keyword relationships to generate more attractive keywords. Additionally, similar keywords to *Real Time* are quite different between two datasets D_1 and D_2 , so we can say that these methods are domain dependent.
- I^g & S^g could help overcome the missing co-occurrence problem. The traditional methods based on occurrences of keywords could not work when there is no co-occurrence in the dataset. For instance, Tab. 4(b) shows that S^c generates only one similar keyword to *Sensor Network* in small dataset D_3 . In contrast, S^g could help us find more acceptable similar keywords.

We also find out some interesting observations about inference particularly:

- *The inference between two keywords is asymmetric and I^g exploits the citation network to generate a clear inference.*

Table 3: Top 5 similar keywords of “*Real Time*” using S^c vs. S^g .

D_1	S^c	S^g	D_2	S^c	S^g
1	Mobile Robot	Path Planning	1	Stream Processing	Data Stream
2	Indexing Terms	Mobile Robot	2	Data Stream	Stream Processing
3	Path Planning	Motion Planning	3	Database System	Database System
4	Obstacle Avoidance	Obstacle Avoidance	4	Sensor Network	Object Oriented
5	Motion Planning	Humanoid Robot	5	Query Processing	Data Model

(a) D_1 in robotics domain, $|K| = 4676$ (b) D_2 in database domain, $|K| = 2755$

Table 4: Top 5 similar keywords of “*Sensor Network*” using S^c vs. S^g .

D_2	S^c	S^g	D_3	S^c	S^g
1	Query Processing	Query Processing	1	Distributed System	Mobile Device
2	Data Management	Database System	2	-	Web Service
3	Real Time	Data Management	3	-	Data Warehouse
4	Data Stream	Data Stream	4	-	Open Source
5	Satisfiability	Query Evaluation	5	-	Middleware

(a) Top 5 on D_2 , $|K| = 2755$. (b) Top 5 on D_3 , $|K| = 1640$.

Unlike similarity between two keywords, inference is asymmetric, i.e., the inference between A and B differs from the one between B and A. Let us see Tab. 5, the inference from *Robot Hand* and *Robot Arm* are almost different. More interestingly, *Robot Hand* could infer *Robot Arm* but *Robot Arm* does not infer *Robot Hand*, so there is a flow of inference here. Further examination shows that, *High Speed* is repeated at top 1 on two inference lists generated by I^c . Whereas, *High Speed* only appears on I^g 's *Robot Arm* inference list, not on *Robot Hand* inference list. So, we have a clear inference flow from *Robot Hand* to *Robot Arm* then to *High Speed* with I^g , not with I^c . To explain this difference, we notice that when we infer from *Robot Hand*, *High Speed* shares more common publications than *Robot Arm*, 4 vs. 2. However, *Robot Hand* has more citations from *Robot Arm* than *High Speed*, 9 vs. 5. So we assume that our approach exploits the citation network, which is an asymmetric structure, to generate a clearer inference.

Table 5: Top 5 inference keywords over D_1 using I^c vs. I^g .

D_1	B from $I^c(A, B)$	B from $I^g(A, B)$	D_1	B from $I^c(A, B)$	B from $I^g(A, B)$
1	High Speed	Robot Arm	1	High Speed	High Speed
2	Control System	Force Control	2	Obstacle Avoidance	Parallel Manipulator
3	Robot Arm	Three Dimensional	3	Control System	Three Dimensional
4	Force Control	Autonomous Robot	4	Configuration Space	Control System
5	Parallel Manipulator	Parallel Manipulator	5	Parallel Manipulator	Autonomous Robot

(a) $A = \textit{Robot Hand}$. (b) $A = \textit{Robot Arm}$.

6.3 SciRecSys Recommendation System

We compare universal ranking scores $R_u^g(p)$ and local ranking score $R_A^g(p)$ and conduct experimental models for recommending keywords. We get some interesting results:

- *Universal ranking prefers most popular papers, whereas local ranking prefers papers being not only popular but also focused on a small set of topics.*

Let us see Tab. 6 (a). Top recommended papers returned by *Universal ranking* shows a large number of citing/cited papers. Whereas, top recommended papers returned by *Local ranking* have less citing/cited papers but their keywords are more specific. The average number of keywords in each recommended papers of *Local ranking* and *Universal ranking* are 2.25 and 6.75, respectively, except the common

top ranked paper with $ID = 395393$. These numbers in D_2 are 3.00 and 10.12. We notice that the average number of keywords in one paper is around 2 and 3 for those two datasets.

Table 6: Top 5 recommended papers for the keyword "Real Time" using R_u^g vs. R_A^g ($|K|$: keyword no., $|C_i|$: citing no., and $|C_e|$: cited no.).

D_1 Local Ranking $R_A^g(P)$					Universal Ranking R_u^g				
No.	PaperID	$ K $	$ C_i $	$ C_e $	PaperID	$ K $	$ C_i $	$ C_e $	
1	395393	10	23	336	395393	10	23	336	
2	1749067	2	11	21	1653515	9	19	272	
3	1867302	1	0	3	278613	6	35	141	
4	1791141	2	4	14	1662450	4	23	171	
5	1662450	4	23	171	1451499	8	13	105	

(a) Top 5 on D_1 , $|P(\text{"Real Time"})| = 422$.

D_2 Local Ranking $R_A^g(P)$					Universal Ranking R_u^g				
No.	PaperID	$ K $	$ C_i $	$ C_e $	PaperID	$ K $	$ C_i $	$ C_e $	
1	2158744	1	12	26	2848	8	19	65	
2	1209177	2	34	1	3045031	12	22	12	
3	1142083	2	10	0	832819	9	32	69	
4	2848	8	19	65	3396132	17	6	0	
5	1340498	2	18	1	308381	10	20	22	

(b) Top 5 on D_2 , $|P(\text{"Real Time"})| = 49$.

- *Keywords recommended with the inference relationship depend on both latent information and data domain.*

Let us see Tab. 7(a) for ICDE, conference specialized in database. Three inference methods *Children*, *Sibling* and *Parent* generate three lists of specialized keywords in database domain. On the other hand, for GI-Jahrestagung, small conference with quite various topics in Tab. 7(b), the recommendation lists are quite diversity. We also notice that D_2 have much more citations information than D_3 .

- *The missing co-occurrence problem can be overcome by using inference relationship.*

As mention above, our approach using stationary probability graph to generate new states follow Markov Chain Monte Carlo method. This helps to create new states that have the co-occurrence of keywords. So, we agree that the recommended lists computed by inference relationship showed in Table 7 are acceptable.

Table 7: Top 5 recommended keywords for the keyword "Sensor Network".

D_2	Children	Sibling	Parent
1	Query Processing	Query Processing	Data Management
2	Database System	Database System	Query Processing
3	Indexation	Data Management	Data Stream
4	Data Stream	Data Stream	Query Evaluation
5	Data Management	Query Evaluation	Multi Dimensional

(a) Top 5 on D_2 , $|K| = 2755$.

D_3	Children	Sibling	Parent
1	Open Source	Mobile Device	Mobile Device
2	Mobile Device	Web Service	Data Warehouse
3	Web Service	Data Warehouse	Self Organization
4	Middleware	Open Source	Distributed System
5	Data Warehouse	Middleware	P2P

(b) Top 5 on D_3 , $|K| = 1640$.

7 Conclusion and future works

We have introduced and studied a new approach on discovering various relationships among keywords from scientific publications. The proposed Markov Chain model combined four main factors of the problem: content, publicity, impact and randomness. The stationary probability of the states in the model helps us ranking and measuring the inference and similarity of keywords.

We have proposed SciRecSys recommendation system for navigating the scientific publications efficiently. By applying the relationships among keywords, we have suggested the solutions for the ranking results of a given keyword, related keywords and recommended papers. The experiments have shown that our methods can reflect how

hot keyword is and overcome the missing co-occurrence problem. Moreover, our approach can exploit the latent information of citation network effectively.

As future work, we are planning to *i*) do experiment on big dataset to upgrade the quality of our ranking and measuring system, *ii*) study how to combine inference relationship by stationary probability graph with a given ranking systems, *iii*) investigate the time series in the keyword relationship and the trend prediction problem, and *iv*) apply model of recommendation systems in various problems, e.g., product recommendation, event recommendation, and so on.

References

1. Anh, V.L., Hoang, H.V., Trung, K.L., Trung, H.L., Jung, J.J.: A general model for mutual ranking systems. In: Nguyen, N.T., Attachoo, B., Trawinski, B., Somboonviwat, K. (eds.) Proceedings of the 6th Asian Conference on Intelligent Information and Database Systems (ACIIDS 2014), Bangkok, Thailand, April 7-9. Lecture Notes in Computer Science, vol. 8397, pp. 211–220. Springer (2014)
2. Bollegala, D., Matsuo, Y., Ishizuka, M.: Measuring semantic similarity between words using web search engines. In: Williamson, C.L., Zurko, M.E., Patel-Schneider, P.F., Shenoy, P.J. (eds.) Proceedings of the 16th International Conference on World Wide Web (WWW 2007), Banff, Alberta, Canada, May 8-12. pp. 757–766. ACM (2007)
3. Cha, S.H.: Comprehensive survey on distance/similarity measures between probability density functions. International Journal of Mathematical Models and Methods in Applied Sciences 1(4), 300–307 (2007)
4. Dagan, I., Lee, L., Pereira, F.C.N.: Similarity-based models of word cooccurrence probabilities. Machine Learning 34(1-3), 43–69 (1999)
5. Fouss, F., Pirotte, A., Renders, J.M., Saerens, M.: Random-walk computation of similarities between nodes of a graph with application to collaborative recommendation. IEEE Transactions on Knowledge and Data Engineering 19(3), 355–369 (2007)
6. Huang, A.: Similarity measures for text document clustering. In: Proceedings of 6th In New Zealand Computer Science Research Student Conference, Christchurch, New Zealand. pp. 49–56 (2008)
7. Keener, J.P.: The perron-frobenius theorem and the ranking of football teams. SIAM review 35(1), 80–93 (1993)
8. Kien, L.T., Hieu, L.T., Hung, T.L., Vu, L.A.: Mpagerank: The stability of web graph. Vietnam Journal of Mathematics 37(4), 475–489 (2009)
9. Lops, P., de Gemmis, M., Semeraro, G.: Content-based recommender systems: State of the art and trends. In: Ricci, F., Rokach, L., Shapira, B., Kantor, P. (eds.) Recommender Systems Handbook, chap. 3, pp. 73–105. Springer (2011)
10. Sánchez, D., Batet, M., Isern, D., Valls, A.: Ontology-based semantic similarity: A new feature-based approach. Expert Systems with Applications 39(9), 7718–7728 (2012)
11. Schickel-Zuber, V., Faltings, B.: Oss: A semantic similarity function based on hierarchical ontologies. In: Veloso, M.M. (ed.) Proceedings of the 20th International Joint Conference on Artificial Intelligence (IJCAI 2007), Hyderabad, India, January 6-12. pp. 551–556 (2007)
12. Singthongchai, J., Niwattanakul, S.: A method for measuring keywords similarity by applying jaccard's, n-gram and vector space. Lecture Notes on Information Theory 1(4), 159–164 (2013)