

On the security of the Blockchain Bix Protocol and Certificates

Riccardo Longo, Federico Pintore, Giancarlo Rinaldo,
Massimiliano Sala*

University of Trento

July 29, 2016

Abstract

The BIX protocol is a blockchain-based protocol that allows distribution of certificates linking a subject with his public key, hence providing a service similar to that of a PKI but without the need of a CA. In this paper we analyze the security of the BIX protocol in a formal way, in four steps. First, we identify formal security assumptions which are well-suited to this protocol. Second, we present some attack scenarios against the BIX protocol. Third, we provide a formal security proof that some of these attacks are not feasible under our previously established assumptions. Finally, we show how another attack may be carried on.

Introduction

Blockchain is an emerging technology that is gaining widespread adoption to solve a myriad of problems where decentralized network computations can substitute a centralized approach. Indeed, centralized computations, albeit efficient, are possible only if there is a Trusted Third Party (TTP) that everybody trusts and nowadays this is sometimes felt as a limitation.

The general idea behind blockchain technology is that blocks containing information are created by nodes in the network, and that these blocks are both public and cryptographically linked, so that an attacker should be unable to modify them without the users noting the tampering. Also, the information contained in any block comes from the users and any user signs his own information cryptographically. Some examples of blockchain applications can be found in [12], [1], [4].

*Mail: riccardo.longo@unitn.it, federico.pintore@unitn.it, giancarlo.rinaldo@unitn.it, maxsalacodes@gmail.com

A very sensitive security aspect which is usually kept centralized is the issuing of digital certificates, which form the core of a Public Key Environment (PKI). A certificate contains at least a cryptographic public key and it is digitally signed by a TTP. An example is given by X.509 certificates [2], mostly containing RSA public keys, which are widely used in the Internet for establishing secure transactions (e.g., an e-payment with an e-commerce site like Amazon). Since every user of a PKI must trust the Certification Authority (CA), which acts as a TTP, the identity of a web site is checked by verifying the CA's signature via the CA's public key. We note that the identity checking is often performed via a hierarchy of CA's.

In [6] Muftic presents a system ("BIX") for the issuing of certificates that is based on blockchain technology and thus avoids the need of a TTP. We find BIX of interest and our paper aims at analyzing BIX from the point of view of security, as follows:

- In Section 1 we summarize some known preliminaries, especially on digital signatures and formal proofs of security, with focus on some notions of their security that we need for our results in Section 3 e 4;
- In Section 2 we provide a sketch of Muftic's scheme, highlighting its characteristics that are instrumental in its security.
- In Section 3 we present our first security proof. Here we suppose that an attacker tries to trick the protocol by attaching a forged block to a preexisting chain, without interacting properly with the last user.
- In Section 4 we present our second security proof. Here we suppose that an attacker tries to modify an existing blockchain.
- In Section 5 we show an attack on the BIX protocol which can alter an existing blockchain when two members of the BIX community collude.
- Finally, we draw some conclusions and suggest further work, possibly improving the BIX protocol.

1 Preliminaries

1.1 Formal Proofs of Security

In cryptography the security of a scheme relies on the hardness of a particular mathematical problem. So, in a formal proof of security the goal is to model the possible attacks on the scheme and prove that a successful breach implies the solution of a hard, well-known mathematical problem. Some security parameters may be chosen in such a way that the problem guaranteeing the security becomes almost impossible to solve (in a reasonable time), and thus the scheme becomes impenetrable.

In a formal proof of security of an encryption scheme there are two parties involved: a *Challenger* \mathcal{C} that runs the algorithms of the scheme and an *Adversary* \mathcal{A} that tries to break the scheme making queries to \mathcal{C} . In a *query* to \mathcal{C} , depending on the security model, \mathcal{A} may request private keys, the encryption of specific plaintexts, the decryption of specific ciphertexts and so on. The goal of \mathcal{A} also depends on the security model, for example it may be to recover a key, to forge a digital signature, to invert a hash function.

The scheme is supposed secure if an *Assumption* holds on the related mathematical problem. Generally an *Assumption* is that there is no *polynomial-time* algorithm that solves a problem \mathcal{P} with *non-negligible* probability. For example see the problem in the following subsection on hash functions. The security proofs follows the following general path. Suppose there is an Adversary \mathcal{A} that breaks the scheme with non-negligible probability p_1 . A *Simulator* \mathcal{S} is built such that if \mathcal{A} breaks the scheme then \mathcal{S} solves \mathcal{P} . So, given an instance of \mathcal{P} , \mathcal{S} runs a challenger \mathcal{C} that interacts with \mathcal{A} , simulating the scheme correctly with non-negligible probability p_2 . Thus \mathcal{S} solves \mathcal{P} with non-negligible probability, which is usually $p_1 p_2$, contradicting the Assumption.

To summarize, a formal proof of security is a *reduction* from the problem *attack the scheme* to the problem *solve* \mathcal{P} . Typically \mathcal{P} is a well-studied problem so the assumption on its insolvability is accepted by the academic community.

1.2 Hash Functions

Commonly, the messages to be signed, seen as binary strings, are compressed in fixed-length binary string via a cryptographic hash function. A hash function H can be idealized as function whose set of inputs is the set of all possible binary strings, denoted by $(\mathbb{F}_2)^*$, while its set of possible outputs is the set of all binary strings of given length (called *digest*). Real-life hash functions have a *finite* input set, but it is so large that can be thought of as infinite. For example, the hash functions used in the Bitcoin protocol are SHA256 ([7]), enjoying a digest length of 256 bits and with input string up to 2^{64} -bit long, and RIPEMD-160, with 160-bit digests.

Cryptographic hash functions can need several security assumptions, however for the goals of this paper the four following definitions are sufficient.

Definition 1.1 (Collision Problem for a Class of Inputs). *Let $r \geq 1$. Let $h : (\mathbb{F}_2)^* \rightarrow (\mathbb{F}_2)^r$ be a hash function, and $L \subseteq (\mathbb{F}_2)^l$ be a class of inputs. The collision problem for h and L consists in finding two different inputs $m_1, m_2 \in L$, with $m_1 \neq m_2$, such that $h(m_1) = h(m_2)$.*

Definition 1.2 (Collision Resistance of Hash Functions). *Let h be a hash function. We say that h is collision resistant for a class of inputs L if there is no polynomial-time algorithm $\mathcal{B}(h, L) \rightarrow \{m_1, m_2\}$ that solves the Collision Problem 1.1 for h and L with non-negligible probability. The complexity parameter is r .*

1.3 Digital Signatures and ECDSA

To validate an action having a legal value we are usually requested to produce our handwritten signature. Assuming that nobody is able to forge a signature while anybody can verify its validity, the signature is used to certify the correspondence of the identities of who is taking the action and in the name of whom the action is being taken. In the digital world, handwritten signatures are substituted by *digital signatures* that satisfy the same conditions seen above. With the name *Digital Signature Scheme* we refer to any asymmetric cryptographic scheme for producing and verifying digital signatures. For us, a Digital Signature Scheme consists of three algorithms:

- *Key Generation* - $\text{KeyGen}(\kappa) \rightarrow (\text{SK}, \text{PK})$: given a security parameter κ generates a public key PK, that is published, and a secret key SK.
- *Signing* - $\text{Sign}(m, \text{SK}) \rightarrow s$: given a message m and the secret key SK, computes a digital signature s of m .
- *Verifying* - $\text{Ver}(m, s, \text{PK}) \rightarrow r$: given a message m , a signature s and the public key PK, it outputs the result $r \in \{\text{True}, \text{False}\}$ that says whether or not s is a valid signature of m computed by the secret key corresponding to PK.

The previous algorithms may require a source of random bits to operate securely.

We will measure the security of a Digital Signature Scheme by the difficulty of forging a signature in the following scheme (which results in an existential forgery):

Definition 1.3 (Digital Signature Security Game). *Let DSS be a Digital Signature Scheme. Its security game for an adversary \mathcal{A} , proceeds as follows:*

Setup. *The challenger runs the KeyGen algorithm, and gives to the adversary the public key PK.*

Query. *The adversary issues signature queries for some messages m_i , the challenger answers giving $s_i = \text{Sign}(m_i, \text{SK})$.*

Challenge. *The adversary is able to identify a message m such that $m \neq m_i \forall i$, and tries to compute s such that $\text{Ver}(m, s, \text{PK}) = \text{True}$. If \mathcal{A} manages to do so, she wins.*

Definition 1.4 (Security of a Digital Signature Scheme). *A Digital Signature Scheme DSS is said secure if there is no polynomial-time algorithm \mathcal{A} (w.r.t. κ) that wins the Digital Signature Security Game 1.3 with non-negligible probability.*

Ideally, a Digital Signature Scheme is designed in such a way that forging a signature in the scheme is equivalent to solving a hard mathematical problem. Although this equivalence is usually assumed but not proved, we say that the Digital Signature Scheme is based on that mathematical problem. Several Digital Signatures Schemes (e.g. [3]), are based on the discrete logarithm problem

(although other approaches exist, see e.g. [10], [11]). Among them, the Elliptic Curve Digital Signature Algorithm (ECDSA), which uses elliptic curves, is widespread. To the sake of easy reference we recall briefly how ECDSA is designed ([5]).

Domain Parameters. An elliptic curve \mathbb{E} defined over a finite field \mathbb{F}_q is fixed together with a rational point $P \in \mathbb{E}(\mathbb{F}_q)$ having order n and a cryptographic hash function h [9]. Let \mathcal{O} be the point at infinity of \mathbb{E} .

Key Generation. Any user A selects a random integer d in the interval $[1, n - 1]$. Then his *public key* is $Q = dP$ while d is his *private key*.

Signing. To sign a message m (a binary string), a user A with key pair (Q, d) selects a random integer k in the interval $[1, n - 1]$ and accepts it if it is relatively prime to n . Then A computes $(x_1, y_1) = kP$ and converts x_1 in an integer \bar{x}_1 . In the unlikely event that $r = \bar{x}_1 \pmod{n}$ is 0, then he has to extract another random integer k . Otherwise, he proceeds to hash the message and to transform the digest $h(m)$ in a non-negative integer e using the standard conversion of the binary representation. The A computes the value $s = k^{-1}(e + dr) \pmod{n}$. In the unlikely event that $s = 0$, the value of k must be randomly selected again, else the pair (r, s) is output as the A's signature for the message m .

Verifying. To verify the signature (r, s) of the public key Q for the message m a user B proceeds as follows: she checks if r and s are integers contained in the interval $[1, n - 1]$; she computes the hash of the message $h(m)$ and converts it to a non-negative integer e . She then computes the point of the elliptic curve $(x, y) = (es^{-1} \pmod{n})P + (rs^{-1} \pmod{n})Q$. If $Q = \mathcal{O}$, then B rejects the signature; otherwise she converts x into an integer \bar{x} and accepts the signature if and only if $(\bar{x} \pmod{n}) = r$.

We observe that if the signature (r, s) of the message m was actually produced by the private key d , then $s = k^{-1}(e + dr) \pmod{n}$ and so:

$$k = s^{-1}(e + dr) = es^{-1} + drs^{-1} \pmod{n}$$

and

$$kP = (x_1, y_1) = (es^{-1} + drs^{-1} \pmod{n})P.$$

Clearly, if an attacker is able to solve the DLOG on \mathbb{E} , then she can break the corresponding ECDSA. The converse is much less obvious. In [8], the authors provide convincing evidence that the unforgeability of several discrete-log based signatures cannot be equivalent to the discrete log problem in the standard model. Their impossibility proofs apply to many discrete-log -based signatures like ElGamal signatures and their extensions, DSA, ECDSA and KCDSA as well as standard generalizations of these. However, their work does not explicitly lead to actual attacks. Assuming that breaking the DLOG is the most efficient attack on ECDSA, then nowadays recommended key lengths start from 160 bits, with 256 being that of the signature employed in the Bitcoin blockchain.

2 A description of BIX certificates

In this section we describe the BIX certificates, the structure containing them, called the BIX Certification Ledger (BCL), and the BIX-protocol. The BCL collects all the BIX certificates filling a double-linked list, in which every certificate is linked to the previous and the next. To simplify our notation we define the BCL as a "chain of certificates", CC, of n certificates, that we may consider as a sequence:

$$CC : c_0, \dots, c_{n-1}.$$

Header (H_i)		
Sequence number Version, Date.		
Issuer (S_{i-1})	Subject (S_i)	Next Subject (S_{i+1})
Bix ID of S_{i-1}	Bix ID of S_i	Bix ID of S_{i+1}
Public key (PK_{i-1})	Public key (PK_i)	Public key (PK_{i+1})
Issuer Signature	Subject Signature	Next Subject Signature
Backward cross-signature		
Signature of $(H_i h(S_{i-1}) h(S_i))$ by SK_{i-1}		
Signature of $(H_i h(S_{i-1}) h(S_i))$ by SK_i		
Forward cross-signature		
Signature of $(H_i h(S_i) h(S_{i+1}))$ by SK_i		
Signature of $(H_i h(S_i) h(S_{i+1}))$ by SK_{i+1}		

Remark 2.1. *The owner of the certificate c_i has a double role:*

user *the owner certifies his identity by c_i ;*

issuer *the owner provides the certificate c_{i+1} to the next user.*

In this way there is no need of a CA (Certification Authority).

Let $\lambda(CC) = n$, that is, λ is a function returning the length of a chain. We will have n users, each having a pair private-key/public key, that we denote with SK_i and PK_i . Certificate c_0 is called the **root certificate** and certificate c_{n-1} is called the **tail certificate**.

In this paper, a certificate c_i for $i = 1, \dots, n - 2$ is defined by the following fields (and subfields) (which are necessary for our proofs of security), while the complete list can be found in [6]. Root and tail certificates are described later on.

Header (H_i)

Sequence number i , the identification number of the certificate that is also the position with respect to certificates of other BIX members.

Subject (S_i) The **Subject** contains two subfields that identify the i -th user (S_i).

Subject BIX ID This is the unique global identifier of the user who owns the certificate.

In particular, all BIX ID's contained in the **Subject** fields of a valid chain are distinct.

Public key The cryptographic public key of the owner of the certificate PK_i .

Subject signature It contains the signature over the Subject attributes via the private key SK_i associated to PK_i .

Issuer (S_{i-1}) The **Issuer** field enjoys the same attribute structure of the **Subject** field, but it identifies the BIX member who certified S_i , i.e., it contains the **Subject** attributes of c_{i-1} , which identifies S_{i-1} (the previous member in the BCI).

Issuer signature This field contains the signature over the Issuer attributes created by the Issuer, that is, performed via the private key SK_{i-1} associated to PK_{i-1} .

Backward cross-signature The **Backward_Cross_Signature** contains two signatures, one created by the Issuer S_{i-1} and the other created by the Subject S_i , over the same message: the concatenation of the Header H_i , the hash of the Issuer $h(S_{i-1})$ and the hash of the Subject $h(S_i)$. Note that this field guarantees validity of the Header and binding between the Subject and the Issuer.

Next Subject (S_{i+1}) The **Next_Subject** field enjoys the same attribute structure of the **Subject** field, but it identifies the BIX member who is certified by S_i , i.e., it contains the **Subject** attributes of c_{i+1} , which identifies S_{i+1} (the next member in the BCI).

Next Subject signature This is the same field as Subject signature, except it is created by the Issuer over the Next Subject data, that is, performed via the private key SK_{i+1} associated to PK_{i+1} .

Forward cross-signature The **Forward_Cross_Signature** contains two signatures, one created by the Subject S_i and the other created by the Next Subject S_{i+1} , over the same message: the concatenation of the Header H_i , the hash of the Subject $h(S_i)$ and the hash of the Next Subject $h(S_{i+1})$. Note that this field guarantees binding between the current user acting as an issuer and the next user (to whom the next certificate c_{i+1} is issued).

We now describe the special certificates:

- The certificate c_0 , called *root certificate*, has the same structure of a standard certificate, but the **Issuer** field and the **Subject** field contain the same data. Indeed, the root user S_0 is not a normal user but rather an entity that initiates the specific BCL.

- Also the certificate c_{n-1} is special. Although it has the same structure of a standard certificate, some fields are not populated because the next user is still unknown: **Next_Subject** , the **Next_Subject** signature, the **Forward_Cross_Signature** .
The last user that owns the last certificate, c_{n-1} will then become the issuer for the next certificate (see 2.1).

We describe briefly how the protocol works.

1. Certification request.

- (a) A new user, who will be S_n , asks for a certificate registers himself to the system (BCI). The system provides him the BIX-ID. Then, the user creates his private and public key, creates and signs his **Subject** and sends both as a request to the system. Since he does not know who is the last user, he sends his request to every user of the BCL.
- (b) The owner of the tail certificate c_{n-1} , namely S_{n-1} , processes this request. That is, she fills the **Issuer** field and the **Issuer Signature** field of c_n , while creating also an intermediate version of the **Backward_Cross_Signature** field with her private key SK_{n-1} . That is, she signs $(H_n || h(S_{n-1}) || h(S_n))$ (where "||" is concatenation of strings) and puts it into c_n .
- (c) At the same time, she updates her BIX certificate c_{n-1} filling the **Next_Subject** field and the **Next Subject Signature** field using the data of user S_n . Moreover, she creates an intermediate version of the **Forward_Cross_Signature** field by signing it with her private key . That is, she signs $(H_{n-1} || h(S_{n-1}) || h(S_n))$ with SK_{n-1} .
- (d) Now S_{n-1} sends three certificates, c_0 , c_{n-1} and c_n to the new user S_n through the system (BCI). Observe that the two certificates c_{n-1} and c_n are still incomplete and that c_n will be the new tail certificate.
- (e) User S_n receives these certificates, completes the counter-signature process by performing two digital signatures and adding them, respectively, to the **Forward_Cross_Signature** of c_{n-1} and the **Backward_Cross_Signature** of c_n .
- (f) User S_n requests the chain CC to the system and checks its integrity, by either traversing it forwards from c_0 to c_{n-1} or backwards from $n-1$ to 0 using c_{n-1} . If CC passes the integrity checks, he broadcasts c_{n-1} and c_n .
At the same time, he stores CC locally for future use.

2. Certificate exchange.

- (a) When a user, S_i , wants to perform a secure communication/transaction with a second user, S_j , and already both have their BIX-certificates, then he sends his certificate c_i to S_j and requests her certificate c_j . Each user needs to verify the certificate of the other. We focus on S_i

since the two procedures are completely symmetric.

User S_i checks certificate c_j in two steps:

- (b) he verifies the Subject signature, the Issuer signature and also the **Backward_Cross_Signature** of her certificate c_j . To this goal, it is sufficient to have PK_{j-1} , the public key of the issuer of c_j , and PK_j , the public key of user S_j , which are both available in the certificate c_j itself.
- (c) S_i verifies that c_j is in CC, which is surely available in his local storage in the case $i > j$ (see point 1.f). If $j > i$ and S_i does not have a local version of CC containing the element c_j , he will update CC in his local storage by a strategy similar to that explained in point 1.f, until he reaches the j -th element.

3 Chain Lengthening

The first attack scenario that we consider supposes that an attacker tries to attach her certificate to a preexisting certificate chain without interacting properly with the last user of the chain. More precisely, the attacker \mathcal{A} should not interact with the subject of the last certificate in the chain according to the BIX protocol.

Definition 3.1 (Static Chain Lengthening (SCL) Game). *In this game an adversary \mathcal{A} aims to add a certificate to the tail of a certificate chain CC.*

It proceeds as follows:

- *The challenger \mathcal{C} builds a certificate chain CC according to the BIX protocol with root certificate c_0 , using a hash function h and a digital signature scheme DSS.*
- *\mathcal{C} passes to \mathcal{A} the complete chain CC together with h and DSS.*
- *\mathcal{C} builds an honest verifier \mathcal{V} that given a certificate c^* and a certificate chain CC^* outputs True if the root certificate of CC^* is c_0 and c^* is a valid certificate of CC^* , False otherwise.*
- *\mathcal{A} tries to build a forged certificate chain CC' , $\lambda(CC') = n$, such that:*
 - *CC' truncated before the last certificate c'_n is identical to CC if the **Next_Subject** and **Forward_Cross_Signature** fields of the second-to-last certificate of CC' are not considered (i.e. we obtain CC' by adding a certificate to CC and completing c_{n-1} accordingly);*
 - *user S_{n-1} did not take part in the creation of c'_n and so in particular he did not perform the **Forward_Cross_Signature** of c_{n-1} and the **Backward_Cross_Signature** of c'_n ;*
 - *$\mathcal{V}(c', CC') = \text{True}$ where c' is the last certificate of CC' .*

\mathcal{A} wins the SCL game if she successfully lengthens CC, i.e. if she builds a CC' that satisfies these last three points.

Definition 3.2 (Security against SCL). *The BIX protocol is said **secure against static chain lengthening** if there is no adversary \mathcal{A} that in polynomial time wins the SCL game 3.1 with non-negligible probability.*

Theorem 3.1. *Let \mathcal{A} be an adversary that wins the SCL game 3.1 with probability ϵ , then a simulator \mathcal{S} might be built that, with probability at least ϵ , either solves the Collision Problem 1.1, with L the set of all possible **Subject** fields, or wins the Digital Signature Security game 1.3.*

Proof. Let \mathcal{DSS} be the digital signature scheme and h the hash function used in the BIX protocol, and $L \subseteq \mathbb{F}_2^l$ be the class of all possible **Subject** fields. We will build a simulator \mathcal{S} that simultaneously plays the Digital Signature Security (DSS) game 1.3 and tries to solve an instance of the Collision Problem 1.1 for L . It does so by simulating an instance of the SCL game 3.1 and exploiting \mathcal{A} . We will prove that if \mathcal{A} wins the SCL game then either \mathcal{S} finds a solution for the Collision Problem or \mathcal{S} wins the DSS game.

\mathcal{S} starts with taking as input an instance (h, L) of 1.1 and a public key PK^* given by the \mathcal{DSS} challenger (i.e., the output of the first phase of 1.3 for the scheme \mathcal{DSS}). \mathcal{S} then proceeds to build a certificate chain CC^* following the BIX protocol. \mathcal{S} builds all but the last certificate normally, running the KeyGen algorithm of the \mathcal{DSS} to choose public keys for the **Subject** fields, so the corresponding secret keys are available to sign these certificates properly. Then let $n = \lambda(CC)^* \geq 2$ (i.e. the number of certificates contained in CC^*), c_0^* its root certificate and c_{n-1}^* the last one. \mathcal{S} sets the **Subject** of c_{n-1}^* , that we will denote by S_{n-1}^* , such that its public key is PK^* , then it queries the challenger of the DSS game to obtain three valid signatures, respectively, on:

- the hash $h(S_{n-1}^*)$ of this subject,
- $(H_{n-1}^* || h(S_{n-2}^*) || h(S_{n-1}^*))$ for the **Backward_Cross_Signature** of c_{n-1}^* ,
- $(H_{n-2}^* || h(S_{n-2}^*) || h(S_{n-1}^*))$ for the **Forward_Cross_Signature** of c_{n-2}^* ,

where H_{n-2}^* is the **Header** of c_{n-2}^* , H_{n-1}^* is the **Header** of c_{n-1}^* , and $h(S_{n-2}^*)$ is the hash of the **Issuer** of c_{n-1}^* , that is the **Subject** of c_{n-2}^* . In this way \mathcal{S} completes a certificate chain CC^* of length n , that it passes to \mathcal{A} .

\mathcal{A} responds with a counterfeit chain CC' of length $\lambda(CC) = n + 1$. If CC' is not valid (the chains CC' and CC^* do not correspond up to the $(n - 1)$ -th certificate, or an integrity check fails) then \mathcal{S} discards this answer and gives up (\mathcal{S} fails).

Otherwise, if the verifier outputs True, the chain CC' is valid. Denote by l' the string $(H_n' || h(S_{n-1}') || h(S_n'))$ signed in the **Backward_Cross_Signature** of c_n' (the last certificate of CC') by the private key corresponding to PK^* . We have two cases:

- l' is equal to a message for which \mathcal{S} requested a signature.
 Because of its length, l' may be equal to $l_0^* := (H_{n-2}^* || h(S_{n-2}^*) || h(S_{n-1}^*))$ or $l_1^* := (H_{n-1}^* || h(S_{n-2}^*) || h(S_{n-1}^*))$, but not to $h(S_{n-1}^*)$. In either case, $l' = l_0^*$ or $l' = l_1^*$, the equality implies that $h(S'_n) = h(S_{n-1}^*)$, but the specification of the BIX protocols supposes that different certificates have a different BIX ID in the **Subject** (and we know that CC' is valid). So $S'_{n-1} = S_{n-1}^* \neq S'_n$, because of the BIX ID's, but they have the same hash so \mathcal{S} may submit (S'_{n-1}, S'_n) as a solution to the Collision Problem.
- l' is different from all messages for which \mathcal{S} requested a signature.
 In the **Backward_Cross_Signature** of c'_n there is a signature s of l' such that $\text{Ver}(l', s, \text{PK}^*) = \text{True}$ (remember that PK^* is the public key of the **Issuer** of c'_n and that CC' is considered valid, so the signatures check out), so \mathcal{S} may submit (l', s) as a winning answer of the challenge phase of the DSS game.

So if \mathcal{S} does not fail it correctly solves the Collision Problem or wins the DSS game, and since \mathcal{A} is a polynomial-time algorithm, \mathcal{S} is a polynomial-time algorithm too, given that the other operations performed correspond to the building of a certificate chain and this must be efficient. \mathcal{S} might fail only if the chain given by \mathcal{A} is not valid (i.e. if \mathcal{A} fails). Since the simulation of the SCL game is always correct, \mathcal{A} 's failure happens with probability $1 - \epsilon$, then the probability that \mathcal{S} wins is $1 - (1 - \epsilon) = \epsilon$. \square

Corollary 3.1 (SCL Security). *If the Digital Signature Scheme is secure (see Assumption 1.4) and the hash function is collision resistant for the class L (Assumption 1.2) where L is the set of all possible **Header** fields, then the BIX protocol is secure against the Static Chain Lengthening.*

Proof. Thanks to Theorem 3.1, given a polynomial-time adversary that wins the SCL game with non-negligible probability ϵ , a polynomial-time simulator might be built that with the same probability either solves the Collision Problem 1.1 or wins the Digital Signature Security game 1.3. So let C be the event "solution of the Collision Problem" and D be the event "victory at the DSS game". We have that

$$\epsilon = P(C \vee D) \leq P(C) + P(D) \quad (3.1)$$

Note that the sum of two negligible quantities is itself negligible, so the fact that ϵ is non-negligible implies that at least one of $P(C)$ and $P(D)$ is non-negligible, and this means that Assumption 1.2 or Assumption 1.4 is broken. \square

Let us call Alice the user of the second-to-last certificate in the chain and Bob the user of the last certificate. We observe that the infeasibility of this attack would guarantee also the non-repudiation property of the last certificate in the chain. That is, if Alice tries to repudiate Bob (with an eye to issuing another certificate), then Bob might claim his righteous place since no one can

attach its certificate to the tail of the certificate chain without being a proper user.

Note also that even though the security of the digital signature is presented in the form of *existential forgery*, in the proof the freedom of the attacker in the choice of the message to be signed is limited. In fact it has to forge a signature of $l' := (H'_n || h(S'_{n-1}) || h(S'_n))$, where $h(S'_{n-1})$ is given by \mathcal{S} , and even H'_n is not completely controlled by \mathcal{A} (the sequence number is given, and the other fields should be given by the IM). So a large part of the string to be signed is beyond the control of the forger, so the challenge is not completely an existential forgery but something in between an existential and a universal forgery.

4 Certificate Tampering

In the second attack scenario that we consider, we suppose that only the root certificate of a certificate chain is publicly available and trustworthy, while a malicious attacker tries to corrupt a chain of certificates built upon this root, resulting in another chain that may re-distribute as a proper chain with same root but with altered information. Note that the security against this attack would guarantee that no external attacker can modify any certificate in the chain, including deleting or inserting a certificate in any non-ending point, as long as the root certificate is safe (no unauthorized usage), secure (cannot be broken) and public (anyone can check it). If the security proved in the previous section is also considered, then a certificate chain is also secure at the end point (no one can wrongfully insert herself at the end or disavow the last certificate) achieving full security from external attacks.

Definition 4.1 (Static Tampering with Subject (STS) Game). *In this game an adversary \mathcal{A} aims to modify information contained in the Subject field of a certificate c_i contained in a certificate chain CC , with $1 \leq i \leq n-2$, $n = \lambda(\text{CC})$. It proceeds as follows:*

- *The challenger \mathcal{C} builds a certificate chain CC with root certificate c_0 , according to the BIX protocol and using a hash function h and a digital signature scheme \mathcal{DSS} . Let $n = \lambda(\text{CC})$.*
- *\mathcal{C} passes to \mathcal{A} the complete chain CC together with h and \mathcal{DSS} .*
- *\mathcal{C} builds an honest verifier \mathcal{V} that, given a certificate c^* and a certificate chain CC^* outputs **True** if the root certificate of CC^* is c_0 and c^* is a valid certificate of CC^* , **False** otherwise.*
- *\mathcal{A} selects a "target certificate" c_i in CC and tries to build a forged certificate chain CC' such that:*
 - *CC' has the same length as CC truncated after c_i , i.e. the last certificate c'_i of CC' is in the same position i as c_i in CC relatively to c_0 , with $\lambda(\text{CC}') = i + 1$.*

- The **Subject** fields of c_i and c'_i are different, that is, $S_i \neq S'_i$.
- $\mathcal{V}(c', CC') = \text{True}$

\mathcal{A} wins the STS game if he achieves the last three items, i.e. he successfully builds such a CC' .

Definition 4.2 (Security against STS). *The BIX protocol is said secure against Static Tampering with Subject if there is no adversary \mathcal{A} that in polynomial time wins the STS game 4.1 with non-negligible probability.*

Theorem 4.1. *Let \mathcal{A} be an adversary that wins the STS game 4.1 with probability ϵ , then a simulator \mathcal{S} might be built that with probability at least $\frac{\epsilon}{n-1}$ either solves the collision problem 1.1, where L is the set of all possible **Subject** fields, or wins the digital signature security game 1.3, where n is the length of the certificate chain that \mathcal{S} gives to \mathcal{A} .*

Proof. Let \mathcal{DSS} be the digital signature scheme and h the hash function used in the BIX protocol, and $L \subseteq (\mathbb{F}_2)^l$ be the class of all possible **Subject** fields. We will build a simulator \mathcal{S} that simultaneously plays the digital signature security (DSS) game 1.3 and tries to solve an instance of the collision problem 1.1 for L . It does so by simulating an instance of the STS game 4.1 and exploiting \mathcal{A} . We will prove that when \mathcal{A} wins the STS game, one in $n - 1$ times \mathcal{S} is successful. To be more precise, if \mathcal{S} does not find a solution for the collision problem then \mathcal{S} wins the DSS game.

\mathcal{S} starts with taking as input an instance (h, L) of 1.1 and a public key PK^* as the output of the first phase of 1.3 for the scheme \mathcal{DSS} .

\mathcal{S} now proceeds to build a certificate chain CC following the BIX protocol, as follows. First, \mathcal{S} chooses $n \geq 2$ (possibly depending on the \mathcal{A} 's requirements). Then \mathcal{S} selects $2 \leq k \leq n - 2n$ at random to be the index of a certificate c_k in CC . \mathcal{S} builds the first $k - 1$ certificates normally, running the **KeyGen** algorithm of the \mathcal{DSS} scheme to choose public keys for the **Subject** fields, so the corresponding secret keys are available (to \mathcal{S}) to sign these certificates properly. So, c_0, \dots, c_{k-3} are complete certificate and c_{k-2} is a tail certificate. Then it sets the **Subject** of c_{k-1} such that its public key is PK^* , and a header H_{k-1} , then it queries the challenger of the DSS game to obtain three valid signatures, respectively, on:

- the hash $h(S_{k-1})$ of this subject,
- on $(H_{k-1} || h(S_{k-2}) || h(S_{k-1}))$ for the **Backward_Cross_Signature** of c_{k-1} ,
- on $(H_{k-2} || h(S_{k-2}) || h(S_{k-1}))$ for the **Forward_Cross_Signature** of c_{k-2} ,

where we recall that H_{k-2} is the **Header** of c_{k-2} , H_{k-1} is the **Header** of c_{k-1} , $h(S_{k-2})$ is the hash of the **Issuer** of c_{k-1} . Then \mathcal{S} builds the k -th certificate, choosing a H_k and S_k , using again the **KeyGen** algorithm to sign S_k , querying the DSS challenger for two valid signatures, respectively, on:

- $(H_k || h(S_{k-1}) || h(S_k))$ for the **Backward_Cross_Signature** of c_k ,

- and on $(H_{k-1}||h(S_{k-1})||h(S_k))$ for the **Forward_Cross_Signature** of c_{k-1} ,

where we recall that H_k is the **Header** of c_k and $h(S_k)$ is the hash of the **Subject** of c_k . Finally, \mathcal{S} completes the chain CC (following the protocol and choosing everything, including the SK_i 's), so that it has n certificates, and passes it to \mathcal{A} .

\mathcal{A} responds with a counterfeit chain CC' of length $i + 1 \leq n$. \mathcal{A} fails if and only if CC' is not valid, which happens when the last **Subject** is not altered ($S'_i = S_i$) or when the integrity check of the verifier fails. If we are in this situation, \mathcal{S} discards CC' and gives up (\mathcal{S} fails).

Otherwise, for $1 \leq j \leq i$, \mathcal{S} controls the forged certificates $c'_j \in \text{CC}'$ and compares them to $c_j \in \text{CC}$. There are three cases to consider:

- for all $1 \leq j \leq i$, $h(S_j) = h(S'_j)$.
Since $S'_i \neq S_i$, \mathcal{S} outputs the pair (S_i, S'_i) as a solution to the collision problem.
- there is $1 \leq j \leq i$ such that $h(S_j) \neq h(S'_j)$, but $h(S_k) = h(S'_k)$ or $k > i$.
In this case \mathcal{S} gives up (\mathcal{S} fails).
- $h(S_{k-1}) = h(S'_{k-1})$ and $h(S_k) \neq h(S'_k)$.
If $S_{k-1} \neq S'_{k-1}$, the \mathcal{S} wins by submitting the pair (S_{k-1}, S'_{k-1}) as a solution to the collision problem. Otherwise, $S_{k-1} = S'_{k-1}$ and PK^* is the public key of the issuer of c'_k . Then in the **Backward_Cross_Signature** of the certificate c'_k there is the digital signature s for which holds the relation $\text{Ver}((H'_k||h(S'_{k-1})||h(S'_k)), s, \text{PK}^*) = \text{True}$ (remember that CC' is considered valid, so the signatures check out), so \mathcal{S} may submit

$$((H'_k||h(S'_{k-1})||h(S'_k)), s)$$

as a winning answer of the challenge phase of the DSS game, since it is different from the messages \mathcal{S} queried for signatures, that are

$$[h(S_{k-1}), (H_{k-1}||h(S_{k-2})||h(S_{k-1})), (H_{k-2}||h(S_{k-2})||h(S_{k-1})), \\ (H_k||h(S_{k-1})||h(S_k)), (H_{k-1}||h(S_{k-1})||h(S_k))] .$$

- $h(S_{k-1}) \neq h(S'_{k-1})$ and $h(S_k) \neq h(S'_k)$.
 \mathcal{S} gives up and fails.

So if \mathcal{S} does not fail, \mathcal{S} correctly solves the collision problem or wins the DSS game, and since \mathcal{A} is a polynomial-time algorithm, \mathcal{S} is a polynomial-time algorithm too.

\mathcal{S} wins at least in the event when \mathcal{A} wins and $S_k \neq S'_k$ (knowing that at least one j exists such that $1 \leq j \leq i \leq n - 1$ $S_j \neq S'_j$). The probability of this event is at least the probability of the two cases and so it is

$$\epsilon \cdot \frac{1}{n-1} = \frac{\epsilon}{n-1} .$$

□

Corollary 4.1 (STS Security). *If the Digital Signature Scheme is secure (see Assumption 1.4) and the hash function is collision resistant for the class L (Assumption 1.2) where L is the set of all possible **Subject** fields, then BIX protocol is secure against the static tampering with subject.*

Proof. For the BIX protocol to be functional the length of the chain must be polynomial, so for the result of Theorem 4.1, given a polynomial-time adversary that wins the STS game with non-negligible probability ϵ , a polynomial-time simulator might be built that with probability at least $\frac{\epsilon}{n}$ either solves the collision problem 1.1 or wins the digital signature security game 1.3, where n is the length of the chain. But $\frac{\epsilon}{n}$ is non-negligible too, so this breaks either Assumption 1.2 or Assumption 1.4. \square

5 Mid-Chain Altering

Our proofs of security in the previous two sections does not show the impregnability of BIX to all protocol attacks. In this section we do present an effective attack, where two non-consecutive members of the BIX community (i.e. whose BIX certificates are not next to each other in the chain) collude to create an alternate version of the chain between the two that is considered valid by the members outside of that section, but that contains subjects chosen arbitrarily by the two malicious users.

Let S_i, S_j be two malicious colluding users, where the indexes i, j of their certificates in the certificate chain are such that $j > i + 1 > i > 0$. Suppose that the chain is built properly up to the j -th certificate. We claim that, once S_j has received his certificate c_j , he may collude with S_i in order to change the information in the certificates c_k with $i < k \leq j$ in such a way that every user S_m with a certificate with index $0 < m < i$ or $m > j$ will consider correct the altered certificates (if they have not already obtained the original certificates).

The first thing they do is to change the information in the **Subject** fields S_j ($i + 1 \leq j \leq j - 1$) by generating private keys and the corresponding public ones (and then they are able to sign everything). Then, the first malicious user S_i changes her certificate c_i so that the fields **Next_Subject** and **Forward_Cross_Signature** link to the altered information and validate it, and similarly does S_j with his fields **Issuer** and **Backward_Cross_Signature** of c_j .

At this point this altered version of the chain is considered valid by unsuspecting users. Moreover, S_j as last user is responsible to supply the certificates in the chain to new users, so he may propagate the altered version, while older users S_m with $0 < m < i$ will unwillingly authenticate altered certificates. Indeed, when checking the integrity by traversing the chain either forward or backward, they find no inconsistency as long as S_i points to the altered version.

6 Conclusions

In this paper the BIX certificates protocol proposed in [6] has been formally analyzed from a security point of view. In particular the security against static attacks that aim to corrupt a chain has been proven, reducing the security to the choice of an adequate hash function and digital signature scheme. For this reason the security of ECDSA, the main DSS nowadays, has also been discussed. Moreover, an attack has been proposed on the BIX protocol in which two malicious users can collude to forge a portion of the certificate chain, suggesting that although the protocols has some solid security features, it still needs improvements to resist to more active attacks.

References

- [1] M. Araoz. Proof of existence. Technical report, 2015.
- [2] D. Cooper and et al. Internet x.509 public key infrastructure certificate and certificate revocation list (crl) profile. Technical report, IETF RFC 5280, 2008.
- [3] T. Elgamal. A public key cryptosystem and a signature scheme based on discrete logarithms. *IEEE Trans. on Inf. Th.*, 31(4):469–472, 1985.
- [4] Ethereum Foundation. Ethereum project. Technical report, 2015.
- [5] D. Johnson, A. Menezes, and S. Vanstone. Technical report.
- [6] Sead Muftic. Bix certificates: Cryptographic tokens for anonymous transactions based on certificates public ledger. *LEDGER*, 1(1):1–12, 2016.
- [7] NIST. Secure hash standard (shs). Technical Report FIPS PUB 180, 2012.
- [8] P. Paillier and D. Vergnaud. Discrete-log-based signatures may not be equivalent to discrete log. *LNCS*, 3788:11–20, 2005.
- [9] B. Preneel. The State of Cryptographic Hash Functions. *LNCS*, 1561:158–182, 1999.
- [10] M. O. Rabin. Digital signatures and public-key functions as intractable as factorization. Technical Report MIT/LCS/TR-212, MIT laboratory for computer science, 01 1979.
- [11] R. L. Rivest, A. Shamir, and L. M. Adleman. A Method for Obtaining Digital Signatures and Public-Key Cryptosystems. *Commun. ACM*, 21(2):120–126, 1978.
- [12] S. Wilkinson, T. Boshevski, J. Brandoff, and V. Buterin. Storj: A peer-to-peer cloud storage network. Technical report, 2014.