Abstract

Many interesting data sets available on the Internet are of a *medium* size—too big to fit into a personal computer's memory, but not so large that they won't fit comfortably on its hard disk. In the coming years, data sets of this magnitude will inform vital research in a wide array of application domains. However, due to a variety of constraints they are cumbersome to ingest, wrangle, analyze, and share in a reproducible fashion. These obstructions hamper thorough peer-review and thus disrupt the forward progress of science. We propose a predictable and pipeable hub-and-spoke framework for R (the state-of-the-art statistical computing environment) that leverages SQL (the venerable database architecture and query language) to make reproducible research on medium data a painless reality.

A Grammar for Reproducible and Painless Extract-Transform-Load Operations on Medium Data

Benjamin S. Baumer *

May 29, 2019

1 Introduction

Scientific research is increasingly driven by "large" data sets. However, the definition of "large" is relative. We define *medium* data to be those who are too big to store in random access memory (RAM) on a personal computer, but not so big that they won't fit on a hard drive. Typically, this means data on the order of several gigabytes. ¹ Publicly accessible medium data sets (PAMDaS) are now available in a variety of application domains. A few examples are the Citi Bike bike-sharing program in New York City, campaign contributions from the Federal Election Commission, and on-time airline records from the Bureau of Transportation Services.

PAMDaS provide *access* to these data, but this is not the only barrier to reproducible research that uses these data. Because of their size, reading these data into memory will either take an unbearably long time, exhaust the computer's memory until it grinds to a halt, or not simply not work at all. The most sensible solution is to download the data to a local storage device and then import it into a relational database management system (RDBMS). RDBMS's have been around since the 1970s, and provide a scalable solution for data of this magnitude. Open source implementations (e.g., MySQL, PostgreSQL, SQLite) are ubitiquitous. However, the process of creating a new database from scratch is time-consuming and requires knowledge of database administration.

The process of downloading the raw data from its authoritative source and importing it into a RDBMS is often called *Extract-Transform-Load* (ETL). Professionals who work with data spend a disproportionate amount of their time on such tasks. Their solutions are sometimes idiosyncratic, platform- or architecture-specific, poorly documented, unshared, and involve custom written

^{*}Program in Statistical and Data Sciences, Smith College, Northampton, MA 01063. Email: bbaumer@smith.edu

 $^{^1 {\}rm In}$ 2017, desktop computers typically ship with hard drives up at most four terabytes. Most laptops use solid-state hard drives which hold less than one terabyte.

scripts in various (and often multiple) languages. Thus, the ETL process erects a barrier to reproducible research, because there is not a good way of verifying that two people downloading data from the same source will end up with the same exact set of data in their local data store. This matters because any subsequent data analysis could be sensitive to small perturbations in the underlying data set.

Sharing the local data store is often also problematic, due to licensing restrictions and the sheer size of the data. While PAMDaS may be free to download, there may be legal barriers to publicly sharing a local data store that is essentially a reproduction of that original data. Moreover, sharing medium data sets through the cloud is expensive or unrealistic for many individuals and small companies.

We propose a hub-and-spoke software framework for facilitating reproducible research on PAMDaS. Our solution consists of a package for R that provides a framework for ETL operations (i.e., the *hub*) along with a series of packages for R that extend the ETL framework for a specific PAMDaS (i.e., a *spoke*). The hub is provided by the **etl** package, which is available on CRAN (Baumer, 2016). Six different spokes are in various states of development, but in principle there is no limit to how many spokes could be created. These packages are all fully open source (hosted on GitHub with Creative Commons licenses) and cross-platform (to the extent allowed by R, MySQL, PostgreSQL, SQLite, etc.).

The etl suite of packages will make it easier to bring PAMDaS to data analysts of all stripes while lowering barriers to entry and enhancing transparency, usability, and reproducibility. For the most part, knowledge of SQL will not be required to access these data through R. (See Kline et al. (2005) for a primer on SQL.)

2 Related Work

In this section we summarize the major considerations that make the etl package a progressive step towards reproducible research on medium data for R users.

2.1 Reproducible research

To understand the current challenges we face in conducting reproducible research on PAMDaS, one must start with the notion of literate programming that began with Knuth (1984). In literate programming, source code is woven into an annotated narrative, so that one could read the source code and understand not just the code itself, but also how each piece of code fits into the larger design.

This idea leads to the notion of *reproducibility* in computational science. Donoho (2010) paraphrases Claerbout (1994):

An article about a computational result is advertising, not scholarship. The actual scholarship is the full software environment, code and data, that produced the result.

Ioannidis (2005) argues that most published research is false, and while his arguments are *statistical* rather than *computational*, they only help to underscore the importance of computational reproducibility.

Together, these ideas suggest a path forward. Namely, data-based research must be backed by open data, with well-documented data analysis code that is shared publicly and executable on open-source platforms.

In academia, a diverse set of fields including computer science (Donoho et al., 2009), economics (Ball and Medeiros, 2012), archeology (Marwick, 2017) and neuroscience (Eglen et al., 2017) are actively debating how they will recognize reproducible research. Organizations like Project TIER (http://www.projecttier.org/) and the Open Science Framework (https://osf.io/) provide protocols for conducting reproducible research, while statistics and data science educators are instilling reproducible practices in their students (Baumer et al., 2014). Top-tier journals like the *Journal of the American Statistical Association* have appointed reproducibility editors (Fuentes, 2016).

Thus, while the need for research in all fields to be reproducible is clear, the specifications for what qualifies as reproducible are less clear, and the path towards achieving reproducibility is murkier still.

2.2 Medium data

In the past few years, *big data* has become an omnipresent buzzword that taps into our collective fascination with things that are massive. However, while a few enormous companies (e.g., Google, Facebook, Amazon, Walmart, etc.) generate and analyze truly big data (on the order of *exabytes* (EB), which are equal to 1000 *petabtyes* (PB), which are equal to 1000 *terabytes* (TB), which are equal to 1000 gigabytes (GB)), most people who analyze data will never interact meaningfully with data of that size.

Most people will only encounter data that is *small* (a few gigabtyes at most). These data fit effortlessly into a computer's random access memory (RAM), and thus the user experiences no challenges related to the data's size. Because a computer can access data in memory at lightning-fast speeds, efficient data analysis algorithms like searching (O(n)), sorting $(O(n \log n))$, and multiplying matrices (e.g., fitting a regression model) $(O(n^{2.376})$ (Williams, 2012)) will run nearly instantly—even on a laptop. Thus, for people working with small data, fundamental computer science concepts like the distinction between hardware and software, algorithmic efficiency, and bus speeds are immaterial.

For the vast majority of us who are unlikely to ever interact meaningfully with truly big data, *medium data* is both a viable solution and an accessible introduction to the challenges of big data (Horton et al., 2015). In Table 1, we constrast the relative sizes of data from the point of view of a personal computer user. Medium data is on the order of several gigabytes to a few terabytes. These data are large enough that they will not comfortably fit in memory on a personal computer without consequences, making a memory-only application

"Size"	actual size	hardware	software
small	< several GB	RAM	R
medium	several $GB - a$ few TB	hard disk	SQL
big	many TB or more	computing cluster	Spark?

Table 1: Relative sizes of data from the point-of-view of personal computer users. We focus on medium data, which are too large to fit comfortably into the random access memory (RAM) of a typical personal computer, but not so large that they won't fit comfortably on the hard drive of such a computer.

like (vanilla) R a dubious candidate for data analysis. However, medium data are not so large they won't fit on a single hard disk, making them accessible to a single user without access to a computing cluster. An SQL-based RDBMS remains an appropriate storage and retrieval solution for medium data.

2.3 The status quo

The fundamental challenge of big data is scalability, but medium data comes with its own challenges. In the end, investment in setting up RDBMS's properly pays off in more efficient analysis.

First, everything takes a little longer, since the aforementioned algorithms are no longer instantaneous. A single line of code might take one minute to execute instead of a millisecond, but these brief delays compound. This sluggishness rewards efficient code and workflows.

Second, a data analyst has to know something about SQL administration in order to set up a database. While these skills are not difficult to acquire, they are not always emphasized in the traditional curriculum in either statistics (American Statistical Association Undergraduate Guidelines Workgroup, 2014) or computer science (on Computing Curricula, 2013). Many introductory data science courses that teach SQL focus on writing SELECT queries to retrieve data from an existing database—not on writing table schemas and defining keys and indexes (Hardin et al., 2015).

Third, getting PAMDaS set up involves often laborious ETL operations. Downloading medium data is not instantaneous and is dependent on the speed of one's Internet connection. Wrangling data is notoriously time-consuming work: reasonable estimates suggest this may occupy as much as 50–80% of a data scientist's time.

For these reasons, a responsible data scientist will record their ETL operations in a script. But these scripts are often problematic, ad hoc solutions. Some common problems include:

Portability Shell scripts may not port across operation systems. While Apple's OS X operating system is POSIX-compliant, not all flavors of GNU/Linux are. Microsoft Windows is not at all compliant and thus any such scripts are not likely to run on Windows without careful modification.

package	timespan	airports	size
hflights	2011	IAH, HOU	2.1 MB
nycflights13	2013	LGA, JFK, EWR	$4.4 \ \mathrm{MB}$
airlines	1987-present	≈ 350	> 6 GB

Table 2: Alternative packaging of on-time flight data from the Bureau of Transportation Statistics in R. We note that the full scope of flight data is only accessible through the **airlines** package.

- **Usability** Under time pressure, data scientists are likely to write scripts that work for them, and not necessarily for other people. Their scripts may be idiosyncratic and difficult for another person to use or modify.
- Version Control Even if a data scientist uses a formal version control system like git and GitHub, a script that ran when it was written may not run at all points in the future.
- Languages ETL scripts may be written in bash, Python, R, SQL, Perl, PHP, Ruby, Scala, Julia, or any combination of these languages and others. There may be good reasons for mixing different languages but ease of portability decreases with each additional language.

One recommended solution for bundling ETL scripts for R users is to write an R package (Wickham, 2015). Packages provide users with software that extends the core functionality of R, and often data that illustrates the use of that functionality. R packages hosted on CRAN—the authoritative central repository—are checked for quality and documentation, helping to ensure their usability. Since R is cross-platform, these packages are portable. CRAN itself maintains distinct versioning, and while R packages are mostly written in R, there are a number of ways in which code from other languages can be embedded into an R package (e.g. Rcpp provides functionality to bundle C++ code (Eddelbuettel and François, 2011)).

However, by design the types of data that can be contained in an R package hosted on CRAN are limited. First, packages are designed to be small, so that the amount of data stored in a package is supposed to be less than 5 megabytes. Furthermore, these data are static, in that CRAN allows only monthly releases. Alternative package repositories—such as GitHub—are also limited in their ability to store and deliver data that could be changing in realtime to R users. In Table 2 we contrast two different CRAN packages for on-time airline flight data (Wickham, 2016b, 2013), with an etl-dependent package that allows the user to build their own database of flight data (Baumer, 2017a). We note the change in scope that the airlines package allows: whereas the two existing data sets are restricted to small, static data from flights departing two Houston-area airports in 2011, or three New York City-area airports in 2013, respectively, the airlines package covers all flights since 1987 departing from more than 350 airports nationwide, with more data available monthly. Many R packages facilitate the retrieval of data from specific sources. In particular, the rOpenSci group maintains dozens of such packages (Boettiger et al., 2015). Other popular small CRAN packages that serve as APIs to large data sets include tigris (Walker and Rudis, 2017) and UScensus2010 (Almquist, 2010). While these packages are undoubtedly useful, they are written by many different authors, and thus the syntax employed across packages varies greatly. In short, there is no consistent "grammar" (see Section 3.4). These packages are spokes without a hub.

Some hub-and-spoke approaches do exist. Peng and Dominici (2008) illustrate how a small package for CRAN that interacts with large data repositories not hosted on CRAN could facilitate research in environmental epidemiology. These repositories are maintained by the package author through the use of a second package (Eckel and Peng, 2009). More recently, the **drat** package provides a hub that facilitates the creation of spoke packages (Anderson and Eddelbuettel, 2017). In this scheme the spoke packages contain large amounts of data. The major drawback to both of these approaches is the requirement that the researcher maintain the large data repositories.

Perhaps the closest competitor to our approach is pitchRx (Sievert, 2014), which performs ETL operations for a specific data set—in this case, detailed pitch information from Major League Baseball. Our approach places similar core functionality in the etl package (i.e. the hub) and separates the data-sourcespecific functionality into small, easy-to-write packages that can be hosted on CRAN (i.e. the spokes). The developer need not maintain any large data repositories—they need only to maintain the small bits of code that interact with the data provider. If, for any reason, the source data changes, etl users still retain copies of the raw data as they downloaded it.

We imagine that many of these aforementioned packages could be re-factored to have **etl** as a dependency.

2.4 Database functionality in R

Recent advances in R computing have made accessing databases through R a relatively painless process.

In R, a data.frame is a two-dimensional array of data that consists of rows and columns. It is logically analogous to a *table* in SQL parlance, but with two crucial differences in implementation: first, a data.frame is always stored in memory, whereas a table is usually written to disk; second, a data.frame need not and cannot be indexed, whereas tables are often indexed. The tibble package in R extends the data.frame to the more flexible tbl data structure (Müller and Wickham, 2017). The dbplyr package further extends the functionality of tbl's to be backed by a local or remote database (Wickham, 2017a). A common interface to such databases is provided by the DBI package (R Special Interest Group on Databases (R-SIG-DB) et al., 2016). Each RDBMS has its own R package that implements the DBI programming interface. For example, the RMySQL package implements the DBI specification for MySQL (Ooms et al., 2017), while the RSQLite package implements the DBI specification for SQLite (Müller et al., 2017). Through this chain of interfaces, a tbl_mysql appears to an R user to be a familiar data.frame, but in fact, it is akin to a VIEW of the underlying MySQL table, and thus occupies virtually no space in R's memory and can make use of SQL indexes.

This infrastructure provides a backdrop for the enormously popular data wrangling package dplyr (Wickham and Francois, 2016), which re-imagines SQL SELECT syntax as a pipeable sequence of five or six data verbs. This approach is attractive because R users can perform SQL-style operations from within R without having to learn SQL. Furthermore, if the dbplyr functionality is employed, R users can offload the execution of these operations to more powerful RDBMS's. However, dplyr's SQL translation function is only designed to handle SELECT queries, and even then only the most common types of these.

2.5 Tidyverse design

The etl package fits into a growing collection of R packages known as the tidyverse (Wickham, 2017b). These packages are designed for interoperability and emphasize functions that are *pure*, *predictable*, and *pipeable*, as described by Hadley Wickham.

- **Pure** The output of a function is entirely dependent on the input to the function. Pure functions make no changes to other objects in the environment.
- **Predictable** Functions names, arguments, and behaviors are consistent, such that if you can learn how to use one function, you have a head start on understanding how to use others.
- **Pipeable** Functions return objects of the same type as their first argument, so that pipeable operations can be chained together to produce *pipelines*.

Functions in the **etl** package are predictable and pipeable, but not pure. This is by design—while the predictability and pipeability make **etl** easy to use and compatible with the **tidyverse**, these functions also necessarily download files, store them locally, and interact with databases outside of R. These changes to the computing environment are unavoidable given the nature of the task.

2.6 Our contribution

Among educators, interest in exposing statistics students to larger and more complex data is growing. Recent guidelines about undergraduate majors in statistics (American Statistical Association Undergraduate Guidelines Workgroup, 2014) and data science (De Veaux et al., 2017) endorsed by the American Statistical Association emphasize the necessity of exposing students to such data. Horton et al. (2015) advocate for discussing medium data as a "precursor" to big data. However, all of the aforementioned challenges to working with medium data present barriers to statistics educators who are quite comfortable with R, but may not have sufficient experience with SQL.

The etl package provides a CRAN-friendly framework that allows R users to work with medium data in a responsible and responsive manner. It leverages the dplyr package to facilitate Extract-Load-Transfer (ETL) operations that bring real-time data into local or remote databases controllable by R users who may have little or no SQL experience. The suite of etl-dependent packages brings the world of medium data—too big to store in memory, but not so big that it won't fit on a hard drive—to a much wider audience.

3 The etl package

In what follows we illustrate a few simple use cases and outline some of the package features.

3.1 A simple example

After installing the package, we must load it.

```
library(etl)
```

The first step is to instantiate an etl object using the etl() function. The canonical example is the mtcars data set, which is built into R. Here we use the etl_create() function to perform the entire ETL cycle on an object named my_cars. During this process, a local SQLite database is created in a temporary directory, that database is initialized, the mtcars data is "downloaded" (i.e., in this case, from memory), transformed, and finally uploaded to that same SQLite database.

```
my_cars <- etl("mtcars") %>%
  etl_create()

## No database was specified so I created one for you at:
## /tmp/Rtmp8p2hkH/file7260550e69dd.sqlite3
## Running SQL script at /home/bbaumer/R/x86_64-pc-linux-gnu-library/3.4/etl/sql/init.sqlite
## Transforming raw data...
## Transforming raw data...
## Loading 1 file(s) into the database...
```

The object my_cars is both an etl_mtcars object and a src_dbi object—and can thus do anything that any other src_dbi object can do. It also maintains a connection to the SQLite database, has two folders (e.g., raw and load) where it can store files, and knows about a table called mtcars that exists in the SQLite database.

```
class(my_cars)
```

```
## [1] "etl_mtcars" "etl" "src_dbi" "src_sql" "src"
```

```
summary(my_cars)
```

```
## files:
## n size
                            path
## 1 1 0 GB /tmp/Rtmp8p2hkH/raw
## 2 1 0 GB /tmp/Rtmp8p2hkH/load
##
        Length Class
                                 Mode
## con
       1
               SQLiteConnection S4
## disco 2
               -none-
                                environment
my_cars
## dir: 2 files occupying 0 GB
## src: sqlite 3.19.3 [/tmp/Rtmp8p2hkH/file7260550e69dd.sqlite3]
## tbls: mtcars
```

Since my_cars is a DBI data source, the data stored in the SQLite database can be accessed in the usual manner. Here, we compute the average fuel economy for these cars. Note that these computations are performed by SQLite.

```
my_cars %>%
  tbl("mtcars") %>%
 group_by(cyl) %>%
 summarize(N = n(), mean_mpg = mean(mpg))
               lazy query [?? x 3]
## # Source:
## # Database: sqlite 3.19.3 [/tmp/Rtmp8p2hkH/file7260550e69dd.sqlite3]
##
       cyl
               N mean_mpg
##
     <int> <int>
                    <dbl>
## 1
         4
              11 26.66364
         6
              7 19.74286
## 2
## 3
         8
           14 15.10000
```

The my_cars object itself occupies very little of R's memory.

```
print(object.size(my_cars), units = "Kb")
## 3.2 Kb
```

3.2 ETL for small data

The etl package can also perform default ETL operations on data stored in any R package. Here, we build a database of five tables included in the nasaweather package (Wickham', 2014).

```
nasa <- etl("nasaweather") %>%
  etl_update()
## No database was specified so I created one for you at:
## /tmp/Rtmp8p2hkH/file72606fd24713.sqlite3
## Loading 5 file(s) into the database...
nasa
## dir: 10 files occupying 0.008 GB
## src: sqlite 3.19.3 [/tmp/Rtmp8p2hkH/file72606fd24713.sqlite3]
```

3.3 A more complex example

tbls: atmos, borders, elev, glaciers, storms

More realistically, the **etl** package simply provides the foundation for **etl**-dependent packages that focus on specific data sets. In this example, we illustrate how the **airlines** package can be used to build a large database of several million flights.

Rather than use SQLite, we will connect to a local MySQL database server. We first have to create an airlines database—this is the only operation that *must* be done in MySQL and cannot be performed from within R. Unlike SQLite, the MySQL server must be configured manually. We then use the src_mysql_cnf() function provided by etl to create a database connection.

```
system("mysql -e 'CREATE DATABASE IF NOT EXISTS airlines;'")
db <- src_mysql_cnf("airlines", host = "127.0.0.1")</pre>
```

Next, we load the **airlines** package and instantiate an ontime object. In this case, we specify the db argument to be the connection to our MySQL database, and the dir argument for local storage. Any files we download or transform will be stored in dir.

```
library(airlines)
ontime <- etl("airlines", db = db, dir = "~/dumps/airlines")</pre>
```

Finally, we perform our ETL operations. In this case, we first initialize the database, and then download data from 1987–2016. While the etl_transform() function takes the same arguments as etl_extract(), those arguments needn't take the same values. For purposes of illustration we choose to transform only the data from the decade of the 1990s. Finally, we load data from 1996 and 1997 into the database, but only from the first half of the year, plus September.

```
ontime %>%
  etl_init() %>%
```

```
etl_extract(years = 1987:2016) %>%
etl_transform(years = 1990:1999) %>%
etl_load(years = 1996:1997, months = c(1:6, 9))
```

Now, we can access the data from Bradley International Airport (BDL), which serves Hartford, CT and Springfield, MA.

```
ontime %>%
  tbl("flights") %>%
  filter(year == 1996, dest == "BDL")
## # Source:
                lazy query [?? x 21]
## # Database: mysql 5.7.19-Oubuntu0.16.04.1 [bbaumer@127.0.0.1:/airlines]
##
       year month
                     day dep_time sched_dep_time dep_delay arr_time
##
      <int> <int> <int>
                             <int>
                                             <int>
                                                        <int>
                                                                  <int>
##
    1 1996
                 1
                       1
                               657
                                               630
                                                           27
                                                                    944
##
    2
                                               655
                                                            4
       1996
                 1
                       1
                               659
                                                                    841
    3
                                                 0
##
       1996
                 1
                       1
                               659
                                                           -1
                                                                    949
##
                                                 0
    4
       1996
                 1
                       1
                               700
                                                           10
                                                                   1053
    5
##
       1996
                 1
                       1
                               716
                                               715
                                                            1
                                                                    854
    6
                                                            2
##
       1996
                 1
                       1
                               817
                                               815
                                                                    933
##
    7
       1996
                 1
                       1
                               856
                                               849
                                                            7
                                                                   1059
    8
                                               900
##
       1996
                 1
                       1
                               859
                                                           -1
                                                                   1001
##
    9
       1996
                 1
                       1
                               926
                                                 0
                                                            9
                                                                   1347
## 10
       1996
                 1
                       1
                               926
                                               930
                                                           -4
                                                                   1252
## # ... with more rows, and 14 more variables: sched_arr_time <int>,
## #
       arr_delay <int>, carrier <chr>, tailnum <chr>, flight <int>,
       origin <chr>, dest <chr>, air_time <int>, distance <int>,
## #
## #
       cancelled <int>, diverted <int>, hour <int>, minute <int>,
## #
       time_hour <chr>
```

3.4 A grammar for ETL

Wilkinson et al. (2006) described a "grammar of graphics" that was implemented in R as ggplot2 (Wickham, 2009). Similarly, dplyr (Wickham and Francois, 2016) provides a "grammar of data manipulation." A grammar consists of verbs and nouns that can be combined in logical ways to intentional effect. The benefit is that once a user understands the grammar, they should be able to read and write longer sequences of code fluently. The use of the pipe operator provided by the magrittr package (Bache and Wickham, 2014) is crucial to allowing pipelines (i.e., "sentences") to be composed from short sequences of commands (i.e., "phrases").

The design of etl is very much in this spirit, albeit less ambitious. We present etl as a grammar for ETL operations.

3.4.1 ETL nouns

At the center of any etl pipeline is an object that inherits from etl. Specifically, the etl-dependent package foo creates objects of class etl_foo. By design, every etl object is also a src_dbi object, and can thus take advantage of functions that work on such objects. print(), summary(), and is() methods for etl objects extend those provided by other packages. Here, we illustrate a few of these features.

```
class(ontime)
## [1] "etl_airlines" "etl"
                                    "src_dbi"
                                                   "src_sql"
## [5] "src"
summary(ontime)
## files:
##
      n
             size
                                               path
## 1 347 6.27 GB /home/bbaumer/dumps/airlines/raw
## 2 345 18.725 GB /home/bbaumer/dumps/airlines/load
##
       Length Class
                               Mode
## con 1
            MySQLConnection S4
## disco 2
               -none-
                              environment
print(ontime)
## dir: 692 files occupying 24.995 GB
## src: mysql 5.7.19-Oubuntu0.16.04.1 [bbaumer@127.0.0.1:/airlines]
## tbls: airports, carriers, flights, planes
src_tbls(ontime)
## [1] "airports" "carriers" "flights" "planes"
```

Moreover, like all src_dbi objects, every etl object is stored as a list and maintains a DBIConnection to a database in con. Accessing this allows one to make use of the extensive functionality provided via DBI.

```
str(ontime)
## List of 2
## $ con :Formal class 'MySQLConnection' [package "RMySQL"] with 1 slot
## ....@ Id: int [1:2] 0 0
## $ disco:<environment: 0x6a9e180>
## - attr(*, "class")= chr [1:5] "etl_airlines" "etl" "src_dbi" "src_sql" ...
## - attr(*, "pkg")= chr "airlines"
## - attr(*, "dir")= chr "/home/bbaumer/dumps/airlines"
```

```
## - attr(*, "raw_dir")= chr "/home/bbaumer/dumps/airlines/raw"
## - attr(*, "load_dir")= chr "/home/bbaumer/dumps/airlines/load"
DBI::dbGetInfo(ontime$con) %>% as.matrix()
##
                   [,1]
## host
                   "127.0.0.1"
                   "bbaumer"
## user
## dbname
                   "airlines"
## conType
                   "127.0.0.1 via TCP/IP"
                   "5.7.19-Oubuntu0.16.04.1"
## serverVersion
## protocolVersion 10
## threadId
                   96
## rsId
                  List,0
DBI::dbListTables(ontime$con)
## [1] "airports" "carriers" "flights" "planes"
```

The main difference between an etl object and a src_dbi object is that an etl object has attributes that point towards dir—a directory where files can be safely read and written. If no dir argument is specified, a temporary folder is created and used. Within dir, two subfolders are automatically created: raw and load. Raw files downloaded via etl_extract() are placed in raw. etl_transform() reads those files and writes the resulting transformed files to load. Finally, the etl_load() function reads files from load and imports them into the database.

```
args(etl)
```

```
## function (x, db = NULL, dir = tempdir(), ...)
## NULL
```

3.4.2 ETL verbs

The workhorses of etl are the three main verbs. Each takes an etl object as its first argument and return an etl object invisibly, enabling these functions to be piped.

- etl_extract(): download data from the Internet and place the raw files in the raw directory
- etl_transform(): read files in the raw directory, perform any data wrangling operations necessary, and write CSV files to the load directory
- etl_load(): import CSV files from the load directory into the database

Writing these three functions becomes each etl-dependent package maintainer's responsibility.

These three main verbs will be used in virtually every pipeline. Two optional verbs are etl_init() and etl_cleanup(). The former initializes the database by either running a SQL initialization script or by simply deleting all of the tables in the existing database. That script can be bundled by the package maintainer or passed as a file path or character vector. It can also be written in generic SQL or in a flavor of SQL specific to a particular database engine. This enables R users to make use of features that exist in one database implementation but not another (e.g., partitions in MySQL which are not available in SQLite). The latter function allows the user to delete files from either the raw or load directories using regular expression pattern matching.

Two additional verbs are provided: etl_update() and etl_create(). The former simply chains the extract, transform, and load phases together, passing the same arguments to each, while the latter runs the full chain including initialization and cleanup.

```
getS3method("etl_update", "default")
## function(obj, ...) {
##
     obj <- obj %>%
       etl_extract(...) %>%
##
##
       etl_transform(...) %>%
##
       etl_load(...)
##
     invisible(obj)
## }
## <environment: namespace:etl>
getS3method("etl_create", "default")
## function(obj, ...) {
     obj <- obj %>%
##
       etl_init(...) %>%
##
       etl_update(...) %>%
##
       etl_cleanup(...)
##
##
     invisible(obj)
## }
## <environment: namespace:etl>
```

3.5 Additional functionality

The etl package contains additional functions that are useful for ETL operations. Some of these may eventually be passed upstream to DBI. Briefly,

• dbRunScript(): execute a sequence of arbitrary SQL commands. This takes a full SQL script and passed the individual commands to DBI::dbExecute().

- dbWipe(): delete all of the tables in a database
- match_files_by_year_months(), extract_date_from_filename(), and valid_year_month() assist with working with dates—specifically in conjunction with files that may encode dates in their names (e.g., 201307-citibike-tripdata.zip)
- smart_download() and smart_upload(): only download and upload files
 that don't already exist
- src_mysql_cnf() use the ~/.my.cnf configuration file to connect to MySQL

4 ETL ecosystem

In this section we list **etl**-dependent packages for PAMDaS that are in various stages of development. The **citibike** package illustrates how reproducibility of published research in the natural and social sciences might be improved through use of the **etl** framework.

4.1 PAMDaS accessible via etl

The following etl-dependent packages are available on GitHub:

- macleish weather and spatial data from the Smith College MacLeish Field Station in Whately, MA (Baumer et al., 2017a)
- airlines on-time flight data from the Bureau of Transportation Services for all domestic flights since October 1987 (Baumer, 2017a)
- imdb a mirror of the Internet Movie Database (Baumer, 2017b)
- nyc311 calls to New York City's non-emergency municipal services hotline (Baumer and Li, 2017)
- fec campaign finance contributions and spending from the Federal Election Commission (Baumer and Gjekmarkaj, 2017)
- citibike trip data for New York City's municipal bike sharing service (Baumer et al., 2017b)

We suggest that these packages can be developed more rapidly using the **etl** framework than would otherwise have been possible. In some cases, these packages can be reduced to a few lines of R code.

4.2 An example using Citi Bike

The lack of reproducibility in published scientific research in the natural and social sciences is problematic. Here, we revisit a series of operations research efforts analyzing load balancing for stations in the Citi Bike municipal bike sharing system in New York City (O'Mahony and Shmoys, 2015; Singhvi et al.,

2015; O'Mahony, 2015) and demonstrate how the etl framework improves data analytic workflows. The data from this system has fueled several research efforts since its launch in July 2013.

The system's engineers face a problem balancing the load of bikes among stations. Since one cannot ensure that bikes rented from one station will be returned to that station, how can one ensure that there will always be enough bikes at a particular station to meet demand?

Singhvi et al. (2015) provided the following description of their data set:

We obtained bike usage statistics for April, May, June and July 2014 from Citi Bike's website (https://www.citibikenyc.com/system-data). This dataset contains start station id, end station id, station latitude, station longitude and trip time for each bike trip. 332 bike stations have one or more originating bike trips. 253 of these are in Manhattan while 79 are in Brooklyn (left panel of Figure 1). We processed this raw data to get the number of bike trips between each station pair during morning rush hours.

This is a fairly specific description of how the data were acquired, since it cites a URL, a specific date range, and the exact number of stations present. However, it is still insufficient information for someone else to verify that they were working with the same data set.

Using the citibike package, we can attempt to reproduce this data set by creating a connection to a database, initializing it, and then populating that database with a single command:

```
bikes %>%
etl_update(years = 2014, months = 4:7)
```

Running the following pipeline confirms the number of unique stations.

```
trips <- bikes %>%
   tbl("trips")
trips %>%
   group_by(Start_Station_ID) %>%
   summarize(num_trips = n()) %>%
   filter(num_trips >= 1) %>%
   collect() %>%
   nrow()
## [1] 332
```

How confident are you that we now have a copy of the same data as these researchers? Behind the scenes, the authors certainly wrote code to download and process these data from the Citi Bike website. Indeed, they admit as much in the last sentence of the quotation above. Moreover, the figures in the paper were clearly produced in R. Thus, this research provides a perfect instance where the use of the citibike package could have standardized the exact data set upon which their research is based. The inclusion of a few short lines of code would ensure that all parties are analyzing the same data set.

Faghih-Imani and Eluru (2016) model bike demand using spatio-temporal data from the Citi Bike system. Their description of the data is less specific than that of Singhvi et al. (2015), however they include an appendix containing some summary statistics. There is no clear way to verify the integrity of the data set. They write:

We focused on the month of September, 2013; i.e. the peak month of the usage in 2013. Therefore, the final sample consists of 237,600 records (330 stations \times 24 hours \times 30 days).

Here again, a single call to etl_update() could have ensured that all users have the same data set:

```
etl_update(bikes, year = 2013, months = 9)
```

The number of records reported is somewhat misleading, since many stations had no trips during some hours of some day. In fact, the following pipeline returns only 167,258 records. Here, we use the lubridate package for assistance with dates, and the dplyr::collect() function to bring the data into R for summarization. (Note, however, that the filter() operation is actually performed by MySQL.)

```
library(lubridate)
system.time(
trips_sept <- trips %>%
  filter(YEAR(Start_Time) == 2013) %>%
  collect() %>%
  group_by(Start_Station_ID, day(Start_Time), hour(Start_Time)) %>%
  summarize(N = n(),
            num_stations = n_distinct(Start_Station_ID),
            num_days = n_distinct(yday(Start_Time)))
)
##
      user
            system elapsed
##
   22.472
            0.520 27.100
nrow(trips_sept)
## [1] 167258
```

Or, we can have SQL do all the work. Note that the capitalized functions here are MySQL functions—not R functions. The latter method is much faster since it only has to transfer 167 thousand records instead of more than 1 million. The delay with the first method is noticeable enough to start a conversation about scalability.

```
system.time(
trips_sept <- trips %>%
  filter(YEAR(Start_Time) == 2013) %>%
  group_by(Start_Station_ID, DAY(Start_Time), HOUR(Start_Time)) %>%
  summarize(N = n(),
            num_stations = COUNT(DISTINCT(Start_Station_ID)),
            num_days = COUNT(DISTINCT(DAYOFYEAR(Start_Time)))) %>%
  collect()
)
##
      user
            system elapsed
##
     0.260
             0.012
                     2.859
nrow(trips_sept)
## [1] 167258
```

In both cases, our ability to verify the data used by these researchers was greatly aided by the citibike package. Moreover, because the citibike package employs the etl grammar and fits into the tidyverse, it is far easier to use than say, a bash script posted on one of these researchers' website.

5 Conclusion

5.1 Future Work

The etl package does not solve all problems for those working with medium data. There is considerable room for improving the performance of the etl package itself. First, some of the ETL operations should be parallelizable. In particular, etl_transform() is a good candidate, since it is always working locally. Conversely, in many cases the bottleneck for etl_extract() will be the user's Internet connection, while for etl_load(), the database engine may not support simultaneous imports to the same table. Second, reading and writing data files to the disk is time-consuming. It is possible that new file formats such as feather could reduce latency (Wickham, 2016a). Third, the data ends up being stored on disk three times: once in its raw format (hopefully compressed), once as a CSV (uncompressed), and once in the database's native file format (optimized). Importing the compressed files directly into the database may be possible in some cases, but care must be taken to ensure the predictability of these functions. Using symbolic links rather than copying files might also be

appropriate in some cases. One can of course use etl_cleanup() to delete either or both of the first two instances, but perhaps a more streamlined process is possible, at least in some cases.

The etl package fuels rapid development of these packages, even among novice R developers. We know this because many of the etl-dependent packages reference above were partially developed by undergraduate students. A broad adoption of these etl-dependent packages and a larger installed user base would increase interest in the project and lead to a more robust infrastructure. We plan to continue this work in the future.

5.2 Discussion

As data grow larger and larger, more and more people will need to develop the skills necessary to work with them. Yet there is limited room in the undergraduate curriculum for such training. Moreover, exposing students to truly big data requires expensive technical infrastructure, training, and support that will remain burdensome to many faculty members for the foreseeable future. A more realistic approach towards helping students develop their capacity to work with larger data sets is to focus on medium data (rather than big data). These data are still challenging and will still help students develop their understanding of scalability issues, while at the same time having a much lower barrier to entry for both students and faculty.

At the same time, producing reproducible research on medium data is more difficult than it is on small data—and many researchers already have a hard time with that. As medium and big data become more prevalent in published research, we must not soften our insistence on reproducibility.

We propose this **etl** package as a mechanism for facilitating reproducible research on medium data for R users. This has the dual benefit of lowering barriers to entry (minimal SQL required) for larger and more complex data sets, while simultaneously aiding the reproducibility of any subsequent research.

References

- Z. W. Almquist. Us census spatial and demographic data in R: The UScensus2000 suite of packages. *Journal of Statistical Software*, 37(6):1–31, 2010. URL http://www.jstatsoft.org/v37/i06/.
- American Statistical Association Undergraduate Guidelines Workgroup. 2014 Curriculum Guidelines for Undergraduate Programs in Statistical Science. American Statistical Association, 2014. http://www.amstat.org/education/curriculumguidelines.cfm.
- G. В. Anderson and D. Eddelbuettel. Hosting Data Packvia drat: А Study Hurricane ages Case with Expo-Rsure Data. TheJournal, 9(1):486-497, 2017.URL https://journal.r-project.org/archive/2017/RJ-2017-026/index.html.

- S. M. Bache and H. Wickham. magrittr: A Forward-Pipe Operator for R, 2014. URL https://CRAN.R-project.org/package=magrittr. R package version 1.5.
- R. Ball and N. Medeiros. Teaching integrity in empirical research: A protocol for documenting data management and analysis. *The Journal of Economic Education*, 43(2):182–189, 2012. doi: 10.1080/00220485.2012.659647. URL http://dx.doi.org/10.1080/00220485.2012.659647.
- B. Baumer, M. Çetinkaya Rundel, A. Bray, L. Loi, and N. J. Horton. R Markdown: Integrating a reproducible analysis tool into introductory statistics. *Technology Innovations in Statistics Education*, 8(1), 2014. URL http://escholarship.org/uc/item/90b2f5xh.
- B. S. Baumer. etl: Extract-Transform-Load Framework for Medium Data, 2016. URL http://github.com/beanumber/etl. R package version 0.3.3.
- B. S. Baumer. *airlines: Historical On-time Flight Data*, 2017a. URL http://github.com/beanumber/airlines. R package version 0.2.2.9011.
- B. S. Baumer. *imdb: Populate a database with data from the IMDB*, 2017b. URL https://github.com/beanumber/imdb. R package version 0.0.2.9004.
- B. S. Baumer and E. Gjekmarkaj. fec: Campaign finance for Federal Elections, 2017. URL http://github.com/beanumber/fec. R package version 0.0.0.9010.
- B. S. Baumer and W. Li. nyc311: Access the NYC 311 Data, 2017. R package version 0.0.1.9002.
- B. S. Baumer, R. Goueth, W. Li, W. Zhang, and N. Horton. macleish: Retrieve Data from MacLeish Field Station, 2017a. URL http://github.com/beanumber/macleish. R package version 0.3.1.
- B. S. Baumer, W. Li, and W. Zhang. *citibike: Data about bike rentals in NYC*, 2017b. URL http://github.com/beanumber/citibike. R package version 0.1.0.9004.
- C. Boettiger, S. Chamberlain, E. Hart, and K. Ram. Building software, building community: lessons from the ropensci project. *Journal of Open Research Software*, 3(1), 2015.
- J. Claerbout. Hypertext documents about reproducible research. Technical report, Stanford University, 1994. URL http://sepwww.stanford.edu/sep/jon/nrc.html.
- R. D. De Veaux, M. Agarwal, M. Averett, B. S. Baumer, A. Bray, T. C. Bressoud, L. Bryant, L. Z. Cheng, A. Francis, R. Gould, A. Y. Kim, M. Kretchmar, Q. Lu, A. Moskol, D. Nolan, R. Pelayo, S. Raleigh, R. J. Sethi, M. Sondjaja, N. Tiruviluamala, P. X. Uhlig, T. M. Washington, C. L.

Wesley, D. White, and P. Ye. Curriculum guidelines for undergraduate programs in data science. Annual Review of Statistics and Its Application, 4(1):1-16, 2017. doi: 10.1146/annurev-statistics-060116-053930. URL http://www.annualreviews.org/doi/abs/10.1146/annurev-statistics-060116-053930.

- D. L. Donoho. An invitation to reproducible computational research. *Biostatistics*, 11(3):385-388, 2010. URL https://academic.oup.com/biostatistics/article/11/3/385/257703.
- D. L. Donoho, A. Maleki, I. U. Rahman, M. Shahram, and V. Stodden. Reproducible research in computational harmonic analysis. *Computing in Science* & Engineering, 11(1), 2009.
- S. P. Eckel and R. D. Peng. Interacting with local and remote data repositories using the stashr package. *Computational Statistics*, 24(2):247–254, 2009.
- D. Eddelbuettel and R. François. Rcpp: Seamless R and C++ integration. *Journal of Statistical Software*, 40(8):1-18, 2011. URL http://www.jstatsoft.org/v40/i08/.
- S. J. Eglen, B. Marwick, Y. O. Halchenko, M. Hanke, S. Sufi, P. Gleeson, R. A. Silver, A. P. Davison, L. Lanyon, M. Abrams, et al. Toward standard practices for sharing computer code and programs in neuroscience. *Nature Neuroscience*, 20(6):770–773, 2017.
- A. Faghih-Imani and N. Eluru. Incorporating the impact of spatio-temporal interactions on bicycle sharing system demand: A case study of new york citibike system. *Journal of Transport Geography*, 54:218–227, 2016.

M. Fuentes, 7 2016. URL http://magazine.amstat.org/blog/2016/07/01/jasa-reproducible16/.

- J. Hardin, R. Hoerl, N. J. Horton, D. Nolan, B. Baumer, O. Hall-Holt, P. Murrell, R. Peng, P. Roback, D. Temple Lang, et al. Data science in statistics curricula: Preparing students to 'think with data'. *The American Statistician*, 69(4):343-353, 2015. URL http://www.tandfonline.com/doi/abs/10.1080/00031305.2015.1077729.
- N. J. Horton, B. S. Baumer, and H. Wickham. Setting the stage for data science: integration of data management skills in introductory and second courses in statistics. *Chance*, 28(2), 2015. URL http://chance.amstat.org/2015/04/setting-the-stage/.
- J. P. Ioannidis. Why most published research findings are false. *PLoS medicine*, 2(8):e124, 2005.
- K. E. Kline, D. Kline, B. Hunt, and D. Heymann-Reder. *SQL in a Nutshell*. O'Reilly: Sebastopol, CA, 2005.
- D. E. Knuth. Literate programming. The Computer Journal, 27(2):97–111, 1984.

- B. Marwick. Computational reproducibility in archaeological research: Basic principles and a case study of their implementation. *Journal of Archaeological Method and Theory*, 24(2):424–450, 2017.
- K. Müller and H. Wickham. *tibble: Simple Data Frames*, 2017. URL https://CRAN.R-project.org/package=tibble. R package version 1.3.3.
- K. Müller, H. Wickham, D. A. James, and S. Falcon. RSQLite: 'SQLite' Interface for R, 2017. URL https://CRAN.R-project.org/package=RSQLite. R package version 2.0.
- E. O'Mahony and D. B. Shmoys. Data analysis and optimization for (citi) bike sharing. In AAAI, pages 687–694, 2015.
- E. D. O'Mahony. *Smarter tools for (Citi) bike sharing*. PhD thesis, Cornell University, 2015.
- T. J. T. F. on Computing Curricula. Curriculum guidelines for undergraduate degree programs in computer science. Technical report, Association for Computing Machinery (ACM) and IEEE Computer Society, 12 2013. URL http://www.acm.org/education/CS2013-final-report.pdf.
- J. Ooms, D. James, S. DebRoy, H. Wickham, and J. Horner. *RMySQL: Database Interface and 'MySQL' Driver for R*, 2017. URL https://CRAN.R-project.org/package=RMySQL. R package version 0.10.12.
- R. D. Peng and F. Dominici. Statistical methods for environmental epidemiology with R. Springer: New York, 2008. URL https://link.springer.com/content/pdf/10.1007/978-0-387-78167-9.pdf.
- R Special Interest Group on Databases (R-SIG-DB), H. Wickham, and K. Müller. *DBI: R Database Interface*, 2016. URL https://CRAN.R-project.org/package=DBI. R package version 0.5.
- С. Sievert. Taming pitchf/x with pitchRx data and XML2R. The2014.RJournal, 6(1),URL http://journal.r-project.org/archive/2014-1/sievert.pdf.
- D. Singhvi, S. Singhvi, P. I. Frazier, S. G. Henderson, E. OMahony, D. B. Shmoys, and D. B. Woodard. Predicting bike usage for New York City's bike sharing system. In AAAI 2015 Workshop on Computational Sustainability. Citeseer, 2015.
- K. Walker and B. Rudis. Tigris: Load Census TIGER/Line Shapefiles into R, 2017. URL https://CRAN.Rproject.org/package=tigris. R package version 0.3.3.
- H. Wickham. ggplot2: Elegant Graphics for Data Analysis. Springer Verlag: New York, NY, 2009. ISBN 978-0-387-98140-6. URL http://ggplot2.org.

- H. Wickham. *hflights: Flights that departed Houston in 2011*, 2013. URL https://CRAN.R-project.org/package=hflights. R package version 0.1.
- H. Wickham'. nasaweather: Collection of datasets from the ASA 2006 data expo, 2014. URL https://CRAN.R-project.org/package=nasaweather. R package version 0.1.
- H. Wickham. *R packages*. O'Reilly Media, Inc.: Sebastopol, CA, 2015. URL http://r-pkgs.had.co.nz/.
- H. Wickham. *feather:* R Bindings to the Feather 'API', 2016a. URL https://CRAN.R-project.org/package=feather. R package version 0.3.1.
- H. Wickham. nycflights13: Flights that Departed NYC in 2013, 2016b. URL https://CRAN.R-project.org/package=nycflights13. R package version 0.2.0.
- H. Wickham. *dbplyr: A 'dplyr' Back End for Databases*, 2017a. URL https://CRAN.R-project.org/package=dbplyr. R package version 1.1.0.
- H. Wickham. tidyverse: Easily Install and Load 'Tidyverse' Packages, 2017b. URL https://CRAN.R-project.org/package=tidyverse. R package version 1.1.1.
- H. Wickham and R. Francois. *dplyr: a grammar of data manipulation*, 2016. URL https://github.com/hadley/dplyr. R package version 0.5.0.9000.
- L. Wilkinson, D. Wills, D. Rope, A. Norton, and R. Dubbs. *The grammar of graphics*. Springer, 2006.
- V. V. Williams. Multiplying matrices faster than coppersmith-winograd. In Proceedings of the forty-fourth annual ACM symposium on Theory of computing, pages 887–898. ACM, 2012.