Test Smell: A Parasitic Energy Consumer in Software Testing

Md Rakib Hossain Misu, Jiawei Li, Adithya Bhattiprolu, Yang Liu, Eduardo Almeida, and Iftekhar Ahmed

Abstract—Traditionally, energy efficiency research has focused on reducing energy consumption at the hardware level and, more recently, in the design and coding phases of the software development life cycle. However, software testing's impact on energy consumption did not receive attention from the research community. Specifically, how test code design quality and test smell (e.g., sub-optimal design and bad practices in test code) impact energy consumption has not been investigated yet. This study examined 12 Apache projects to analyze the association between test smell and its effects on energy consumption in software testing. We conducted a mixed-method empirical analysis from two dimensions; software (data mining in Apache projects) and developers' views (a survey of 62 software practitioners). Our findings show that: 1) test smell is associated with energy consumption in software testing. Specifically smelly part of a test case consumes 10.92% more energy compared to the non-smelly part. 2) certain test smells are more energy-hungry than others, 3) refactored test cases tend to consume less energy than their smelly counterparts, and 4) most developers lack knowledge about test smells' impact on energy consumption. We conclude the paper with several observations that can direct future research and developments.

Index Terms—Test Smell, Energy, Green Software Engineering

I. INTRODUCTION

TODAY, millions—if not billions—of software applications govern countless aspects of our lives. These software consume energy while being used as well as while being developed. Energy consumption of the software products and services sector reached 15% of the world's total energy consumption in 2020 [1], and it is predicted to be responsible for 20% of global energy usage by 2025 [2], [3]. Therefore, the software sector has already become one of the major contributors (2.3%) of global Green House Gases [4] and growing at a much faster rate than initially predicted [5], [6]. So it is critical to understand and control energy consumption and ultimately reduce Green House Gas production due to software, while it is being developed and used, to ensure the future of human life on Earth [7].

The primary focus of research pertaining to energy-efficient solutions has been on the optimization of the hardware with the aim of making it more energy-efficient for executing software. [8]–[11]. More recently, energy consumption incurred by software executions and software runtime performance [12], [13], especially in mobile [14]–[16] and embedded software

Md Rakib Hossain Misu (Corresponding author), Jiawei Li, Adithya Bhattiprolu, Yang Liu and Iftekhar Ahmed are with the Donald Bren School of Information and Computer Sciences, University of California Irvine, Irvine CA, USA [17], received more attention from the research community as energy efficiency is crucial for mobile applications and embedded systems.

Another thread of research investigated various aspects of the Software Development Life Cycle (SDLC) and their association with energy efficiency [6], [18]. For instance, in the design and coding phase, following a software architecture, applying a design pattern [19]–[23], adopting a specific programming language and framework all have impact on energy consumption [24]–[26].

Prior work however is limited to only some phases of the SDLC and provides a fragmented view of the possible energy-efficient techniques associated with the SDLC. For example, none of the existing work has looked into the effect of testing on energy consumption even though millions of lines of test code that test various aspects of software [27] are being executed daily in developers' IDEs or in the Continues Integration (CI) pipeline [28], which consume a considerable amount of energy every day [29].

Our goal is to investigate the effect of test code on software energy consumption during software testing. We posit that a bad test case design (a.k.a, a test smell [30]–[32]) contributes to higher energy consumption than required due to the suboptimal design induced unnecessary energy overhead.

Figure 1 demonstrates a motivating example that shows how the presence of test smells can significantly increase the energy consumption of running the test suite. The example code snippet represents a General Fixtures (GF) test smell [33] that occurs when a test class contains a setUp() method that may not be directly relevant to the executed test case, that is, the test case testRangeOfChats() has never utilized any field variables initialized in the setUp() method. However, the setUp() is invoked before every execution of this test case. Consequently, the presence of this test smell can lead to additional computations and memory usage because of unnecessary setup and teardown operations. While the direct impact may not be significant for individual test runs, the cumulative effect can substantially affect energy consumption in large-scale software projects with extensive test suites and frequent test executions.

A plethora of studies have investigated test smells' impacts on software maintainability, comprehension, and defect proneness [34]–[36]. Researchers also investigated automated test smell detection [37]–[39], and refactoring [40]–[43]. However, to the best of our knowledge, no study has investigated the association between test smell and software energy consumption. Given the widespread prevalence of test smells [35], and developers' unawareness regarding the relation between test

Eduardo Almeida is with the Federal University of Bahia, Salvador, Brazil

General Fixture (GF) Test Smell

```
public class IntegerRangeTest extends AbstractLangTest {
   private IntegerRange range1, range2, range3, rangeFull;
   /**Initializing field variables before each test method**/
   @BeforeEach
   public void setUp() {
       range1 = of(10, 20);
       range2 = of(10, 20);
       range3 = of(-2, -1);
       rangeFull=of(Integer.MIN_VALUE, Integer.MAX_VALUE);
   }
   . . . . . . . . . . . .
    /** Field variables were never utilized in test method**/
   @Test
   public void testRangeOfChars() {
       final IntegerRange chars = of('a', 'z');
       assertTrue(chars.contains((int) 'b'));
       assertFalse(chars.contains((int) 'B'));
   }
3
```

Figure 1. An Example of Smelly Test in Apache Commons-Lang Project.

smell and energy consumption as indicated by some of the respondents in our survey "*I have no idea how these things are related to each other*"[*S*-6]¹ or "*They seem like two unrelated concepts*."[*S*-17], it is of utmost importance that developers and researchers are aware of the relationship between test smell and energy consumption. Our study aims to take the first step toward achieving that goal.

In this paper, we aim to contribute to the literature by providing a comprehensive study on the impact of test smells on software energy consumption. We design the study from two perspectives, software and developer. We first investigate whether the smelly test code in a test case consumes more energy than its clean part. If so, does a test case with more test smell instances consume more energy than the ones with less smell instances (software) (RQ1). We conducted a case study where we manually removed the test smells to create test cases without smells. We analyzed the energy consumption difference between clean and smelly test cases that test the same functionality to explore the impact of test smells on energy consumption. To further understand different test smell types' impacts on energy consumption, we conduct a correlation analysis between the number of instances of each test smell type and an estimate of energy consumption per smell instance. The goal is to see which test smell types are the most energy-hungry (software) (RQ2).

Finally, we collected developers' perceptions of test smells' impacts on energy consumption and the underlying reasons for them to introduce such test smells (*developers' views*) (RQ3, RQ5). In addition, we also perform empirical analysis to explore who is the most responsible for introducing the energy-hungry test smells (*developers' views*) (RQ4).

Overall this paper makes the following contributions:

- We conduct the first study to investigate the association between test smell and energy consumption in software testing.
- 2) We present the findings of a survey with 62 software practitioners that reflect the developers' perception of

test smell and its impact on software energy consumption.

 We perform data analysis to identify the most responsible developer group (core, non-core, and bot) for introducing energy-hungry test smells.

The paper is structured as follows: we describe the prior research on test smell's impact and software energy efficiency in Section II, followed by our approach of detecting test smells in software repositories, profiling energy consumption, and surveying developers for understanding developers' views in Section III. In Section IV, we present our analysis and finding, and Section V provides the results' implications for researchers and software developers.

II. RELATED WORKS

A. The Impact of Test Smells

Test smells refer to symptoms of sub-optimal design choices or bad programming practices in software test code [30]. Researchers have defined various types of test smells that occur in large software projects, such as Assertion Roulette (AR), Lazy Test (LT), and Mystery Guest (MG) etc [30]-[32]. These smells have been proven to have a negative effect on test quality [44]. The impacts of test smell on software readability, understandability, maintainability, and performance have also been widely studied in literature [36], [45]. For example, Bavota et al. [33] conducted experiments to investigate the impact of test smells on program comprehension. Their results showed that test smells have a negative impact on both the comprehensibility and maintainability of the test code. Spadini et al. [46] found that smelly test cases are more change- and defect-prone, and they could cause the tested production code to be more defect-prone. However, no existing research has investigated the impacts of test smells on energy consumption in software testing.

B. Software Energy Efficiency

Building software that is more energy-efficient has become an integral concern in improving sustainability. In the past, researchers have been trying to identify the factors that might lead to energy inefficiencies in software [47]-[51]. Liu et al. [52] found that wakelock deactivation and missing sensors as two of the main causes of energy inefficiencies in Android applications. Baberhee et al. [53] proposed several guidelines to refactor Android apps affected by energy-oblivious design practices, such as balancing the quality of service and functionality and restricting resource leaks. Bruce et al. [54] employed search-based software engineering techniques to automatically identify more energy-efficient versions of the MiniSAT Boolean satisfiability solver. Manotas et al. [55] built a framework that improves the energy efficiency of Java software by automatically using the most energy-efficient library implementations. Such energy-aware implementations made in practice have also been explored and analyzed by Moura et al. [56], which suggests that developers mostly utilize low-level energy management approaches such as idleness.

More recently, Song et al. [48] defined four anti-patterns of service usage inefficiency in Android applications, including

¹Here [S-6] refers to our survey respondent's anonymous Id.

premature create, late destroy, premature destroy, and service leak, which could lead to high energy consumption. Song et al. [50] found that the high average energy consumption is due to some methods that are frequently invoked by test cases (i.e., energy hotspots). In addition, Li et al. [51] explored various root causes of energy issues in mobile apps, such as unnecessary workload and wasted background processing. However, none of the existing works have investigated the antipatterns/bad practices in software testing that could contribute to energy overhead, and we aim to fill that gap.

III. METHODOLOGY

This study aims to understand how the test code quality measured by test smells affects energy consumption. Figure 2 demonstrates the overview of our study design. Specifically, we seek to answer the following research questions.

- **RQ1** [Test Smells vs. Energy]: How do smelly tests, in general, impact energy consumption?
- **RQ2** [Test Smell Types vs. Energy]: How does each test smell type impact energy consumption?
- **RQ3** [Developers' Awareness]: Are developers aware of the impact of test smells on energy consumption?
- **RQ4** [Developers' Group]: Who is the most responsible for introducing energy-hungry test smells?
- **RQ5** [**Provenance of Test Smell**]: What are the underlying reasons for developers to introduce test smells that could cause unnecessary energy consumption?

In the following sections, we describe the processes we carried out to answer these research questions, such as selecting subject systems, mining test smell instances, profiling energy consumption in both smelly and refactored test case executions as well as conducting a developer survey.

A. Subject Systems

In this phase, we selected the subject systems that satisfy our selection criteria and experimental attributes.

1) Project Selection: We started our experiment with a sample of 44 open-source Java software projects from the Apache Software Foundation [57]. We decided to select these projects for three reasons. First, we chose the Apache projects as these projects are well-maintained and supported by a large developer community. Besides, numerous prior research works have been conducted on these Apache projects [58]. Second, we selected projects written in Java since it is considered one of the most widely-used programming languages [59]. Third, in the literature, most of the test smell detection tools are available for Java compared to other languages [60]. For our analysis, we needed to build the projects and execute the test cases. To avoid complications related to building a project, we selected projects using Maven [61] as its build system. Next, we selected projects that use JUnit [62] as the unit testing framework, since it is one of the most widely-used unit testing frameworks for Java. We identified 25 projects that met all these criteria.



Figure 2. Overview of The Study Design with Experimental Phases

2) Unit of Measure Selection: We decided to perform our analysis at the test case granularity to analyze test code quality and measure energy consumption. According to JUnit documentation, a method in the test code with @Test annotation represents a test case, and it can be executed inside the complete test suit or explicitly invoked with its Fully Qualified Name (FQN) from the command line. To locate a test case and its Lines Of Code (LOC), we employed the static code analysis technique utilizing the Eclipse JDT Core Abstract Syntax Tree (AST) traverse tool [63]. These projects allowed us to run each test case individually with the help of Maven and JUnit. During the execution, we discarded a project if a test case failed to execute independently.

Following this process, we recognized a subset of 12 projects where all test cases are executable independently and from the command line. Finally, we ended up with 12 Apache Java projects with 13,103 test cases in total. Table I exhibits the summary of the selected projects' statistics.

B. Test Smell Detection

1) **Tool Selection:** In the literature, researchers have proposed various test smell detectors where we found 18 tools that can detect test smells in JUnit-based Java projects [60]. We observed that among these tools, tsDetect [64] can detect the presence of 19 types of test smells, achieving the highest precision and recall [60], [64]. However, in the test smell detection report, tsDetect does not provide the locations of the smells in the test code.

In our study, we are interested in analyzing both the smelly and non-smelly parts of the test code. Therefore, we searched for an extension of tsDetect that can also identify test smell locations in the test code. We encountered JNose [37], which has reused the same test smell detection rules employed in tsDetect and can detect 21 types of test smells, including the 19 types of tsDetect detected smells. In addition, JNose provides the locations (i.e., line numbers) and test case names where a test smell is identified in the test code and the number of each type of test smell identified in a test class. To assess

TABLE ISUBJECT SYSTEMS' STATISTICS

Dimension	Min	Median	Max	Average
Loc	101111 (252		1V1ax	Average
LOC	6,253	32,253.50	89,748	34,522.33
#Files	48	186.50	606	290.91
#Test Cases	141	657.50	4,067	1,091.91
#Developers	24	40.50	68	40.83
#Commits	878	2,124	7,050	2,540.08

the correctness of JNose in terms of precision and recall, we utilized a benchmark of 65 JUnit test files containing instances from various smell types. This benchmark has been created and employed in an earlier qualitative study to evaluate tsDetect [64]. We executed JNose on that benchmark dataset and compared its test smell detection results with tsDetect. We observed that both JNose and tsDetect got the same overall precision score ranging from 85% to 100% and a recall score from 90% to 100% with an average F-score of 95%.

Besides, we also found that JNose has successfully been adopted by researchers in many recent studies [65]–[67]. This inspired us to utilize JNose in our experiment. A summary of JNose-detected test smells is demonstrated in Table II.

2) Mining Test Smells: To detect and locate test smells in a given repository, JNose first parses the source code into Abstract Syntax Tree (AST) and then traverses the AST applying detection rules for identifying test smells [37]. Once the detection is completed, JNose generates a report containing information, for instance, test class, number of different types of smells, smelly test cases, and the source code line numbers where the test smell appears. Our experiment requires detecting the presence of different test smells in each test case. To do so, we executed JNose on the subject systems. Utilizing these reports, in a test case, we extracted the instance of various test smells and counted the total number of smell instances, smell count (SC). In total, we detected 56,908 test smell instances in 12 projects, and the frequency of each type of smell is shown in Table II. We also parsed the location where these smells were identified and calculated the smelly line of code $(LOC_{(smell)})$ and clean line of code $(LOC_{(clean)})$ of a test case. At the end of this phase, we created a tuple of the test case, LOC, $LOC_{(smell)}$, LOC(clean), SC, and the count of each type of test smell, such as: $testcase \rightarrow \{LOC, LOC_{(smell)}, LOC_{(clean)}, SC, \}$ $s_1, s_2, s_3, \dots s_{21}$

C. Energy Measurement

In this stage, we executed each test case with a profiler that monitors the energy consumption rate during the test case execution.

1) Experimental Environment Setup: To create an experimental environment and conduct our analysis, we used five MacBook Airs (13-inch, Mid-2012) laptops. All these laptops have the same hardware configuration containing a 1.8GHz dual-core Intel® CoreTM i5 processor, 8GB RAM, and 256 GB SSD running macOS Catalina 10.15.7. To support the build configuration and test case execution of projects, we used Maven 3.8.6 build system.

2) *Energy Profiler*: We used Intel PowerLog to measure the energy consumption [68]. It is a command-line tool provided by the Intel Power Gadget toolkit, a power usage monitoring tool. Intel PowerLog precisely estimates power usage from a software level without any hardware instrumentation [68]. It is supported on macOS to monitor and assess real-time processor package power information using the energy counters in the Intel® CoreTM processors [68]. The primary motivation for adopting Intel PowerLog is that it provides a convenient technique to measure processor power usage while executing a specific command in the command line and storing energy profiling into a log file. The log file contains values representing energy, power, and the total time duration in a sequence of times lap, including the total energy consumption E(Joules), required power P(Watt), and entire time duration T(sec), respectively. Since it measures these metrics while executing a specific user command at the process level, it minimizes the effects of other processes. Moreover, Intel PowerLog has been used in prior research, increasing the confidence in using this for our analysis [69]. We installed the latest Intel PowerLog version: 3.7.0, on all these laptops.

3) Test Case Execution: We ran each test case with the mvn test -Dtest="<test case FQN>" command while monitoring energy usage using the Intel PowerLog. To minimize external interference, we configured the laptops to Zen Mode [69] before executing the test cases which prevents these laptops from interacting with external networks, and devices. We maintained the following configurations on each laptop to keep it in Zen Mode during the execution of the test cases.

- We fully charged the laptop to 100% (■). However, to provide equal battery capacity for test case runs, we kept the laptop plugged (♥) in throughout the experiment.
- All active applications were quit and unnecessary background services were killed except the terminal (≻_). The auto-dim of an inactive screen was turned off. The screen saver was set up to appear for one hour, and the sleep time was set *never* to prevent the laptop from falling into sleep mode. Microphone (★) and Speaker (◀*) were also turned off.
- Automatic adjusting of brightness was turned off. Brightness (♣) was also lowered to 50%, and the keyboard lighting, automatic logged out, notifications, AirDrop, Bluetooth (♣), and WiFi (♠) were turned off.

In order to obtain accurate energy measurements, it was necessary to execute a test case multiple times with the Intel PowerLog while the assigned laptop was in Zen Mode. We conducted a preliminary experiment to determine the ideal number of test case runs for reliable energy measurements. Initially, we employed a stratified random sampling, aiming for a 90% confidence interval and a 10% margin of error that led us to select 68 test cases out of 13,103 test cases. Subsequently, we designed a script that automates the execution of a test case with Intel PowerLog for a predetermined number of iterations, incorporating a 30-second cool-down interval after each run. The cool-down period prevents both tail energy consumption from the previous measurement and the collateral tasks of the last execution from affecting the subsequent measurement.

Next, we executed that script to run each sampled test case 5, 15, and 25 times. From the resulting log files, we individually extracted the median values of energy E(Joules), power P(Watts), and time T(seconds). We generated a plot illustrating the relationship between the number of runs and the median energy values. Our analysis revealed that the median values exhibited insignificant variances when the

ID	Test Smell Name	Abbreviation	Definition	Frequency
<i>s</i> ₁	Assertion Roulette	AR	Appears when a test case contains several assertions without explanation messages.	
s_2	Lazy Test	LT	Appears when multiple test cases check the same method of a production object	
s_3	Magic Number Test	MNT	Appears when a test case contains undocumented numerical values	
s_4	Eager Test	ET	Occurs when a test case invoking multiple methods of the product object to be tested	
s_5	Duplicate Assert	DA	Appears when a test case has the identical assertion multiple times.	2.95%
s_6	Sensitive Equality	SE	Appears when a test case has an assertion that checks equality with toString method	2.34%
s_7	Conditional Test Logic	CTL	Occurs when a test case contains a conditional statement like (i.e., if/else) as a	
			prerequisite to executing other test statements	
s_8	Unknown Test	UT	Appears when a test case has no assertions statement or non-descriptive name	2.18%
s_9	Exception Handling	EH	Found when a test case includes custom exception handling instead of utilizing JUnit's	2.08%
			exception handling features	
s_{10}	General Fixture	GF	Emerges when in a test class, the setUp() fixture creates many objects, and the test	0.36%
			case only uses a subset of those objects.	
s_{11}	Redundant Assertion	RA	Occurs if a test case contains an assertion statement that is permanently true or false	0.29%
s_{12}	Ignored Test	IgT	Occurs when a test case has an ignore annotation that prevents the test case's execution.	0.24%
s_{13}	Constructor Initialization	CI	A test class contains a constructor declaration	0.23%
s_{14}	Resource Optimism	RO	Emerges when a test case assumes the existence of external resources.	0.19%
s_{15}	Mystery Guest	MG	Exists if a test case accesses external resources such as a database, directory, or file	0.17%
			that contains test data.	
s_{16}	Verbose Test	VT	Occurs if a test case runs additional staff and becomes complex	0.8%
s_{17}	Sleepy Test	ST	Occurs when a test case calls an explicit wait like Thread.sleep().	0.02%
s_{18}	Empty Test	EmT	Found when a test case has an empty body or does not have executable any statements	0.02%
s_{19}	Redundant Print	RP	Occurs when a test case contains print statements.	0.01%
s ₂₀	Dependent Test	DepT	Arises when a test case only runs on the successful execution of other test cases.	0.0%
s21	Default Test	DT	Default or scaffold test cases created by IDEs or frameworks.	0.0%

 TABLE II

 JNOSE DETECTED TEST SMELLS AND THEIR FREQUENCY IN 12 APACHE PROJECTS

test cases were executed 5, 15, and 25 times, indicating overall consistency. Based on these experimental findings, we determined that the number of runs had no significant impact on the median energy consumption. Consequently, we proceeded with five runs of each test case.

In total, we executed 13,103 test cases five times, each with 30 second cool-down period. The whole experiment took approximately 874 hours (37 days) of execution time on each laptop. We then extracted five generated energy log files for each test case and calculated the median value of energy, power, and time. Thus, for a project, we created a list of test cases with their corresponding energy E(Joules), power P(Watt), and time T(sec) values in the form of tuples as follows: $testcase \rightarrow \{E, P, T\}$.

D. Impact Analysis: Test Smell vs. Energy Consumption

During test smell detection and energy measurement, we generated two types of tuples for the test cases. We then joined them and created a list of test cases with their smell and energy-associated values. This list of tuples helps us analyze test smell's impact on energy consumption.

 $testcase \rightarrow \{LOC, LOC_{(smell)}, LOC_{(clean)}, SC, E, P, T, s_1, s_2, \dots s_{21}\}.$

1) Group Analysis: We first investigated smelly tests' impact on energy consumption. Our goal in this step is to see if the test smells are associated with increased energy consumption. To do so, for each test case, we calculated the energy $E_{LOC(smell)}(Joules)$ required to execute a smelly line of code $(LOC_{(smell)})$ and the energy $E_{LOC_{(clean)}}(Joules)$ for clean line of code $(LOC_{(clean)})$. According to Equations 1 and 2, we computed these energy values. We believe these two values could serve as estimates for the energy consumption of smelly and clean parts of the test code in a test case. Next,

we categorized all the test cases into multiple groups based on their total smell count (SC). The goal is to analyze if more test smell instances increase the energy overhead incurred by test smells. We created these groups with the interval of various smell counts, such as 5, 10, and 25 to mitigate the bias brought upon by selected group size. Then for each group, we calculated mean and median energy consumption of $E_{LOC(smell)}$ to analyze the trend of energy consumption. We also conducted Welch's t-test [70], [71] and Cohen's D [72] to measure the statistical significance and effect size of the differences in energy consumption between different groups.

$$E_{LOC_{(smell)}} = E * \frac{LOC_{(smell)}}{LOC_{(test)}} (Joules)$$
(1)

$$E_{LOC_{(clean)}} = E * \frac{LOC_{(clean)}}{LOC_{(test)}} (Joules)$$
(2)

$$E_{(N)} = \frac{E}{SC}(Joules) \tag{3}$$

2) Correlation Analysis: To further understand how individual test smell type impacts energy consumption, we investigate the relationship between energy consumption and each test smell type. However, we don't have a one-to-one mapping between smell type vs. energy consumption to establish the relationship. We illustrate it by provide an example: Supposes a test case contains 12 test smells (e.g., SC = 12) in 3 different types, for example, $S_1 = 7$, $S_4 = 3$, and $S_{15} = 2$. The energy consumption (E) reflects the complete execution of that test case with the presence of all those 12 test smells. Hence, it is not possible to differentiate which test smell affects what portion of the energy consumption. Therefore, establishing a relation between (E vs. S_1),(E vs. S_4), and (E vs. S_{15}) would not be accurate. To normalize the energy consumption for each smell, we measured the energy consumption per test smell using $E_{(N)}$ according to Equation 3, where SC is the total smell count. For a test case, the normalized value $E_{(N)}$ represents the energy consumption per test smell that relates to its effect on energy consumption. With this one-to-one mapping, we conducted a Kendall's Tau (τ_b) correlation analysis [71] between energy consumption per test smell and the number of test smell instances for each test smell type. We used Kendall's Tau since it has smaller gross error sensitivity and smaller asymptotic variance compared to Spearman correlation [73].

E. Impact Analysis: Case Study of Test Smell Refactoring

To gain a comprehensive understanding of the impact of test smells on energy consumption, we conducted a case study. We began by selecting the largest project from our pool of subject systems. Next, we sampled test cases and manually refactored them to eliminate any existing test smells, creating test case pairs (i.e., with and without test smells) that test the same production code functionality. We executed these refactored test cases using an energy profiler to measure the energy consumption rate. The following subsections provide details of each step undertaken in the case study.

1) Subject Selection: In order to refactor the test cases of a project, it is essential to possess a reasonable comprehension of the project's codebase and its test suite. Nevertheless, comprehending the codebase of all 12 projects from our subject systems and refactoring 21 distinct types of smells in thousands of test cases present a challenging and demanding task. Therefore, we have opted to refactor a random sample of smelly test cases in a single project, which makes the codebase understanding and manual test smell refactoring manageable. For this purpose, we have selected the Apache Commons Lang project due to having the largest number of test cases (4,067), lines of code (89K LOC), and smelly test cases (2,032) among all our subject systems.

2) Sampling Test Cases: Existing literature has demonstrated that certain test smells tend to co-occur together. Refactoring test smells like Lazy Test (LT), Eager Test (ET), and Conditional Test Logic (CTL) often involves modifying multiple test cases or introducing new ones. Consequently, developers may perform partial or complete refactoring. In partial refactoring, developers address some test smells in a test case, reducing the overall number of smells. On the other hand, complete refactoring involves removing all types of smells, resulting in a clean test case. To analyze the impact of energy consumption in both of these situations, we created two types of sampled test cases. These test cases represent the scenarios of partial refactoring, where only some test smells are addressed, and complete refactoring, where all test smells are removed, allowing us to study the energy consumption variations comprehensively.

To analyze the energy impact of partial refactoring, we created a stratified sample of test cases that contain different types of smells. We first determined the size of the random sample by utilizing a 90% confidence interval and a 10%

margin of error, giving us a sample size of 66. In the Apache Commons Lang project, there were a total of 2,032 smelly test cases. We proceeded to select a stratified random sample of 66 test cases from this pool of 2,032 smelly test cases. These 66 test cases contain various types and numbers of test smells. We tagged them as "Smelly-66".

To observe the energy consumption impact of complete refactoring, we filtered out test cases that contained test smells highly associated with energy consumption. Our analysis in Section IV-A2 revealed that certain test smells, namely Assertion Roulette (AR), Lazy Test (LT), and Eager Test (ET), have high correlations with energy consumption, with AR having the highest correlation. However, refactoring ET and LT may require changes in multiple test cases or the introduction of new ones which goes beyond the scope of our study. Therefore, we focused on refactoring test cases that solely contained Assertion Roulette (AR) smells. After filtering, we identified 79 test cases out of the initial 2,032 that only contained AR smells. We tagged these test cases as "Smelly-AR-79" for further analysis.

3) Manual Refactoring of Test Smells: Automated test smell refactoring tools are not yet widely available. We conducted an exhaustive search of the existing literature and found only a few works proposing automated test smell refactoring approaches [74]–[79]. However, none of these works reported any executable tools that we can readily utilize to do the automated test smell refactoring. We contacted the authors of these existing works and received several replies. None of the responses provide the proposed tool. Therefore, we took the refactoring strategies recommended by Soares et al. [78] to refactor some of the test smell categories, namely Assertion Roulette (AR), Conditional Test Logic (CTL), Duplicate Assert (DA), Mystery Guest (MG), and Exception Handling (EH).

Since no automated test smell refactoring tool was available, we manually refactored the collected test cases by following the refactoring strategies proposed by Soares et al. [78]. We performed partial refactoring for the "Smelly-66" test cases, focusing on addressing test smells that could be handled without modifying multiple test cases or introducing new ones. However, we performed complete refactoring for the "Smelly-AR-79" test cases and removed all instances of the Assertion Roulette (AR) smells. Two of the authors collaborated to perform the test smell refactoring together. To ensure that the refactoring changes did not affect other test cases or existing features, we repeatedly executed the regression test suite provided by the project after refactoring. This step was taken to verify that the refactoring process did not introduce regressions or negatively impact the existing functionality. We also ensured that the code coverage did not change after refactoring. We posit that the combination of not introducing regression and unchanged code coverage ensures that the refactored test case is semantically similar to the original test case.

4) **Energy Measurement:** Finally, we have the smelly and refactored version of "Smelly-66" and "Smelly-AR-79" sampled test cases. We executed the refactored test case for five iterations of each test case with a 30-second cool-down period and measured the energy consumption. We describe

the complete process of energy measurement in detail in Section III-C. After the execution, we collected the energy consumption (E) for both smelly and refactored versions of the "Smelly-66" and "Smelly-AR-79" sampled test cases. Finally, we conducted Welch's t-test [70], [71] and Cohen's D [72] to measure the statistical significance and effect size of the differences in energy consumption between smelly and refactored test cases.

F. Developers Survey

To validate our findings and understand developers' perceptions about test smell and its relationship to software energy consumption, we conducted an online survey with software developers. The following subsections describe our survey design, participation selection, pilot survey, data collection, and analysis. This survey was conducted following the guidelines and protocols approved by the Institutional Review Board (IRB).

Survey Design: Our survey consists of 12 questions, including multiple-choice, ranking, and open-ended questions. We began by collecting demographic information from respondents (Q2-Q3) to understand their background and experience in software development and writing unit test cases. We then asked about their familiarity with test smells and their practice writing unit test cases (Q4-Q5). Additionally, we inquired whether they pay attention to test smells (Q6). Next, we investigated the impact of test smells on energy consumption during software testing (Q7-Q8). We identified specific test smells that had a higher energy consumption impact, and participants familiar with these were asked to rate the test smells based on their perceived impact severity on energy consumption (Q8-Q9). Additionally, we inquired whether participants' organizations provide guidelines for monitoring energy consumption during software testing. Participants were asked to mention any tools or services they use to monitor energy consumption during testing (Q10-Q12). A text box option was also provided for respondents if they wanted to share the reason behind their choice. A complete list of questions for this survey is provided on the companion website [80].

Participants Selection: For our survey, we targeted the software developers from the 12 subject Apache projects in our study. To develop a list of survey participants, we mined a list of unique email addresses of contributors from the version control systems. In total, we collected 490 individual email addresses and recognized them as our potential participants. We utilized this email list to send the survey invitation to these developers.

Pilot Survey: To review the survey's validity, we asked Software Engineering professors and graduate students (two professors and two Ph.D. students) with experience in software development, writing unit test cases, and survey design. To enhance the clarity of the questions, we performed several iterations of the survey and rephrased and reorganized some questions according to their feedback. Considering software developers' hectic schedules, we emphasized the time required to complete the survey. We ensure that participants can complete the survey in 8 to 10 minutes. The pilot survey aimed only to improve the questions, and the responses are not included in the reported results.

Data Collection: To distribute our survey, we used Qualtrices [81] as a design and distribution platform. We emailed 490 developers from 12 Apache projects, following our organizational guidelines (with the approved University IRB protocol). To maximize survey participation, we followed the guidelines and best practices described by Smith et al. [82], such as allowing respondents to remain anonymous and sending personalized invitations. After publishing the survey, the survey was kept open for two weeks in total, and meanwhile, we also sent a reminder email at the end of the first week. Within these two weeks, we received completed responses from 62 participants. Overall, we got a response rate of 12.7%, consistent with the prior studies conducted in the software engineering areas [82], [83]. The software development experience of our respondents varies from 1 year to more than 20 years, and 80.6% of them have over two years of software testing experience.

Data Analysis: During the data analysis process, we consider the majority vote from developers as the final overall rating for a specific item. For example, when ranking test smell types in terms of the severity of their impacts on energy consumption, we determine the final ranking based on the majority consensus among the developers' responses. This approach ensures that the final results represent the collective perspective of the surveyed developers.

G. Developer Experience Analysis

One of our research questions was related to investigating whether the developer's experience has any association with creating energy-hungry test smells. We analyzed developers in groups. Following existing software engineering studies [84], we categorized developers into three groups, core developers, non-core developers, and bots. It's widely accepted that a relatively small number of core developers are responsible for more than 80% of the contributions in any open-source project [84]. We used this principle to classify a developer as a core developer if they are among the top 20% of the developers in terms of the number of commits authored and a non-core developer otherwise. In this study, we used emails as developers' identifiers. We collected their emails and contributions by using git commands (i.e., git log) in the downloaded git repositories. In addition, some development activities are performed by automated tools (i.e., bots) that run at specific events. We detected these bots by using the same approach as in [85]. That is, we analyzed the variability of all contributors' commit message writing patterns, and we identified bots if the variability of the messages generated is lower than a threshold proposed by [85].

IV. RESULTS

In this section, we present the results of our study from two complementary perspectives: *Software* and *Developers*'.

A. Software Perspective

We start this section by reporting our findings on how software energy consumption is associated with the presence of test smells.

1) **RO1 [Test Smells vs. Energy]** How do smelly tests, in general, impact energy consumption?: To answer this research question, we first investigate if the smelly part of a test case consumes more energy than its clean part. We calculate the energy consumption for smelly lines of code $(E_{LOC_{(smell)}})$ and clean line of code $(E_{LOC(clean}))$ following Equations 1 and 2 mentioned in Section III-D1 for all smelly test cases in our selected projects. The values $E_{LOC(smell)}$ and $E_{LOC(clean)}$ represent an estimate of the energy consumption for smelly and clean test codes in a test case. We found that the mean value for the smelly test code is 109.93 Joule, which is greater than that of the clean test code, which is 88.27 Joule. The median value also follows the same trend with a higher energy consumption value for the smelly test code (102.61 Joule) compared to the clean test code (91.66 Joule). Further, to check whether the difference between the energy consumption of the smelly test code and the clean test code across all 12 projects is statistically significant, we performed Welch's t-test [70] after checking for the normality assumption of the data using Shapiro-Wilk's test [86]. We used Cohen's D [72] to measure the effect size. Our results show that the difference is statistically significant (Welch's t-test, p-value <6.27e-120, Cohen's D (0.37, small), indicating that in a test case, the smelly lines consume more energy than the clean lines of code.

In addition, we also examine if more test smell instances in a smelly test case would cause it to consume more energy. To do so, we grouped all test cases based on the count of total number of smell instances it contains (SC). To prevent outliers from skewing our results, we removed 79 test cases having more than 50 test smell instances from our analysis (3 standard deviations away from the mean [87]). This process left us with 7,748 test cases containing at least one but no more than 50 test smell instances. Next, we group test cases based on the number of test smell instances each test case has. Figure 3 shows the mean and median energy consumption in terms of smelly line of code ($E_{LOC(smell)}$) values for the group size of 5. As we can see, the energy consumption of smelly line of code ($E_{LOC(smell)}$) grows with the increasing number of test



Figure 3. Mean $(E_{LOC_{smell}})$ and Median $(E_{LOC_{smell}})$ energy consumption with Test Smells Count (SC) in Group size 5. Energy Unit Measured in Joules.

Test Smell	Rank	Kendall (τ_b)	p-value
AR	1	0.615	< 0.002
LT	2	0.449	< 0.002
ET	3	0.432	< 0.002
MNT	4	0.385	< 0.002
DA	5	0.290	< 0.002
UT	6	0.247	< 0.002
VT	7	0.246	< 0.002
SE	8	0.177	< 0.002
CLT	9	0.172	< 0.002
RA	10	0.072	< 0.002

smells. For group sizes 10 and 25, we found the same pattern. In general, it exhibits that the presence of more test smell instances increases the energy consumption for a test case, which implies test smell, in general, impacts energy consumption in software testing. To validate the statistical significance of the difference between groups, we also conducted Welch's t-test and Cohen's D between contiguous groups (i.e., group 6-10 with group 11-15, group 11-15 with group 16-20, etc.) Due to space limitation, we put the complete group analysis results in our replication package [80].

Observation 1: The smelly part of a test case consumes more energy than its non-smelly part.

2) **RQ2** [Test Smell Types vs. Energy] How does each test smell type impact energy consumption?: We next seek which test smell types have a more severe impact on energy consumption than others. As discussed in Section III-D2, it is not possible to collect the actual one-to-one mapping of energy consumption and each type of smell. Therefore, we computed a normalized energy consumption value $E_{(N)} = (E/SC)$ as an indicator of test smell's impact on energy consumption (shown in equation 3). In a test case, the normalized value $E_{(N)}$ helps us to create a one-to-one mapping between $E_{(N)}$ and the each type of test smells such as $testcase \rightarrow$ $\{E_{(N)}, s_1, s_2, s_3...s_{21}\}$.

With this mapping, we then performed Kendall's Tau (τ_b) correlation analysis between $E_{(N)}$ and each type of smell (e.g., $s_1, s_2, s_3...s_{21}$). Table III demonstrates our correlation results with the top 10 types of smells. Since we perform multiple-statistical tests, we applied Bonferroni correction to adjust P values [88], which gives an adjusted $\alpha = 0.002$. As we can see, the correlation values Kendall (τ_h) are statistically significant (i.g., *p*-value < 0.002) for all these test smells. Assertion Roulette (AR), Lazy Test (LT), Eager Test (ET), and Magic Number Test (MNT) are the smells with strong $(\tau_b > 0.30)$ correlation with energy consumption. On the other hand, Dependent Test (DT), Unknown Test (UT), and Verbose Test (VT) are moderately ($\tau_b > 0.20$) correlated with energy consumption. Sensitive Equality (SE) and Conditional Test Logic (CLT) show a weak correlation. For the remaining test smells types, we found a very weak correlation ($\tau_b < 0.10$).

Observation 2: Assertion Roulette (AT), Lazy Test (LT) and Eager Test (ET) test smells are strongly associated with energy consumption.

3) Case Study [Smelly/refactored Test vs. Energy]: To complement our results from RQ1 and RQ2, we conducted a case study on test cases with and without test smells (See Section III-E). For "Smelly-66", a significant difference (Welch's t-test, *p-value* <6.727e-46, Cohen's D (3.910, large)) was found between the energy consumption (*E*) of smelly test cases (204.922 Joule) and partially refactored test cases (184.974 Joule). Similarly, for "Smelly-AR-79", we also found a significant difference (Welch's t-test, *p-value* <4.508e-05, Cohen's D (0.672, medium)) between the energy consumption (*E*) of smelly test cases (204.048 Joules) and clean test cases (185.017 Joules). Our results show that the total energy consumption decreased significantly after removing test smells for both partial and complete refactoring. This indicates that test smells incur more energy consumption in software testing.

B. Developers' Perspective

Here, we explain our results regarding the developer's practices and perception of test smells.

1) **RQ3** [Developers' Awareness] Are developers aware of the impact of test smells on energy consumption?: Only 29.4% of our survey respondents who know about test smells expressed that they are confident that the presence of test smells in test cases has an impact on energy consumption, while 70.6% answered "Maybe" or "No." This indicates that most developers are not fully aware of the test smell's impact on energy consumption, which may contribute to the introduction of test smells during software testing.

We asked the survey participants to rank the test smell types we found in RQ2 based on their perceived severity of impacts on energy consumption. We show survey respondents' provided rankings in Figure 4. We could see that the rankings are widely spread among developers, which indicates that developers have conflicting opinions regarding the severity of different test smell types' impacts on energy consumption. We took the ranking that is voted by most respondents as the



Figure 4. Rankings of the Severity of Test Smell Types' Impact on Energy Consumption from Survey Respondents

TABLE IV Comparison of Rankings Based on Empirical Analysis and Developers' Response

Test Smell	Rank (Empirical Analysis)	Rank (Developers)
AR	1	4
LT	2	3
ET	3	4
MNT	4	6
DA	5	1
UT	6	3

overall ranking from developers for a specific test smell type. We list our results in Table IV. We found multiple ranking mismatches between our empirical analysis and our survey respondents, such as Duplicate Assert (DT), Unknown Test (UT), and Assertion Roulette (AR). This, again, shows that developers have a limited understanding of the test smell's impact on energy consumption.

Observation 3: Most developers are unaware of the impact of test smells on energy consumption.

Observation 4: There is a mismatch in the ranking of the impact severity between developers' perception and our empirical analysis.

2) **RQ4** [Developers' Group] Who is the most responsible for introducing energy-hungry test smells?: In this study, we identified the developers who last modified at least one of the test code lines that are part of a test smell instance as the one who is responsible for the test smell instance. We used "git blame" command for this. For each test smell type, we found that all three groups (core, non-core, and bot) introduced a similar number of test smells. This indicates that core, noncore, and bot developers all play role in introducing energyhungry test smells almost equally. While non-core developers contributed less in open-source software projects than core developers, they are still responsible for introducing a comparable amount of test smells as core developers. In addition, bot committers also introduced almost the same amount of test smells as human developers (for some test smell types such as Assertion Roulette (AR), they introduced even more test smells than human developers), which suggests that the automation tools used in open-source software development contain issues in generating or updating test cases. This observation is similar to what Virginio et al. [89] found where the human-written tests showed a higher quality than their studied automated tools regarding the presence of test smells. Also, all three groups tend to introduce more Assertion Roulette (AR) than other test smell types, while AR has the highest correlation with the average energy cost per smell instance $(E_{(N)})$. In addition, they also tend to introduce a relatively large amount of Lazy Test (LT), Eager Test (ET), and Magic Number Test (MNT), which we showed to be highly correlated with energy consumption (See Subsection IV-A). The complete numbers are reported in the companion website [80]. These findings indicate that both developer groups should raise their awareness of energy-hungry test smells, and better test case

generation tools with quality checks in terms of test smells should be developed.

Observation 5: Core, non-core, and bot developers are similarly responsible for introducing energyhungry test smells.

3) RO5 [Provenance of Test Smell] What are the underlying reasons developers introduce test smells that could cause additional energy consumption?: First, 45.2% of our survey participants do not know about test smells, so they may unknowingly introduce test smells when writing and updating test cases. Then, 5.9% of our survey respondents who know about test smells do not pay attention to test smells when writing test cases. One of them explicitly mentioned that "My organization doesn't have any policy/requirement regarding test smells" and "I don't care about test smells in test cases" [S-18]. In addition, 61.8% of the developers replied that their organizations do not follow any guidelines regarding monitoring energy consumption during software testing, while 76.5% do not know or use any tools for monitoring energy consumption in the testing phase. The complete results of our survey is provided in our replication package [80]. From our survey results, we could see that even well-established organization like Apache lacks the proper guidelines for test smells and energy consumption monitoring in regular software testing, which might be one of the main reasons developers introduced energy-hungry test smells.

Observation 6: Lack of guidelines, tools, and incentives are probable reasons developers introduce energy-hungry test smells.

V. DISCUSSION

The results of our study reveal that test smells, in general, have a negative impact on energy consumption during software testing. This finding complements previous research on the impact of test smells on various other aspects of software quality. Our study provides valuable evidence for developers, highlighting that the presence of test smells can lead to a significant amount of energy overhead, especially in large organizations where millions of test cases are executed daily.

To address this issue and promote energy-efficient software development practices, tool builders should consider providing Just In Time automated tools and IDE plugins. One surprising finding was the lack of automated test smell refactoring tools. As explained in Section III-E, even though there is prior work on test smell refactoring, no tool is available to refactor test smells off the shelf. Providing tools that can help developers by offering real-time feedback and suggestions for refactoring, developers can make more informed decisions to create cleaner and more energy-efficient test cases, ultimately leading to improved software quality and reduced energy consumption in the testing process.

Our analysis also revealed that the top three test smells with the highest association with energy consumption are Assertion Roulette (AR), Lazy Test (LT), and Eager Test (ET). To understand why AR is particularly energy-intensive, we manually inspected samples of AR test smell instances. Our investigation showed that most test cases containing AR have multiple assertion statements without any explanation, and all of these statements are considered smelly. In contrast, clean test cases usually contain only one assertion statement, which is more focused and purposeful. From an execution perspective, multiple assertion statements in Assertion Roulette (AR) test cases require more energy during testing than clean test cases with only one assertion statement. The repeated execution of multiple statements adds to the overall energy consumption, making test cases with Assertion Roulette (AR) more energy-intensive. We believe more research is needed to systematically investigate why these test smell types are the most energy-hungry ones.

Our analysis found a mismatch between the developer's perception and our empirical analysis result regarding the severity of test smell types' impacts on energy consumption. For example, the most energy-hungry test smell type recognized by developers is Duplicate Assert (DA) while it only ranks 5 in our empirical analysis. One possible explanation could be that developers assumed multiple unnecessary assertions in a test case could contribute to more execution time and energy consumption. Such mismatches between perception and reality have been observed in numerous other instances where long-held beliefs proved incorrect or outdated when actual evidence was collected through empirical analysis [90], [91]. Since the developers do not have tools for monitoring energy consumption during software testing, tool builders should create such tools that can be seamlessly integrated into the existing development workflow.

In terms of introducing energy-hungry test smells, bot committers (i.e., automated tools) are responsible for a comparable number of test smell instances to core and non-core developers. Combined with observations from [89], [92], [93], we believe that researchers should investigate ways to consider energy consumption as a factor while generating test cases automatically. Another interesting observation is that non-core developers are responsible for a similar amount of test smell instances as core developers, even though they contribute much less than core developers. Further investigation in the future is required to understand the underlying reason for this.

VI. THREATS TO VALIDITY

In our study, we have tried to eliminate bias and the effects of random noise. However, a few biases are unavoidable, and our mitigation strategies may not have been effective for them.

Bias due to confounding factors: The potential confounding effect of the production code's complexity or LOC is a concern when studying the correlation between test smells and energy consumption. However, the case study conducted in Section III-E effectively mitigated this bias by ensuring that the production code remained the same across test cases with and without test smells. By keeping the production code consistent, we isolate the impact of test smells on energy consumption and ensure that any observed changes in energy consumption are attributed only to the presence or absence of test smells in the test cases.

Bias due to sampling: The projects we have used in our study includes 12 Apache Java projects. We picked these projects from the Apache Software Foundation. Besides, we surveyed the developers who contributed to these 12 Apache projects. The responses of these developers may not represent all developers in other open-source projects and therefore, our findings may not generalize to all open-source projects.

We mined in total 13,103 test cases. We detect the test case based on the presence of @Test annotation. However, developers may write test cases without the @Test annotation by extending the JUnit Test class. We followed the developer's best practices and guidelines mentioned in JUnit documentation to identify test cases. However, it is also possible that other libraries are used to write unit test cases. In our study, we didn't consider test cases written using other libraries.

It is possible that our sampled test cases for manual refactoring are not representative of all test cases. However, to mitigate this threat, we utilized a 90% confidence interval and a 10% margin of error to calculate the sample size and used stratified random sampling. This statistical approach should mitigate the mentioned bias.

We categorized the developers into core and non-core groups based on the number of commits they contributed. According to this criteria, some of the developers could have been categorized as non-core though they were core developers who worked on significant contributions such as architectural refactoring or high-level design changes instead of frequently contributing to code changes. Since this is one of the most frequently used approaches in the literature, we relied on this approach. Also, we identified the bot committers based on the commit messages they wrote, which could have mistakenly classified some human developers as bots.

Bias due to tools used: In our study, we utilized a test smell detection tool and an energy profiler. Our analysis depended on these tool-generated outputs. Therefore, any errors in these tools may affect findings. To minimize the risk, we used tools that were validated by prior research. We used JNose to detect test smells. JNose can detect 21 types of test smells. However, there could be other test smell types that JNose can not detect.

We employed Intet PowerLog as an energy profiler. Although it reports energy consumption at the software level, some environmental factors, such as room temperature and outage in electricity, can affect its reported energy consumption result. We followed the procedure used in other work; we kept our experimental laptops at normal room temperature and placed them at a reasonable distance from each other to avoid heat transmission. We also ensured a cool-down period after every test case execution to avoid any impact of heating of the laptop itself on the results.

Bias due to the survey: It is possible that the survey participants misunderstood some of the survey questions. To alleviate this threat, we conducted a pilot study with experts having experience in software development, writing unit test cases, and survey design. We updated the survey questions according to their feedback.

VII. CONCLUSION

Our ultimate goal is to help catalyze advances in energyefficient software testing and this paper takes the first step towards that by shedding light on the current state of affairs. We presented the results of our empirical study aimed at understanding the state of energy consumption occurring due to test smells. Overall, our analysis reveals that the smelly part of a test case generally consumes more energy than its clean part. Also, not all test smell types are equally energyhungry. Our analysis revealed that Assertion Roulette (AR), Lazy Test (LT), and Eager Test (ET), tend to consume more energy compared to other smell types. Moreover, our test smell refactoring results indicate that smelly tests consume more energy than their clean counterparts. Our findings highlight the need for increased developer awareness regarding the impact of test smells on energy consumption and opportunities for researchers and tool builders to address the lack of tools and guidelines. The research artifacts for this study are publicly available at the companion website [80].

REFERENCES

- E. Gelenbe and Y. Caseau, "The impact of information technology on energy consumption and carbon emissions," *ubiquity*, vol. 2015, no. June, pp. 1–15, 2015.
- [2] T. Guardian, "Tsunami of data' could consume one fifth of global electricity by 2025," https://www.theguardian.com/environment/2017/dec/ 11/tsunami-of-data-could-consume-fifth-global-electricity-by-2025, 2017, [Online], [Accessed: 2023-01-20].
- [3] A. Fonseca, R. Kazman, and P. Lago, "A manifesto for energy-aware software," *IEEE Softw.*, vol. 36, no. 6, pp. 79–82, 2019.
- [4] "Smart," http://smarter2030.gesi.org/downloads.php, 2015.
- [5] GeSI, "Global e-sustainability initiative," http://smarter2030.gesi.org/ downloads.php, 2023, [Online], [Accessed: 2023-01-20].
- [6] S. Georgiou, S. Rizou, and D. Spinellis, "Software development lifecycle for energy efficiency: Techniques and tools," ACM Comput. Surv., vol. 52, no. 4, pp. 81:1–81:33, 2019.
- [7] "Unitedn nations," https://www.un.org/sustainabledevelopment/ sustainable-development-goals/, 2023.
- [8] W. L. Bircher and L. K. John, "Analysis of dynamic power management on multi-core processors," in *Proceedings of the 22nd Annual International Conference on Supercomputing, ICS 2008, Island of Kos, Greece, June 7-12, 2008.* ACM, 2008, pp. 327–338.
- [9] A. Iyer and D. Marculescu, "Power efficiency of voltage scaling in multiple clock, multiple voltage cores," in *Proceedings of the 2002 IEEE/ACM International Conference on Computer-aided Design, ICCAD 2002, San Jose, California, USA, November 10-14, 2002.* ACM / IEEE Computer Society, 2002, pp. 379–386.
- [10] A. Merkel and F. Bellosa, "Balancing power consumption in multiprocessor systems," in *Proceedings of the 2006 EuroSys Conference, Leuven, Belgium, April 18-21, 2006*, Y. Berbers and W. Zwaenepoel, Eds. ACM, 2006, pp. 403–414.
- [11] K. K. Rangan, G. Wei, and D. M. Brooks, "Thread motion: finegrained power management for multi-core systems," in *36th International Symposium on Computer Architecture (ISCA 2009), June 20-24, 2009, Austin, TX, USA*, S. W. Keckler and L. A. Barroso, Eds. ACM, 2009, pp. 302–313.
- [12] H. Ribic and Y. D. Liu, "Energy-efficient work-stealing language runtimes," in Architectural Support for Programming Languages and Operating Systems, ASPLOS 2014, Salt Lake City, UT, USA, March 1-5, 2014, R. Balasubramonian, A. Davis, and S. V. Adve, Eds. ACM, 2014, pp. 513–528.
- [13] N. Vijaykrishnan, M. T. Kandemir, S. Kim, S. S. Tomar, A. Sivasubramaniam, and M. J. Irwin, "Energy behavior of java applications from the memory perspective," in *Proceedings of the 1st Java Virtual Machine Research and Technology Symposium, April 23-24, 2001, Monterey, CA,* USA, S. Wold, Ed. USENIX, 2001, pp. 207–220.

- [14] R. J. Behrouz, A. Sadeghi, J. Garcia, S. Malek, and P. Ammann, "Ecodroid: An approach for energy-based ranking of android apps," in 4th IEEE/ACM International Workshop on Green and Sustainable Software, GREENS 2015, Florence, Italy, May 18, 2015. IEEE Computer Society, 2015, pp. 8–14.
- [15] C. Wilke, S. Richly, S. Götz, C. Piechnick, and U. Aßmann, "Energy consumption and efficiency in mobile applications: A user feedback study," in 2013 IEEE International Conference on Green Computing and Communications (GreenCom) and IEEE Internet of Things (iThings) and IEEE Cyber, Physical and Social Computing (CPSCom), Beijing, China, August 20-23, 2013. IEEE, 2013, pp. 134–141.
- [16] Y. Kwon and E. Tilevich, "Reducing the energy consumption of mobile applications behind the scenes," in 2013 IEEE International Conference on Software Maintenance, Eindhoven, The Netherlands, September 22-28, 2013. IEEE Computer Society, 2013, pp. 170–179.
- [17] V. Tiwari, S. Malik, and A. Wolfe, "Power analysis of embedded software: a first step towards software power minimization," *IEEE Trans. Very Large Scale Integr. Syst.*, vol. 2, no. 4, pp. 437–445, 1994.
- [18] G. Pinto, F. Castor, and Y. D. Liu, "Mining questions about software energy consumption," in 11th Working Conference on Mining Software Repositories, MSR 2014, Proceedings, May 31 - June 1, 2014, Hyderabad, India, P. T. Devanbu, S. Kim, and M. Pinzger, Eds. ACM, 2014, pp. 22–31.
- [19] E. Jagroep, J. M. E. M. van der Werf, R. Spauwen, L. Blom, R. van Vliet, and S. Brinkkemper, "An energy consumption perspective on software architecture - A case study on architectural change," in *Software Architecture - 9th European Conference, ECSA 2015, Dubrovnik/Cavtat, Croatia, September 7-11, 2015, Proceedings*, ser. Lecture Notes in Computer Science, vol. 9278. Springer, 2015, pp. 239–247.
- [20] S. Maleki, C. Fu, A. Banotra, and Z. Zong, "Understanding the impact of object oriented programming and design patterns on energy efficiency," in *Eighth International Green and Sustainable Computing Conference, IGSC 2017, Orlando, FL, USA, October 23-25, 2017.* IEEE Computer Society, 2017, pp. 1–6.
- [21] S. A. Chowdhury, A. Hindle, R. Kazman, T. Shuto, K. Matsui, and Y. Kamei, "Greenbundle: an empirical study on the energy impact of bundled processing," in *Proceedings of the 41st International Conference* on Software Engineering, ICSE 2019, Montreal, QC, Canada, May 25-31, 2019. IEEE / ACM, 2019, pp. 1107–1118.
- [22] D. Feitosa, R. Alders, A. Ampatzoglou, P. Avgeriou, and E. Y. Nakagawa, "Investigating the effect of design patterns on energy consumption," J. Softw. Evol. Process., vol. 29, no. 2, 2017.
- [23] C. C. Venters, R. Capilla, S. Betz, B. Penzenstadler, T. Crick, S. Crouch, E. Y. Nakagawa, C. Becker, and C. Carrillo, "Software sustainability: Research and practice from a software architecture viewpoint," *J. Syst. Softw.*, vol. 138, pp. 174–188, 2018.
- [24] M. Couto, R. Pereira, F. Ribeiro, R. Rua, and J. Saraiva, "Towards a green ranking for programming languages," in *Proceedings of the* 21st Brazilian Symposium on Programming Languages, SBLP 2017, Fortaleza, CE, Brazil, September 21-22, 2017. ACM, 2017, pp. 7:1–7:8.
- [25] R. Pereira, M. Couto, F. Ribeiro, R. Rua, J. Cunha, J. P. Fernandes, and J. Saraiva, "Energy efficiency across programming languages: how do energy, time, and memory relate?" in *Proceedings of the 10th ACM SIGPLAN International Conference on Software Language Engineering*, *SLE 2017, Vancouver, BC, Canada, October 23-24, 2017.* ACM, 2017, pp. 256–267.
- [26] R. Pereira, M. Couto, J. Saraiva, J. Cunha, and J. P. Fernandes, "The influence of the java collection framework on overall energy consumption," in *Proceedings of the 5th International Workshop on Green and Sustainable Software, GREENS@ICSE 2016, Austin, Texas,* USA, May 16, 2016. ACM, 2016, pp. 15–21.
- [27] G. Petrovic, M. Ivankovic, G. Fraser, and R. Just, "Practical mutation testing at scale: A view from google," *IEEE Trans. Software Eng.*, vol. 48, no. 10, pp. 3900–3912, 2022.
- [28] C. Zhang, B. Chen, L. Chen, X. Peng, and W. Zhao, "A largescale empirical study of compiler errors in continuous integration," in *Proceedings of the ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering, ESEC/SIGSOFT FSE 2019, Tallinn, Estonia, August 26-30,* 2019, M. Dumas, D. Pfahl, S. Apel, and A. Russo, Eds. ACM, 2019, pp. 176–187.
- [29] J. Drangmeister, E. Kern, M. Dick, S. Naumann, G. Sparmann, and A. Guldner, "Greening software with continuous energy efficiency measurement," in 43. Jahrestagung der Gesellschaft für Informatik, Informatik angepasst an Mensch, Organisation und Umwelt, INFOR-MATIK 2013, Koblenz, Germany, September 16-20, 2013, ser. LNI, M. Horbach, Ed., vol. P-220. GI, 2013, pp. 940–951.

- [30] A. Van Deursen, L. Moonen, A. Van Den Bergh, and G. Kok, "Refactoring test code," in *Proceedings of the 2nd international conference* on extreme programming and flexible processes in software engineering (XP2001). Citeseer, 2001, pp. 92–95.
- [31] M. Greiler, A. Van Deursen, and M.-A. Storey, "Automated detection of test fixture strategies and smells," in 2013 IEEE Sixth International Conference on Software Testing, Verification and Validation. IEEE, 2013, pp. 322–331.
- [32] A. Peruma, K. S. Almalki, C. D. Newman, M. W. Mkaouer, A. Ouni, and F. Palomba, "On the distribution of test smells in open source android applications: An exploratory study," 2019.
- [33] G. Bavota, A. Qusef, R. Oliveto, A. De Lucia, and D. Binkley, "Are test smells really harmful? an empirical study," *Empirical Software Engineering*, vol. 20, no. 4, pp. 1052–1094, 2015.
- [34] L. Moonen, A. Van Deursen, A. Zaidman, and M. Bruntink, "On the interplay between software testing and evolution and its effect on program comprehension," in *Software evolution*. Springer, 2008, pp. 173–202.
- [35] G. Bavota, A. Qusef, R. Oliveto, A. De Lucia, and D. Binkley, "An empirical analysis of the distribution of unit test smells and their impact on software maintenance," in 2012 28th IEEE international conference on software maintenance (ICSM). IEEE, 2012, pp. 56–65.
- [36] T. Virgínio, R. Santana, L. A. Martins, L. R. Soares, H. Costa, and I. Machado, "On the influence of test smells on test coverage," in *Proceedings of the XXXIII Brazilian Symposium on Software Engineering*, 2019, pp. 467–471.
- [37] T. Virgínio, L. A. Martins, L. R. Soares, R. Santana, A. Cruz, H. A. X. Costa, and I. Machado, "Jnose: Java test smell detector," in 34th Brazilian Symposium on Software Engineering, SBES 2020, Natal, Brazil, October 19-23, 2020, E. Cavalcante, F. Dantas, and T. Batista, Eds. ACM, 2020, pp. 564–569.
- [38] T. Wang, Y. Golubev, O. Smirnov, J. Li, T. Bryksin, and I. Ahmed, "Pynose: A test smell detector for python," in 36th IEEE/ACM International Conference on Automated Software Engineering, ASE 2021, Melbourne, Australia, November 15-19, 2021. IEEE, 2021, pp. 593– 605.
- [39] M. Taniguchi, S. Matsumoto, and S. Kusumoto, "Jtdog: a gradle plugin for dynamic test smell detection," in 36th IEEE/ACM International Conference on Automated Software Engineering, ASE 2021, Melbourne, Australia, November 15-19, 2021. IEEE, 2021, pp. 1271–1275.
- [40] E. Soares, M. Ribeiro, R. Gheyi, G. Amaral, and A. M. Santos, "Refactoring test smells with junit 5: Why should developers keep upto-date," *IEEE Transactions on Software Engineering*, pp. 1–1, 2022.
- [41] S. Lambiase, A. Cupito, F. Pecorelli, A. D. Lucia, and F. Palomba, "Justin-time test smell detection and refactoring: The DARTS project," in *ICPC '20: 28th International Conference on Program Comprehension*, *Seoul, Republic of Korea, July 13-15, 2020.* ACM, 2020, pp. 441–445.
- [42] N. A. Nagy and R. Abdalkareem, "On the co-occurrence of refactoring of test and source code," in 19th IEEE/ACM International Conference on Mining Software Repositories, MSR 2022, Pittsburgh, PA, USA, May 23-24, 2022. ACM, 2022, pp. 122–126.
- [43] A. Pizzini, "Behavior-based test smells refactoring : Toward an automatic approach to refactoring eager test and lazy test smells," in 44th IEEE/ACM International Conference on Software Engineering: Companion Proceedings, ICSE Companion 2022, Pittsburgh, PA, USA, May 22-24, 2022. ACM/IEEE, 2022, pp. 261–263.
- [44] M. M. Hassan and A. Rahman, "As code testing: Characterizing test quality in open source ansible development," in 2022 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, 2022, pp. 208–219.
- [45] M. Tufano, F. Palomba, G. Bavota, M. Di Penta, R. Oliveto, A. De Lucia, and D. Poshyvanyk, "An empirical investigation into the nature of test smells," in *Proceedings of the 31st IEEE/ACM international conference* on automated software engineering, 2016, pp. 4–15.
- [46] D. Spadini, F. Palomba, A. Zaidman, M. Bruntink, and A. Bacchelli, "On the relation of test smells to software code quality," in 2018 IEEE international conference on software maintenance and evolution (ICSME). IEEE, 2018, pp. 1–12.
- [47] M. Linares-Vásquez, G. Bavota, C. Bernal-Cárdenas, R. Oliveto, M. Di Penta, and D. Poshyvanyk, "Mining energy-greedy api usage patterns in android apps: an empirical study," in *Proceedings of the 11th* working conference on mining software repositories, 2014, pp. 2–11.
- [48] W. Song, J. Zhang, and J. Huang, "Servdroid: detecting service usage inefficiencies in android applications," in *Proceedings of the 2019 27th* ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering, 2019, pp. 362– 373.

- [49] W. Oliveira, R. Oliveira, F. Castor, B. Fernandes, and G. Pinto, "Recommending energy-efficient java collections," in 2019 IEEE/ACM 16th International Conference on Mining Software Repositories (MSR). IEEE, 2019, pp. 160–170.
- [50] S. Song, F. Wedyan, and Y. Jararweh, "Empirical evaluation of energy consumption for mobile applications," in 2021 12th International Conference on Information and Communication Systems (ICICS). IEEE, 2021, pp. 352–357.
- [51] X. Li, J. Chen, Y. Liu, K. Wu, and J. P. Gallagher, "Combatting energy issues for mobile applications," ACM Transactions on Software Engineering and Methodology, 2022.
- [52] Y. Liu, C. Xu, S. Cheung, and J. Lü, "Greendroid: Automated diagnosis of energy inefficiency for smartphone applications," *IEEE Transactions* on Software Engineering, vol. 40, no. 9, pp. 911–940, 2014.
- [53] A. Banerjee and A. Roychoudhury, "Automated re-factoring of android apps to enhance energy-efficiency," in *Proceedings of the International Conference on Mobile Software Engineering and Systems*, 2016, pp. 139–150.
- [54] B. R. Bruce, J. Petke, and M. Harman, "Reducing energy consumption using genetic improvement," in *Proceedings of the 2015 Annual Conference on Genetic and Evolutionary Computation*, 2015, pp. 1327–1334.
- [55] I. Manotas, L. Pollock, and J. Clause, "Seeds: A software engineer's energy-optimization decision support framework," in *Proceedings of the* 36th International Conference on Software Engineering, 2014, pp. 503– 514.
- [56] I. Moura, G. Pinto, F. Ebert, and F. Castor, "Mining energy-aware commits," in 2015 IEEE/ACM 12th Working Conference on Mining Software Repositories. IEEE, 2015, pp. 56–67.
- [57] A. S. Foundation, "Apache software foundation," https://www.apache. org/, 2023, [Online], [Accessed: 2023-01-20].
- [58] S. Kabinna, C. Bezemer, W. Shang, and A. E. Hassan, "Logging library migrations: a case study for the apache software foundation projects," in *Proceedings of the 13th International Conference on Mining Software Repositories, MSR 2016, Austin, TX, USA, May 14-22, 2016*, M. Kim, R. Robbes, and C. Bird, Eds. ACM, 2016, pp. 154–164.
- [59] TIOBE, "Tiobe index," .https://www.tiobe.com/tiobe-index/, 2023, [Online], [Accessed: 2023-01-20].
- [60] W. Aljedaani, A. Peruma, A. Aljohani, M. Alotaibi, M. W. Mkaouer, A. Ouni, C. D. Newman, A. Ghallab, and S. Ludi, "Test smell detection tools: A systematic mapping study," in *Evaluation and Assessment in Software Engineering*. Association for Computing Machinery, 2021, p. 170–180.
- [61] Apache, "Apache maven project," https://maven.apache.org/, 2023, [Online], [Accessed: 2023-01-20].
- [62] V. Massol, JUnit in action, 2004.
- [63] eclipse jdt, "eclipse.jdt.core," 2001. [Online]. Available: https://github. com/eclipse-jdt/eclipse.jdt.core
- [64] A. Peruma, K. Almalki, C. D. Newman, M. W. Mkaouer, A. Ouni, and F. Palomba, "Tsdetect: An open source test smells detection tool," in *Proceedings of the 28th ACM joint meeting on european software* engineering conference and symposium on the foundations of software engineering, 2020, pp. 1650–1654.
- [65] T. Sharma, S. Georgiou, M. Kechagia, T. A. Ghaleb, and F. Sarro, "Investigating developers' perception on software testability and its effects," *Empirical Software Engineering*, vol. 28, no. 5, pp. 1–29, 2023.
- [66] L. Martins, H. Costa, and I. Machado, "On the diffusion of test smells and their relationship with test code quality of java projects," *Journal* of Software: Evolution and Process, p. e2532, 2023.
- [67] D. Campos, L. Martins, and I. Machado, "An empirical study on the influence of developers' experience on software test code quality," in *Proceedings of the XXI Brazilian Symposium on Software Quality*, 2022, pp. 1–10.
- [68] Intel, "Intel® power gadget," https://www.intel.com/content/www/us/en/ developer/articles/tool/power-gadget.html, 2023, [Online], [Accessed: 2023-01-20].
- [69] J. S. Luís Cruz, "Sustainable se," https://luiscruz.github.io/course_ sustainableSE/2022/p1_measuring_software/, 2023, [Online], [Accessed: 2023-01-20].
- [70] G. D. Ruxton, "The unequal variance t-test is an underused alternative to student's t-test and the mann-whitney u test," *Behavioral Ecology*, vol. 17, no. 4, pp. 688–690, 2006.
- [71] P. Cohen, S. G. West, and L. S. Aiken, Applied multiple regression/correlation analysis for the behavioral sciences. Psychology press, 2014.

- [72] M. J. Diener, "Cohen's d," *The Corsini encyclopedia of psychology*, pp. 1–1, 2010.
- [73] P. K. Sen, "Estimates of the regression coefficient based on kendall's tau," *Journal of the American statistical association*, vol. 63, no. 324, pp. 1379–1389, 1968.
- [74] R. Santana, L. Martins, L. Rocha, T. Virgínio, A. Cruz, H. Costa, and I. Machado, "Raide: a tool for assertion roulette and duplicate assert identification and refactoring," in *Proceedings of the XXXIV Brazilian Symposium on Software Engineering*, 2020, pp. 374–379.
- [75] S. Lambiase, A. Cupito, F. Pecorelli, A. De Lucia, and F. Palomba, "Just-in-time test smell detection and refactoring: The darts project," in *Proceedings of the 28th international conference on program comprehension*, 2020, pp. 441–445.
- [76] L. Martins, C. Bezerra, H. Costa, and I. Machado, "Smart prediction for refactorings in the software test code," in *Proceedings of the XXXV Brazilian Symposium on Software Engineering*, 2021, pp. 115–120.
- [77] A. Pizzini, "Behavior-based test smells refactoring: Toward an automatic approach to refactoring eager test and lazy test smells," in *Proceedings of* the ACM/IEEE 44th International Conference on Software Engineering: Companion Proceedings, 2022, pp. 261–263.
- [78] E. Soares, M. Ribeiro, R. Gheyi, G. Amaral, and A. Santos, "Refactoring test smells with junit 5: Why should developers keep up-to-date?" *IEEE Transactions on Software Engineering*, vol. 49, no. 3, pp. 1152–1170, 2022.
- [79] R. Santana, L. Martins, T. Virgínio, L. Soares, H. Costa, and I. Machado, "Refactoring assertion roulette and duplicate assert test smells: a controlled experiment," arXiv preprint arXiv:2207.05539, 2022.
- [80] Supplementary, "Replication Package," 2023. [Online]. Available: https://figshare.com/s/da2b1903e7b209b1f77e
- [81] Qualtrics, "Qualtrics xm experience management software," https:// www.qualtrics.com/, 2023, [Online], [Accessed: 2023-01-20].
- [82] E. Smith, R. Loftin, E. Murphy-Hill, C. Bird, and T. Zimmermann, "Improving developer participation rates in surveys," in 2013 6th International workshop on cooperative and human aspects of software engineering (CHASE). IEEE, 2013, pp. 89–92.
- [83] D. Lo, N. Nagappan, and T. Zimmermann, "How practitioners perceive the relevance of software engineering research," in *Proceedings of the* 2015 10th Joint Meeting on Foundations of Software Engineering, 2015, pp. 415–425.
- [84] U. A. Mannan, I. Ahmed, C. Jensen, and A. Sarma, "On the relationship between design discussions and design quality: a case study of apache projects," in *Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations* of Software Engineering, 2020, pp. 543–555.
- [85] T. Dey, S. Mousavi, E. Ponce, T. Fry, B. Vasilescu, A. Filippova, and A. Mockus, "Detecting and characterizing bots that commit code," in *Proceedings of the 17th international conference on mining software repositories*, 2020, pp. 209–219.
- [86] B. Yazici and S. Yolacan, "A comparison of various tests of normality," *Journal of Statistical Computation and Simulation*, vol. 77, no. 2, pp. 175–183, 2007.
- [87] I. F. Ilyas and X. Chu, Data cleaning. Morgan & Claypool, 2019.
- [88] M. A. Napierala, "What is the bonferroni correction?" Aaos Now, pp. 40–41, 2012.
- [89] T. Virgínio, L. A. Martins, L. R. Soares, R. Santana, H. Costa, and I. Machado, "An empirical study of automatically-generated tests from the perspective of test smells," in *Proceedings of the XXXIV Brazilian Symposium on Software Engineering*, 2020, pp. 92–96.
- [90] P. Devanbu, T. Zimmermann, and C. Bird, "Belief & evidence in empirical software engineering," in 2016 IEEE/ACM 38th International Conference on Software Engineering (ICSE). IEEE, 2016, pp. 108–119.
- [91] T. Menzies, W. Nichols, F. Shull, and L. Layman, "Are delayed issues harder to resolve? revisiting cost-to-fix of defects throughout the lifecycle," *Empirical Software Engineering*, vol. 22, no. 4, pp. 1903–1935, 2017.
- [92] F. Palomba, D. Di Nucci, A. Panichella, R. Oliveto, and A. De Lucia, "On the diffusion of test smells in automatically generated test code: An empirical study," in *Proceedings of the 9th international workshop* on search-based software testing, 2016, pp. 5–14.
- [93] G. Grano, F. Palomba, D. Di Nucci, A. De Lucia, and H. C. Gall, "Scented since the beginning: On the diffuseness of test smells in automatically generated test code," *Journal of Systems and Software*, vol. 156, pp. 312–327, 2019.