Onset of global instability in a premixed annular V-flame

Chuhan Wang^{1,2}[†], Christopher M. Douglas^{2,3}, Yu Guan⁴, Chunxiao Xu¹ and Lutz Lesshafft²

¹AML, Department of Engineering Mechanics, Tsinghua University, 100084 Beijing, PR China

²LadHyX, CNRS, École Polytechnique, Institut Polytechnique de Paris, 91120 Palaiseau, France

³Department of Mechanical Engineering and Materials Science, Duke University, Durham, NC, USA

⁴Department of Aeronautical and Aviation Engineering, The Hong Kong Polytechnic University, Kowloon, Hong Kong

(Received xx; revised xx; accepted xx)

We investigate self-excited axisymmetric oscillations of a lean premixed methane-air V-flame in a laminar annular jet. The flame is anchored near the rim of the centrebody, forming an inverted cone, while the strongest vorticity is concentrated along the outer shear layer of the annular jet. Consequently, the reaction and vorticity dynamics are largely separated, except where they coalesce near the flame tip. The global eigenmodes corresponding to the linearised reacting flow equations around the steady base state are computed in an axisymmetric setting. We identify an arc branch of eigenmodes exhibiting strong oscillations at the flame tip. The associated eigenvalues are robust with respect to domain truncation and numerical discretisation, and they become destabilised as the Reynolds number increases. The frequency of the leading eigenmode is found to correspond to the Lagrangian disturbance advection time from the nozzle outlet to the flame tip. This linear result suggests a non-local feedback mechanism consistent with the scenario of 'intrinsic thermoacoustic instability'. Nonlinear time-resolved simulation further reveals notable hysteresis phenomena in the subcritical regime prior to instability. Hence, even when the flame is linearly stable, perturbations of sufficient amplitude can trigger limit-cycle oscillations and higher-dimensional dynamics sustained by nonlinear feedback. Notably, linear analysis of the subcritical time-averaged limit-cycle state yields eigenvalues that do not match the nonlinear periodic oscillation frequencies, emphasising the essential role of nonlinear harmonic interactions in the system dynamics.

Key words:

1. Introduction

Canonical configurations of premixed laminar flames attract significant research interest because their unsteady dynamics are rich and representative of many practical configurations, yet relatively simple in comparison to turbulent flames (Lieuwen 2003; Schuller *et al.* 2020). A V-flame, the configuration considered in the present study, is an inverted conical flame anchored on the centrebody of an annular burner. In industrial applications, V-flames are often enhanced with swirl to stabilise the flame and prevent blow-off (Candel *et al.* 2014). However, even in the absence of swirl, V-flame dynamics remain intricate. Flow fields corresponding to a non-swirling



FIGURE 1. Steady base states of the calculated V-flame at (a) Re = 1674 and (b) Re = 2891. Top of each plot: azimuthal vorticity Ω_z . Bottom of each plot: heat release rate $\dot{\omega}_T$. Both variables are normalised by their maximum. Streamlines are superposed.

V-flame, computed on a two-dimensional axisymmetric grid at two different Reynolds numbers, are presented in figure 1. The flame surface region, characterised by high-magnitude heat release rates, is anchored to the centrebody. A strong free shear layer is shed from the outer corner of the jet nozzle, as illustrated by the vorticity distribution. Unlike the cylinder-anchored flame investigated in our previous study (Wang et al. 2022b), the superposed streamlines in the present V-flame indicate no prominent recirculation region behind the annular centrebody. As a result, the V-flame dynamics more closely resemble those of amplifier flows such as a jet, resulting in increased sensitivity to acoustic perturbations (Schuller et al. 2003; Schuller 2003). Numerous studies have been dedicated to the exploration of the linear and nonlinear dynamics of V-flames under various forcing scenarios, both in confined and unconfined arrangements (Durox et al. 2005; Birbaud et al. 2007; Durox et al. 2009). Self-excited oscillations have been observed in confined V-flames, which are furthermore prone to chaotic dynamics (Vishnu et al. 2015). In the case of unconfined configurations, although self-excited oscillations were observed in the experiments conducted by Durox et al. (2005), a comprehensive understanding of the critical conditions and the dynamics associated with instability onset remains elusive. This present work aims to elucidate the onset of axisymmetric instability in a non-swirling annular V-flame through a combined approach of linear analysis and nonlinear time-domain simulation.

Unsteadiness and instability in flames is a fascinating field of application for linear instability analysis because of the rich dynamics that can result from the interplay of vortical, thermal, chemical, and acoustic elements. However, reactive flows are associated with steep gradients, stiff reaction terms in the governing equations, and additional unknown variables for each chemical species, posing challenges for global linear stability analysis computations. As a result, many pioneering works invoked simplifications involving parallel flow and decoupled chemistry assumptions. For example, Emerson et al. (2012) modelled the reacting wake flow behind a bluff body as an incompressible flow using discontinuous local profiles of velocity and density in the spanwise direction. Similar local analyses have also been performed on profiles measured experimentally in swirling jet flames (Oberleithner et al. 2015; Douglas et al. 2021a), backwardfacing step flames (Manoharan & Hemchandra 2015), and bluff body wake flames (Emerson et al. 2016), among others. However, reacting flow fields are generally strongly non-parallel in the streamwise direction and flames interact with the flow through more than just density gradients. In recent years, there has been a gradual integration of more comprehensive global linear stability analysis methods, which preserve the streamwise variations of the base state, into canonical premixed laminar flame configurations. For example, Qadri et al. (2015) investigated the selfsustained oscillations in lifted jet diffusion flames with a heat release source term included in the governing flow equations. Using compressible reacting flow equations, Avdonin *et al.* (2019) calculated the eigenvalues and the associated eigenmode structures of a premixed slot flame, revealing significant fluctuations of streamwise velocity and chemical heat release rate along the flame surface region. In previous work, we investigated self-excited oscillations of a premixed laminar flame stabilised by a square cylinder in a channel (Wang *et al.* 2022*b*). The study involved the examination of global eigenmodes associated with the steady base state of the reacting cylinder wake as well as nonlinear simulations, employing a one-step methane–air reaction in the low Mach number limit. The critical Reynolds number, corresponding to zero temporal growth rate, was identified, marking the onset of limit-cycle oscillations through a supercritical Hopf bifurcation. Endogeneity analysis (Marquet & Lesshafft 2015) further indicated that this global instability was driven by momentum feedback in the wake recirculation zone, with only marginal contributions from additional feedback in the flame region, characterising the flame oscillations as a passive effect of the essentially hydrodynamic wake instability.

Other studies using global linear analysis focus on flame responses to external perturbations, including acoustic forcing, inertial waves, and optimal forcing identified through resolvent analysis. Novel reduced-order models and predictive tools for the dynamic response of flames have emerged by building upon these methods. In the case of premixed slot flames, flame transfer functions have been computed using linearised reacting flow equations with one-step (Avdonin et al. 2019; Brokof et al. 2024) and two-step chemistry schemes (Meindl et al. 2021; Wang et al. 2022a), and their quantitative validation against reference results has been achieved. Resolvent analysis (Wang et al. 2022a) revealed that the identified optimal excitation frequency corresponds to an intrinsic thermoacoustic mode (Silva 2023). In the context of M-flames, computations were carried out to determine the linear response to impulsive and harmonic perturbations (Blanchard et al. 2015; Blanchard 2015). An adjoint analysis (Skene & Schmid 2019) was also employed to assess the sensitivity of the M-flames' optimal response gain to swirl. For a swirling V-flame, impulse response calculations were conducted to investigate the modulation of flame fronts by inertial waves (Albayrak et al. 2018). Recent studies have also calculated the linear responses of turbulent jet flames (Casel et al. 2022; Kaiser et al. 2023) and a reacting jet in cross flow (Sayadi & Schmid 2021).

The global linear stability analysis procedure employed to study the present V-flame closely follows our previous work (Wang et al. 2022b) concerning a flame stabilised by a square cylinder. However, based on local stability intuition, the unsteady dynamics in these two configurations are expected to be distinct: wake recirculation as a source of local absolute instability is almost absent in the V-flame, whereas a strong convective instability resides in the jet shear layer. Moreover, the characteristic global eigenspectrum of a jet exhibits marked differences from that of a wake. In both non-reacting and reacting wakes, the global dynamics are dominated by an isolated linear eigenmode, which leads to the nonlinear shedding of counter-rotating vortices (Noack & Eckelmann 1994; Barkley 2006; Wang et al. 2022b). In the context of round jets, such an isolated mode only exists in the presence of strong density contrast (Lesshafft et al. 2006; Coenen et al. 2017; Chakravarthy et al. 2018), where self-excited oscillations have been observed (Monkewitz et al. 1990; Kyle & Sreenivasan 1993; Hallberg & Strykowski 2006). In isothermal jets, the numerical eigenspectrum is typically dominated by artificial modes that arise from spurious pressure feedback between the boundaries (Garnaud et al. 2013; Coenen et al. 2017). Such artificial modes do not converge with respect to domain size, and they are highly affected when a sponge layer is employed to artificially dampen pressure feedback (Cerqueira & Sipp 2014; Lesshafft 2018).

Recent findings indicate that the onset of instability in a jet flows can be subcritical in many circumstances. Zhu *et al.* (2017) identified a hysteretic bistable region when incrementally adjusting the jet velocity in their helium-air jet experiment. This observation suggests a subcritical

Hopf bifurcation, which may be modelled through a truncated Landau equation. Demange *et al.* (2022) investigated the self-sustained oscillation of a heated jet with real gas effects through numerical simulation and stability analysis. The critical temperature ratio for the Hopf bifurcation, predicted by the global stability analysis around the steady base flow, was found to be considerably lower than in nonlinear simulation, indicating subcriticality. Other recent work has identified subcritical instability dynamics in constant-density, swirling circular jets (Douglas *et al.* 2021*b*) as well as swirling and non-swirling annular jets (Douglas *et al.* 2022) using nonlinear branch tracing.

The remainder of this paper is structured as follows. In §2, we present the flame configuration and describe the governing equations. §3 focuses on the global linear analysis around the steady base state, where various categories of eigenmodes are characterised. In §4, nonlinear time stepping and analysis of the nonlinear flame dynamics are carried out. §5 presents a linear analysis around time-averaged mean flows and discusses the ambiguity of linearised chemical reaction terms in the limit-cycle regime. Conclusions are provided in §6.

2. Calculation of steady V-flames

The burner geometry aligns with the numerical study by Birbaud *et al.* (2008) on an inverted dihedral flame, but the burner considered here is axisymmetric, formulated in the cylindrical coordinates $\mathbf{x} = (x, r)$. Here, x represents the streamwise direction, and r represents the radial direction. Figure 2(a) illustrates the entire calculation domain. The streamwise position x = 0 is defined as the outer nozzle outlet, r = 0 is the symmetry axis. Lean premixed methane–air reactant is injected from the bottom of a cylindrical nozzle measuring 30 mm in length and D = 11 mm in diameter. The V-flame is anchored on a centre rod with a diameter of 3 mm, protruding 2 mm from the nozzle. The domain extends to $x_{max} = 200$ mm downstream and $r_{max} = 50$ mm radially. An axisymmetric condition is applied at the centerline to confine the calculation to a two-dimensional setting.

The governing equations for the reacting flow, considering an ideal gas in the low Mach number limit, are the same as in Wang *et al.* (2022*b*), except that they are formulated here in axisymmetric coordinates. Primitive variables (ρ , \boldsymbol{u} , h, Y_{CH_4} , p) are chosen, where $\boldsymbol{u} = (u_x, u_r)$ represents the streamwise and radial velocity components, ρ denotes density, h stands for sensible enthalpy, Y_{CH_4} is the mass fraction of methane, and p is the hydrodynamic pressure. The governing equations are expressed as

$$\frac{\partial \rho}{\partial t} = -\nabla \cdot \left(\rho \boldsymbol{u}\right),\tag{2.1}$$

$$\rho \frac{\partial \boldsymbol{u}}{\partial t} = -\rho \boldsymbol{u} \cdot \nabla \boldsymbol{u} - \nabla \boldsymbol{p} + \nabla \cdot \boldsymbol{\tau}, \qquad (2.2)$$

$$\rho \frac{\partial Y_{\mathrm{CH}_4}}{\partial t} = -\rho \boldsymbol{u} \cdot \nabla Y_{\mathrm{CH}_4} + \nabla \cdot \left(D_s \nabla Y_{\mathrm{CH}_4} \right) + \dot{\omega}_{\mathrm{CH}_4}, \tag{2.3}$$

$$\rho \frac{\partial h}{\partial t} = -\rho \boldsymbol{u} \cdot \nabla h + \nabla \cdot (D_h \nabla h) + \dot{\omega}_T, \qquad (2.4)$$

$$p_0 = R_s \rho T. \tag{2.5}$$

The molecular stress tensor τ is defined as

$$\tau = \mu \left(\nabla \boldsymbol{u} + \nabla \boldsymbol{u}^{\mathrm{T}} - \frac{2}{3} \left(\nabla \cdot \boldsymbol{u} \right) \boldsymbol{I} \right),$$
(2.6)

where the molecular viscosity follows Sutherland's law $\mu = A_s T^{1/2} / (1 + T_s / T)$ with constants



FIGURE 2. The standard mesh with 180 481 elements used in the study. Colors represent the normalised base flow heat release. (a) The complete numerical domain. (b) Zoom on a flame surface region.

 $A_s = 1.672 \times 10^{-6} \text{ kg/(m.s.K}^{1/2})$ and $T_s = 170.672 \text{ K}$. The diffusive transport coefficients D_s and D_h are assumed to be proportional to the molecular viscosity, with constant values of Schmidt number $\text{Sc} = \mu/D_s = 0.7$ and Prandtl number $\text{Pr} = \mu/D_h = 0.7$. Enthalpy is expressed as $h = C_p T$, where the specific heat capacity $C_p = 1.3 \text{ kJ/(kg.K)}$ is assumed constant. Following the original low-Mach-number expansion of McMurtry *et al.* (1986), the thermodynamic pressure p_0 in the ideal gas law (2.5) is the zeroth-order pressure component, prescribed as $p_0 = 1$ atm, while the unknown hydrodynamic pressure p in the momentum equation (2.2) is its first-order complement in the squared Mach number. $R_s = 287.2 \text{ J/(kg.K)}$ in the ideal gas law represents the specific gas constant. The one-step reaction scheme 1S_CH4_MP1 from CERFACS (2017) is used, as it is sufficient to accurately reproduce the laminar burning speed of lean premixed methane-air mixtures with the current set of parameters (Birbaud *et al.* 2008). This scheme was also employed in our previous calculations of a bluff-body flame, successfully reproducing the length of the recirculation bubble compared to reference calculations (Wang *et al.* 2022*b*). The reaction rate *Q* is governed by an Arrhenius law:

$$Q = A_r [X_{CH_4}]^{n_{CH_4}} [X_{O_2}]^{n_{O_2}} \exp\left(-\frac{T_a}{T}\right).$$
(2.7)

For the global methane–air reaction modelled here, the values of the reaction exponents are $n_{\text{CH}_4} = 1$ and $n_{\text{O}_2} = 1/2$. With these exponents, the values of the Arrhenius pre-exponential factor and activation temperature are, respectively, $A_r = 1.1 \times 10^7 \text{ m}^{3/2}/(\text{s.mol}^{1/2})$ and $T_a = 1.007 \times 10^4 \text{ K}$ (CERFACS 2017). The molar concentrations of CH₄ and O₂ are given by $[X_{\text{CH}_4}] = \rho \frac{Y_{\text{CH}_4}}{W_{\text{CH}_4}}$ and $[X_{\text{O}_2}] = \rho \frac{Y_{\text{O}_2}}{W_{\text{O}_2}}$, respectively, where $W_{\text{CH}_4} = 16.0 \text{ g/mol}$ and $W_{\text{O}_2} = 32.0 \text{ g/mol}$ represent their molecular masses. The reaction rate in the species equation is denoted by $\dot{\omega}_{\text{CH}_4} = -W_{\text{CH}_4}Q$, and the heat release due to combustion in the enthalpy equation is expressed as $\dot{\omega}_T = -\Delta h_f^o Q$, where $\Delta h_f^o = -804.1 \text{ kJ/mol}$ is the standard enthalpy of reaction.

Figure 3 shows the base flow streamwise velocity and temperature fields at a bulk velocity of $U_0 = 3.0 \text{ m.s}^{-1}$. For this condition, the corresponding inflow Reynolds number defined as $Re = \rho_0 U_0 D/\mu_0$ is equal to 2282. A simple parabolic profile is prescribed as the inlet velocity. The inflow conditions for temperature and mass fraction of methane–air gas compositions are set as $T_0 = 300 \text{ K}$, $Y_{\text{CH}_4} = 0.043$, $Y_{\text{O}_2} = 0.213$ and $Y_{\text{N}_2} = 0.744$, corresponding to fuel-oxidizer equivalence ratio $\phi = \frac{Y_{\text{CH}_4}/Y_{\text{O}_2}}{(Y_{\text{CH}_4}/Y_{\text{O}_2})_{\text{st}}} = 0.8$, where the stoichiometric ratio $(Y_{\text{CH}_4}/Y_{\text{O}_2})_{\text{st}} = 0.25$. No-slip and adiabatic conditions are imposed on the inflow channel walls. The dump-plane wall (x = 0) connected to the outer corner of the annular nozzle is assumed to be no-slip and isothermal at $T_0 = 300 \text{ K}$. Note that the use of a slow coflow, as employed for stabilisation purposes in Birbaud *et al.* (2008), is not considered here. No-slip and isothermal conditions are also imposed on the annular centrebody, with the wall temperature fixed at $T_r = 700 \text{ K}$, as in



FIGURE 3. Streamwise velocity and temperature associated with the steady base state at Re = 2282.

Case	Marker	$x_{\rm sg}/D$	$r_{\rm sg}/D$	α^{-1}	Mesh elements
(<i>a</i>)	+	13.6	2.7	20	180 481
(<i>b</i>)	Δ	10.9	2.3	40	180 481
(<i>c</i>)	0	9.1	1.8	60	180 481
(<i>d</i>)	\$	13.6	2.7	20	221 019
(e)	П	13.6	2.7	20	251 757

TABLE 1. Sponge layer parameters and number of mesh elements for eigenmode calculations in figure 4.

the reference. Testing reveals that varying the centrebody temperature within the range 700 K to 1200 K only meaningfully alters the temperature field in the immediate vicinity of the rod, without noticeable changes to the base flame position. At the lateral boundary far from the flame $(r = r_{\text{max}})$, a free-slip condition is imposed on the velocity, and the temperature and equivalence ratio are set as $T_0 = 300$ K and $\phi = 0$. A symmetry condition is imposed along the centreline. Finally, a stress-free condition is employed at the downstream boundary, with Neumann conditions on the temperature and equivalence ratio $(x = x_{\text{max}})$.

In the following, we investigate V-flames in a range of bulk velocities from $U_0 = 2.2 \text{ m.s}^{-1}$ to $U_0 = 3.8 \text{ m.s}^{-1}$. The prescribed conditions result in a Reynolds number $Re = \rho_0 U_0 D/\mu_0$ ranging from 1674 to 2891, where ρ_0 and μ_0 denote the density and molecular viscosity at the inflow. Figure 1 shows the base flame shape and vorticity distribution at both ends of the Reynolds number range investigated. The flame is elongated downstream as the velocity is increased.

Sponge layers are introduced at the downstream ($x = x_{max}$) and lateral boundaries ($r = r_{max}$) to prevent spurious back-scattering (Lesshafft 2018). The sponge layer implementation from (Meliga *et al.* 2010) is employed, wherein viscosity is artificially increased in the sponge regions. The

molecular viscosity μ is divided by the sponge layer expression sg(r, x), formulated as

$$sg(r, x) = 1 \text{ if } r \leqslant r_{\text{sg}} \text{ and } x \leqslant x_{\text{sg}},$$

$$sg(r, x) = 1 + (\alpha - 1)\zeta(x, x_{\text{sg}}) \text{ if } r \leqslant r_{\text{sg}} \text{ and } x > x_{\text{sg}},$$

$$sg(r, x) = sg(r_{\text{sg}}, x) + \left[\alpha - sg(r_{\text{sg}})\right]\zeta(r, r_{\text{sg}}) \text{ if } r > r_{\text{sg}},$$

(2.8)

where α^{-1} is listed in table 1. Here, x_{sg} and r_{sg} denote the starting position of the sponge layers in the streamwise and radial directions. The function ζ , defined by

$$\zeta(a,b) = \frac{1}{2} + \frac{1}{2} \tanh\left\{\gamma \tan\left(-\frac{\pi}{2} + \pi \frac{|a-b|}{l}\right)\right\},$$
(2.9)

yields a smooth transition of μ from the inner region to the truncated boundaries. In this expression, the constant γ is set to 4 and *l* denotes the sponge layer thickness, equal to $x_{\text{max}} - x_{\text{sg}}$ or $r_{\text{max}} - r_{\text{sg}}$ in the streamwise and radial directions, respectively. It is important to note that the transport coefficients D_s and D_h are also increased in the sponge layer as they are proportional to μ . This implementation is applied both in the computation of the base flow and in the subsequent linear analysis.

The nonlinear governing equations are discretised on the unstructured mesh presented in figure 2 using 180 481 triangular elements. High grid resolution is allocated at the flame surface, as shown in figure 2(b), with a maximum mesh resolution of $\Delta x = 0.08$ mm. A continuous Galerkin method is employed using mixed Taylor–Hood finite elements, of quadratic order for the velocity and linear order for other flow variables. The base states are calculated by Newton iteration. Readers may refer to Appendix B of Wang (2022) for more details on the numerical methods.

3. Global linear stability analysis

To analyse the onset and behaviour of self-sustained oscillations in V-flames, a global linear stability analysis is conducted by computing the eigenmodes associated with the Jacobian matrix of the governing equations, which are linearised around the steady base state. Equations (2.1-2.4) are linearised with respect to the primitive variables (ρ , u, h, Y_{CH_4} , p) at each grid point of the entire numerical domain. The flow fluctuations q'(x, t) can be expanded in the basis of eigenmodes $q'_i(x, t) = \phi_i(x) \exp(\lambda_i t)$ obtained from the generalised eigenvalue problem,

$$\lambda_j \boldsymbol{B} \boldsymbol{\phi}_j = \boldsymbol{A} \boldsymbol{\phi}_j. \tag{3.1}$$

The matrices **B** and **A** are constructed from the linearisation of (2.1-2.4). The eigenvalues λ_j and associated eigenvectors ϕ_j are computed using a Krylov-Schur method. The frequency is defined as $2\pi f_j = \text{Im}[\lambda_j]$, and the growth rate is defined as $2\pi \sigma_j = \text{Re}[\lambda_j]$, so that $\lambda_j/(2\pi) = \sigma_j + if_j$. Furthermore, their non-dimensional counterparts are defined as the Strouhal number St $= \frac{fD}{U_0}$ and $\tilde{\sigma} = \frac{\sigma D}{U_0}$. Instabilities associated with non-zero azimuthal numbers are not considered in this study, although they are known to arise spontaneously in isothermal annular jets (Douglas *et al.* 2022) or in conical flames (Douglas *et al.* 2023).

3.1. Survey of the global eigenspectrum

The linear eigenmodes associated with steady base states at Reynolds numbers ranging from Re = 1674 to Re = 2891 with an increment of $\Delta Re = 76$ are calculated (corresponding to an inflow velocity increment of $\Delta U_0 = 0.1 \text{ m.s}^{-1}$). Different families of eigenmodes are identified based on their dependence on boundary conditions, their eigenmode structures, and their trends



FIGURE 4. Eigenspectra at Re = 2282. (a) Convergence with respect to parameters of sponge layers. (b) Convergence with respect to grid resolution. Legends are given in table 1. Different categories of eigenmodes are marked with colors: flame-column modes (green "+") in figure 5(a-c), plume modes (blue "+") in figure 5(d-f), flame-tips modes (red "+") in figure 6 and flame-tip-downstream modes (brown "+") in figure 5(g-i).



FIGURE 5. Three families of eigenmodes at Re = 2282. Radial velocity fluctuations are shown. (*a-c*) Flame column modes: first three modes with green markers "+" in figure 4. (*d-f*) Plume modes: first three modes with blue markers "+". (*g-i*) flame-tip-column modes: first three modes with brown markers "+". Black contour: an isocontour of base state vorticity illustrating the free shear layer position; yellow contour: an isocontour of base state net release rate illustrating the flame front position.

with respect to the Reynolds number. Specifically, their convergence with respect to parameters of the sponge layers is examined, by using the different values given in rows (a-c) of table 1. From case (a) to (c), the sponge layers are increasingly large and viscous. The sponge layer in case (c) corresponds to around one-half of the whole domain length, with a sixty-fold increased molecular viscosity at the boundaries. The results are presented in figure 4(a), where the eigenmodes that overlap with the three different markers are considered converged.

The eigenfunctions associated with the identified categories are shown in figures 5 and 6, marked with different cross colors in figure 4(a), using the parameters of case (a) in table 1. In each figure, the position of the flame surface is illustrated by a yellow isocontour corresponding to 10% of the maximum heat release rate, while the shear is illustrated by a black isocontour corresponding to 33% of the maximum azimuthal vorticity. The eigenmode spectra at Reynolds



FIGURE 6. Branch of flame tip modes at Re = 2282. First three modes (*a*-*c*) with red markers "+" in figure 4. Top of each plot: heat release rate fluctuation. Bottom of each plot: radial velocity fluctuation. Black contour: an isocontour of base state vorticity illustrating the free shear layer position; yellow contour: an isocontour of base state heat release rate illustrating the flame front position.



FIGURE 7. Eigenspectra at different Reynolds number. Branches of flame-tip modes are marked as red. The dimensional temporal growth rates and frequencies are used for comparison.

numbers equal to 1978, 2282, 2586, and 2891 are presented in figure 7. Four main families of eigenmodes are identified:

(i) *Flame-column modes* (green crosses "+" in figure 4, eigenmodes shown in 5a-c). These modes are characterised by their low frequencies; they are the least stable family of eigenmodes for Re < 2586. These modes do not undergo destabilisation as the Reynolds number increases but are notably influenced by the parameters of the sponge layer. The eigenmode structures exhibit spatial growth primarily in the streamwise direction. Specifically, the mode associated with the lowest frequency, illustrated in figure 5(a), displays maximum amplitude at the downstream end of the computational domain. This fluctuation expands radially to both sides of the shear layer, with the inner side extending close to the centerline. At higher frequencies, the peak fluctuation moves upstream, and spreads closer to both sides of the shear layer. Such modes, characterised

by an amplitude maximum near the domain's downstream end, are commonly encountered in incompressible and compressible jets, where they are attributed to the stable advection of nearly neutral structures within the shear layer (Garnaud *et al.* 2013). In general, these modes do not converge with larger domain sizes and are influenced by the sponge layers at the boundary (Lesshafft 2018). Given that the fluctuations fill the column of the plume, we denote these modes as flame-column modes, akin to jet-column modes.

(ii) Plume modes (blue crosses "+" in figure 4, eigenmodes associated with the three lowest frequencies shown in 5d-f). Along this branch, identified at relatively low frequencies, the temporal growth rates exhibit an increasing trend with frequency. Remarkably, these modes remain unaffected by the sponge layer, suggesting that they form a family distinct from the flame column modes. Although the branch experiences a slight destabilisation with growing Reynolds numbers, all modes within this range of *Re* remain stable. The fluctuation structures are primarily localised slightly downstream of the flame surface and within the jet shear region, corresponding to areas of heightened base vorticity. Notably, the maximum perturbation is consistently observed around x/D = 4 for the three leading eigenmodes, positioned closely along the shear in the radial direction. This specific location corresponds to the point where the base flow velocity and temperature profiles develop to be parallel in the streamwise direction, creating a base flow reminiscent of a non-reacting hot jet. Similar eigenmode structures were previously identified in the mixing layer of a plume, as illustrated in figure 4(b) of Chakravarthy et al. (2018). In their study of plumes, the maximum fluctuation amplitude is found very close to the inflow, corresponding to the region with the maximum density gradient in the base flow and confined within the mixing layer. Despite the absence of buoyancy effects in the present governing equations, we refer to this branch as plume modes.

(iii) *Flame-tip modes* (red crosses "+" in figure 4, leading eigenmodes shown in figure 6, red crosses "+" in figure 7). This branch constitutes a prominent feature in V-flames, notably separated from other more stable eigenvalues in the spectra. The eigenmodes along this branch remain unaffected by the sponge layer. However, with an increase in Reynolds number, the certain members of this branch become unstable. Specifically, the mode associated with the lowest frequency becomes unstable at Re = 2815, suggesting a Hopf bifurcation. Subsequently, we refer to this mode as the "leading flame-tip mode." The fluctuation of heat release rate and velocity is confined to the inner mixing layer, extending closely downstream from the intersection of the flame surface and the jet shear. The maximum fluctuation is identified in the flame extinction zone at around x/D = 3 for the leading flame-tip mode. For higher-frequency flame-tip modes, the maximum is located further upstream, closer to the flame surface, and the associated fluctuations exhibit higher wavenumbers.

(iv) *Flame-tip-column modes* (brown crosses "+" in figure 4, eigenmodes shown in 5g-*i*). This branch encompasses stable eigenmodes across a broad range of frequencies. The eigenmodes exhibit fluctuations at the flame extinction region and downstream close to the centreline. Notably, the fluctuation amplitudes at the downstream end become more pronounced with higher frequency. However, these modes are sensitive to the sponge layer parameters and remain unaffected by changes in Reynolds number.

The convergence of eigenmodes with respect to the mesh refinement is examined at Re = 2282 using meshes with 180 481, 221 019 and 251 757 elements. Figure 4(*b*) shows that convergence has been achieved on the reference mesh with 180 481 elements for all the eigenmodes described above except certain plume modes. The poor convergence of the plume modes seems to result from the fact that the maximum fluctuation of those plume modes are located at around x/D = 4 where the change of local refinement is relatively abrupt. Nonetheless, as the least stable plume mode is converged with respect to refinement on the reference mesh and its associated growth rate is negative, we conclude that further refinement is not necessary for our global instability study.



FIGURE 8. Calculation of Lagrangian advection time and comparison with leading flame-tip mode frequencies. (a) Steady base states at Re = 2282. Top: vorticity Ω . Bottom: heat release rate ω_T . Both variables are normalised with their maximum. Marker " Δ " represents the grid associated with maximum vorticity. Marker " \blacksquare " represents the intersection of backward integration and x = 0. Marker " \bullet " represents the peak of Lagrangian heat release rate along the streamline stemming from " \blacksquare ". (b) Lagrangian heat release as a function of time t normalised by D/U_0 . The advection time is obtained as the time lag between " \blacksquare " and " \bullet ". (c) Evolution of the Strouhal number with Reynolds number. Marker " \bullet " denotes the leading flame-tip modes. Marker \circ represents the Strouhal number calculated from the average advection time over all starting grid points where the vorticity exceeds 99% of its global maximum magnitude. The associated error bars are shown.

To summarise, the flame-column modes and the flame-tip-column modes exhibit intense oscillations at the end of the numerical domain, with their associated eigenvalues significantly influenced by sponge layer parameters. This suggests that these modes arise from spurious pressure feedback from the outflow, rather than from physical instabilities. In contrast, the plume and the flame-tip modes remain unaffected by the sponge layers, indicating a more physical nature. The plume modes appear to result from the extended shear layer located downstream from x/D = 4, sharing similar base flow and eigenmode structures with a non-reacting plume. Conversely, the flame-tip modes, characterised by strong oscillations at the flame extinctions around x/D = 3, become considerably more destabilised as the Reynolds number increases, leading to a positive growth rate at Re = 2891. The leading flame-tip mode, *i.e.*, the least stable mode along the flame-tip branch, demonstrates an increased frequency with the Reynolds number, as shown in figure 7.

3.2. Analysis of the flame-tip mode mechanisms

We now aim to characterise the physical mechanisms governing the behaviour of the leading flame-tip modes, drawing inspiration from earlier experimental work by Schuller (2003) and Durox *et al.* (2005). In their studies of perturbed laminar V-flames, the flame oscillations were interpreted as a consequence of vortex structures, advected from the burner exit along the shear layer, modulating the flame shape. Building upon this interpretation, the time delay between the heat release rate and an imposed velocity perturbation at the inlet can be linked to the convective velocity of the vortices and the convective velocity was estimated as one-half of the

maximum streamwise velocity at the burner exit. The convection distance was then determined by multiplying the time delay by the convective velocity, revealing a correspondence with a region where the roll-up of the flame surface was notably pronounced.

In contrast to these acoustically-forced experimental investigations, our focus is specifically toward the frequency of the leading flame-tip eigenmode, which is representative of intrinsic flame dynamics in the absence of external forcing. When the leading eigenmode is unstable, self-excited flame oscillations are expected. In our approach, we posit that the eigenfrequency of a flame-tip mode in a V-flame is linked to the advection time from the nozzle exit to the flame surface along the outer shear layer. The assumption of linearity underlines that the base flow remains unaffected by perturbations, ensuring steady streamlines and a steady flame shape in the base state. This allows for a more precise calculation of the convective velocity and distance compared to the finite-amplitude (i.e. nonlinear) oscillating flame scenarios explored experimentally by Schuller (2003) and Durox *et al.* (2005). However, the calculation is not without challenges, primarily due to the following factors. Firstly, the start- and endpoints of the convective distance are not clearly defined. Secondly, the shear layer exhibits a continuum of advection velocities across its finite thickness, and the precise streamline along which the vortices are advected remains to be chosen. Finally, hydrodynamic perturbations are generally dispersive, and are not advected by the base flow in a completely passive manner.

To address these challenges, we rely on two key assumptions in our calculation. First, we presume that the eigenmode oscillation stems from a non-local interaction between known upand downstream points. The upstream interaction initiates at the nozzle exit (x = 0), while the downstream interaction concludes at the point where the streamline intersects with the flame front. Second, we assume that the perturbations in the shear layer traverse through the region marked by the highest base flow vorticity without dispersion. Based on these assumptions, the advection time is computed from the base flow in three sequential steps:

(i) We identify the points corresponding to the strongest vorticity in the shear layer, denoted by " Δ " in figure 8(*a*).

(ii) A backward integration is executed from " \triangle " based on the base flow velocity field. The starting point where the obtained streamline intersects with the burner exit at x = 0 is then determined and marked as " \blacksquare ".

(iii) A forward integration is initiated from " \blacksquare ", through " \triangle ". Along this trajectory, we record the Lagrangian heat release rate, as illustrated in figure 8(*b*). The intersection between the streamline and the flame surface is defined by the peak of the Lagrangian heat release rate. This point is interpreted as the downstream terminus of the non-local interaction and is marked as " \bullet ". The advection time is subsequently determined as the time lag along the streamline between " \blacksquare " and " \bullet ".

This process is repeated for all points in the shear layer where the vorticity exceeds 99% of its global maximum magnitude. Consequently, a collection of differing advection times is obtained for each base flow at a specified Reynolds number. In figure 8(c), the black dots depict the averaged values of the Strouhal number, calculated as the inverse of the advection time, with error bars indicating the maximum and minimum within each set. The red dots represent the Strouhal number associated with the leading flame tip eigenmode. Remarkably, over the extensive range of Reynolds numbers investigated, the frequency of the leading flame tip mode closely aligns with the Lagrangian advection time. It is crucial to again note that the calculation does not consider the dispersion of perturbations, and instead assumes that perturbations travel at the base flow velocity. This assumption, along with spatial variations in the effective centre of the up- and downstream interaction regions, may explain the small errors observed at certain Reynolds number ranges.

This outcome suggests that the identified flame-tip modes indeed originate from a non-local feedback between the nozzle exit and the flame surface with a frequency characterised by the advection time of downstream traveling hydrodynamic perturbations along the outer shear layer.



FIGURE 9. Normalised temporal growth rate of the leading flame-tip mode with Reynolds number.



FIGURE 10. Illustration of subcritical behaviour at Re = 1978. Streamwise velocity signal recorded at (x/D, y/D) = (2.7, 1.2) with initial velocity perturbations of (a) 20% and (b) 50% magnitude. The snapshots of flame movement are shown in (a1-a4) and (b1-b4), corresponding to the time steps marked with red dots "·". A zoom-in of the time series is given in (b) over one period of the limit-cycle oscillation.

It can be hypothesised that the non-local feedback loop is closed by upstream-travelling pressure waves generated by the fluctuations at the flame tip. In the low Mach number limit, this pressure impulse is felt instantaneously at the nozzle outlet.

4. Nonlinear time-series analysis

The outcomes derived from the linear analysis indicate a Hopf bifurcation at Re = 2815, as evidenced by the temporal growth rate evolution associated with the flame-tip modes in figure 9. In this section, we delve into the nonlinear dynamics of the V-flame by superimposing finite-amplitude perturbations to the steady base states at each Re and conducting nonlinear time integration using a first-order implicit scheme. The results depicted in figure 10 correspond to a linearly stable base state at Re = 1978. The superposed perturbations are prescribed as the velocity components of the leading flame-tip mode. Both components of the velocity perturbation are normalised and then multiplied by 20% and 50% of the maximum amplitude associated with the streamwise base flow velocity. In each scenario, the temporal signal of the streamwise velocity is recorded at (x/D, r/D) = (2.7, 1.2) in a region proximal to the flame extinction zone. Figure 10 also presents snapshots of the flame surface at the time steps marked with red dots in the time signal.



FIGURE 11. Bifurcation diagram. The backward continuation path is represented with black dots (\cdot) , corresponding to the local maxima of streamwise velocity perturbation signal measured. The stable range of forward continuation path is represented by red squares (\blacksquare). The Hopf bifurcation point of the steady state is represented by a blue diamond (\diamond) .

At the initial perturbation amplitude of 20%, the velocity perturbation undergoes transient growth before it enters modal decay. Only a small section of the flame surface near the downstream edge (x/D > 2) displays visible oscillations during the transient growth, after which the flame surface converges to the steady base state. This transient growth is an indicator of the strong nonnormality of the system, which may promote bypass to other sub- or non-critical attractors, as in classical Poiseuille and Couette flows (Schmid & Henningson 2001). Indeed, at a larger initial amplitude of 50%, the perturbation undergoes growth before settling into a limit-cycle oscillation. Four snapshots in an oscillation cycle are presented in figure 10(b1-b4). A considerable portion of the flame surface (x/D > 1) exhibits oscillations, resulting in pronounced wrinkling along the length of the flame as well as dramatic flapping of the flame tip, resembling the oscillating flame surfaces observed in Durox *et al.* (2005). The results indicate that the system has at least two distinct nonlinear attractors at Re = 1978, which may or may not be connected to subcritical dynamics of the critical eigenmode.

The bifurcation diagram with respect to the Reynolds number is depicted in figure 11, revealing the presence of a bi-stable region between Re = 1750 and Re = 2815. Both forward and backward continuation paths, characterised by the streamwise velocity perturbation u'_x , are displayed in the figure, and the methods for tracking both paths are distinct.

Forward path: the forward continuation path along the steady base state is traced by introducing small-amplitude velocity fluctuations of the leading flame-tip mode onto the steady states at each investigated Reynolds number. The initial perturbation is set to the velocity of the leading eigenmode with a small amplitude of 1% of the maximum base flow streamwise velocity. For Re < 2815, all flames disturbed in this way reconverge to the original steady states, akin to the time series in figure 10(*a*). These steady states are represented by the red squares (**■**) in figure 11. At Re = 2815, marked by the blue diamond (\diamond), the disturbed flame undergoes temporal growth before entering an unsteady fluctuating state. A similar dynamic process is observed for the disturbed steady flame at Re = 2891. At both Reynolds numbers, the simulation duration corresponds to around six flow-through times of the computational domain including the sponge layer. This long duration was necessary to ensure subsidence of the initial transient, such that the fluctuations converge to a statistically stationary state. The resulting loss of stability of the steady state apparent from the time-domain simulations aligns with the critical Re for instability identified via global linear analysis in § 3.

Backward path: the backward continuation path is identified by gradually reducing the Reynolds





FIGURE 12. (a, d, g) Time signal of streamwise velocity perturbation measured at (x/D, r/D) = (2.7, 1.2). (b, e, k) 3D Poincaré sphere. (c, f, i) Poincaré section. (a, b, c) Re = 1978. (d, e, f) Re = 2358. (g, h, i) Re = 2815.

number with $\Delta Re = 76$, starting with the unsteady fluctuating state at the next-highest Re. (For example, the Re = 2815 case is initialised with the final state from the Re = 2891 case). The black dots (•) in figure 11 represent any local maxima identified in the velocity fluctuation signal at the probe location (x/D, r/D) = (2.7, 1.2). The cut-off time horizon before recording the local maxima corresponding to three flow-through times for the Reynolds number $2130 \le Re \le 2815$. The values of the local maxima are normalised by the temporal average of the velocity time series, representing the relative fluctuation amplitudes. The results show that fluctuations persist even when Re is decreased below the critical Reynolds number to Re = 2663. This indicates that the system exhibits subcritical dynamics and possesses at least two attractors below the critical point. The distribution of local maxima markedly narrows when the Reynolds number is reduced to 2510, indicating a change in the dynamic state. The distribution then further narrows when reducing the Reynolds number from 2510 to 2130. At Re = 2130, the distribution of local maxima collapses essentially to a single value, with the local maxima varying by less than 1% of the sliding average of ten successive local maxima samples. The presence of a single local maxima value is consistent with the limit-cycle oscillation behaviour observed in figure 12(a). Once the Reynolds number is reduced below 1750, the self-sustained oscillations vanish, and the system converges



FIGURE 13. Power density spectra along the backward continuation path by tracking (*a*) local streamwise velocity and (*b*) the global heat release rate. The frequencies of the leading linear flame-tip mode are superposed as white dots. The white dashed lines represent the Reynolds number associated with Hopf bifurcation. The spectra are displayed in the Reynolds number range $1750 \le Re \le 2891$. No flame oscillation is observed for $Re \le 1674$.

again to the steady state, as shown by the collapse of red squares and black dots at Re = 1598 and Re = 1674, the lower limit of our investigation.

The dynamic states associated with the oscillating flame at Re = 1978, Re = 2358 and Re = 2815 are further characterised by plotting the temporal signal of $u'_x(t)$ at (x/D, r/D) = (2.7, 1.2), the associated 3-D Poincaré trajectory computed with a time delay of $\tau = 5 \times 10^{-3}$ s and the corresponding 2-D Poincaré section in figure 12. Figure 12(b-c) illustrate that the associated phase space at Re = 1978 is an enclosed trajectory with two points depicted in the intersection plane, indicating a limit-cycle state. At Re = 2358, the temporal signal displays a nearly enclosed trajectory and plane intersection points scattered in clusters, a pattern representative of quasi-periodic dynamics. Finally, unlike the organised state-space nature identified for the lower Reynolds numbers, the temporal signal for Re = 2815 reveals erratic and intermittent behaviours, corresponding to the local maxima in figure 11 being densely distributed from zero to the maximum amplitude. In particular, the Poincaré section of figure 12(f) exhibits scattered points that suggest a chaotic nature of the flame fluctuations. Overall, this progression is consistent with a Reulle–Takens–Newhouse scenario for the onset of chaos in the annular V-flame.

Power Spectral Density (PSD) contours, computed along the backward continuation path, are depicted in figure 13, tracking the axial velocity perturbation at (x/D, r/D) = (2.7, 1.2) and the global heat release rate. The abscissa ranges from Re = 1750, the lower extent of the identified bistable region, to the upper limit represented by the critical Re at the white dashed line. The linear flame-tip mode frequencies obtained from the imaginary part of the leading linear eigenvalue is overlaid on the PSD. Tracking the point velocity evolution reveals a single fundamental frequency peak for Re < 2586, distinct from the flame-tip modes. At Re = 2586, another incommensurate frequency peak more closely aligning with the linear flame-tip mode frequency emerges. This suggests that a 2-torus is born in the phase space via a Neimark–Sacker bifurcation, and the system has transitioned from periodicity now to two-frequency quasiperiodicity. In contrast to the two-frequency quasiperiodicity presented in a previous forced synchronisation study (Guan *et al.* 2019), where quasiperiodicity arises from the competition between a self-excited mode and a forced mode, this one arises from the competition between two incommensurate self-excited modes. Further increases in Reynolds number result in more continuously distributed frequency spectra, indicative of the non-periodic state observed at Re > 2586. Examining the global heat release rate unveils dominant frequency components at twice the frequency observed when tracking point velocity. This indicates nonlinear harmonic interactions – a notable feature of the flame dynamics that cannot be captured by linear analysis.

In summary, increasing *Re* along the forward continuation path confirms that even smallamplitude perturbations lead to unsteady oscillations above the critical Reynolds number identified through linear analysis. Subcritical dynamics corresponding to hysteresis is identified along the backward continuation path when gradually reducing the Reynolds number, resulting in progressive transitions among unsteady dynamic states before the end of the hysteresis interval. At *Re* = 2510, close to the critical Reynolds number at *Re* = 2815, the dominant nonlinear oscillation frequency peak aligns with the linear flame-tip mode frequency, though other frequencies remain present. The nonlinear frequency associated with the subcritical oscillation below *Re* = 2510 is apparently unrelated to the flame-tip mode frequencies identified in the linearly stable subcritical base flows. A qualitative interpretation of the subcritical dynamics can be hypothesised from the flame shape snapshots in figure 10: nonlinear oscillations are self-sustaining when a sufficiently large portion of the downstream flame edge is perturbed with sufficiently large amplitude and vice versa.

5. Global linear analysis of the nonlinear mean flow

Finally, we compute the global eigenmodes of the time-averaged mean flow to investigate the potential recovery of the nonlinear oscillation frequency and/or structure by these mean flow eigenmodes. From the outset, this procedure is complicated by the non-unique definition of a mean flow, exposed by Karban *et al.* (2020), that arises from nonlinearity. Those authors demonstrated the issue by comparing resolvent analysis results for a compressible jet, obtained from averaging the same LES data in either primitive or conservative variables. The present reacting flow case provides an even more compelling illustration of mean-flow ambiguity. We will consider two equally plausible definitions of the mean reaction rate Q, noting that many more are possible. Representing the time average by an overbar, the first definition is the average of Q itself,

$$\bar{Q}(X_i, T) = A_r [X_{\text{CH}_4}]^{n_{\text{CH}_4}} [X_{\text{O}_2}]^{n_{\text{O}_2}} \exp\left(-\frac{T_a}{T}\right).$$
(5.1)

The second definition inserts the mean flow variables into the definition of Q,

$$Q(\bar{X}_{i},\bar{T}) = A_{r} [\bar{X}_{CH_{4}}]^{n_{CH_{4}}} [\bar{X}_{O_{2}}]^{n_{O_{2}}} \exp\left(-\frac{T_{a}}{\bar{T}}\right).$$
(5.2)

The mean reaction rate, assessed by both definitions, is depicted in figure 14. $\bar{Q}(X_i, T)$ reveals pronounced oscillations of the flame surfaces, leading to the progress rate being distributed in a region around flame extinction. Conversely, $Q(\bar{X}_i, \bar{T})$ displays only a thin flame surface and fails to represent the unsteady oscillations. It is worthwhile to note that in turbulent reacting flows, the difference between two reaction rates is often employed to assess the turbulence–chemistry interaction, which is important in turbulent reaction modelling (Poinsot & Veynante 2005; Duan & Martín 2011; Di Renzo & Urzay 2021). Conventionally, the second definition $Q(\bar{X}_i, \bar{T})$, called the *laminar chemistry* or *laminar reaction rate* model, only takes the frozen mean flow quantity into account, as if in a steady laminar flame. Conversely, the first definition $\bar{Q}(X_i, T)$, called



FIGURE 14. Time-averaged reaction rate $Q(Y_{CH_4}, T)$ (top) and reaction rate of time-averaged variables $Q(\bar{Y}_{CH_4}, \bar{T})$ (bottom). The variables are normalised by their maximum.



FIGURE 15. Reaction rate fluctuation Q' at Re = 1978. (a) Fourier modes at the limit-cycle fundamental frequency of 110.0 Hz, obtained from nonlinear simulation. (b) A-priori test at 110.0 Hz. (c) Computed mean flow eigenmode corresponding to the eigenvalue at (108.8 – 45.8i) Hz. (d) Computed mean flow eigenmode corresponding to the eigenvalue at (159.1 – 0.7i) Hz.

the *turbulent reaction rate*, includes the species and temperature fluctuations modulated by the turbulent flow field. Figure 14 shows that even in a laminar flame, unsteadiness can lead to significant differences between the mean reaction rates evaluated by these definitions. Thus, the conventional notion of a *laminar chemistry* model requires caution.

In the linearised reacting flow equations, the expression for the linearised reaction rate, Q', is derived as

$$Q' = \bar{Q} \left((n_{\text{CH}_4} + n_{\text{O}_2}) \frac{\rho'}{\bar{\rho}} + n_{\text{CH}_4} \frac{Y'_{\text{CH}_4}}{\bar{Y}_{\text{CH}_4}} + n_{\text{O}_2} \frac{Y'_{\text{O}_2}}{\bar{Y}_{\text{O}_2}} + \frac{T_a T'}{\bar{T}^2} \right),$$
(5.3)

where the mean reaction rate \bar{Q} is factored out and provided by the second expression $Q(\bar{X}_i, \bar{T})$. The species' primitive variable is chosen as Y_{CH_4} , allowing the fluctuation of oxygen to be expressed as $Y'_{O_2} = (2W_{O_2}/W_{CH_4}) Y'_{CH_4}$ (Avdonin *et al.* 2019). A mean flow analysis is conducted at Re = 1978, where the saturated unsteady dynamics

A mean flow analysis is conducted at Re = 1978, where the saturated unsteady dynamics correspond to a subcritical limit-cycle oscillation. The Fourier mode is extracted at the limit-cycle fundamental frequency of 110.0 Hz, as identified in figure 12(a-c) and 13. Figure 15(a) presents the associated Fourier mode of progress rate fluctuation, serving as a reference for fluctuation structures. These structures manifest as progress rate wrinkles convecting along the distributed mean reaction zone, as assessed through $\bar{Q}(Y_{CH_4}, T)$. Concurrently, figure 17(a) illustrates the Fourier mode of radial velocity, revealing oscillations in both the flame region and the extended shear layer. The identified Fourier mode structures underscore the distinctive characteristics of



FIGURE 16. Eigenspectrum of the time-averaged mean flow at Re = 1978. Blue dashed line indicates the limit-cycle frequency of the velocity perturbation at 110.0 Hz. Eigenvalues marked in red are (108.8 – 45.8i) Hz and (159.1 – 0.7i) Hz, for which the corresponding eigenmode structures are given in figure 15 and 17, respectively.



FIGURE 17. Radial velocity fluctuation u'_r at Re = 1978. (a) Fourier modes at the limit-cycle fundamental frequency of 110.0 Hz, obtained from nonlinear simulation. (b) Computed mean flow eigenmode corresponding to the eigenvalue at (108.8 – 45.8i) Hz. (c) Computed mean flow eigenmode corresponding to the eigenvalue at (159.1 – 0.7i) Hz.

subcritical nonlinear dynamics in the V-flame compared to the linear flame-tip modes. Note that the extracted frequency 110.0 Hz is not the dominant frequency of the heat release rate, which appears at the first harmonic (*cf.* Figure 13(b)).

The outcomes of the *a priori* assessments for Q' utilising $\overline{Q} = Q(\overline{Y}_{CH_4}, \overline{T})$ in its formulation are displayed. Fourier modes of the flow variables Y'_{CH_4} and T' are inserted into (5.3), following the methodology employed for *a priori* tests in turbulent reaction models (Kaiser *et al.* 2023). The structure of Q' acquired using $\overline{Q} = Q(\overline{Y}_{CH_4}, \overline{T})$ is depicted in figure 15(*b*), showcasing travelling waves along the thin flame surface. These structures are akin to the shape of mean flow chemical progress rates; however, they deviate markedly from the reference Fourier mode structures.

The resulting mean flow spectrum presented in figure 16 reveals a separated branch of eigenvalues, akin to the flame-tip modes identified for the base flow in § 2. The two leading eigenvalues on this branch exhibit temporal growth rates close to zero, but their associated frequencies are distinct from the 110.0 Hz fundamental frequency of the nonlinear limit-cycle state as indicated by the dashed blue line. The mean flow eigenmode structures associated with the eigenvalues marked with red are also displayed. Of these, one occurs at (108.8 - 45.8i) Hz, a heavily damped eigenvalue with a frequency close to the fundamental tone of the nonlinear oscillation. Another is the leading, marginally-damped eigenvalue on the separated branch at (159.1 - 0.7i) Hz. The mean flow modes of progress rate fluctuation in figure 15(c-d) and

those of radial velocity fluctuation in figure 17(b-c) were found not to align with the reference Fourier modes. The strong velocity fluctuations downstream in figure 17(b) indicates that the eigenvalue (108.8 - 45.8i) Hz is similar to a flame-column mode, and it is not relevant to the fundamental frequency of the nonlinear oscillation. The structure of velocity fluctuation of the leading eigenvalue (159.1 - 0.7i) Hz in figure 17(c) shares a certain resemblance to the Fourier mode in figure 17(a), although the identified eigenvalue frequency is notably different.

A strong intrinsic nonlinearity of the mean reaction rate was encountered in our prior work on flames anchored in the wake of a 2-D square cylinder in a channel (Wang et al. 2022b). Intriguingly, however, the mean flow analysis in that work accurately captured the oscillation frequency. This discrepancy can be mainly attributed to the different instability mechanisms in a 2-D square cylinder flame and an annular V-flame, already inferred from their distinct eigenspectra. The dominant dynamics in the former case arose from a hydrodynamic shear instability (the Bénard-Von Kármán instability) in the wake recirculation zone, with only secondary influences from the spatially-separated flame front region. Conversely, the dynamics of the flame surface region in the current case likely play a crucial role in the V-flame instability due to the non-local feedback mechanism discussed in § 3.2. The global heat release rate oscillates at the first harmonic of the fundamental oscillation tone (see figure 13), while linear analysis assumes that all flow fields (including the heat release rate) oscillate at a single frequency. Hence, the harmonic interaction between the heat release rate and flow velocity can not be captured - it is fundamentally nonlinear. Overall, the results highlight that the success of flame dynamics modelling based on linear mean flow analysis is not guaranteed. In general, agreement between linear models and nonlinear reality are configuration-specific and should not be expected without extensive and thorough validation.

6. Conclusions

This study computationally investigates the self-excited axisymmetric oscillations of a lean premixed V-flame in a laminar annular jet. The reactive flow is simulated using an irreversible single-step global chemistry model representing a lean premixed methane—air reaction coupled to the low-Mach number compressible Navier—Stokes equations. Following the identification of steady states of the linearised reacting flow equations, we conduct a detailed survey of the axisymmetric global eigenmodes computed around these base states. For sufficiently high Reynolds number, destabilisation occurs for an eigenmode on an "arc branch" separated from other families of more stable eigenmodes. These arc branch modes, which we term "flame-tip" modes, are characterised by strong fluctuations near the flame tip and are independent of numerical domain truncation. A detailed, quantitative description of the linear feedback mechanism driving their destabilisation is provided by associating the frequency of the leading flame-tip mode with the Lagrangian advection time along the outer shear layer from the nozzle exit to the flame tip. This mechanism is thereby identified as an instance of intrinsic thermoacoustic instability.

Upon assessing these linear results against nonlinear time-domain simulations, however, a more complex picture emerged. For small initial perturbations, the onset of sustained unsteadiness corresponds to the critical Reynolds number identified by linear analysis. Conversely, for sufficiently large perturbations, self-sustained oscillations occur even at Reynolds number values where the flame is linearly stable, revealing a substantial interval of hysteresis. Continuation analysis along this branch of unsteady solutions reveals an ordered sequence of state transitions in the subcritical regime. Along most of the unsteady branch, the unsteady flow settles into a limit-cycle state with a periodicity that does not match any linear eigenmodes of the base flow along the steady solution branch. However, as the Reynolds number approaches the critical value for linear instability of the steady state, the dynamics become enriched by an ordered sequence of increasingly high-dimensional features, including apparent quasi-periodicity and chaos. Interestingly, the frequency associated with the leading (stable) eigenmode of the base state

becomes prominently represented in the power density spectrum during this process, suggesting a Neimark–Sacker bifurcation arising from two competitive modes. This dynamics is consistent with a Reulle–Takens–Newhouse scenario for the onset of chaos in the V-flame. Together, these findings shed new light on the nonlinear dynamical elements underpinning the observed V-flame behaviours.

Finally, we assess the capacity of linear methods to predict basic features of the V-flame dynamics, as is commonly attempted in the reduced-order modelling literature. Aiming to predict the subcritical limit-cycle oscillation frequency and/or structure by computing eigenmodes of the time-averaged mean flow, we encounter issues stemming from the strong nonlinearity of the system, particularly the reaction rate term. Both *a priori* assessment and the computed mean flow eigenmodes reveal notable disparities in the mean flow eigenvalues and eigenmodes when compared to the reference Fourier modes associated with the nonlinear frequency of the limit-cycle fundamental. This result highlights a key limitation of linear mean flow analysis, which cannot accommodate such fundamentally nonlinear behaviour as harmonic interactions. This failure in the V-flame configuration should be contrasted with our successful linear modelling assessments in earlier work on a cylinder-stabilised flame (Wang *et al.* 2022*b*), which featured supercritical bifurcation behaviour dominated by hydrodynamic feedback mechanisms.

Declaration of Interests

The authors report no conflict of interest.

Author ORCIDs

- C.-H. Wang: 0000-0002-4522-1320
- C. Douglas: 0000-0002-5968-3315
- Y. Guan: 0000-0003-4454-3333
- C.-X. Xu: 0000-0001-5292-8052
- L. Lesshafft: 0000-0002-2513-4553

Acknowledgements

This study was inspired by the chapter "Modal analysis of a V-shaped flame" of C.-H. Wang's PhD thesis. For the original work in that chapter, C.-H. Wang and L. Lesshafft worked in collaboration with Grégoire Varillon and Wolfgang Polifke (TU Munich), who computed base states and conducted time-resolved simulation of V-flames with OpenFOAM. The authors would like to express their sincere gratitude for the scientific inputs from G. Varillon and W. Polifke in the original work that inspired the present study. C.-H. Wang was supported through a PhD scholarship from École Polytechnique and by the Shuimu postdoc fellowship from Tsinghua University. C.-H. Wang acknowledges the China Postdoctoral Science Foundation (CPSF) and the National Natural Science Foundation of China (NSFC) for funding this work (Grant No. 2022TQ0181, 12388101). C. Douglas acknowledges funding for this project from the European Union's Horizon 2020 research and innovation program under the Marie Skłodowska–Curie Grant Agreement No. 899987. Y. Guan was supported by the PolyU Start-up Fund (Project No. P0043562) and the NSFC (Grant No. 52306166).

REFERENCES

ALBAYRAK, A., BEZGIN, D. & POLIFKE, W. 2018 Response of a swirl flame to inertial waves. *Int. J. Spray Combust. Dyn.* **10** (4), 277–286.

- AVDONIN, A., MEINDL, M. & POLIFKE, W. 2019 Thermoacoustic analysis of a laminar premixed flame using a linearized reactive flow solver. *Proc. Combust. Inst.* **37** (4), 5307–5314.
- BARKLEY, D 2006 Linear analysis of the cylinder wake mean flow. EPL 75 (5), 750.
- BIRBAUD, A. L., DUCRUIX, S., DUROX, D. & CANDEL, S. 2008 The nonlinear response of inverted "V" flames to equivalence ratio nonuniformities. *Combust. Flame* 154 (3), 356–367.
- BIRBAUD, A. L., DUROX, D., DUCRUIX, S. & CANDEL, S. 2007 Dynamics of confined premixed flames submitted to upstream acoustic modulations. *Proc. Combust. Inst.* **31** (1), 1257–1265.
- BLANCHARD, M. 2015 Linear and nonlinear dynamics of laminar premixed flames submitted to flow oscillations. PhD thesis, Ecole Polytechnique.
- BLANCHARD, M., SCHULLER, T., SIPP, D. & SCHMID, P. 2015 Response analysis of a laminar premixed M-flame to flow perturbations using a linearized compressible Navier-Stokes solver. *Phys. Fluids* 27 (4), 043602.
- BROKOF, P., DOUGLAS, C. M. & POLIFKE, W. 2024 The role of hydrodynamic shear in the thermoacoustic response of slit flames. In *Proceedings of the 40th International Symposium on Combustion*. Milan, Italy.
- CANDEL, S., DUROX, D., SCHULLER, T., BOURGOUIN, JEAN-F. & MOECK, J. P. 2014 Dynamics of swirling flames. *Annu. Rev. Fluid Mech.* 46, 147–173.
- CASEL, M., OBERLEITHNER, K., ZHANG, F., ZIRWES, T., BOCKHORN, H., TRIMIS, D. & KAISER, T. 2022 Resolvent-based modelling of coherent structures in a turbulent jet flame using a passive flame approach. *Combust. Flame* **236**, 111695.
- CERFACS 2017 CANTERA User's Guide. (https://www.cerfacs.fr/cantera/mechanisms/meth.php).
- CERQUEIRA, S. & SIPP, D. 2014 Eigenvalue sensitivity, singular values and discrete frequency selection mechanism in noise amplifiers: the case of flow induced by radial wall injection. J. Fluid Mech. 757, 770–799.
- CHAKRAVARTHY, R. V. K., LESSHAFFT, L. & HUERRE, P. 2018 Global stability of buoyant jets and plumes. J. Fluid Mech. 835, 654–673.
- COENEN, W., LESSHAFFT, L., GARNAUD, X. & SEVILLA, A. 2017 Global instability of low-density jets. J. Fluid Mech. 820, 187–207.
- DEMANGE, S., QADRI, U. A., JUNIPER, M. P. & PINNA, F. 2022 Global modes of viscous heated jets with real gas effects. *J. Fluid Mech.* **936**, A7.
- DI RENZO, M. & URZAY, J. 2021 Direct numerical simulation of a hypersonic transitional boundary layer at suborbital enthalpies. *J. Fluid Mech.* **912**, A29.
- DOUGLAS, C. M., EMERSON, B. L., HEMCHANDRA, S. & LIEUWEN, T. C. 2021*a* Forced flow response analysis of a turbulent swirling annular jet flame. *Phys. Fluids* **33** (8), 085124.
- DOUGLAS, C. M., EMERSON, B. L. & LIEUWEN, T. C. 2021b Nonlinear dynamics of fully developed swirling jets. J. Fluid Mech. 924, A14.
- DOUGLAS, C. M., EMERSON, B. L. & LIEUWEN, T. C. 2022 Dynamics and bifurcations of laminar annular swirling and non-swirling jets. J. Fluid Mech. 943, A35.
- DOUGLAS, C. M., POLIFKE, W. & LESSHAFFT, L. 2023 Flash-back, blow-off, and symmetry breaking of premixed conical flames. *Combust. Flame* 258, 113060.
- DUAN, L. & MARTÍN, M.P. 2011 Assessment of turbulence-chemistry interaction in hypersonic turbulent boundary layers. AIAA J. 49 (1), 172–184.
- DUROX, D., SCHULLER, T. & CANDEL, S. 2005 Combustion dynamics of inverted conical flames. Proc. Combust. Inst. 30 (2), 1717–1724.
- DUROX, D., SCHULLER, T., NOIRAY, N. & CANDEL, S. 2009 Experimental analysis of nonlinear flame transfer functions for different flame geometries. *Proc. Combust. Inst.* 32 (1), 1391–1398.
- EMERSON, B., LIEUWEN, T. & JUNIPER, M. 2016 Local stability analysis and eigenvalue sensitivity of reacting bluff-body wakes. J. Fluid Mech. 788, 549–575.
- EMERSON, B., O'CONNOR, J., JUNIPER, M. & LIEUWEN, T. 2012 Density ratio effects on reacting bluff-body flow field characteristics. J. Fluid Mech. 706, 219–250.
- GARNAUD, X., LESSHAFFT, L., SCHMID, P. & HUERRE, P. 2013 Modal and transient dynamics of jet flows. *Phys. Fluids* **25** (4), 044103.
- GUAN, Y., GUPTA, V., KASHINATH, K. & LI, L. K. B. 2019 Open-loop control of periodic thermoacoustic oscillations: experiments and low-order modelling in a synchronization framework. *Proc. Combust. Inst.* 37 (4), 5315–5323.
- HALLBERG, M. P. & STRYKOWSKI, P. J. 2006 On the universality of global modes in low-density axisymmetric jets. J. Fluid Mech. 569, 493–507.

- KAISER, T. L., VARILLON, G., POLIFKE, W., ZHANG, F., ZIRWES, T., BOCKHORN, H. & OBERLEITHNER, K. 2023 Modelling the response of a turbulent jet flame to acoustic forcing in a linearized framework using an active flame approach. *Combust. Flame* 253, 112778.
- KARBAN, U., BUGEAT, B., MARTINI, E., TOWNE, A., CAVALIERI, A. V. G. & LESSHAFFT, L. 2020 Ambiguity in mean-flow-based linear analysis. J. Fluid Mech. 900.
- KYLE, D. M. & SREENIVASAN, K. R. 1993 The instability and breakdown of a round variable-density jet. J. *Fluid Mech.* **249**, 619–664.
- LESSHAFFT, L. 2018 Artificial eigenmodes in truncated flow domains. *Theor. Comput. Fluid Dyn.* **32** (3), 245–262.
- LESSHAFFT, L., HUERRE, P., SAGAUT, P. & TERRACOL, M. 2006 Nonlinear global modes in hot jets. J. Fluid Mech. 554, 393–409.
- LIEUWEN, T. 2003 Modeling premixed combustion-acoustic wave interactions: A review. J. Propuls. Power 19 (5), 765–781.
- MANOHARAN, K. & HEMCHANDRA, S. 2015 Absolute/convective instability transition in a backward facing step combustor: Fundamental mechanism and influence of density gradient. J. Eng. Gas Turb. Power 137 (2).
- MARQUET, O. & LESSHAFFT, L. 2015 Identifying the active flow regions that drive linear and nonlinear instabilities. ArXiv:1508.07620.
- MCMURTRY, P., JOU, W., RILEY, J. & METCALFE, R. 1986 Direct numerical simulations of a reacting mixing layer with chemical heat release. *AIAA J.* **24** (6), 962–970.
- MEINDL, M., SILVA, C. & POLIFKE, W. 2021 On the spurious entropy generation encountered in hybrid linear thermoacoustic models. *Combust. Flame* 223, 525–540.
- MELIGA, P., SIPP, D. & CHOMAZ, J-M. 2010 Effect of compressibility on the global stability of axisymmetric wake flows. J. Fluid Mech. 660, 499–526.
- MONKEWITZ, P. A., BECHERT, D. W., BARSIKOW, B. & LEHMANN, B. 1990 Self-excited oscillations and mixing in a heated round jet. J. Fluid Mech. 213, 611–639.
- NOACK, B. R. & ECKELMANN, H. 1994 A global stability analysis of the steady and periodic cylinder wake. *J. Fluid Mech.* **270**, 297–330.
- OBERLEITHNER, K., STÖHR, M., IM, S., ARNDT, C. & STEINBERG, A. 2015 Formation and flame-induced suppression of the precessing vortex core in a swirl combustor: experiments and linear stability analysis. *Combust. Flame* **162** (8), 3100–3114.
- POINSOT, T. & VEYNANTE, D. 2005 Theoretical and numerical combustion. RT Edwards, Inc.
- QADRI, U. A., CHANDLER, G. J. & JUNIPER, M. P. 2015 Self-sustained hydrodynamic oscillations in lifted jet diffusion flames: origin and control. J. Fluid Mech. 775, 201–222.
- SAYADI, T. & SCHMID, P. 2021 Frequency response analysis of a (non-)reactive jet in crossflow. J. Fluid Mech. 922, A15.
- SCHMID, P. & HENNINGSON, D. 2001 Stability and transition in shear flows. Springer.
- SCHULLER, T. 2003 Mécanismes de couplage dans les interactions acoustiques-combustion. PhD thesis, Ecole Centrale Paris.
- SCHULLER, T., DUROX, D. & CANDEL, S. 2003 A unified model for the prediction of laminar flame transfer functions: comparisons between conical and v-flame dynamics. *Combust. Flame* 134 (1-2), 21–34.
- SCHULLER, T., POINSOT, T. & CANDEL, S. 2020 Dynamics and control of premixed combustion systems based on flame transfer and describing functions. *J. Fluid Mech.* **894**, P1.
- SILVA, C. F. 2023 Intrinsic thermoacoustic instabilities. PECS 95, 101065.
- SKENE, C. & SCHMID, P. 2019 Adjoint-based parametric sensitivity analysis for swirling M-flames. J. Fluid Mech. 859, 516–542.
- VISHNU, R., SUJITH, R. I. & AGHALAYAM, P. 2015 Role of flame dynamics on the bifurcation characteristics of a ducted v-flame. *Combust. Sci. Technol.* 187 (6), 894–905.
- WANG, C. 2022 Global linear analysis of flame instability. PhD thesis, Ecole Polytechnique.
- WANG, C., KAISER, T., MEINDL, M., OBERLEITHNER, K., POLIFKE, W. & LESSHAFFT, L. 2022a Linear instability of a premixed slot flame: flame transfer function and resolvent analysis. *Combust. Flame* 240, 112016.
- WANG, C., LESSHAFFT, L. & OBERLEITHNER, K. 2022b Global linear stability analysis of a flame anchored to a cylinder. J. Fluid Mech. 951, A27.
- ZHU, Y., GUPTA, V. & LI, L. K. B. 2017 Onset of global instability in low-density jets. J. Fluid Mech. 828, R1.