

Binary Hypothesis Testing for Softmax Models and Leverage Score Models

Yeqi Gao*

Yuzhou Gu †

Zhao Song‡

Abstract

Softmax distributions are widely used in machine learning, including Large Language Models (LLMs) where the attention unit uses softmax distributions. We abstract the attention unit as the softmax model, where given a vector input, the model produces an output drawn from the softmax distribution (which depends on the vector input). We consider the fundamental problem of binary hypothesis testing in the setting of softmax models. That is, given an unknown softmax model, which is known to be one of the two given softmax models, how many queries are needed to determine which one is the truth? We show that the sample complexity is asymptotically $O(\epsilon^{-2})$ where ϵ is a certain distance between the parameters of the models.

Furthermore, we draw analogy between the softmax model and the leverage score model, an important tool for algorithm design in linear algebra and graph theory. The leverage score model, on a high level, is a model which, given vector input, produces an output drawn from a distribution dependent on the input. We obtain similar results for the binary hypothesis testing problem for leverage score models.

*a916755226@gmail.com. The University of Washington.

†sevenkplus@gmail.com. Institute for advanced study.

‡zsong@adobe.com. Adobe Research.

Contents

1	Introduction	2
1.1	Main Result	3
1.2	Related Work	3
1.3	Roadmap	5
2	Preliminaries	5
2.1	Information Theory	5
2.2	Hypothesis Testing	6
2.3	Softmax Model	7
2.4	Leverage Score Model	7
3	Softmax Model	8
3.1	General Result	8
3.2	Lower Bound	8
3.3	Upper Bound	9
4	Leverage Score Model	10
4.1	General Result	10
4.2	Lower Bound	10
4.3	Upper Bound	12
5	Conclusion and Future Directions	13
A	Missing Proofs	15
A.1	General Result for Softmax Model	15
A.2	Lower Bound for Softmax Model	16
A.3	Local Upper Bound for Softmax Model	17
A.4	Local Upper Bound for Leverage Score Model	18

1 Introduction

In transforming various aspects of people’s lives, Large Language Models (LLMs) have exhibited tremendous potential. In recent years, numerous content learning and LLMs have been developed, including notable models such as Adobe firefly, Microsoft 365 Copilot [Spa23], Adobe Photoshop, and Google’s Meena chatbot [Rat20], along with the GPT series and others [RNS⁺18, RWC⁺19, DCLT18, RWC⁺19, YDY⁺19, BMR⁺20, BMR⁺20, Cha22, Ope23]. These models, together with those built upon them, have demonstrated significant prowess across diverse fields.

The robustness and vitality of their development are attested to by the widespread integration of LLMs. In the realm of Natural Language Processing (NLP), evaluations by [LBL⁺22, LBR⁺23, CPK⁺23, BCL⁺23] center around natural language understanding, while [WLJ⁺23, QZZ⁺23, PD23, CHBP23, CWJ⁺23] delve into natural language generation. LLMs have found applications in diverse fields, including both social science and science [GGL⁺23, DGG23, Fer23, NKL⁺23], medical applications [CLBBJ23, JGP⁺23], and engineering [PMM⁺23, SM⁺23, BCE⁺23, LXWZ23], showcasing their potent capabilities.

A consistent theme among these models is the adoption of the transformer architecture, a proven and highly efficient framework. The prevailing prevalence of models like ChatGPT [Ope23] further underscores the transformative impact of this architecture.

However, there is a crucial problem with large language models: their training costs and uncertainty regarding their inference ability in different parts of the whole. Understanding how different domains work is important in retrieval argument generation (RAG) [SWW⁺23, ZB24, SZ24], as well as sparsity for large language models by identifying the ability domain in the model which are important in solving the problem above. Then a question arose.

Can we distinguish different ability parts of Large Language Models by limited parameters sampling?

We give an initial step to the question from the theoretical perspective. As we delve deeper into large language models, softmax mechanism plays an important role in the computation of self-attention. But how the self-attention mechanism works, why it dedicates a lot to impressive ability in large language models, and what role it plays is still undiscovered.

So in this work, we want to explore the mechanism of softmax distribution from a binary hypothesis testing perspective. By delving into the intricacies of the softmax formulation, we explore which parameters are important by explaining how the softmax can be distinguished from each other. By delving into this idea, we can determine how many parameters are important in the inference of transformers [VSP⁺17].

In continuation of the paper and drawing upon a formulation similar to softmax, we also direct our attention to the distribution of leverage scores. Much like softmax, the leverage score is a distribution parameterized by a matrix. Both softmax and leverage score can be treated as functions of distribution within this context. Importantly, resembling softmax, leverage score assumes significance across various fields.

Leverage scores have demonstrated their significant utility in both linear algebra and graph theory. In the field of graph theory, researchers have extensively explored the application of leverage scores in various areas such as the generation of random spanning trees [Sch18], max-flow problems [DS08, Mad13, Mad16, LS20], maximum matching [vdBLN⁺20, LSZ20], and graph sparsification [SS08a]. Many studies have delved into the deep exploration of leverage scores, showcasing their effectiveness in optimization tasks such as linear programming [LS14, vdBLSS20], cutting-plane methods [Vai89, LSW15, JLSW20], semi-definite programming [JKL⁺20], and the approximation

of the John Ellipsoid [CCLY19]. These applications underscore the importance of leverage scores in the context of theory of computer science and linear algebra.

Based on the analysis provided, both the leverage score and softmax computation are parameterized by a single matrix. Given the significance of the application of softmax and computation, understanding the influence on parameter behavior becomes crucial. Hence, we delve into this inquiry by differentiating the model through parameter sampling and discussing how the number of samples affects the distinguishing ability. Our formal problem definition is now presented.

A softmax model is parameterized by a matrix $A \in \mathbb{R}^{n \times d}$, and denoted SoftMax_A . Given $x \in \mathbb{R}^d$, the model outputs an element $i \in [n]$ with probability $p_i = \langle \exp(Ax), \mathbf{1}_n \rangle^{-1} \exp(Ax)_i$. In the binary hypothesis testing problem, we are given access to a softmax model which is either SoftMax_A or SoftMax_B . We have query access to the model, that is, we can feed the model an input $x \in \mathbb{R}^d$, and it will produce an output. The goal is to determine whether the model is SoftMax_A or SoftMax_B , using the fewest number of queries possible.

We can similarly define the question for leverage score models. A leverage score model is parameterized by a matrix $A \in \mathbb{R}^{n \times d}$, and denoted Leverage_A . Given input $s \in (\mathbb{R} \setminus 0)^n$, the model returns an element $i \in [n]$ with probability $p_i = (A_s (A_s^\top A_s)^{-1} A_s^\top)_{i,i} / d$, where $A_s = S^{-1}A$, and $S = \text{Diag}(s)$ is the diagonal matrix with diagonal s . We define the binary hypothesis testing problem for leverage score models similarly to the softmax case.

1.1 Main Result

We now state informal versions of our main results.

Theorem 1.1 (Informal statement for softmax models). *Consider the binary hypothesis testing problem with two softmax models SoftMax_A and SoftMax_B .*

(Lower bound) If $\|B - A\|_{2 \rightarrow \infty} \leq \epsilon$, then any successful algorithm uses $\Omega(\epsilon^{-2})$ queries.

(Upper bound) If $B = A + \epsilon M$ for some small ϵ then the hypothesis testing problem can be solved in $O(\epsilon^{-2\nu})$ queries, where ν depends on A and M .

See Theorem 3.2 and Theorem 3.5 for formal statements.

Theorem 1.2 (Informal statement for leverage score models). *Consider the binary hypothesis testing problem with two leverage score models Leverage_A and Leverage_B .*

(Lower bound) If $\sum_{i \in [n]} \|B_{i,}^\top - A_{i,*}^\top\|_{\text{op}} \leq \epsilon$, then any successful algorithm uses $\Omega(\epsilon^{-1})$ queries.*

(Upper bound) If $B = A + \epsilon M$ for some small ϵ then the hypothesis testing problem can be solved in $O(\epsilon^{-2\nu})$ queries, where ν depends on A and M .

See Theorem 4.2 and Theorem 4.3 for formal statements.

1.2 Related Work

Theoretical Large Language Models (LLMs) Several investigations [CLMY21, LLH⁺23, RYW⁺19, HM19] have concentrated on theoretical analyses concerning LLMs.

The algorithm presented by [CLMY21], named ZO-BCD, introduces a novel approach characterized by advantageous overall query complexity and reduced computational complexity in each iteration. The work by [LLH⁺23] introduces Sophia, a straightforward yet scalable second-order optimizer. Sophia demonstrates adaptability to curvature variations across different parameter regions, a feature particularly advantageous for language modeling tasks with strong heterogeneity. Importantly, the runtime bounds of Sophia are independent of the condition number of the loss function.

Studies by [WWZ+22, LL21, DDH+21, BYKS22, HBKG23, XQP+22] investigate the knowledge and skills of LLMs. In the realm of optimization for LLMs, [KMH+20, CLMY21, RSM+23, LLH+23] have delved into this domain.

Demonstrating the effectiveness of pre-trained models in localizing knowledge within their feed-forward layers, both [HBKG23] and [MBAB22] contribute valuable insights to the field. The exploration of distinct "skill" neurons and their significance in soft prompt-tuning for language models is a central theme in the analysis conducted by [WWZ+22], building upon the groundwork laid out in a prior discussion by [LL21]. The activation of skill neurons and their correlation with the expression of relevant facts is a focal point in the research presented by [DDH+21], particularly in the context of BERT. In contrast, the work of [BYKS22] takes an entirely unsupervised approach, leveraging the internal activations of a language model to extract latent knowledge. Lastly, the investigation by [LYB+22] sheds light on the sparsity observed in feedforward activations of large trained transformers, uncovering noteworthy patterns in their behavior. In addition to the above, [MGN+23, DLMS23, ZHL+23] explore Zero-th order algorithms for LLMs.

Softmax Computation and Regression Softmax computation, a crucial element in attention computation [VSP+17], plays a pivotal role in the development of large language models. Several studies [AS23, BSZ23, LSZ+23, DMS23] delve into the efficiency of softmax computation.

To improve computational efficiency, [AS23] presents a quicker attention computation algorithm utilizing implicit matrices. Similarly, [BSZ23] utilizes lazy updates to speed up dynamic computation, while [DMS23] employs a randomized algorithm for similar efficiency gains. Conversely, [LSZ+23] utilizes an approximate Newton method that operates in nearly linear time.

[GMS23] centers on the convergence of overparameterized two-layer networks with exponential activation functions, whereas [DLS23, LSZ+23] explore regression analysis within the framework of attention computation. All of these studies specifically focus on softmax-based regression problems.

Leverage Scores Given $A \in \mathbb{R}^{n \times d}$ and $i \in [n]$, a_i represents the i -th row of matrix A . We use $\sigma_i(A) = a_i^\top (A^\top A)^\dagger a_i$ to denote the leverage score for the i -th row of matrix A . The concept of leverage score finds extensive applications in the domains of machine learning and linear algebra. In numerical linear algebra and graph theory, leverage scores serve as fundamental tools.

In the context of matrices, both the tensor CURT decomposition [SWZ19] and the matrix CUR decomposition [BW14, SWZ17, SWZ19] heavily rely on leverage scores. In optimization, areas such as linear programming [LS14, vdBLSS20], the approximation of the John Ellipsoid [CCLY19], cutting-plane methods [Vai89, LSW15, JLSW20], and semi-definite programming [JKL+20] incorporate leverage scores.

Within graph theory applications, leverage scores play a crucial role in max-flow problems [DS08, Mad13, Mad16, LS20], maximum matching [vdBLN+20, LSZ20], graph sparsification [SS08a], and the generation of random spanning trees [Sch18].

Several studies, such as [SS08b, DMIMW12, CW13], focus on the approximation of leverage scores. Simultaneously, Lewis weights, serving as a generalization of leverage scores, are explored in depth by [BLM89, CP15].

Hypothesis Testing Hypothesis testing is a central problem in statistics. In hypothesis testing, two (or more) hypotheses about the truth are given and an algorithm needs to distinguish which hypothesis is true.

The most classic testing problem is the binary hypothesis testing. In this problem, two distributions P_0 and P_1 are given, and there is an unknown distribution P which is either P_0 or P_1 . The

goal is to distinguish whether $P = P_0$ or $P = P_1$ by drawing samples from P . This problem is well-studied, with [NP33] giving tight characterization of the possible error regions in terms of the likelihood ratio. It is known that the asymptotic sample complexity of binary hypothesis testing for distributions is given by $\Theta(H^{-2}(P_0, P_1))$, where H denotes the Hellinger distance, see e.g., [PW23].

There are other important kinds of hypothesis testing problems. In the goodness-of-fit testing problem, a distribution Q is given, and there is an unknown distribution P which is known to be either equal to Q or far away from Q . The goal is to distinguish which is the true by drawing samples from P . In the two-sample testing problem, two unknown distributions P and Q are given, and it is known that either $P = Q$ or P and Q are far away from each other. The goal is to distinguish which is true by drawing samples from P and Q . For these problems there are no simple general characterization as in the binary hypothesis testing. However, for reasonable classes of distributions such as Gaussian distributions or distributions on discrete spaces, a lot of nice results are known [Ing87, Ing82, GR11, VV17, CDVV14, ACPS18, LY19].

We are not aware of any previous work that study hypothesis testing problems for the class of softmax models or leverage score models.

1.3 Roadmap

In Section 2, we introduce notations, basic definitions, and concepts relevant to information theory and hypothesis testing. Our results are presented in Section 3 and Section 4. Specifically, Section 3 establishes upper and lower bounds on the sample complexity for distinguishing two different softmax models, while Section 4 delves into the case of leverage scores. We conclude and make further discussions in Section 5.

2 Preliminaries

Notations Given $x \in \mathbb{R}^n$, we use $\|x\|_p$ to denote ℓ_p norm of x , where $\|x\|_0 = \sum_{i=1}^n \mathbb{1}(x_i \neq 0)$, $\|x\|_1 := \sum_{i=1}^n |x_i|$ (ℓ_1 norm), $\|x\|_2 := (\sum_{i=1}^n x_i^2)^{1/2}$ (ℓ_2 norm), and $\|x\|_\infty := \max_{i \in [n]} |x_i|$ (ℓ_∞ norm). For a square matrix, $\text{tr}[A]$ is used to represent the trace of A . Given $1 \leq p \leq \infty$ and $1 \leq q \leq \infty$, $\|A\|_{p \rightarrow q}$ represents the p -to- q operator norm

$$\|A\|_{p \rightarrow q} = \sup_{x: \|x\|_p \leq 1} \|Ax\|_q.$$

In particular, $\|A\|_{2 \rightarrow \infty} = \max_{i \in [n]} \|A_{i,*}\|_2$. For $x \in \mathbb{R}^n$, let $\text{Diag}(x) \in \mathbb{R}^{n \times n}$ denote the diagonal matrix with diagonal x . For square matrix $A \in \mathbb{R}^{n \times n}$, let $\text{diag}(A) \in \mathbb{R}^n$ denote the diagonal of A . For a non-negative integer n , let $[n]$ denote the set $\{1, \dots, n\}$. For a sequence X_1, \dots, X_m of random variables, we use X^m to denote the whole sequence (X_1, \dots, X_m) .

2.1 Information Theory

Definition 2.1 (TV distance). *For two distribution P, Q on the same measurable space, their total variation (TV) distance is*

$$\text{TV}(P, Q) = \frac{1}{2} \int |P(dx) - Q(dx)|.$$

In particular, if P and Q are on the discrete space $[n]$ and $P = (p_1, \dots, p_n)$, $Q = (q_1, \dots, q_n)$, then

$$\text{TV}(P, Q) = \frac{1}{2} \sum_{i=1}^n |p_i - q_i|.$$

Definition 2.2 (Hellinger distance). For two distributions P, Q on the same measurable space, their squared Hellinger distance is

$$H^2(P, Q) = \frac{1}{2} \int (\sqrt{P(dx)} - \sqrt{Q(dx)})^2.$$

In particular, if P and Q are on the discrete space $[n]$ and $P = (p_1, \dots, p_n)$, $Q = (q_1, \dots, q_n)$, then

$$H^2(P, Q) = \frac{1}{2} \sum_{i=1}^n (\sqrt{p_i} - \sqrt{q_i})^2 = 1 - \sum_{i=1}^n \sqrt{p_i q_i}.$$

The Hellinger distance $H(P, Q)$ is the square root of the squared Hellinger distance $H^2(P, Q)$.

We recall the following relationship between the Hellinger distance and the TV distance. For any distributions P, Q on the same space, we have

$$H^2(P, Q) \leq \text{TV}(P, Q) \leq \sqrt{2}H(P, Q).$$

Definition 2.3 (Expectation and variance). Let P be a distribution on a measurable space \mathcal{X} and f be a continuous function on \mathcal{X} . Then $\mathbb{E}_P[f]$ is the expectation of f under P and $\text{Var}_P(f)$ is the variance of f under P .

In particular, if $\mathcal{X} = [n]$, $P = (p_1, \dots, p_n) \in \mathbb{R}^n$, and $x \in \mathbb{R}^n$, then

$$\begin{aligned} \mathbb{E}_P[x] &= \sum_{i=1}^n p_i x_i, \\ \text{Var}_P(x) &= \sum_{i=1}^n p_i (x_i - \mathbb{E}_P[x])^2. \end{aligned}$$

2.2 Hypothesis Testing

We review the classic hypothesis testing problem for distributions.

Definition 2.4 (Binary hypothesis testing for distributions). Let P_0, P_1 be two distributions on the same space. We have sample access to a distribution P , which is known to be either P_0 or P_1 . The goal is to determine whether $P = P_0$ or $P = P_1$, using as few samples as possible. We say an algorithm successfully distinguishes P_0 and P_1 is at least $2/3$ under both hypotheses.

In the above definition, the constant $2/3$ can be replaced by any constant $> 1/2$, and the asymptotic sample complexity of the binary hypothesis testing problem does not change. The reason is that if we have an algorithm that achieves success probability $\delta > \frac{1}{2}$, then we can run it independently a constant number of times and take the majority of the outputs. In this way we can boost the success probability to an arbitrarily high constant.

A classic result in information theory states that the sample complexity of the binary hypothesis testing problem is determined by the Hellinger distance.

Lemma 2.5 (e.g., [PW23]). The sample complexity of the binary hypothesis testing problem for distributions is $\Theta(H^{-2}(P_0, P_1))$. That is, there is an algorithm that solves the problem using $O(H^{-2}(P_0, P_1))$ queries, and any algorithm that solves the problem uses $\Omega(H^{-2}(P_0, P_1))$ queries.

2.3 Softmax Model

Definition 2.6 (Softmax model). *The softmax model $\mathbf{SoftMax}_A$ associated with $A \in \mathbb{R}^{n \times d}$ is a model such that on input $x \in \mathbb{R}^d$, it outputs a sample $y \in [n]$ from the distribution $\mathbf{SoftMax}_A(x)$, defined as follows: the probability mass of $i \in [n]$ is equal to $\langle \exp(Ax), \mathbf{1}_n \rangle^{-1} \exp(Ax)_i$.*

We can verify that $\sum_{i=1}^n \langle \exp(Ax), \mathbf{1}_n \rangle^{-1} \exp(Ax)_i = 1$, so the above definition gives a valid distribution.

Definition 2.7 (Binary hypothesis testing for softmax models). *Let $A, B \in \mathbb{R}^{n \times d}$ be two matrices. Let $P_0 = \mathbf{SoftMax}_A, P_1 = \mathbf{SoftMax}_B$ be two softmax models. Let P be the softmax model which is either P_0 or P_1 . In each query, we can feed $x \in \mathbb{R}^d$ into P , and retrieve a sample $y \in [n]$ from $P(x)$. The goal is to determine whether the model P is P_0 or P_1 in as few samples as possible. We say an algorithm successfully distinguishes P_0 and P_1 , if the correctness probability is at least $2/3$ under both hypotheses.*

The above definition is valid. However, if we make no restrictions on the input x , then there would be undesirable consequences. For example, suppose $n = 2, d = 1, A = \begin{bmatrix} \epsilon \\ 0 \end{bmatrix}, B = \begin{bmatrix} 0 \\ \epsilon \end{bmatrix}$ for some very small $\epsilon > 0$. Because A and B are close to each other, we should expect it to be difficult to distinguish $\mathbf{SoftMax}_A$ and $\mathbf{SoftMax}_B$. However, if we allow any $x \in \mathbb{R}^d$ as input, then we could take x to be a very large real number. Then $\mathbf{SoftMax}_A(x)$ has almost all mass on $1 \in [n]$, while $\mathbf{SoftMax}_B(x)$ has almost all mass on $2 \in [n]$, and we can distinguish the two models using only one query. To avoid this peculiarity, we make the assumption that there is an energy constraint on x .

Definition 2.8 (Energy constraint for softmax model). *We assume that there is an energy constraint, that is, input $x \in \mathbb{R}^n$ should satisfy $\|x\|_2 \leq E$, for some given constant E .*

The energy constraint is a reasonable assumption in the context of LLMs and more generally neural networks, because of the widely used batch normalization technique [IS15].

2.4 Leverage Score Model

Definition 2.9 (Leverage score model). *The leverage score model $\mathbf{Leverage}_A$ associated with $A \in \mathbb{R}^{n \times d}$ is a model such that on input $s \in (\mathbb{R} \setminus 0)^n$, it outputs a sample $y \in [n]$ from the distribution $\mathbf{Leverage}_A(s)$, defined as follows: the probability mass of $i \in [n]$ is equal to*

$$\|(A_s^\top A_s)^{-1/2} (A_s)_{*,i}\|_2^2 / d = (A_s (A_s^\top A_s)^{-1} A_s^\top)_{i,i} / d,$$

where $A_s = S^{-1}A$, and $S = \text{Diag}(s)$.

Definition 2.10 (Binary hypothesis testing for leverage score model). *Let $A, B \in \mathbb{R}^{n \times d}$ be two matrices. Let $P_0 = \mathbf{Leverage}_A, P_1 = \mathbf{Leverage}_B$ be two leverage score models. Let P be the leverage score model which is either P_0 or P_1 . In each query, we can feed $s \in (\mathbb{R} \setminus 0)^n$ into P , and retrieve a sample $y \in [n]$ from $P(s)$. The goal is to determine whether the model P is P_0 or P_1 in as few samples as possible. We say an algorithm successfully distinguishes P_0 and P_1 , if the correctness probability is at least $2/3$ under both hypotheses.*

Similar to the softmax model case, if we do not put any restrictions on s , then there will be certain weird behavior. For example, if we take $n = 2, d = 1, A = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$ and $B = \begin{bmatrix} 1 \\ \epsilon \end{bmatrix}$ for some small $\epsilon > 0$. Because A and B are close to each other, we should expect it to be difficult to distinguish

Leverage_A and Leverage_B . However, if we allow any $s \in (\mathbb{R} \setminus 0)^n$ as input, then we can take $s = [1 \ \delta]$ for some very small $\delta > 0$. In this way, we can verify that $\text{Leverage}_A(s)$ has all mass on $1 \in [n]$, while $\text{Leverage}_B(s)$ has almost all mass on $2 \in [n]$. So we can distinguish the two models using only one query. To avoid such cases we put additional constraints on s .

Definition 2.11 (Constraint for leverage score model). *We assume that input $s \in (\mathbb{R} \setminus 0)^d$ should satisfy the constraint such that $c \leq s_i^2 \leq C$ for some given constants $0 < c < C$.*

3 Softmax Model

3.1 General Result

We first prove a general result which relates the binary hypothesis testing problem with Hellinger distance.

Theorem 3.1. *Let $A, B \in \mathbb{R}^{n \times d}$ be two matrices. Consider the binary hypothesis testing problem of distinguishing SoftMax_A and SoftMax_B using energy-constrained queries (Definition 2.8). Define $\delta = \sup_{x: \|x\|_2 \leq E} H(\text{SoftMax}_A(x), \text{SoftMax}_B(x))$. Then the sample complexity of the binary hypothesis testing problem is $\Theta(\delta^{-2})$. That is, there is an algorithm that successfully solves the problem using $O(\delta^{-2})$ energy-constrained queries, and any algorithm that successfully solves the problem uses $\Omega(\delta^{-2})$ energy-constrained queries.*

Proof of Theorem 3.1 is deferred to Appendix A.1.

3.2 Lower Bound

The goal of this section is to prove the following lower bound for binary hypothesis testing for softmax models.

Theorem 3.2 (Lower bound). *If two softmax models (Definition 2.6) with parameters $A \in \mathbb{R}^{n \times d}$ and $B \in \mathbb{R}^{n \times d}$ satisfy $\|A - B\|_{2 \rightarrow \infty} \leq \epsilon$ (i.e., $\max_{j \in [n]} \|A_{j,*} - B_{j,*}\|_2 \leq \epsilon$), then any algorithm with energy constraint E that distinguishes the two models with success probability $\geq \frac{2}{3}$ uses at least $\Omega(\epsilon^{-2} E^{-2})$ samples.*

Before giving the proof of Theorem 3.2, we state a useful lemma.

Lemma 3.3. *Let $a, b \in \mathbb{R}^n$ be such that $\|a - b\|_\infty \leq \epsilon$. Let P be the distribution on $[n]$ with $p_i = \exp(a_i) / \langle \exp(a), \mathbf{1}_n \rangle$. Let Q be the distribution on $[n]$ with $q_i = \exp(b_i) / \langle \exp(b), \mathbf{1}_n \rangle$. Then*

$$\begin{aligned} H^2(P, Q) &= O(\epsilon^2) \\ \text{TV}(P, Q) &= O(\epsilon). \end{aligned}$$

Proof of Lemma 3.3 is deferred to Appendix A.2.

Corollary 3.4. *If matrices $A \in \mathbb{R}^{n \times d}, B \in \mathbb{R}^{n \times d}$ satisfy $\max_{j \in [n]} \|A_{j,*} - B_{j,*}\|_2 \leq \epsilon$, then for any $x \in \mathbb{R}^d$, the distributions $P = \text{SoftMax}_A(x)$ and $Q = \text{SoftMax}_B(x)$ satisfy*

$$\begin{aligned} H^2(P, Q) &= O(\epsilon^2 \|x\|_2^2), \\ \text{TV}(P, Q) &= O(\epsilon \|x\|_2). \end{aligned}$$

Proof. For any $x \in \mathbb{R}^n$, we have

$$\begin{aligned} \|Ax - Bx\|_\infty &= \max_{j \in [n]} |A_{j,*}x - B_{j,*}x| \\ &\leq \max_{h \in [n]} \|A_{h,*} - B_{h,*}\|_2 \|x\|_2 \\ &\leq \epsilon \|x\|_2. \end{aligned}$$

The result then follows from Lemma 3.3. \square

Proof of Theorem 3.2. By Corollary 3.4, for any $\|x\|_2 \leq E$, we have $H^2(\text{SoftMax}_A(x), \text{SoftMax}_B(x)) = O(\epsilon^2 E^2)$. Therefore δ in the statement of Theorem 3.1 satisfies $\delta^2 = O(\epsilon^2 E^2)$. Applying Theorem 3.1 we finish the proof. \square

3.3 Upper Bound

In the previous section we established an $\Omega(\epsilon^{-2})$ lower bound for solving the hypothesis testing problem for the softmax model. The upper bound is more subtle. Let us discuss a few difficulties in establishing the upper bound.

Let $A, B \in \mathbb{R}^{n \times d}$ be parameters of the softmax models, $x \in \mathbb{R}^d$ be the input vector, $P = \text{SoftMax}_A(x) = (p_1, \dots, p_n)$, $Q = \text{SoftMax}_B(x) = (q_1, \dots, q_n)$.

Firstly, two different matrices A and B could give rise to the same softmax model. If $B = A + \mathbf{1}_n^\top w$ for some $w \in \mathbb{R}^d$, then for any $x \in \mathbb{R}^d$, we have

$$\begin{aligned} q_i &= \frac{\exp(Bx)_i}{\langle \exp(Bx), \mathbf{1}_n \rangle} \\ &= \frac{\exp(Ax)_i \exp(w^\top x)}{\langle \exp(Ax) \exp(w^\top x), \mathbf{1}_n \rangle} \\ &= \frac{\exp(Ax)_i}{\langle \exp(Ax), \mathbf{1}_n \rangle} \\ &= p_i \end{aligned}$$

for all $i \in [d]$. Therefore in this case $\text{SoftMax}_A(x) = \text{SoftMax}_B(x)$ for all $x \in \mathbb{R}^d$ and it is impossible to distinguish the two models. This issue may be resolved by adding additional assumptions such as $\mathbf{1}_n^\top A = \mathbf{1}_n^\top B$.

A more important issue is that A and B may differ only in rows with very small probability weight under any input x . For example, suppose A is the zero matrix, and B differ with A only in the first row. For any $x \in \mathbb{R}^d$, the distribution $\text{SoftMax}_A(x)$ is the uniform distribution on $[d]$. If $\|B_{1,*} - A_{1,*}\|_2 = \epsilon$, then for any x with $\|x\|_2 \leq E$, we have

$$\exp(-\epsilon E) \leq \frac{\exp(Bx)_1}{\exp(Ax)_1} \leq \exp(\epsilon E).$$

A simple calculation shows that in this case,

$$H^2(P, Q) = O(\epsilon^2 E^2 / n).$$

So the sample complexity of any hypothesis testing algorithm is at least $\Omega(n/(\epsilon^2 E^2))$, which grows with n . This shows that the sample complexity may depend on n .

Nevertheless, using Theorem 3.1, we show a local upper bound, which says that for fixed A and fixed direction M , there is an algorithm that distinguishes SoftMax_A and $\text{SoftMax}_{A+\epsilon M}$ using $O(\epsilon^{-2})$ queries, for small enough $\epsilon > 0$.

Theorem 3.5. Fix $A, M \in \mathbb{R}^{n \times d}$ where $\|M\|_{2 \rightarrow \infty} = O(1)$. For $\epsilon > 0$, define $B_\epsilon = A + \epsilon M$. We consider the binary hypothesis testing problem with SoftMax_A and $\text{SoftMax}_{B_\epsilon}$, for small ϵ . Let $\nu = \sup_{x: \|x\|_2 \leq E} \text{Var}_{\text{SoftMax}_A(x)}(Mx)$. Then for $\epsilon > 0$ small enough, there is an algorithm that uses $O(\epsilon^{-2}\nu^{-1})$ energy-constrained queries and distinguishes between SoftMax_A and $\text{SoftMax}_{B_\epsilon}$.

Proof of Theorem 3.5 is deferred to Appendix A.3.

From Theorem 3.5 we see that it is an interesting problem to bound $\nu = \sup_{x: \|x\|_2 \leq E} \text{Var}_{\text{SoftMax}_A(x)}(Mx)$ for fixed $A, M \in \mathbb{R}^{n \times d}$. For different A and M the value of ν can be quite different. For example, if A is the all zero matrix and M is zero except for row 1 (and $\|M\|_{2 \rightarrow \infty} = O(1)$), then $\nu = O(E^2/n)$ for any $\|x\|_2 \leq E$.

On the other hand, if A is the zero matrix, and the first column M are i.i.d. Gaussian $\mathcal{N}(0, \Theta(1))$, then with high probability, $\nu = \Omega(E^2)$ for $x = (E, 0, \dots, 0)$.

We remark that Theorem 3.5 is in fact tight. We have a matching lower bound.

Theorem 3.6. Work under the same setting as Theorem 3.5. For $\epsilon > 0$ small enough, any algorithm that distinguishes between SoftMax_A and $\text{SoftMax}_{B_\epsilon}$ must use $\Omega(\epsilon^{-2}\nu^{-1})$ energy-constrained queries.

Proof. The proof is by combining the proof of Theorem 3.5 and Theorem 3.1. We omit the details. \square

4 Leverage Score Model

4.1 General Result

We first prove a general result which is the leverage score version of Theorem 3.1.

Theorem 4.1. Let $A, B \in \mathbb{R}^{n \times d}$ be two matrices. Consider the binary hypothesis testing problem of distinguishing Leverage_A and Leverage_B using constrained queries (Definition 2.11). Define $\delta = \sup_{s: c \leq s_i^2 \leq C\forall i} H(\text{Leverage}_A(s), \text{Leverage}_B(s))$. Then the sample complexity of the binary hypothesis testing problem is $\Theta(\delta^{-2})$. That is, there is an algorithm that successfully solves the problem using $O(\delta^{-2})$ energy-constrained queries, and any algorithm that successfully solves the problem uses $\Omega(\delta^{-2})$ energy-constrained queries.

Proof. The proof is similar to Theorem 3.1 and omitted. \square

4.2 Lower Bound

The goal of this section is to prove the following lower bound for binary hypothesis testing for leverage score models.

Theorem 4.2. Consider two leverage score model Leverage_A and Leverage_B . Assume that there exists $\delta > 0$ such that $A^\top A \succeq \delta I$. If

$$\sum_{i \in [n]} \|B_{i,*}^\top B_{i,*} - A_{i,*}^\top A_{i,*}\|_{\text{op}} \leq \epsilon$$

(where $\|\cdot\|_{\text{op}}$ denotes the 2-to-2 operator norm), then any algorithm that solves the binary hypothesis testing problem takes at least $\Omega(c\delta/(C\epsilon))$ constrained queries.

Proof. Let $P = \text{Leverage}_A(s) = (p_1, \dots, p_n)$ and $Q = \text{Leverage}_B(s) = (q_1, \dots, q_n)$.

By Theorem 4.1, it suffices to prove that $H^2(P, Q) = O(\epsilon C / (c\delta))$.

We first consider the case where A and B differ in exactly one row i . Fix $s \in \mathbb{R}^d$ with $c \leq s_j \leq C$ for all $j \in [n]$.

Let $A_s = S^{-1}A$ and $B_s = S^{-1}B$, where $S = \text{Diag}(s)$.

Because $A^\top A \succeq \delta I$, we have

$$A_s^\top A_s \succeq (\delta/C) \cdot I.$$

Because $\|B_{i,*}^\top B_{i,*} - A_{i,*}^\top A_{i,*}\|_{\text{op}} \leq \epsilon$, we have

$$-\epsilon_i C / \delta A_s^\top A_s \preceq B_{i,*}^\top B_{i,*} - A_{i,*}^\top A_{i,*} \preceq \epsilon_i C / \delta A_s^\top A_s.$$

Recall that A and B differ in exactly one row i . Therefore

$$\left(1 - \frac{\epsilon C}{c\delta}\right) A_s^\top A_s \preceq B_s^\top B_s \preceq \left(1 + \frac{\epsilon C}{c\delta}\right) A_s^\top A_s. \quad (1)$$

For $j \neq i$, we have

$$\begin{aligned} q_j &= s_j^{-2} B_{j,*} (B_s^\top B_s)^{-1} (B^\top)_{*,j} / d \\ &= \text{tr}[s_j^{-2} (B^\top)_{*,j} B_{j,*} (B_s^\top B_s)^{-1}] / d \\ &= (1 \pm O(\epsilon C / (c\delta))) \text{tr}[s_j^{-2} A_{j,*}^\top A_{j,*} (A_s^\top A_s)^{-1}] / d \\ &= (1 \pm O(\epsilon C / (c\delta))) p_j, \end{aligned} \quad (2)$$

where the first step is by definition of the leverage score model, the second step is by property of trace, the third step is Eq. (1), the fourth step is by definition of the leverage score model.

Upper bound for TV. For the TV distance, we have

$$\begin{aligned} \text{TV}(P, Q) &= \frac{1}{2} \sum_{j=1}^n |p_j - q_j| \leq \sum_{j \neq i} |p_j - q_j| \\ &\leq \sum_{j \neq i} O(\epsilon C / (c\delta)) p_i \leq O(\epsilon C / (c\delta)). \end{aligned}$$

where the first step is by definition of TV distance, the third step is by Eq. (2). Therefore $\text{TV}(P, Q) \leq O(\epsilon C / (c\delta))$.

Upper bound for $H^2(P, Q)$.

Using

$$H^2(P, Q) \leq \text{TV}(P, Q)$$

we also get

$$H^2(P, Q) \leq O(\epsilon C / (c\delta)).$$

Now we have established the result when A and B differ in exactly one row. Let us now consider general case.

If $\epsilon \geq 0.1\delta$, then $c\delta / (C\epsilon) = O(1)$ and there is nothing to prove. In the following, assume that $\epsilon \leq 0.1\delta$.

For $0 \leq k \leq n$, define $B^k \in \mathbb{R}^{n \times d}$ be the matrix with $B_{i,*}^k = B_{i,*}$ for $i \leq k$ and $B_{i,*}^k = A_{i,*}$ for $i \geq k$. Then $B^0 = A$, $B^n = B$, and B^k and B^{k+1} differ exactly in one row. Let $\epsilon_i = \|B_{i,*}^\top B_{i,*} - A_{i,*}^\top A_{i,*}\|_{\text{op}}$. Then by the above discussion, we have

$$\begin{aligned} & \text{TV}(\text{Leverage}_{B^k}(s), \text{Leverage}_{B^{k+1}}(s)) \\ &= O(\epsilon_k C / (c\delta)) \end{aligned}$$

for all $0 \leq k \leq n-1$. By metric property of TV, we have

$$\begin{aligned} & \text{TV}(P, Q) \\ & \leq \sum_{0 \leq k \leq n-1} \text{TV}(\text{Leverage}_{B^k}(s), \text{Leverage}_{B^{k+1}}(s)) \\ &= \sum_{0 \leq k \leq n-1} O(\epsilon_k C / (c\delta)) \\ &= O(\epsilon C / (c\delta)). \end{aligned}$$

Using $H^2(P, Q) \leq \text{TV}(P, Q)$ we also get $H^2(P, Q) = O(\epsilon C / (c\delta))$. This finishes the proof. \square

In Theorem 4.2, the bound has linear dependence in ϵ^{-1} . An interesting question is the improve the bound to quadratic dependence ϵ^{-2} .

4.3 Upper Bound

Let $A, B \in \mathbb{R}^{n \times d}$ be parameters of the leverage score models, $s \in \mathbb{R}^n$ be the input vector, $P = \text{Leverage}_A(s) = (p_1, \dots, p_n)$, $Q = \text{Leverage}_B(s) = (q_1, \dots, q_n)$.

For upper bounds for the leverage score model, we run into similar difficulties as for the softmax model. Firstly, different matrices A and B could give rise to the same leverage score model. If $B = AR$ for some invertible matrix $R \in \mathbb{R}^{d \times d}$, then we have

$$\begin{aligned} q_i &= (B_s (B_s^\top B_s)^{-1} B_s^\top)_{i,i} / d \\ &= (A_s R (R^\top A_s^\top A_s R)^{-1} R^\top A_s^\top)_{i,i} / d \\ &= (A_s (A_s^\top A_s)^{-1} A_s^\top)_{i,i} / d = p_i. \end{aligned}$$

Then $\text{Leverage}_A(s) = \text{Leverage}_B(s)$ for all $s \in (\mathbb{R} \setminus 0)^n$ and it is impossible to distinguish the two models.

Furthermore, there exist scenarios where A and B differ only in rows with very small probability weight under any input s . We now give an example where $\|A_{1,*}^\top A_{1,*} - B_{1,*}^\top B_{1,*}\| = \Omega(1)$ but $\text{TV}(\text{Leverage}_A(s), \text{Leverage}_B(s)) = O(1/n)$ for any s satisfying $c \leq s_i^2 \leq C$ for all $i \in [n]$. Suppose $A = [I_d \ e_1 \ \dots \ e_1]^\top$ (that is, the first d rows of A is equal to I_d , and all remaining rows are equal to $e_1^\top = (1, 0, \dots, 0)$). Then for s satisfying $c \leq s_i^2 \leq C$ for all $i \in [n]$, the distribution $P = \text{Leverage}_A(s)$ has probability mass $O(1/n)$ on every element $i \in \{1, d+1, d+2, \dots, n\}$ (hiding constants depending on c and C). Now suppose B differs with A only in the first entry $(1, 1)$, and $B_{1,1} = A_{1,1} + \Theta(1)$. Then for fixed s , $q_j = p_j$ for $j \in \{2, \dots, d\}$, $q_1 \geq p_1$, and $q_j \leq p_j$ for $j \in \{d+1, \dots, n\}$. So $H^2(P, Q) \leq \text{TV}(P, Q) = q_1 - p_1 = \Theta(1/n)$.

This shows that the sample complexity may depend on n .

After discussing the difficulties in establishing an upper bound, we now show a local upper bound, which says for fixed A and fixed direction M , there is an algorithm that distinguishes Leverage_A and $\text{Leverage}_{A+\epsilon M}$ using $O(\epsilon^{-2})$ queries, for small enough $\epsilon > 0$.

Theorem 4.3. Fix $A, M \in \mathbb{R}^{n \times d}$ where $\|M\|_{2 \rightarrow \infty} = O(1)$. For $\epsilon > 0$, define $B_\epsilon = A + \epsilon M$. We consider the binary hypothesis testing problem with Leverage_A and $\text{Leverage}_{B_\epsilon}$, for small ϵ . Let $\nu = \sup_s \text{Var}_{\text{Leverage}_A(s)}(w_s)$ where

$$w_s = \frac{\text{diag}((I - A_s(A_s^\top A_s)^{-1}A_s^\top)(M_s(A_s^\top A_s)^{-1}A_s^\top))}{\text{diag}(A_s(A_s^\top A_s)^{-1}A_s^\top)}$$

where the division between vectors is entrywise division. Then for $\epsilon > 0$ small enough, there is an algorithm that uses $O(\epsilon^{-2}\nu^{-1})$ queries and distinguishes between Leverage_A and $\text{Leverage}_{B_\epsilon}$.

Proof of Theorem 4.3 is deferred to Appendix A.4.

Similarly to the softmax model case, Theorem 4.3 is also tight.

Theorem 4.4. Work under the same setting as Theorem 4.3. For $\epsilon > 0$ small enough, any algorithm that distinguishes between SoftMax_A and $\text{SoftMax}_{B_\epsilon}$ must use $\Omega(\epsilon^{-2}\nu^{-1})$ energy-constrained queries.

Proof. The proof is by combining the proof of Theorem 4.3 and Theorem 4.1. We omit the details. \square

5 Conclusion and Future Directions

Widely applied across various domains, softmax and leverage scores play crucial roles in machine learning and linear algebra. This study delves into the testing problem aimed at distinguishing between different models of softmax and leverage score distributions, each parameterized by distinct matrices. We establish bounds on the number of samples within the defined testing problem.

With the rapidly escalating computational costs in current machine learning research, our work holds the potential to offer valuable insights and guidance for distinguishing between the distributions of different models.

We discuss a few possible directions for further research.

In Theorem 3.5 and Theorem 4.3, we determine the local sample complexity of the binary hypothesis testing problems for softmax models and leverage score models. In particular, the sample complexity is $\Theta(\epsilon^{-2}\nu)$, where ν is a certain function depending on A and M (where $B = A + \epsilon M$). The form of ν is an optimization problem over the space of possible inputs. An interesting question is to provide bounds on the quantity ν , or to provide computation-efficient algorithms for determining the value of ν of finding the optimal input (x for softmax, s for leverage score). This will lead to computation-efficient algorithms for solving the binary hypothesis testing problem in practice.

In this paper we focused on the binary hypothesis testing problem, where the goal is to distinguish two models with different parameters. There are other hypothesis testing problems that are of interest both in theory and practice. For example, in the goodness-of-fit problem, the goal is to determine whether an unknown model is equal to or far away from a given model. In the two-sample testing problem, the goal is to determine whether two unknown models are the same or far away from each other. These problems have potential practical applications and we leave them as an interesting future direction.

Impact Statement

By conducting a rigorous theoretical analysis, we can minimize the need for repetitive experiments. Although our work may inadvertently result in unexpected carbon emissions, leveraging theoretical

insights enables us to streamline experiments and address this issue. Additionally, we delve into system-level applications, leveraging our theoretical analysis to establish a robust foundation for successful evaluations.

Appendix

A Missing Proofs

A.1 General Result for Softmax Model

Proof of Theorem 3.1. Lower bound. If $\delta \geq 0.1$ then there is nothing to prove. In the following assume that $\delta < 0.1$. Suppose that there is an algorithm that successfully solves the binary hypothesis testing problem. Suppose it makes queries $x_1, \dots, x_m \in \mathbb{R}^d$ where x_i may depend on previous query results. Let $Y_1, \dots, Y_m \in [n]$ denote the query results. Let P_{Y^m} and Q_{Y^m} denote the distribution of Y^m under P and Q , respectively. By definition of δ , we have

$$H^2(P_{Y_k|Y^{k-1}}, Q_{Y_k|Y^{k-1}}) \leq \delta^2.$$

for any $k \in [m]$ and Y^{k-1} . Then

$$\begin{aligned} & 1 - H^2(P_{Y^m}, Q_{Y^m}) \\ &= \int \sqrt{P_{y^m} Q_{y^m}} dy^m \\ &= \int \sqrt{P_{y^{m-1}} Q_{y^{m-1}}} \\ &\quad \left(\int \sqrt{P_{y_m|y^{m-1}} Q_{y_m|y^{m-1}}} dy_m \right) dy^{m-1} \\ &\geq \int \sqrt{P_{y^{m-1}} Q_{y^{m-1}}} (1 - \delta^2) dy^{m-1}. \end{aligned}$$

Repeating this computation, in the end we get

$$1 - H^2(P_{Y^m}, Q_{Y^m}) \geq (1 - \delta^2)^m.$$

Because $\delta \leq 0.1$, we have $1 - \delta^2 \geq \exp(-2\delta^2)$. If $m \leq 0.01\delta^{-2}$, then

$$\begin{aligned} 1 - H^2(P_{Y^m}, Q_{Y^m}) &\geq \exp(-2\delta^2 m) \\ &\geq \exp(-0.02) > 0.98, \end{aligned}$$

and

$$H^2(P_{Y^m}, Q_{Y^m}) \leq 0.02.$$

This implies

$$\text{TV}(P_{Y^m}, Q_{Y^m}) \leq \sqrt{2}H(P_{Y^m}, Q_{Y^m}) \leq 0.2,$$

which implies the success rate for binary hypothesis testing cannot be $\geq \frac{2}{3}$.

In conclusion, any algorithm that successfully solves the hypothesis testing problem need to use $\Omega(\delta^{-2})$ queries.

Upper bound. Take $x \in \mathbb{R}^d$ such that $\|x\|_2 \leq E$ and $\delta = H(\text{SoftMax}_A(x), \text{SoftMax}_B(x))$. By Lemma 2.5, using $O(\delta^{-2})$ samples we can distinguish $\text{SoftMax}_A(x)$ and $\text{SoftMax}_B(x)$. Therefore we can distinguish SoftMax_A and SoftMax_B in $O(\delta^{-2})$ queries by repeatedly querying x . \square

A.2 Lower Bound for Softmax Model

Before giving the proof of Lemma 3.3, we prove a weaker version of the lemma.

Lemma A.1. *Let $a, b \in \mathbb{R}^n$. Suppose there exists an $\epsilon \geq 0$ such that for every $i \in [n]$, $b_i - a_i \in \{0, \epsilon\}$. Let P be the distribution on $[n]$ with $p_i = \exp(a_i) / \langle \exp(a), \mathbf{1}_n \rangle$. Let Q be the distribution on $[n]$ with $q_i = \exp(b_i) / \langle \exp(b), \mathbf{1}_n \rangle$. Then*

$$H^2(P, Q) = \frac{(1 - \exp(\epsilon/4))^2}{1 + \exp(\epsilon/2)} = O(\epsilon^2),$$

$$\text{TV}(P, Q) = \tanh(\epsilon/4) = O(\epsilon).$$

Proof. Assume that a and b differ in m coordinates. By permuting the coordinates, WLOG assume that $b_i = a_i + \epsilon$ for $1 \leq i \leq m$ and $b_i = a_i$ for $m+1 \leq i \leq n$.

Write

$$s = \sum_{i=1}^m \exp(a_i)$$

and

$$t = \sum_{i=m+1}^n \exp(a_i).$$

Then

$$H^2(P, Q) = 1 - \sum_{i \in [n]} \sqrt{p_i q_i}$$

$$= 1 - \frac{s \exp(\epsilon/2) + t}{\sqrt{(s+t)(s \exp(\epsilon) + t)}}.$$

For fixed t and ϵ , the above is maximized at

$$s = t \exp(-\epsilon/2).$$

Plugging in the above s , we get

$$H^2(P, Q) \leq 1 - \frac{2}{\sqrt{(\exp(-\epsilon/2) + 1)(\exp(\epsilon/2) + 1)}}$$

$$= \frac{(1 - \exp(\epsilon/4))^2}{1 + \exp(\epsilon/2)}.$$

For TV, we have

$$\text{TV}(P, Q) = \sum_{m+1 \leq i \leq n} (q_i - p_i)$$

$$= \frac{t}{s+t} - \frac{t}{s \exp(\epsilon) + t}.$$

For fixed t and ϵ the above is maximized at $s = t \exp(-\epsilon/2)$. Plugging in this s , we get

$$\text{TV}(P, Q) \leq \tanh(\epsilon/4).$$

□

Proof of Lemma 3.3. We first prove the case where $b_i \geq a_i$ for all $i \in [n]$. Define $\epsilon_i = b_i - a_i$ for all $i \in [n]$. By permuting the coordinates, WLOG assume that $\epsilon_1 \leq \dots \leq \epsilon_n$. Specially, define $\epsilon_0 = 0$. For $0 \leq k \leq n$, let $b^k \in \mathbb{R}^n$ denote the vector where $b_i^k = a_i + \min\{\epsilon_i, \epsilon_k\}$ for all $i \in [k]$. Then we can see that $b^0 = a$ and $b^n = b$, and for every $0 \leq k \leq n-1$, the pair (b^k, b^{k+1}) satisfies the assumption in Lemma A.1. For $0 \leq k \leq n$, let P^k denote the softmax distribution corresponding to b^k . By Lemma A.1, for every $0 \leq k \leq n-1$, we have

$$\begin{aligned} H(P^k, P^{k+1}) &= O(\epsilon_{k+1} - \epsilon_k), \\ \text{TV}(P^k, P^{k+1}) &= O(\epsilon_{k+1} - \epsilon_k). \end{aligned}$$

Because Hellinger distance and TV distance are both metrics, we have

$$\begin{aligned} H(P, Q) &= H(P^0, P^n) \\ &\leq \sum_{k=0}^{n-1} H(P^k, P^{k+1}) \\ &= O(\epsilon), \end{aligned}$$

and

$$\begin{aligned} \text{TV}(P, Q) &= \text{TV}(P^0, P^n) \\ &\leq \sum_{k=0}^{n-1} \text{TV}(P^k, P^{k+1}) \\ &= O(\epsilon). \end{aligned}$$

This finishes the proof of the result when $b_i \geq a_i$ for all $i \in [n]$.

Now let us consider the general case. Let $c \in \mathbb{R}^n$ be defined as $c_i = \max\{a_i, b_i\}$ for all $i \in [n]$. Then

$$\max\{\|a - c\|_\infty, \|c - b\|_\infty\} \leq \|a - b\|_\infty \leq \epsilon.$$

Let R be the softmax distribution corresponding to c . By our previous discussion, we have

$$H(P, R), H(R, Q), \text{TV}(P, R), \text{TV}(R, Q) = O(\epsilon).$$

By metric property of Hellinger distance and TV distance, we get

$$H(P, Q), \text{TV}(P, Q) = O(\epsilon)$$

as desired. □

A.3 Local Upper Bound for Softmax Model

Proof of Theorem 3.5. We take an x satisfying $\|x\|_2 \leq E$ that maximizes $\text{Var}_{\text{SoftMax}_A(x)}(Mx)$ and repeatedly query x . We would like to apply Theorem 3.1. To do that, we need to show that

$$H^2(\text{SoftMax}_A(x), \text{SoftMax}_{B_\epsilon}(x)) = \Omega(\epsilon^2 \nu).$$

Let $P = \text{SoftMax}_A(x) = (p_1, \dots, p_n)$, $Q_\epsilon = \text{SoftMax}_{B_\epsilon}(x) = (q_{\epsilon,1}, \dots, q_{\epsilon,n})$. Write $Z_A = \langle \exp(Ax), \mathbf{1}_n \rangle$, $Z_{B_\epsilon} = \langle \exp(B_\epsilon x), \mathbf{1}_n \rangle$.

Then, it follows that

$$\begin{aligned}
Z_B &= \sum_{j \in [n]} \exp(Ax)_j \exp(\epsilon(Mx)_j) \\
&= \sum_{j \in [n]} \exp(Ax)_j + \sum_{j \in [n]} \exp(Ax)_j (\exp(\epsilon(Mx)_j) - 1) \\
&= \sum_{j \in [n]} \exp(Ax)_j + \sum_{j \in [n]} \exp(Ax)_j (\epsilon(Mx)_j + O(\epsilon^2)) \\
&= Z_A(1 + \epsilon \langle p, Mx \rangle + O(\epsilon^2)).
\end{aligned} \tag{3}$$

where the initial step is because of $B = A + \epsilon M$, the second step is a result of simple algebra, the third step is a consequence of the Taylor expansion of $\exp(\cdot)$, assuming ϵ is sufficiently small and the fourth step is the result of the definition of Z_A and involves the consolidation of addition, introducing the common term Z_A .

Then

$$\begin{aligned}
q_{\epsilon,i} &= \frac{\exp(B_\epsilon x)_i}{Z_B} \\
&= \frac{\exp(Ax)_i \exp(\epsilon Mx)_i}{Z_A(1 + \epsilon \langle p, Mx \rangle + O(\epsilon^2))} \\
&= p_i(1 + \epsilon((Mx)_i - \langle p, Mx \rangle) + O(\epsilon^2)).
\end{aligned} \tag{4}$$

where the initial step is because of the definition of $q_{\epsilon,i}$, the subsequent step is a result of Eq.(3), and the third step is due to the definition of q_i along with the Taylor expansion of $f(x) = 1/(1+x)$ and $\exp(\cdot)$, considering ϵ as a sufficiently small value.

So, we have that

$$\begin{aligned}
H^2(P, Q_\epsilon) &= \frac{1}{2} \sum_{i=1}^n (\sqrt{p_i} - \sqrt{q_{\epsilon,i}})^2 \\
&= \frac{1}{2} \sum_{i=1}^n p_i (\epsilon^2 ((Mx)_i - \langle p, Mx \rangle)^2 + O(\epsilon^3)) \\
&= \frac{1}{2} \epsilon^2 \text{Var}_P(Mx) + O(\epsilon^3) \\
&= \frac{1}{2} \epsilon^2 \nu + O(\epsilon^3).
\end{aligned}$$

where the first step is the result of Definition 2.2, the second step is because of Eq.(4), the third step the result of definition of $\text{Var}_P(Mx)$ (See Definition 2.3) and the forth step follows from the expression $\nu = \sup_{x: \|x\|_2 \leq E} \text{Var}_{\text{SoftMax}_A(x)}(Mx)$.

Applying Theorem 3.1 we finish the proof. \square

A.4 Local Upper Bound for Leverage Score Model

Proof of Theorem 4.3. We take an s satisfying $c \leq s_i^2 \leq C$ and $\forall i \in [n]$ that maximizes $\sup_s \text{Var}_{\text{Leverage}_A(s)}(w_s)$ and repeatedly query s . We need to show that

$$H^2(\text{Leverage}_A(s), \text{Leverage}_{B_\epsilon}(s)) = \Omega(\epsilon^2 \nu).$$

Let $P = \text{Leverage}_A(s) = (p_1, \dots, p_n)$, $Q_\epsilon = \text{Leverage}_{B_\epsilon}(x) = (q_{\epsilon,1}, \dots, q_{\epsilon,n})$. We can compute that

$$\frac{d}{d\epsilon} q_{\epsilon,i} = (2(I - A_s(A_s^\top A_s)^{-1} A_s^\top)(M_s(A_s^\top A_s)^{-1} A_s^\top))_{i,i}.$$

Define $W = (I - A_s(A_s^\top A_s)^{-1} A_s^\top)(M_s(A_s^\top A_s)^{-1} A_s^\top)$. Then

$$q_{\epsilon,i} = p_i + 2W_{i,i}\epsilon + O(\epsilon^2).$$

Computing $H^2(P, Q_\epsilon)$ we get

$$\begin{aligned} H^2(P, Q_\epsilon) &= \frac{1}{2} \sum_{i \in [n]} (\sqrt{q_{\epsilon,i}} - \sqrt{p_i})^2 \\ &= \sum_{i \in [n]} p_i \left(\frac{W_{i,i}}{p_i} \epsilon + O(\epsilon^2) \right)^2 \\ &= \sum_{i \in [n]} \frac{W_{i,i} \epsilon^2}{p_i} + O(\epsilon^3) \\ &= \epsilon^2 \nu + O(\epsilon^3). \end{aligned}$$

□

References

- [ACPS18] Ery Arias-Castro, Bruno Pelletier, and Venkatesh Saligrama. Remember the curse of dimensionality: The case of goodness-of-fit testing in arbitrary dimension. *Journal of Nonparametric Statistics*, 30(2):448–471, 2018.
- [AS23] Josh Alman and Zhao Song. Fast attention requires bounded entries. *arXiv preprint arXiv:2302.13214*, 2023.
- [BCE⁺23] Sébastien Bubeck, Varun Chandrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, et al. Sparks of artificial general intelligence: Early experiments with gpt-4. *arXiv preprint arXiv:2303.12712*, 2023.
- [BCL⁺23] Yejin Bang, Samuel Cahyawijaya, Nayeon Lee, Wenliang Dai, Dan Su, Bryan Wilie, Holy Lovenia, Ziwei Ji, Tiezheng Yu, Willy Chung, et al. A multitask, multilingual, multimodal evaluation of chatgpt on reasoning, hallucination, and interactivity. *arXiv preprint arXiv:2302.04023*, 2023.
- [BLM89] Jean Bourgain, Joram Lindenstrauss, and Vitali Milman. Approximation of zonoids by zonotopes. 1989.
- [BMR⁺20] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

- [BSZ23] Jan van den Brand, Zhao Song, and Tianyi Zhou. Algorithm and hardness for dynamic attention maintenance in large language models. *arXiv preprint arXiv:2304.02207*, 2023.
- [BW14] Christos Boutsidis and David P Woodruff. Optimal cur matrix decompositions. In *Proceedings of the forty-sixth annual ACM symposium on Theory of computing*, pages 353–362, 2014.
- [BYKS22] Collin Burns, Haotian Ye, Dan Klein, and Jacob Steinhardt. Discovering latent knowledge in language models without supervision. *arXiv preprint arXiv:2212.03827*, 2022.
- [CCLY19] Michael B Cohen, Ben Cousins, Yin Tat Lee, and Xin Yang. A near-optimal algorithm for approximating the john ellipsoid. In *Conference on Learning Theory*, pages 849–873. PMLR, 2019.
- [CDVV14] Siu-On Chan, Ilias Diakonikolas, Paul Valiant, and Gregory Valiant. Optimal algorithms for testing closeness of discrete distributions. In *Proceedings of the twenty-fifth annual ACM-SIAM symposium on Discrete algorithms*, pages 1193–1203. SIAM, 2014.
- [Cha22] ChatGPT. Optimizing language models for dialogue. *OpenAI Blog*, November 2022.
- [CHBP23] Yew Ken Chia, Pengfei Hong, Lidong Bing, and Soujanya Poria. Instructeval: Towards holistic evaluation of instruction-tuned large language models. *arXiv preprint arXiv:2306.04757*, 2023.
- [CLBBJ23] Joseph Chervenak, Harry Lieman, Miranda Blanco-Breindel, and Sangita Jindal. The promise and peril of using a large language model to obtain clinical information: Chatgpt performs strongly as a fertility counseling tool with limitations. *Fertility and Sterility*, 2023.
- [CLMY21] HanQin Cai, Yuchen Lou, Daniel McKenzie, and Wotao Yin. A zeroth-order block coordinate descent algorithm for huge-scale black-box optimization. In *International Conference on Machine Learning*, pages 1193–1203. PMLR, 2021.
- [CP15] Michael B Cohen and Richard Peng. Lp row sampling by lewis weights. In *Proceedings of the forty-seventh annual ACM symposium on Theory of computing*, pages 183–192, 2015.
- [CPK⁺23] Minje Choi, Jiaxin Pei, Sagar Kumar, Chang Shu, and David Jurgens. Do llms understand social knowledge? evaluating the sociability of large language models with socket benchmark. *arXiv preprint arXiv:2305.14938*, 2023.
- [CW13] Kenneth L Clarkson and David P Woodruff. Low-rank approximation and regression in input sparsity time. In *STOC*, 2013.
- [CWJ⁺23] Yi Chen, Rui Wang, Haiyun Jiang, Shuming Shi, and Ruifeng Xu. Exploring the use of large language models for reference-free text quality evaluation: A preliminary empirical study. *arXiv preprint arXiv:2304.00723*, 2023.

- [DCLT18] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.
- [DDH⁺21] Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. Knowledge neurons in pretrained transformers. *arXiv preprint arXiv:2104.08696*, 2021.
- [DGG23] Aniket Deroy, Kripabandhu Ghosh, and Saptarshi Ghosh. How ready are pre-trained abstractive models and llms for legal case judgement summarization? *arXiv preprint arXiv:2306.01248*, 2023.
- [DLMS23] Yichuan Deng, Zhihang Li, Sridhar Mahadevan, and Zhao Song. Zero-th order algorithm for softmax attention optimization. *arXiv preprint arXiv:2307.08352*, 2023.
- [DLS23] Yichuan Deng, Zhihang Li, and Zhao Song. Attention scheme inspired softmax regression. *arXiv preprint arXiv:2304.10411*, 2023.
- [DMIMW12] Petros Drineas, Malik Magdon-Ismail, Michael W Mahoney, and David P Woodruff. Fast approximation of matrix coherence and statistical leverage. *The Journal of Machine Learning Research*, 13(1):3475–3506, 2012.
- [DMS23] Yichuan Deng, Sridhar Mahadevan, and Zhao Song. Randomized and deterministic attention sparsification algorithms for over-parameterized feature dimension. *arxiv preprint: arxiv 2304.03426*, 2023.
- [DS08] Samuel I Daitch and Daniel A Spielman. Faster approximate lossy generalized flow via interior point algorithms. In *Proceedings of the fortieth annual ACM symposium on Theory of computing*, pages 451–460, 2008.
- [Fer23] Emilio Ferrara. Should chatgpt be biased? challenges and risks of bias in large language models. *arXiv preprint arXiv:2304.03738*, 2023.
- [GGL⁺23] Taicheng Guo, Kehan Guo, Zhengwen Liang, Zhichun Guo, Nitesh V Chawla, Olaf Wiest, Xiangliang Zhang, et al. What indeed can gpt models do in chemistry? a comprehensive benchmark on eight tasks. *arXiv preprint arXiv:2305.18365*, 2023.
- [GMS23] Yeqi Gao, Sridhar Mahadevan, and Zhao Song. An over-parameterized exponential regression. *arXiv preprint arXiv:2303.16504*, 2023.
- [GR11] Oded Goldreich and Dana Ron. On testing expansion in bounded-degree graphs. *Studies in Complexity and Cryptography. Miscellanea on the Interplay between Randomness and Computation: In Collaboration with Lidor Avigad, Mihir Bellare, Zvika Brakerski, Shafi Goldwasser, Shai Halevi, Tali Kaufman, Leonid Levin, Noam Nisan, Dana Ron, Madhu Sudan, Luca Trevisan, Salil Vadhan, Avi Wigderson, David Zuckerman*, pages 68–75, 2011.
- [HBKG23] Peter Hase, Mohit Bansal, Been Kim, and Asma Ghandeharioun. Does localization inform editing? surprising differences in causality-based localization vs. knowledge editing in language models. *arXiv preprint arXiv:2301.04213*, 2023.
- [HM19] John Hewitt and Christopher D Manning. A structural probe for finding syntax in word representations. In *Proceedings of the 2019 Conference of the North American*

Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers), pages 4129–4138, 2019.

- [Ing82] Yuri Izmailovich Ingster. On the minimax nonparametric detection of signals in white gaussian noise. *Problemy Peredachi Informatsii*, 18(2):61–73, 1982.
- [Ing87] Yu I Ingster. Minimax testing of nonparametric hypotheses on a distribution density in the L_p metrics. *Theory of Probability & Its Applications*, 31(2):333–337, 1987.
- [IS15] Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pages 448–456. pmlr, 2015.
- [JGP⁺23] Douglas Johnson, Rachel Goodman, J Patrinely, Cosby Stone, Eli Zimmerman, Rebecca Donald, Sam Chang, Sean Berkowitz, Avni Finn, Eiman Jahangir, et al. Assessing the accuracy and reliability of ai-generated medical responses: an evaluation of the chat-gpt model. ., 2023.
- [JKL⁺20] Haotian Jiang, Tarun Kathuria, Yin Tat Lee, Swati Padmanabhan, and Zhao Song. A faster interior point method for semidefinite programming. In *2020 IEEE 61st annual symposium on foundations of computer science (FOCS)*, pages 910–918. IEEE, 2020.
- [JLSW20] Haotian Jiang, Yin Tat Lee, Zhao Song, and Sam Chiu-wai Wong. An improved cutting plane method for convex optimization, convex-concave games and its applications. In *STOC*, 2020.
- [KMH⁺20] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.
- [LBL⁺22] Percy Liang, Rishi Bommasani, Tony Lee, Dimitris Tsipras, Dilara Soylu, Michihiro Yasunaga, Yian Zhang, Deepak Narayanan, Yuhuai Wu, Ananya Kumar, et al. Holistic evaluation of language models. *arXiv preprint arXiv:2211.09110*, 2022.
- [LBR⁺23] Md Tahmid Rahman Laskar, M Saiful Bari, Mizanur Rahman, Md Amran Hossen Bhuiyan, Shafiq Joty, and Jimmy Xiangji Huang. A systematic study and comprehensive evaluation of chatgpt on benchmark datasets. *arXiv preprint arXiv:2305.18486*, 2023.
- [LL21] Xiang Lisa Li and Percy Liang. Prefix-tuning: Optimizing continuous prompts for generation. *arXiv preprint arXiv:2101.00190*, 2021.
- [LLH⁺23] Hong Liu, Zhiyuan Li, David Hall, Percy Liang, and Tengyu Ma. Sophia: A scalable stochastic second-order optimizer for language model pre-training. *arXiv preprint arXiv:2305.14342*, 2023.
- [LS14] Yin Tat Lee and Aaron Sidford. Path finding methods for linear programming: Solving linear programs in o (vrnk) iterations and faster algorithms for maximum flow. In *2014 IEEE 55th Annual Symposium on Foundations of Computer Science*, pages 424–433. IEEE, 2014.

- [LS20] Yang P Liu and Aaron Sidford. Faster energy maximization for faster maximum flow. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 803–814, 2020.
- [LSW15] Yin Tat Lee, Aaron Sidford, and Sam Chiu-wai Wong. A faster cutting plane method and its implications for combinatorial and convex optimization. In *2015 IEEE 56th Annual Symposium on Foundations of Computer Science*, pages 1049–1065. IEEE, 2015.
- [LSZ20] S Cliff Liu, Zhao Song, and Hengjie Zhang. Breaking the n-pass barrier: A streaming algorithm for maximum weight bipartite matching. *arXiv preprint arXiv:2009.06106*, 2020.
- [LSZ⁺23] S Cliff Liu, Zhao Song, Hengjie Zhang, Lichen Zhang, and Tianyi Zhou. Space-efficient interior point method, with applications to linear programming and maximum weight bipartite matching. In *ICALP*, 2023.
- [LXWZ23] Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation. *arXiv preprint arXiv:2305.01210*, 2023.
- [LY19] Tong Li and Ming Yuan. On the optimality of gaussian kernel based nonparametric tests against smooth alternatives. *arXiv preprint arXiv:1909.03302*, 2019.
- [LYB⁺22] Zonglin Li, Chong You, Srinadh Bhojanapalli, Daliang Li, Ankit Singh Rawat, Sashank J Reddi, Ke Ye, Felix Chern, Felix Yu, Ruiqi Guo, et al. Large models are parsimonious learners: Activation sparsity in trained transformers. *arXiv preprint arXiv:2210.06313*, 2022.
- [Mad13] Aleksander Madry. Navigating central path with electrical flows: From flows to matchings, and back. In *2013 IEEE 54th Annual Symposium on Foundations of Computer Science*, pages 253–262. IEEE, 2013.
- [Mad16] Aleksander Madry. Computing maximum flow with augmenting electrical flows. In *2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 593–602. IEEE, 2016.
- [MBAB22] Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. *Advances in Neural Information Processing Systems*, 35:17359–17372, 2022.
- [MGN⁺23] Sadhika Malladi, Tianyu Gao, Eshaan Nichani, Alex Damian, Jason D Lee, Danqi Chen, and Sanjeev Arora. Fine-tuning language models with just forward passes. *arXiv preprint arXiv:2305.17333*, 2023.
- [NKL⁺23] John J Nay, David Karamardian, Sarah B Lawskey, Wenting Tao, Meghana Bhat, Raghav Jain, Aaron Travis Lee, Jonathan H Choi, and Jungo Kasai. Large language models as tax attorneys: A case study in legal capabilities emergence. *arXiv preprint arXiv:2306.07075*, 2023.

- [NP33] Jerzy Neyman and Egon Sharpe Pearson. Ix. on the problem of the most efficient tests of statistical hypotheses. *Philosophical Transactions of the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character*, 231(694-706):289–337, 1933.
- [Ope23] OpenAI. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- [PD23] Dongqi Pu and Vera Demberg. Chatgpt vs human-authored text: Insights into controllable text summarization and sentence style transfer. *arXiv preprint arXiv:2306.07799*, 2023.
- [PMM⁺23] Vishal Pallagani, Bharath Muppasani, Keerthiram Murugesan, Francesca Rossi, Biprav Srivastava, Lior Horesh, Francesco Fabiano, and Andrea Loreggia. Understanding the capabilities of large language models for automated planning. *arXiv preprint arXiv:2305.16151*, 2023.
- [PW23] Yury Polyanskiy and Yihong Wu. *Information Theory: From Coding to Learning*. Cambridge University Press, 2023+.
- [QZZ⁺23] Chengwei Qin, Aston Zhang, Zhuosheng Zhang, Jiaao Chen, Michihiro Yasunaga, and Diyi Yang. Is chatgpt a general-purpose natural language processing task solver? *arXiv preprint arXiv:2302.06476*, 2023.
- [Rat20] Kovid Rathee. Meet google meena, 2020.
- [RNS⁺18] Alec Radford, Karthik Narasimhan, Tim Salimans, Ilya Sutskever, et al. Improving language understanding by generative pre-training. ., 2018.
- [RSM⁺23] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *arXiv preprint arXiv:2305.18290*, 2023.
- [RWC⁺19] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.
- [RYW⁺19] Emily Reif, Ann Yuan, Martin Wattenberg, Fernanda B Viegas, Andy Coenen, Adam Pearce, and Been Kim. Visualizing and measuring the geometry of bert. *Advances in Neural Information Processing Systems*, 32, 2019.
- [Sch18] Aaron Schild. An almost-linear time algorithm for uniform random spanning tree generation. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pages 214–227, 2018.
- [SM⁺23] Giriprasad Sridhara, Sourav Mazumdar, et al. Chatgpt: A study on its utility for ubiquitous software engineering tasks. *arXiv preprint arXiv:2305.16837*, 2023.
- [Spa23] Jared Spataro. Introducing microsoft 365 copilot – your copilot for work, 2023.
- [SS08a] Daniel A Spielman and Nikhil Srivastava. Graph sparsification by effective resistances. In *Proceedings of the fortieth annual ACM symposium on Theory of computing*, pages 563–568, 2008.

- [SS08b] Daniel A Spielman and Nikhil Srivastava. Graph sparsification by effective resistances. In *Proceedings of the fortieth annual ACM symposium on Theory of computing*, pages 563–568, 2008.
- [SWW⁺23] Shamane Siriwardhana, Rivindu Weerasekera, Elliott Wen, Tharindu Kaluarachchi, Rajib Rana, and Suranga Nanayakkara. Improving the domain adaptation of retrieval augmented generation (rag) models for open domain question answering. *Transactions of the Association for Computational Linguistics*, 11:1–17, 2023.
- [SWZ17] Zhao Song, David P Woodruff, and Peilin Zhong. Low rank approximation with entrywise l1-norm error. In *Proceedings of the 49th Annual ACM SIGACT Symposium on Theory of Computing*, pages 688–701, 2017.
- [SWZ19] Zhao Song, David P Woodruff, and Peilin Zhong. Relative error tensor low rank approximation. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms*, pages 2772–2789. SIAM, 2019.
- [SZ24] Alireza Salemi and Hamed Zamani. Evaluating retrieval quality in retrieval-augmented generation. *arXiv preprint arXiv:2404.13781*, 2024.
- [Vai89] Pravin M Vaidya. A new algorithm for minimizing convex functions over convex sets. In *30th Annual Symposium on Foundations of Computer Science*, pages 338–343. IEEE Computer Society, 1989.
- [vdBLN⁺20] Jan van den Brand, Yin-Tat Lee, Danupon Nanongkai, Richard Peng, Thatchaphol Saranurak, Aaron Sidford, Zhao Song, and Di Wang. Bipartite matching in nearly-linear time on moderately dense graphs. In *2020 IEEE 61st Annual Symposium on Foundations of Computer Science (FOCS)*, pages 919–930. IEEE, 2020.
- [vdBLSS20] Jan van den Brand, Yin Tat Lee, Aaron Sidford, and Zhao Song. Solving tall dense linear programs in nearly linear time. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing*, pages 775–788, 2020.
- [VSP⁺17] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.
- [VV17] Gregory Valiant and Paul Valiant. An automatic inequality prover and instance optimal identity testing. *SIAM Journal on Computing*, 46(1):429–455, 2017.
- [WLJ⁺23] Longyue Wang, Chenyang Lyu, Tianbo Ji, Zhirui Zhang, Dian Yu, Shuming Shi, and Zhaopeng Tu. Document-level machine translation with large language models. *arXiv preprint arXiv:2304.02210*, 2023.
- [WWZ⁺22] Xiaozhi Wang, Kaiyue Wen, Zhengyan Zhang, Lei Hou, Zhiyuan Liu, and Juanzi Li. Finding skill neurons in pre-trained transformer-based language models. *arXiv preprint arXiv:2211.07349*, 2022.
- [XQP⁺22] Shuo Xie, Jiahao Qiu, Ankita Pasad, Li Du, Qing Qu, and Hongyuan Mei. Hidden state variability of pretrained language models can guide computation reduction for transfer learning. *arXiv preprint arXiv:2210.10041*, 2022.

- [YDY⁺19] Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. *Advances in neural information processing systems*, 32, 2019.
- [ZB24] Hamed Zamani and Michael Bendersky. Stochastic rag: End-to-end retrieval-augmented generation through expected utility maximization. *arXiv preprint arXiv:2405.02816*, 2024.
- [ZHL⁺23] Eric Zelikman, Qian Huang, Percy Liang, Nick Haber, and Noah D Goodman. Just one byte (per gradient): A note on low-bandwidth decentralized language model finetuning using shared randomness. *arXiv preprint arXiv:2306.10015*, 2023.