Optimal Uniform Circle Formation by Asynchronous Luminous Robots

Caterina Feletti^{*}

Debasish Pattanayak[†]

Gokarna Sharma[‡]

Abstract

We study the UNIFORM CIRCLE FORMATION (UCF) problem for a swarm of n autonomous mobile robots operating in Look-Compute-Move (LCM) cycles on the Euclidean plane. We assume our robots are luminous, i.e. embedded with a persistent light that can assume a color chosen from a fixed palette, and opaque, i.e. not able to see beyond a collinear robot. Robots are said to collide if they share positions or their paths intersect within concurrent LCM cycles. To solve UCF, a swarm of n robots must autonomously arrange themselves so that each robot occupies a vertex of the same regular n-gon not fixed in advance. In terms of efficiency, the goal is to design an algorithm that optimizes (or provides a tradeoff between) two fundamental performance metrics: (i) the execution time and (ii) the size of the color palette. There exists an O(1)-time O(1)-color algorithm for this problem under the fully synchronous and semi-synchronous schedulers and a $O(\log \log n)$ -time O(1)-color or O(1)-time $O(\sqrt{n})$ -color algorithm under the asynchronous scheduler, avoiding collisions. In this paper, we develop a deterministic algorithm solving UCF avoiding collisions in O(1)-time with O(1) colors under the asynchronous scheduler, which is asymptotically optimal with respect to both time and number of colors used, the first such result. Furthermore, the algorithm proposed here minimizes for the first time what we call the computational SEC, i.e. the smallest circular area where robots operate throughout the whole algorithm.

Keywords: Uniform Circle Formation, Robots with Lights, Autonomous Robots, Rank Encoding, Time and Color Complexities, Computational SEC

1 Introduction

1.1 Background and Motivation

In the field of robotics, a new approach has been established over the past few years: instead of developing *ad hoc* powerful and monolithic robots for specific tasks, *swarm robotics* involves solving different problems by swarms of small, even tiny, simple and autonomous agents, which can be programmed to cooperate. Besides the practical and engineering factors that robotics must consider (hardware, control, data processing, etc.), other theoretical aspects must be investigated: distributed computability, design of (self-stabilizing) algorithms, correctness and complexity analysis. According to this, research has proposed various theoretical models to formalize such distributed systems and to develop distributed algorithms on them [29].

In the classical macro-model [19], robots are assumed to be *autonomous* (no external control), *anony-mous* (no unique identifiers), *indistinguishable* (no external identifiers), and *homogeneous* (execute the same algorithm). Robots are modeled as pointlike agents that act on the plane through a sequence of *Look-Compute-Move* (LCM) cycles: when a robot is activated, it first obtains a snapshot of its surroundings (*Look*), then computes a destination based on the snapshot (*Compute*), and finally moves to the destination (*Move*). Most of the literature considers *disoriented* robots: each robot has its local coordinate system without any assumption of global orientation. The sensory capability of a robot, generally called *vision*, allows a robot to determine the positions of other robots in its own local coordinate system. Robots are traditionally

^{*}Department of Computer Science, Università degli Studi di Milano, Italy, caterina.feletti@unimi.it

[†]School of Computer Science, Carleton University, Canada, drdebmath@gmail.com

[‡]Department of Computer Science, Kent State University, USA, gsharma2@kent.edu

assumed to be *transparent* (so that each robot has complete visibility of the swarm), *oblivious* (they cannot store any information about past LCM cycles), and *silent* (they do not have any direct communication means) [19].

In this paper, we consider a more recent model, the robots with lights (aka luminous) model [7, 11, 19, 28], where robots are embedded with a light whose color can be chosen from a fixed palette and persists cycle by cycle until its next update. Since such a light is visible to both the robot itself and the other robots, the luminous model grants robots both a persistent internal state (memory) and a direct communication means. Additionally, we assume our robots are opaque, thus they experience obstructed visibility in case of collinearities (if robots a, b, c are collinear, a and c cannot see each other). Note that, since by default the size of the swarm n is not known in advance by the robots, they may not realize if they are experiencing complete or obstructed visibility in the Look phase.

We say that two robots *collide* if either (i) they share the same position at a given time or (ii) their paths towards their destinations intersect within concurrent LCM cycles. We assume robot movements are *rigid*, i.e., in each *Move*, the robot stops only after reaching its destination.

In this paper, we study the fundamental UNIFORM CIRCLE FORMATION (UCF) problem for luminousopaque robots. Starting from an arbitrary configuration where n robots occupy distinct points on a plane, the problem aims at relocating them autonomously on the vertices of a regular n-gon not fixed in advance. Namely, UCF is solved if the n robots are equally distributed on the same circle. Thanks to the well-known properties of such a geometric configuration, UCF is deemed an important special case of the GEOMETRIC PATTERN FORMATION problem [5, 19, 20, 31, 32]. A geometric pattern (or, simply, pattern) is defined as a set of points on a plane. The GEOMETRIC PATTERN FORMATION problem for a pattern P is said to be solved by a swam of robots if they form a stable configuration (i.e. where robots no longer move) where the set of their positions is similar to P up to scaling, rotation, translation, and reflection.

Related to UCF, it is noteworthy to mention its precursor, the CIRCLE FORMATION problem [1, 8]: robots are required to relocate on the boundaries of the same circle, without any other requirement. The uniform version of this problem, namely UCF, has been investigated by multiple works [4, 9, 10, 12, 13, 14, 21, 22, 24, 25, 26] in the classic *oblivious-transparent* robot model (see [33] for an excellent survey). Many of the cited works focused mostly on the solvability of the problem in finite time, considering different model assumptions (e.g. specific initial configurations [13, 22], only 3 or 4 robots [14, 24]), without examining the time complexity of the proposed algorithm [21, 33].

Time complexity is measured based on the underlying scheduler under which robots operate. Generally, literature considers three main schedulers. Under the *fully synchronous* scheduler (\mathcal{FSYNC}), the robots perform their LCM cycles in perfect synchrony and hence time is measured in rounds of LCM cycles. Under the *semi-synchronous* (\mathcal{SSYNC}) and *asynchronous* (\mathcal{ASYNC}) schedulers, a robot may stay inactive for a finite but indeterminate time and hence time is measured using the idea of epoch. An *epoch* is the smallest time interval within which each robot performs its LCM cycle at least once [6]. We will use the term "time" generically to mean rounds for the \mathcal{FSYNC} and epochs for the \mathcal{SSYNC} and \mathcal{ASYNC} schedulers.

Feletti *et al.* [15, 16, 17, 18] are the first to consider UCF in the *luminous-opaque* robot model. They presented a deterministic O(1)-time O(1)-color solution under the \mathcal{FSYNC} and \mathcal{SSYNC} schedulers, and a deterministic $O(\log n)$ -time O(1)-color solution under the \mathcal{ASYNC} scheduler, avoiding collisions. Recently, Pattanayak and Sharma [27] developed a framework that provides a deterministic O(x)-time solution using $O(n^{1/2^x})$ colors under the asynchronous scheduler. Setting x to some constant, it gives a O(1)-time solution (i.e. asymptotically optimal) with $O(\sqrt{n})$ colors. Setting $x = O(\log \log n)$, it gives a $O(\log \log n)$ -time solution which uses O(1) colors.

1.2 Our Result

In this paper, we propose a deterministic algorithm for solving UCF in the luminous-opaque model under \mathcal{ASYNC} , avoiding collisions. Our algorithm runs in O(1) time with O(1) colors. Compared to the state-of-the-art result of Pattanayak and Sharma [27] which is either optimal in time with $O(\sqrt{n})$ colors or optimal in colors with $O(\log \log n)$ time, our algorithm is simultaneously optimal on both time and number of colors. Another important aspect of our proposed algorithm is that, in addition to optimizing both runtime and color complexity, it minimizes a spatial metric that we call *computational SEC*, i.e. the smallest circle containing all the points the robots touch during the execution of the algorithm. This objective is driven by a recent

Algorithm	Time (in epochs)	Number of Colors	Computational SEC	Scheduler
[15]	O(1)	O(1)	Not minimized	FSYNC
[18]	O(1)	O(1)	Not minimized	SSYNC
[18]	O(n)	O(1)	Not minimized	
[16]	$O(\log n)$	O(1)	Not minimized	-
Generic [27]	O(x)	$O\left(n^{1/2^x}\right)$	Not minimized	ASVNC
OptTime [27]	O(1)	$O(\sqrt{n})$	Not minimized	AOJNC
OptColor [27]	$O(\log \log n)$	O(1)	Not minimized	
OptTime&Color (this paper)	O(1)	O(1)	Minimized	-

Table 1: Existing UCF deterministic solutions for $n \ge 1$ luminous-opaque robots on the plane, avoiding collisions. $x \in [1, O(\log \log n)]$.

research direction on robot computing which aims to solve *space-constrained* versions of classic distributed problems. Given a problem P for a swarm of robots, a *space-constrained version of* P requires optimizing some spatial metrics (e.g. the maximum distance traveled by a robot [1, 5]) while solving P. Although, in most cases of our algorithm, the computational SEC minimization turns out to be a byproduct of the technique used to optimize time and color complexity, a particular configuration needed an *ad hoc* technique to be designed to minimize the computational SEC. Note that the existing UCF solutions do not minimize the computational SEC. Table 1 summarizes our result by comparing it with the existing UCF solutions.

1.3 Challenges

Performing in \mathcal{ASYNC} , our algorithm had to face the intrinsic issues that asynchrony entails. Such issues derive from the discrepancy in the duration of the LCM cycles each robot follows. This discrepancy can affect the correctness of algorithmic strategies (e.g. a robot may work on an outdated snapshot of the system it takes on its *Look* portion of the cycle), the integrity of the system (e.g. two robots may collide if their motions are not synchronized), and the algorithmic runtime (e.g. robots may be forced to perform sequentially to avoid erroneous computations or collisions). Moreover, *opaqueness* (and so *obstructed visibility*) posed an additional challenge under \mathcal{ASYNC} , since moving robots can hide or be hidden by other robots.

However, moving in parallel is essential in reaching a O(1)-time algorithm. The main challenge of this work was to make robots exploit parallelism even in conditions of asynchrony and obstructed visibility, always keeping the size of the color palette constant. Indeed, this paper shows that robots can move in parallel to solve UCF without colliding, using O(1) colors. As in [15, 16, 17, 18, 27], we factorize UCF into three sub-problems (see Table 2): (i) COMPLETE VISIBILITY, (ii) CIRCLE FORMATION, and lastly (iii) UNIFORM TRANSFORMATION. Given an arbitrary initial configuration of robots on distinct points on the plane, we (i) exploit the deterministic COMPLETE VISIBILITY result of Sharma *et al.* [30] under ASYNC to arrange robots on the vertices of a convex polygon in O(1) time using O(1) colors, avoiding collisions. After that, (ii) a simple procedure will safely move the robots to the perimeter of a circle, say Cir, in O(1) epochs using O(1) colors. The remaining step (iii) aims to equally distribute the robots on the perimeter of Cir, thus solving UCF. This last step represents the real challenge for the time-color optimization of UCF.



Table 2: Sub-problems composing UNIFORM CIRCLE FORMATION.

Up to now, step (*iii*) was solved in a binary tournament fashion in Feletti *et al.* [16] achieving an $O(\log n)$ -time solution using O(1) colors under ASYNC. Afterward, the step was expedited by Pattanayak and Sharma [27] by dividing the robots in \sqrt{x} groups in each step for x robots in a group achieving an $O(\log \log n)$ -time solution using O(1) colors and O(1)-time solution using $O(\sqrt{n})$ colors. In this paper, we optimize step (*iii*) by developing a O(1)-time and O(1)-color algorithm, forgoing the use of both binary and square root tournament.

The other main challenge of this work has been minimizing the computational SEC, i.e. the circular area in which robots operate. Note that, to minimize the computational SEC, robots have to always stay within the smallest enclosing circle of the initial configuration. The solutions used to solve (i) COMPLETE VISIBILITY [30] and (ii) CIRCLE FORMATION guarantee to minimize the computational SEC. Thus, to minimize the computational SEC throughout the whole UCF solution, our solution for step (iii) must guarantee robots operate within the initial circle. Note that the $O(\log n)$ -time UNIFORM TRANSFORMATION solution provided in [16] makes robots move out from the initial circle Cir, before having them positioned uniformly on it. Indeed, requiring robots to move internally to Cir complicated the investigation for a O(1)-time solution, since internal moving robots can obstruct the visibility of the robots on the perimeter of Cir. However, our UNIFORM TRANSFORMATION solution proposed in this paper guarantees robots always stay within Cir (perimeter included), thus minimizing its computational SEC.

1.4 Techniques

Let us briefly introduce our algorithmic strategies. Our algorithm for step (*iii*) receives in input a circle configuration, where all n robots lay on distinct points of a circle, Cir. The target n-gon will be inscribed in Cir. Identifying the type of symmetry of the configuration turns out to be necessary to address the input robot disposition. In particular, we classify the configuration into three categories: regular, biangular, or periodic. The regular configuration immediately solves UCF. A biangular configuration can be converted into a regular configuration through a similar approach to the strategy introduced in [13] in order to minimize the computational SEC. The most challenging is the periodic configuration, for which we developed a sequence of multi-step procedures to form a regular polygon by the robots. At first, we divide Cir into $k \geq 2$ uniform sectors (depending on periodicities) with each arc containing n/k vertices of the target n-gon to be formed. The algorithm then works in parallel in each of the k uniform sectors. Within each sector, two robots are elected as guards to fix the chirality of a structure called odd-block. Let \mathcal{L} be the chord joining the left guard with the right guard. The other robots on the sector arc are now moved to the chord \mathcal{L} . One robot is elected as the median robot and reaches the midpoint of the arc cut by \mathcal{L} . A (inner) circle \mathcal{C} is now drawn such that it passes through the median robot and such that the chord becomes its tangent. All the robots on the chord now move to be positioned on the perimeter of \mathcal{C} .

We now use a procedure to provide a rank to the robots on C so that a robot with rank j moves to the target n-gon vertex j. Indeed, rank encoding is an important task involved in UCF and it belongs to that part of literature that attempted to provide efficient strategies to encode non-constant data (e.g. swarm cardinality, robot ranks, configuration properties, etc.) through the swarm configuration, in a sort of stigmergic behavior [2, 3, 16, 23]. In [3], Bramas et al. develop the level-slicing technique for solving the fault-tolerant GATHERING problem using the mutual distance of another robot. In particular, robots operate according to their level previously encoded in their distance from another robot. In [16], authors use the pairing technique to solve UCF in that pairs of robots exploit their mutual distance to encode their rank, guaranteeing that half of the robots can reach the target position in a binary tournament fashion. To achieve a parallel fashion, one can suggest making robots encode their rank through their mutual distance from a selected robot. However, this general strategy is not sufficient to guarantee robots can reach such a mutual distance in O(1) time without colliding or creating dangerous collinearities (in fact, robots need to count themselves to compute their rank).

To cope with these complications, we split the inner circle C into slice units (equal to the minimum angular distance between any two robots) and make each robot encode its rank by properly positioning *within* its slice, thus ensuring complete visibility during collision-free motions in a parallel fashion. Besides the closeness with the level-slicing technique [3], our rank encoding presents some peculiar differences: robots operate on a circle instead of a line, the slices are fixed for the whole procedure, and they have the same length instead of exponential lengths. Such differences have been necessary to cope with opaque and collision-intolerant

robots and provide a robust rank encoding that retains effectiveness in complete asynchrony so that a robot must be able to recompute its rank j even when all the other robots are moving. Specifically, let ρ be the diameter of C passing through the median robot. The robots on the inner circle are equally partitioned into two groups so that one group is positioned on the left half-perimeter of C and the other group on its right half-perimeter. The robots in the left group then move along the perimeter to encode their rank using the angular distance with a fixed robot. Then, the right group can obtain its rank using the left group as a reference. Then, the robots of each group (first the right one, then the left one) migrate on ρ on their projections, then they recompute their rank and reach their target vertices on the *Cir*-arc belonging to their uniform sector. After each uniform sector completes the algorithm, the *n* robots are equally distributed on *Cir*, thus solving UCF. Care should be taken in synchronizing all these steps to ensure robots never collide even in ASYNC. We show that all the steps can be executed correctly and safely (avoiding collisions) in O(1) epochs.

1.5 Related Works

UCF has been investigated in the luminous-opaque robot model by Feletti *et al.* [15, 16, 17, 18] and Pattanayak and Sharma [27]. Feletti *et al.* [15, 16, 17, 18] exhibited a O(1)-time algorithm in \mathcal{FSYNC} and \mathcal{SSYNC} , and a $O(\log n)$ -time algorithm under \mathcal{ASYNC} , both using O(1) colors and avoiding collisions. Pattanayak and Sharma [27] showed that UCF can be solved in O(1) time with $O(\sqrt{n})$ colors, or in $O(\log \log n)$ time with O(1) colors in \mathcal{ASYNC} .

Previous works have studied UCF in the classic oblivious-transparent robot model. The state-of-the-art result by Flocchini *et al.* [21] shows that UCF can be solved under \mathcal{ASYNC} starting from any arbitrary configuration of n > 5 robots initially being on distinct locations, without any additional assumption (i.e., chirality, rigidity, etc.). However, their paper focuses on the computability of UCF and not on its complexity in terms of execution time. Prior to [21], other different assumptions [4, 9, 10, 12, 13, 14, 22] had been considered in the study of UCF. An excellent discussion can be found in [33]. The case of $n \leq 5$ can be solved using ad-hoc algorithms. The special case of the SQUARE FORMATION has been solved in [24]. Recently, UCF has been studied with additional objectives or features: minimizing the maximum distance traveled by a robot [1] and considering transparent/opaque fat robots (of diameter 1) [8, 25, 26].

GEOMETRIC or ARBITRARY PATTERN FORMATION is the macro-problem which encompasses UCF. Due to its importance, this problem has been heavily studied under different models (oblivious and luminous) [19, 20, 32]. Starting from arbitrary configurations of robots initially on distinct points on a plane, robots must autonomously arrange themselves to form the target pattern given to robots as input. Vaidyanathan *et al.* [32] showed that ARBITRARY PATTERN FORMATION can be solved in $O(\log n)$ epochs using O(1) colors under ASYNC. According to that result, UCF can also be solved in $O(\log n)$ epochs using O(1) colors, provided that the target *n*-gon positions are given to robots as input a priori. However, since the target circle is not known in advance in this paper, the strategies in [32] are not compliant with our assumptions.

1.6 Paper Organization

We introduce the model and some preliminaries in Section 2. We present a high-level overview of the three components of our algorithm in Section 3. The first two components are described in Sections 4 and 5. The discussion on the second component focuses on minimizing the computational SEC. Then, we describe the third component in Section 6, which develops novel ideas allowing us to achieve complete parallelism using O(1) colors. Section 7 describes how the techniques developed in the three components collectively solve UNIFORM CIRCLE FORMATION and prove its time- and color-optimization properties as well as computational SEC minimization property. Finally, we conclude with a short discussion in Section 8. The pseudo-code and correctness proofs are provided in Appendices A and B: complexity analysis directly follows from the correctness proofs.

2 Model and Preliminaries

Robots. We consider a swarm of *n* dimensionless robots (agents) $\mathcal{R} = \{r_1, r_2, \ldots, r_n\}$ that can move in an Euclidean plane \mathbb{R}^2 . They enjoy the classical features of these models: they are *autonomous*, *anonymous*,

indistinguishable, and *homogeneous*. They are completely disoriented (no global agreement on coordinate systems, chirality, unit distance, or origin). We consider *collision-intolerant* robots, i.e. robots must avoid collisions at any time. Two robots r_i, r_j are *mutual visible* to each other iff there does not exist a third robot r_k in the line segment joining r_i and r_j , such that $r_k \notin \{r_i, r_j\}$. Clearly, mutual visibility is reflexive and symmetric. The cardinality of the swarm n is not a given parameter of the algorithm robots must execute. We will often use r_i to denote the robot as well as its position.

Lights. Each robot is embedded with a light that can assume one color at a time from a fixed O(1)-size palette.

Look-Compute-Move. By default, a robot r_i is inactive. A robot can be activated by an adversarial scheduler. When activated, it performs a "Look-Compute-Move" cycle as described below. After that, the robot becomes inactive until its next activation. Let us describe each LCM phase:

- Look: r_i takes an instantaneous snapshot of the current configuration, i.e. it takes the positions and the colors of all the robots visible to it. Robot positions are taken according to the coordinate system of r_i .
- Compute: Robot r_i performs a deterministic algorithm with infinite precision using the taken snapshot as the sole input. The algorithm produces in output a (possibly) new position and light color for r_i .
- Move: Robot r_i updates its light to the new color and moves to its new position along a straight trajectory. The move is rigid and hence r_i always reaches its calculated position.

Robot Activation and Synchronization. Generally, three schedulers are considered in the literature. Under the synchronous schedulers, time is divided in atomic *rounds*: at each round, a subset of robots is activated and they perform each phase of one LCM cycle in perfect synchrony. Specifically, under the fully synchronous scheduler (\mathcal{FSYNC}), all robots are activated at each round, while under the semi-synchronous scheduler (\mathcal{FSYNC}), an arbitrary non-empty subset of robots is activated at each round. Under the asynchronous scheduler (\mathcal{ASYNC}), robots act without any activation/synchronization assumption except for the fact that the Look phase is always instantaneous. The duration of each cycle is finite but unpredictable. Indeed, an arbitrary amount of time may elapse between Look/Compute and Compute/Move. Both in \mathcal{SSYNC} and in \mathcal{ASYNC} , we assume the *fairness assumption* which states that each robot is activated infinitely often. An activated robot cannot distinguish between active and inactive robots from the snapshot.

Runtime. In \mathcal{FSYNC} , time is measured in rounds of LCM cycles. However, since in \mathcal{SSYNC} and \mathcal{ASYNC} a robot could stay inactive for an indeterminate time, the concept of *epoch* [6] has been introduced to have a proper measure to analyze algorithm runtimes. We will use the term "time" generically to mean rounds for the \mathcal{FSYNC} and epochs for the \mathcal{SSYNC} and \mathcal{ASYNC} schedulers.

Configurations. Let the *initial* configuration be denoted as $Conf_{init}$. In $Conf_{init}$, the *n* robots in \mathcal{R} are positioned on *n* distinct points on the plane, all with the same light color (w.l.o.g. off). We denote with $Conf_{convex}$ a configuration where the *n* robots lay on the vertices of a convex *n*-gon. If this *n*-gon is inscribed into a circle, we denote this configuration as $Conf_{circle}$. If this *n*-gon is regular, we denote the configuration as $Conf_{regular}$.

Definition 1 (UNIFORM CIRCLE FORMATION). Given any $Conf_{init}$ with n luminous-opaque robots on the Euclidean plane, the UNIFORM CIRCLE FORMATION (UCF) problem asks the robots to autonomously reposition themselves to reach $Conf_{regular}$ without colliding, and terminate.

Terminology. Given two circles Ω_1 , Ω_2 on the Euclidean plane, we say that Ω_1 is enclosed in Ω_2 , denoted as $\Omega_1 \sqsubseteq \Omega_2$, if all the points of Ω_1 belong to the enclosed region delimited by Ω_2 (perimeter included). Indeed, \sqsubseteq is reflexive and transitive. Given two points A, B, \overline{AB} denotes the line segment connecting such points. If A and B lay on a circle, \widehat{AB} denotes the smaller arc between the points A and B. If points A and B are antipodal (i.e., diametrically opposite), we identify the arc by \widehat{ACB} where C is a point on the circle that is contained in the arc \widehat{AB} . We say that an arc is *chiral* if the robots on it are arranged in an asymmetrical pattern. Given a point D and a segment \overline{EF} , we define the *mirror projection* (or, simply, *projection*) of

D on \overline{EF} the point $D' \in \overline{EF}$ (if it exists) such that $\overline{DD'} \perp \overline{EF}$. The smallest enclosing circle (SEC) of a given configuration Conf, denoted as SEC(Conf), is the (unique) smallest circle containing all the robot positions in Conf. We denote with Cir the circle $SEC(Conf_{convex})$. Cir can be divided into n arcs of equal length. We call these arcs uniform segments and the corresponding endpoints are uniform positions. Table 3 summarizes the essential notations here or later introduced and mainly used throughout the whole paper.

$\Omega_1 \sqsubseteq \Omega_2$	Circle Ω_1 is enclosed in circle Ω_2	
AB	The line segment joining points A and B	
\widehat{AB}	The smallest arc joining two points on the circle	
SEC(Conf)	SEC of the configuration Conf	
Cir	$SEC(Conf_{convex})$	
$lpha,eta,\mu$	Angular Sequences	
BDCP	BEACON DIRECTED CURVE POSITIONING	
Φ	The set of robots with the smallest angular sequence	
$\Upsilon_0,\ldots,\Upsilon_{k-1}$	Uniform sectors	
B_i, B_{i+1}	Boundaries of Υ_i	
q	The total number of robots inside each uniform sector	
U_1,\ldots,U_q	Uniform positions inside a block	
\mathcal{L}	The block chord joining the left guard with the right guard	
Г	The Block Arc	
\mathcal{C}	The small circle inside an odd block	
ρ	The median diameter of \mathcal{C}	
m	Number of west (and so east) robots on \mathcal{C}	
δ	The small angle for Procedure SLICE	

Table 3: Terminology.



Figure 1: Different types of $Conf_{circle}$: (a) $Conf_{regular}$, (b) $Conf_{biangular}$, (c) $Conf_{uniperiodic}$, (d) $Conf_{biperiodic}$ without robots on the axis of symmetry, (e) $Conf_{biperiodic}$ with robots on the axis of symmetry.

2.1 Classes of Circle Configurations

Consider $Conf_{circle}$ where *n* robots colored onSEC are located on Cir. Let r_0, \ldots, r_{n-1} be their positions. We define the *angular sequence* for a robot r_j as the sequence of angles in the clockwise order represented by $\alpha(j) = a_j a_{j+1} \ldots a_{j-1}$, where $a_i = \angle r_i Or_{i+1}$, *O* is the center of Cir, and the indices are considered modulo *n*. Similarly, we define $\beta(j) = b_j b_{j-1} \ldots b_{j+1}$, where $b_i = \angle r_i Or_{i-1}$ considered in the counterclockwise direction. Let $\mu(j) = \min\{\alpha(j), \beta(j)\}$ be the lexicographical minimum sequence for r_j . Let $\hat{\mu} = \min\{\mu(0), \ldots, \mu(n-1)\}$. Note that, there may be multiple robots corresponding to the *smallest angular sequence* $\hat{\mu}$. We define $\Phi = \{r_i : \mu(i) = \hat{\mu}\}$.

A configuration is *reflective* (i.e., a mirror symmetry) if there exists a pair of robots r_p and $r_{p'}$ in Φ such that $\alpha(p) = \beta(p')$. Now, we distinguish between two cases, according to the cardinality of Φ :

2.1.1 Case $|\Phi| = n$ – Regular and Biangular Configurations

In this case, all the robots correspond to the smallest angular sequence. There are two types of configurations.

- 1. Regular Configuration: In $Conf_{regular}$, we have $\alpha(0) = \alpha(i)$, for all i = 0, ..., n-1 (Figure 1a).
- 2. Biangular Configuration: In Conf_{biangular}, we have $\alpha(0) = \alpha(2i) = (a_0a_1)^{\frac{n}{2}}$ where $a_0 \neq a_1$ and $n \geq 2$, for any $i = 0, \ldots, \frac{n}{2} 1$ (Figure 1b).

Observation 1. If $|\Phi| = n$ and $\alpha(i) = \beta(i)$ for some $0 \le i \le n-1$, then the configuration is Conf_{regular}.

In $Conf_{biangular}$, an axis of symmetry always passes through the midpoint between any pair of adjacent robots on Cir. Also, no robot lies on this axis of symmetry (Figure 1b).

2.1.2 Case $1 \le |\Phi| < n$ – Periodic Configurations

In a periodic configuration $Conf_{periodic}$, there are $|\Phi|$ groups of robots creating some form of symmetry (reflective or rotational). $Conf_{periodic}$ can be classified into two subclasses as follows. If $Conf_{periodic}$ is not reflective, we call it uniperiodic and denote as $Conf_{uniperiodic}$ (Figure 1c). The special case $|\Phi| = 1$ gives us an asymmetric configuration, denoted as $Conf_{asymmetric}$. If the configuration is reflective, we call it biperiodic and denote as $Conf_{asymmetric}$. If the configuration is reflective, we call it biperiodic and denote as $Conf_{biperiodic}$. Given a diameter d lying on an axis of symmetry, there are three cases: (i) no robot lies on the endpoints of d (Figure 1d), (ii) each endpoint of d is covered by one robot (Figure 1e), and (iii) a robot lies on one endpoint of d whereas the other endpoint is robot-free.

Algorithm 1: BEACON DIRECTED CURVE POSITIONING [30]

Input Assumptions:

- 1. Ω , a k-point curve, with $k \in \{2, 3\}$;
- 2. 2k beacons lay on Ω (k left beacons and k right beacons);
- 3. *m* waiting robots r_1, \ldots, r_m s.t.
 - (a) they are external to Ω belonging to the same half-plane (if k = 2) or the convex side (if k = 3);
 - (b) they can see all the 2k original beacons;
 - (c) they have to reach Ω
 - in some points between the original *left* beacons and the *right* beacons;
 - traveling along disjoint paths π_1, \ldots, π_m ;
 - so that their paths intersect Ω only once;
 - so that if a waiting robot r_i sees at least k beacons, then it can compute its path π_i ;
 - (d) a waiting robot becomes a new beacon once it reaches Ω .

Result: All the waiting robots reach Ω without colliding in $O(\log k)$ epochs.

2.2 Beacon Directed Curve Positioning

BEACON DIRECTED CURVE POSITIONING (BDCP) is a procedure developed by Sharma *et al.* in [30] that uses some robots as *beacons* to define a k-point curve, and then guide other *waiting* robots (external to the curve all on one side) from their initial positions to their final positions on the curve in \mathcal{ASYNC} . A k-point curve Ω is a curve on \mathbb{R}^2 where k is the minimal number of points necessary to define Ω . Here, we consider only straight lines and circular arcs (so $k \in \{2,3\}$). Beacons and waiting robots have different colors, w.l.o.g. **beacon** and **waiting**. BDCP starts placing 2k beacon robots on Ω (divided in k left and k right beacons) to define the curve. Specifically, the beacons are positioned at their final positions on the curve. After that, all the m waiting robots move to be positioned on Ω between left and right beacons (Figure 2). Once a robot reaches Ω , it changes its color to beacon becoming a new beacon. It was shown in [30] that if the first epoch started with m waiting robots wanting to move to the curve (i.e., not already in transit to the curve) and an epoch $e \geq 1$ starts with $v \geq 2k$ beacons, then epoch e + 1 starts with min $\{m + 2k, 3v/2\}$ beacons, hence relocating all the robots to the curve in $O(\log k)$ epochs, using O(1) colors. In our framework, we borrow the idea of Sharma *et al.* [30] and use BDCP to relocate robots on line segments (k = 2) and circular



Figure 2: BDCP on a circular arc, where b_1, b_2, b_3 (b_4, b_5, b_6 , resp.) are the left (right, resp.) beacons.



Figure 3: Transition diagram among configurations while solving UCF. The arrows without numbering denote a transition with only color change (no robot moves). The parameter q is the number of robots in each uniform sector of $Conf_{unisect}$.

arcs (k = 3) using 2k beacons in $O(\log k) = O(1)$ epochs in ASYNC. Algorithm 1 summarizes the input assumptions and the resulted output of the BDCP procedure.

3 Overview of the Algorithm

In this section, we provide an overview of our O(1)-time O(1)-color algorithm for UCF under ASYNC, avoiding collisions. Starting from an arbitrary configuration $Conf_{init}$ where n off-colored robots lay on distinct points of the plane, the proposed algorithm includes three major components:

- (I) circle formation;
- (II) transforming biangular configurations to regular configurations;
- (III) transforming periodic configurations to regular configurations.

In the next Sections, we will provide the details on each of these components. The proposed algorithm runs Component I and, subsequently, either Component II or Component III. The diagram in Figure 3 depicts the configuration transitions induced by the execution of each step of our algorithm.

Starting from $Conf_{init}$, robots execute Procedure COMPLETE VISIBILITY [30] to form a convex configuration $Conf_{convex}$, (transition 1). Afterward, robots execute Procedure CIRCLE FORMATION to achieve $Conf_{circle}$ (transition 2). Pattanayak and Sharma [27] showed that $Conf_{init}$ can be transformed to $Conf_{circle}$ in O(1) epochs using O(1) colors under ASYNC, avoiding collisions.

Once in $Conf_{circle}$, if robots satisfy $Conf_{biangular}$, they use Procedure BIANGULAR to arrange themselves to satisfy $Conf_{regular}$, thus solving UCF (transition (3)).

Indeed, the most challenging case results when $Conf_{circle}$ satisfies $Conf_{periodic}$. Our contribution in this paper will establish that $Conf_{periodic}$ can be transformed into $Conf_{regular}$ in O(1) epochs under ASYNC, avoiding collisions, using O(1) colors (**transitions** (4)–(8)). Specifically, $Conf_{periodic}$ is first transformed into $Conf_{unisect}$ (a configuration containing uniform sectors as defined later), using Procedure SPLIT (**transition** (4)). Then $Conf_{unisect}$ is transformed into $Conf_{oddblock}$ (an odd block configuration defined later) using Procedure ODD BLOCK (**transition** (5)). Then, $Conf_{oddblock}$ is transformed into $Conf_{smallcircle}$ using Procedure SMALL CIRCLE (**transition** (6)). Finally $Conf_{smallcircle}$ is transformed into $Conf_{regular}$ using Procedure SLICE (**transition** (7)), thus solving UCF. When $Conf_{unisect}$ has less than 12 robots in each uniform sector, we directly solve UCF using Procedure SEQUENTIAL MATCH (**transition** (8)). We will show that each of these procedures takes O(1) time and colors. Light colors are also used to synchronize robots to decide on the subsequent configuration to achieve, avoiding ambiguous situations. Moreover, we will show that our solution minimizes the computational SEC by proving that $SEC(Conf) \sqsubseteq SEC(Conf_{init})$ for any intermediate configuration *Conf* achieved throughout the execution of the whole algorithm.

We now provide details of the algorithm. We give particular focus on Components II and III since Component I can be run using the techniques of Feletti *et al.* [16, 17, 18] and Pattanayak and Sharma [27]. Therefore, we describe Component I in brief in Section 4 and move on to describing techniques for Components II and III in Sections 5 and 6, respectively. Notice that the techniques of Feletti *et al.* [16, 17, 18] and Pattanayak and Sharma [27] can be used in Component II but those techniques only optimize time and color complexities but not minimize the computational SEC. Our new idea both optimizes time/color complexities and minimizes the computational SEC.

4 Component I - Circle Formation (Transitions (1) and (2))

Given $Conf_{init}$, the robots use the COMPLETE VISIBILITY algorithm of Sharma *et al.* [30] to reach $Conf_{convex}$ where robots occupy the vertices of a convex *n*-gon, thus guaranteeing complete visibility to the whole swarm. Let Cir be $SEC(Conf_{convex})$. The COMPLETE VISIBILITY algorithm in [30] works using O(1) time and colors, and guarantees that any robot in the swarm operates within $SEC(Conf_{init})$ (thus minimizing the computational SEC). W.l.o.g. we assume that each robot is colored as **convex** in $Conf_{convex}$.

Starting from $Conf_{convex}$, robots execute Procedure CIRCLE FORMATION. Let r be a convex robot. If r already lays on the perimeter of Cir, it sets its color as onSEC. Note that at least 2 (if antipodal) or 3 robots (if not antipodal) on Cir set their color as onSEC without moving, while the remainder lies in the interior of Cir. Otherwise (i.e. if r is internal to Cir), r moves radially towards Cir until reaching the perimeter of the circle. After reaching Cir, r assumes color onSEC. Once every robot turns into onSEC, CIRCLE FORMATION is solved. Pattanayak and Sharma [27] showed that this process avoids collisions and robots correctly position themselves on Cir in O(1) epochs with O(1) colors.

Lemma 1 (Circle Formation [27]). Given $Conf_{init}$ with n off-colored robots on distinct points on a plane, robots reposition themselves in $Conf_{circle}$ using O(1) epochs and O(1) colors under ASYNC, avoiding collisions, guaranteeing that robots operate within $SEC(Conf_{init})$.

5 Component II - Transforming Biangular Configurations into Regular Configurations (Transition ③)

Each onSEC robot on $Conf_{circle}$ can check whether the current configuration satisfies either $Conf_{regular}, Conf_{biangular}$, or $Conf_{periodic}$. Thus, each robot changes its color accordingly (without moving) to either regular, biangular, or periodic, respectively. Colors are used to make robots agree on the procedure to be executed. Indeed, $Conf_{regular}$ solves UCF, so robots will no longer update their color or position.



Figure 4: Arrangement of $Conf_{biangular}$ in a regular *n*-gon.

We discuss here Conf_{biangular}. Conf_{periodic} is treated in Component III and discussed in the next section. To solve this special configuration, we take inspiration from an idea of Dieudonné et al. [13], although we implement a new approach to transform $Conf_{biangular}$ into $Conf_{regular}$ which suits our objective. In $Conf_{biangular}$, n is even and the configuration has n/2 axes of symmetry. Let n = 2k, and let P be the n-gon formed by the robots in $Conf_{biangular}$ (i.e. each vertex of P is covered by a robot). The strategy developed by Dieudonné et al. [13] was to spot the target regular n-gon P' which encloses P, such that robots lay on alternative edges of P' (Figure 4b), and make robots slide on the edges of P' until they stop to the vertices of P'. If on the one hand this strategy solves UCF even under \mathcal{ASYNC} , on the other hand it leads the robots to move outside $SEC(Conf_{biangular})$ to reach the vertices of P'. Seeing that our objective is also to minimize the computational SEC, we propose a target n-gon P'' that is inscribed inside P. Specifically, the inscribed polygon P'' has its vertices on the larger edge of P (being biangular, P has two different edge lengths). After detecting the target polygon P'', the robots are made to move along the larger edges of P towards the vertices of P'', thus achieving $Conf_{regular}$. We now show that, as in [13], our strategy works also considering asynchronous robots. Given P, we form a regular k-gon by extending the larger edges of P(see Figure 4c). We call this extended k-gon as the exogenous polygon (EP for short). Notice that, as long as the robots move along the larger edges of P such that the larger edge remains the larger edge, the EPalso remains the same. For an EP, there exists a unique regular 2k-gon inscribed in it (see Figure 4d). This property guarantees that the target polygon P'' (i.e. the regular 2k-gon inscribed in EP) is maintained even when some robots are in transit, and so it can be correctly computed even when robots no longer form P. In particular, the location of the vertices of P'' is located at a distance y from the vertex of the EP, where z is the edge length of the EP. The value of y is given by

$$y = \frac{z}{2 + \sqrt{2 - 2\cos\left(\frac{(k-2)\pi}{k}\right)}}$$

After reaching a vertex of P'', the robots assume color **regular**. In summary, robots form $Conf_{regular}$ from $Conf_{biangular}$ in three epochs: (i) robots change color to **biangular**, (ii) then they head to the vertices of P'', traveling along the edges of EP, and (iii) lastly they color as **regular**.

Lemma 2 (Biangular to Regular Configuration). Given $Conf_{biangular}$ of n biangular-colored robots, the robots reposition to $Conf_{regular}$ in O(1) epochs using O(1) colors under ASYNC, avoiding collisions, guaranteeing that robots always operate within $SEC(Conf_{biangular})$.

6 Component III - Transforming Periodic Configurations into Regular Configurations (Transitions (4–8))

Before diving into the deep of our algorithm, we mention two strategic usages of robot lights to ensure a correct evolution of the algorithm under ASYNC. For the sake of conciseness, we will often omit the details of these two strategies while explaining the algorithm, assuming their rationale is understood.

- Elections under ASYNC. In some points of our algorithm, a group of robots is elected to perform a movement, in parallel. Being under ASYNC, we need to ensure that all robots can correctly elect themselves even if part of the elected group is already moving. For this reason, our algorithm requires *all* the elected robots in the group to synchronize themselves setting their colors as **pre_<color>** before starting moving, where **<color>** will be the color they have to set once stopped and reactivated.
- Movements under ASYNC. In the remainder, our algorithm makes a robot color itself as to_<color> before starting moving, where <color> will be the color it has to set once stopped and reactivated. This strategy guarantees robots recognize moving robots in ASYNC (those not hidden by other robots), thus avoiding ambiguous situations.

6.1 Procedure Split (Transition (4))

Procedure SPLIT takes in input $Conf_{periodic}$ where all *n* robots are periodic-colored and lay on Cir in a periodic pattern. This procedure partitions $Conf_{periodic}$ into $k \ge 2$ circular sectors $\Upsilon_0, \ldots, \Upsilon_{k-1}$ such that

(i) they have the same arc length and (ii) they are size-balanced (i.e. containing the same number of robots), and (iii) they are chiral (i.e. the robots are arranged in an asymmetric pattern along the arc of each Υ_i). We call such sectors as *uniform sectors*. In this procedure, some robots will be elected as *leaders* to fix the boundaries of each Υ_i , and some robots will be elected and made to move to fix the chirality of the sector. Leaders will turn their color into **regular** if they lay on the boundaries of uniform sectors, or, otherwise, into **leader** (i.e. if the boundary of a uniform sector lies in the middle point between two consecutive **leader** robots). We proceed as follows, distinguishing two cases based on $|\Phi|$.



Figure 5: *Conf_{unisect}* where *Cir* is split into uniform sectors (here delimited by dotted lines) using the light color: regular (here *red*), left (here *cyan*), right (here *lime*), and leader (here *lightgray*). All the other robots are omitted.

out regular robots.

regular robots.

Case $|\Phi| = 1$: In this case, we form two uniform sectors Υ_0, Υ_1 . There are two subcases.

- *n* odd: It is possible to unambiguously select a diameter *d* passing through only one robot *r* and splitting *Cir* into two size-balanced halves. These two *Cir*-halves correspond to Υ_0, Υ_1 . The robot *r* changes its color to regular. Then, for each Υ_i , let U_1 be the uniform position on the arc Υ_i such that $\angle rOU_1 = 2\pi/n$ and $U_{(n-1)/2}$ be the uniform position such that $\angle rOU_{(n-1)/2} = (n-1)\pi/n$. Two robots from each Υ_i are elected and made to move to U_1 and $U_{(n-1)/2}$, setting their colors as left and right, respectively. See Figure 5a.
- *n* even: It is possible to unambiguously select a diameter *d* either *(i)* passing through two antipodal robots *r* and *r'*, and splitting *Cir* into two size-balanced halves, or *(ii)* passing through only one robot *r* and splitting *Cir* into two halves with n/2 and n/2 1 robots. This diameter acts as the delimiter for the uniform sectors. The robot *r* turns its color into regular. When only one robot is located on *d*, then a robot *r'* from the half containing n/2 robots reaches the empty endpoint of *d*. Similar to the odd case, two robots are elected in each sector, and reach the uniform positions U_1 (such that $\angle rOU_1 = 2\pi/n$) and $U_{(n-2)/2}$ (such that $\angle r'OU_{(n-2)/2} = 2\pi/n$), setting their colors as left and right, respectively. Finally, *r'* sets its color to regular.

Case $|\Phi| > 1$: In this case, we form $|\Phi|$ uniform sectors. Let $(r_0, r_1, \ldots, r_{|\Phi|-1})$ be the robots from Φ in a cyclic order. In the following, we consider indices $i \in \{0, \ldots, |\Phi| - 1\}$ modulo n. We distinguish between uniperiodic and biperiodic configurations as defined in Section 2.1.

Uniperiodic: All the robots in Φ set their color as regular. They define the boundaries of the uniform sectors so that each Υ_i is delimited by *r_ir_{i+1}*. In a uniperiodic configuration, all the uniform sectors have the same chirality, w.l.o.g. clockwise. Now, inside each Υ_i, two robots have to move and update their color to fix this chirality. Let q be the number of periodic robots in the uniform sectors. Let U₁ (U_q, resp.) be the uniform positions on the arc of Υ_i such that ∠r_iOU₁ = 2π/n (∠U_qOr_{i+1} = 2π/n, resp.). Within each Υ_i, two periodic robots are elected to be intended for the points U₁ and U_q. In at most two epochs, the elected periodic robots reach the uniform positions U₁ and U_q, setting their colors as left and right, respectively. Note that, in this case, robots always enjoy complete visibility of the swarm, even if some robots are moving. See Figure 5b.

• **Biperiodic:** All the robots in Φ change their color to leader. In this case, $|\Phi|$ is always even, and leaders never lay on the axes of reflective symmetry of the configuration. Let B_i be the midpoint of the arc $\widehat{r_{i-1}r_i}$ for each *i*. We define Υ_i as the sector whose arc is $\widehat{B_iB_{i+1}}$. If a robot lies on a boundary B_i for some i, it sets its color as regular. Notice that each uniform sector Υ_i has a central angle $2\pi/|\Phi|$ and contains the leader-colored robot r_i (not necessary on the middle point of the arc of Υ_i). In a biperiodic configuration, two adjacent sectors have opposite chirality. Let us consider a uniform sector Υ_i , and suppose that B_i is the left boundary according to the chirality of Υ_i . Let U_1 (U_q , resp.) be the point on the arc Υ_i such that it forms a central angle with B_i $(B_{i+1}, \text{ resp.})$ equal to $(i) \frac{2\pi}{n}$ if a robot lies on B_i (B_{i+1} , resp.), (ii) $\frac{\pi}{n}$ otherwise. In the first epoch, two robots are elected from each sector Υ_i and they set their color as pre_left and pre_right so that the pre_left (pre_right, resp.) robot is intended to travel towards U_1 (U_q , resp.). If the elected pre_left (pre_right, resp.) robot already lies on U_1 (U_q , resp.), then it can directly assume the color left (right, resp.). Such two robots are unambiguously elected within each Υ_i among the closest adjacent periodic robots to the points U_1 and U_q . In the second epoch, all the pre_left robots reach the U_1 point on the corresponding sector and change their color to left. In the third epoch, all the pre_right robots reach the U_q point on the corresponding sector and set their color as right. See Figures 5c and 5d.

Let $Conf_{unisect}$ be the configuration obtained at the end of Procedure SPLIT (see Figure 5). In $Conf_{unisect}$, all the *n* robots lay on Cir, and they are partitioned in $k \geq 2$ uniform sectors $\Upsilon_0, \ldots, \Upsilon_{k-1}$. All the robots laying on the boundaries of uniform sectors are **regular**-colored. Each Υ_i contains a **left** robot and a **right** robot, which set the chirality of Υ_i . All the robots that are not {**regular**, **left**, **right**}-colored change their color to **split**. Note that all the {**regular**, **left**, **right**}-colored robots will not move anymore: they already lay on uniform positions. From now on, no robot will move out from its original uniform sector, and each of the subsequent procedures will run in parallel inside each uniform sector. See Appendix B.1 for the correctness proofs and complexity analysis of Procedure SPLIT.

Lemma 3 (Split). Starting from $Conf_{periodic}$, $Conf_{unisect}$ is reached in O(1) epochs using O(1) colors under ASYNC, avoiding collisions, guaranteeing that robots always operate within $SEC(Conf_{periodic})$. Robots are evenly partitioned in uniform sectors, whose chirality is set by right- and left-colored robots.

6.2 Procedure ODD BLOCK (Transition (5))

Given $Conf_{unisect}$, Procedure ODD BLOCK acts on each uniform sector independently. As the name suggests, we build an *odd block* inside each uniform sector Υ_i . Before describing the details of Procedure ODD BLOCK, we depict the target configuration that we want to achieve at the end of this procedure.

Odd block. An odd block of size 2l + 1, for an integer l, is a circular sector of Cir whose central angle measures $\frac{4l\pi}{n}$. When l is known, we will refer to the odd block as l-block. An l-block contains 2l + 1 uniform positions along its arc, which we denote as Γ . Let $U_1, U_2, \ldots, U_{2l+1}$ be the uniform positions of this block, where U_1 and U_{2l+1} lay on the endpoints of Γ . The block contains two robots on U_1 and U_{2l+1} . We will refer to such two robots as the left and the right guard. A robot, called the median robot, is located at position U_{l+1} . Let \mathcal{L} be the block chord $\overline{U_1 U_{2l+1}}$. At the end of Procedure ODD BLOCK, the guards and the median robot are colored as blockL (left), blockR (right), and median, respectively. These robots do not move anymore. Instead, all the other 2l - 2 robots will have moved to distinct points of \mathcal{L} , with the chord color. Through the subsequent procedures (Procedure SMALL CIRCLE and Procedure SLICE), the chord robots will uniformly arrange themselves on Γ , in order to cover the unoccupied uniform positions $U_2, \ldots, U_l, U_{l+2}, \ldots, U_{2l}$. An odd block is built *inside* each uniform sector Υ_i . The guards of the block fix the *block chirality*, which is local and is the same as the chirality of the related uniform sector.

Given a uniform sector Υ_i in *Confunisect*, Procedure ODD BLOCK works in three stages.

- Stage 1. Defining the guards of the odd block within Υ_i by adding a padding robot if necessary.
- Stage 2. Moving the robots located between the boundaries of Υ_i and U_1 (resp. U_{2l+1}) to the block chord \mathcal{L} .
- Stage 3. Moving the robots from Γ to the block chord \mathcal{L} .



Figure 6: Odd block formation if q is even.



Figure 7: Stages in Procedure ODD BLOCK.

Let Υ_i be a uniform sector in $Conf_{unisect}$, and let q be the number of robots in Υ_i (except for those on its boundaries). Indeed, all the uniform sectors contain q robots. Let U_1, \ldots, U_q be the uniform positions along the arc of Υ_i , such that the left robot lies on U_1 whereas the right robot lies on U_q . We describe separately below how we perform the movement of robots in each of the five stages. All the robots involved in the following stages belong to Υ_i . Note that some robots use the pre_<color> colors to synchronize themselves in the various uniform sectors before starting to move (as explained at the beginning of Section 6).

Stage 1. If q is even, the split robot closest to U_{q-1} sets its color as pre_blockR and, after the synchronization with all the other pre_blockR in the other uniform sectors, it reaches U_{q-1} where $\angle U_{q-1}OU_q = 2\pi/n$, and it changes its color to blockR. The right robot changes its color to padding. The padding robot will no longer move. The left robot changes its color to blockL. If q is odd, then the robots with color left and right change their colors to blockL and blockR, respectively. In both cases, blockL and blockR robots act as the left and right guards for each odd block. The block chord \mathcal{L} is defined as the chord joining the guards, and the block arc Γ is the arc cut by \mathcal{L} . Then, the split robot closest to the midpoint of Γ elects itself as pre_median and then moves to the midpoint, changing its color to median (see Figure 6).

Stage 2. Let us consider the *l*-odd block built within Υ_i . Let B_i and B_{i+1} be the boundaries of Υ_i , and let U_1 and U_{2l+1} be the boundaries of Γ (i.e. where the guards lay on). All the split robots which lay on Γ change their color to in_chord, otherwise they change into out_chord (i.e. if they lay on $\widehat{B_iU_1}$ and on $\widehat{U_{2l+1}B_{i+1}}$). This stage aims to make all the out_chord robots migrate to \mathcal{L} . If no robot with color out_chord exists in Υ_i , then Stage 3 begins directly. Let M be the middle point of the arc of Υ_i . If the median robot does not lay on M, then the split robot closest to M elects itself as pre_mid and then it moves to M changing its color to mid. Otherwise, the median robot sets its color to mid. Notice that, for $q \geq 12$, M always lies on Γ . Now, we use BDCP to make out_chord robots migrate to \mathcal{L} . Firstly, we set two beacons on \mathcal{L} : one left beacon next to U_1 and one right beacon next to U_{2l+1} . Such two beacons together with the guards on U_1 and U_{2l+1} form the 4 beacons needed to implement BDCP. Let us show how to select the left beacon b (a complement strategy holds for the selection of the right beacon). If there exists an out_chord robot on $\widehat{B_iU_1}$, then the closest out_chord robot to U_1 is elected as b. In this case, bchanges its color to pre_beacon and moves to the intersection of the line segments \overline{DM} and \mathcal{L} , where D was the position of b. Otherwise, b is the farthest robot to U_1 selected from the other out_chord robots on the arc of Υ_i .

In this case, b reaches a position on \mathcal{L} so that it can play the role of the left beacon and it does not create collinearities with the mid robot. Once on \mathcal{L} , b sets its color as **beacon**. An analogous procedure is repeated

to choose the right beacon close to U_{2l+1} . The two beacon robots together with the blockL and blockR robots act as the four beacons for the BDCP procedure (see Figure 7a). By BDCP, each out_chord robot r located at E heads to \mathcal{L} to the point intersecting \overline{EM} and \mathcal{L} . Once r reaches \mathcal{L} , it changes its color to chord. Note that the setting of the mid robot at the midpoint of the arc Υ_i was necessary to make r select the mid robot belonging to Υ_i (in fact, no ambiguity arises since the mid robot of Υ_i is always closer to rthan the other mid robots). Stage 2 ends when no more out_chord robots are located in Υ_i .

Stage 3. In this stage, we apply BDCP to make the in_chord robots migrate from Γ to \mathcal{L} . From now on, the mid robot is no longer necessary, so it changes its color to in_chord if the median exists on the block arc. Otherwise, the mid robot resets its color to median. At the end of Stage 2, there are beacon- and chord-colored robots on \mathcal{L} . Such robots can act as beacons for fixing the chord \mathcal{L} for the in_chord robots. Let r be a in_chord robot located at F on Γ . Let F' be the projection of F on \mathcal{L} , i.e., $\overline{FF'}$ is perpendicular to \mathcal{L} . Let Z be the robot location such that the projection Z' on \mathcal{L} is the closest to F'. If F' is already occupied by a robot, then the revised destination is computed as F'' where $|\overline{F'F''}| = |\overline{F'Z'}|/3$ (see Figure 7b). Once r reaches \mathcal{L} , it changes its color to chord. Note that, if there were no robots colored out_chord in Stage 2, then the closest in_chord colored robots to U_1 and U_{2l+1} move to their projection to act as beacons at the beginning of Stage 3. This ensures that all robots reach \mathcal{L} in O(1) time by implementing BDCP.

See Appendix B.2 for the correctness proofs of Procedure ODD BLOCK.

Lemma 4 (Odd Block). Starting from $Conf_{unisect}$, $Conf_{oddblock}$ is reached in O(1) epochs using O(1) colors under ASYNC, avoiding collisions, guaranteeing robots always operate within $SEC(Conf_{unisect})$. In each odd block, the guards are colored as blockL and blockR, the median robot is colored as median, whereas all the other robots are located on the block chord \mathcal{L} with color chord.

6.3 Procedure SMALL CIRCLE (Transition (6))

Consider an *l*-block in $Conf_{oddblock}$. W.l.o.g., let the block chirality be clockwise. First, the left guard, the median robot, and the right guard change their color to scL, scMedian, and scR, respectively. Let ρ be the line segment connecting U_{l+1} to the projection of U_{l+1} on the block chord \mathcal{L} . We define the *small circle* \mathcal{C} as the circle such that ρ is its diameter (i.e. U_{l+1} lays on \mathcal{C} and \mathcal{L} is its tangent). We say that ρ splits \mathcal{C} into two halves \mathcal{C}_w (left) and \mathcal{C}_e (right). We will refer to ρ as the *median diameter*. See Figure 8.



Figure 8: An odd-block at the beginning of Procedure SMALL CIRCLE, containing the small circle C. All the chord robots (here *black*) lay on \mathcal{L} .

Now, Procedure SMALL CIRCLE proceeds in three stages as described in the following.

- Stage 1 Moving robots to the small circle: Each chord robot moves along the line joining its position and the scMedian robot, until it reaches C.
- Stage 2 Moving all robots to the right half: The robots on C_w migrate to C_e .
- Stage 3 Balancing robots on the small circle: The robots on C_e split into two equal groups, and one of the groups comes back to C_w forming a reflective symmetric configuration on C.

Stage 1. Let r be a chord robot on the block chord \mathcal{L} . It always sees the scMedian robot of its block. Thanks to the presence of the other robots on \mathcal{L} (chord-, scR- or scL-colored), r reconstructs the supporting line of \mathcal{L} , and so ρ and \mathcal{C} . Then, r reaches \mathcal{C} traveling along the trajectory connecting its own position to the scMedian robot (see Figure 9), and it updates its color to smallcircle. Consider the line connecting the left (right, resp.) guard of the block with the median robot such that it splits \mathcal{C}_w (\mathcal{C}_e , resp.) into two arcs. Indeed, all the smallcircle robots on \mathcal{C} lay on the lower arcs of \mathcal{C}_w and \mathcal{C}_e . We call such arcs the *safe arcs* of \mathcal{C} (see Figure 9). When the scR (resp. scL) robot does not see any chord or to_smallcircle (i.e the moving robots towards \mathcal{C} before becoming smallcircle) robots on its half-block, then it sets its color as scR_complete (resp. scL_complete). When a smallcircle robot on \mathcal{C}_e (resp. \mathcal{C}_w) sees the scR_complete (resp. scL_complete) robot on its half-block, it sets its colors as smallcircle_complete. These color updates are needed to synchronize all robots on \mathcal{C} before proceeding with the next stage.

See Lemma 18 in Appendix B.3 for the correctness proof of Stage 1.



Figure 9: Stage 1 of Procedure SMALL CIRCLE: trajectories of chord robots to reach C. The two dashed lines delimit the *safe arcs* on C_e and C_w .

Stage 2. At the beginning of this stage, all the robots on \mathcal{L} have reached the safe arcs of \mathcal{C} . Specifically, we have two groups of smallcircle_complete robots on \mathcal{C}_e and \mathcal{C}_w , possibly with different cardinalities. We assume all the smallcircle_complete robots on \mathcal{C}_e (\mathcal{C}_w , resp.) set their color as smallcircle_east (smallcircle_west, resp.). If the robots on \mathcal{C}_e and \mathcal{C}_w lay in a reflective symmetry, they do nothing else in this stage. Otherwise, let r be a smallcircle_west robot on \mathcal{C}_w . If a smallcircle_east robot lies on \mathcal{C}_e , symmetrical with respect to r, then r moves to another position x on \mathcal{C}_w such that (i) r does not collide with other robots or change its rank in the displacement of robots, (ii) the symmetrical position of x on \mathcal{C}_e is robot-free, and (iii) r does not leave the safe arc of \mathcal{C}_w . When all the smallcircle_west robots have properly shifted their positions (if necessary), then they use BDCP to migrate on their projection on \mathcal{C}_e . After the migration, we assume that all the robots on \mathcal{C}_e (except for the median one) are colored as smallcircle_east. See Lemma 19 in Appendix B.3 for the correctness proof of Stage 2.

Stage 3. The smallcircle_east robots update their color alternating two colors, west and east, so that the closest robot to the median robot is colored as east. After that, each west robot heads to the projection on C_w of its upper-adjacent east robot (see Figure 10). See Lemma 20 in Appendix B.3 for the correctness proof of Stage 3.

Lemma 5 (Small Circle). Starting from $Conf_{oddblock}$, $Conf_{smallcircle}$ is reached in O(1) epochs using O(1) colors in the ASYNC setting, avoiding collisions, guaranteeing robots operate within $SEC(Conf_{oddblock})$. In $Conf_{smallcircle}$, the robots in each odd block (guards and median robot excluded) are arranged on the same small circle C in a mirror-symmetric pattern where the line of symmetry lies on the median diameter ρ .

6.4 Procedure SLICE (Transition $\overline{7}$)

Consider an *l*-block in *Conf_{smallcirle}* (see Figure 11). First, the guards and the median robots turn into sliceL, sliceR and sliceMedian, respectively. Let Q be the center of C. Let e_1, \ldots, e_m (resp., w_1, \ldots, w_m) be the ordered sequences of east (resp., west) robots which lay on C_e (resp., C_w) starting from the closest to the median robot. Note that e_j and w_j lay on symmetric positions in the two half-circles, for each $1 \le j \le m$.



Figure 10: Stage 3 of Procedure SLICE: west robots reach C_e .

We say that the median robot splits Γ into the right arc Γ_e and the left arc Γ_w . Procedure SLICE aims at moving the robots from C to Γ to the vertices of the target regular *n*-gon. Let us present the three main stages that constitute the entire procedure:

- Stage 1 Rank encoding: Each w_i encodes its rank j by reaching a specific position on \mathcal{C}_w .
- Stage 2 Moving towards the right target vertices: Each e_i reaches its uniform position on Γ_e .
- Stage 3 Moving towards the left target vertices: Each w_j reaches its uniform position on Γ_w .



Figure 11: Conf_{smallcirle} at the beginning of Procedure SLICE.

Stage 1. Let us denote with w_0 and w_{m+1} the two endpoints of \mathcal{C}_w (the median robot laying on w_0). Let $\alpha_j = \angle w_j Q w_{j+1}$, for each $0 \le j \le m$. At the beginning of this stage, robot w_1 computes $\delta = \min\{\alpha_j\}_{0 \le j \le m}$, moves to a position w'_1 on \mathcal{C}_w so that $\angle w_0 Q w'_1 = \delta$ setting its color as angle (see Figure 12a). In this way, the angle robot fixes the amplitude of the slices both \mathcal{C}_e and \mathcal{C}_w will be split throughout this procedure. After this setting, each west robot splits \mathcal{C}_w into δ -slices, starting from the point w_0 (see Figure 12b). Let $\eta_0, \ldots, \eta_{\lfloor \frac{\pi}{\delta} \rfloor - 1}$ be the ordered sequence of such δ -slices, starting from the median robot. We ignore the possible remaining slice of amplitude $< \delta$ that can exist between $\eta_{\lfloor \frac{\pi}{\delta} \rfloor - 1}$ and w_{m+1} . Indeed, the arc of each δ -slice contains at most two robots: in the case of exactly two robots, both of them must lay on the endpoints of the slice arc. Let w_j be a west robot and let η_k be the slice it lays on (if w_j lays on the endpoint between two slices, then it chooses the slice with the smaller rank k). Then, w_j moves to a new position w'_j on \mathcal{C}_w such that $\angle w_0 O w'_j = k\delta + \frac{j\delta}{m+1}$. Note this strategy always guarantees w'_j is strictly contained in η_k , thus ensuring these movements never create collisions or collinearities among west robots. See Lemma 21 in Appendix B.4 for the correctness proof of Stage 1.

Stage 2. In this stage, each east robot reaches its uniform position on Γ_e in two steps. Let e_1, \ldots, e_m be the sequence of the east robots and let U_1, \ldots, U_m be the sequence of the uniform positions on Γ_e so that U_j is intended for e_j . In the first step, robots e_1, e_2 and e_3 turn their color as beacon. Afterward, all the other east robots $\{e_j\}_{4 \le j \le m}$ on Γ_e migrate towards ρ . Specifically, each east robot e_j directly heads



Figure 12: Steps of Stage 1 in Procedure SLICE.

to the projection e'_j of its position on C_e along ρ , setting its color as east_diameter. This migration is accomplished to make robots be aligned and so to avoid collisions and collinearities which might not allow a complete parallelism in the second step. Finally, the three beacons e_1, e_2 and e_3 migrate on Γ_w in order to fix Γ and so to help the east_diameter robots to uniformly arrange themselves on the arc Γ_e in the second step. The beacons must safely migrate to some positions that are visible to the robots on ρ . Let u be the intersection point between Γ_w and the line connecting e_1 (the first beacon) with w_1 (the angle robot). Let v be the intersection point between Γ_w and the line connecting e'_m with w_2 . We call \widehat{uv} the safe arc of Γ_w . So, e_1, e_2 and e_3 reach some deterministic and internal points of the safe arc \widehat{uv} (see Figure 13a).

In the second step, all the east_diameter robots on ρ compute and reach their uniform position. Let e be an east_diameter robot on ρ . To compute its uniform position, e needs to recover the arc Γ_e and its rank j. The rank j can be obtained by slicing C_w (resp., C_e) in $\eta_0, \ldots, \eta_{\lfloor \frac{\pi}{\delta} \rfloor - 1}$ (resp., $\eta'_0, \ldots, \eta'_{\lfloor \frac{\pi}{\delta} \rfloor - 1}$). Let η'_k be the slice where e originally laid on (before its migration on ρ). Since e can see all the west robots, it is sufficient for e to compute the rank j of the west robot located on η_k . After having obtained its rank j and the arc Γ_e (thanks to the presence of the beacons fixing Γ), e heads to U_j setting its color as regular (see Figure 13b). Finally, the beacons e_1, e_2, e_3 reach the missing uniform positions U_1, U_2, U_3 . See Lemma 22 in Appendix B.4 for the correctness proof of Stage 2.

Stage 3. In this stage, each west robot reaches its uniform position on Γ_w in two steps. Let w_2, \ldots, w_m be the sequence of the west robots and let U'_2, \ldots, U'_m be the sequence of the uniform positions on Γ_w so that U'_j is intended for w_j . Recall that robot w_1 updated its color to angle in Stage 1. This robot is destined for position U'_1 .

In the first step, the angle robot moves perpendicularly to ρ and reaches its symmetric position on C_e . Then, w_2 reaches a position on C_e to form an angle $\frac{\delta}{m}$ with angle, setting its color as anglem. After this setting, all the west robots migrate from C_w to their projection on ρ in constant time by implementing the BDCP strategy $(w_0, w_3, w_{m-1}, w_m$ as beacons) and change their color in west_diameter.

In the second step, all the west_diameter robots along ρ compute and reach their uniform position. Let w be a west_diameter robot on ρ . It needs Γ_w and its rank to compute its target uniform position. To obtain its rank, w must exploit the slicing technique of C to decode its rank. So, w recomputes C_w and C_e through the presence of the angle and anglem robots, and the line where ρ lies. Then, w splits C_w in δ -slices and determines the slice η_k where it originally laid on. Then, w decodes its rank j inverting the formula $\angle w_0 Ow' = k\delta + \frac{j\delta}{m+1}$, where w' is the projection of w on C_w . Recall that w_0 is the position of the median robot. Note that w can determine m through the presence of the slice R robot and the regular robots on Γ_e), w heads towards U'_j and sets its color as regular. At the end of Procedure SLICE, all the uniform positions of the block are occupied by a robot, and no other robot lays on C (except for the median one). See Lemma 23 in Appendix B.4 for the correctness proof of Stage 3.

Since Procedure SLICE is repeated for each block of Cir, the target *n*-gon is achieved. Eventually, all robots turn into regular.



(b) Step 2: the east_diameter robots reach their uniform positions.

Figure 13: Stage 2, starting with m = 6 east robots.



Figure 14: Stage 3, Step 2: west_diameter robots reach their uniform positions (here m = 6).

Lemma 6 (Slice). Starting from $Conf_{smallcircle}$, $Conf_{regular}$ is reached in O(1) epochs using O(1) colors in the ASYNC setting, avoiding collisions, guaranteeing robots always operate within $SEC(Conf_{smallcircle})$. Each robot is colored *regular*.

6.5 Procedure SEQUENTIAL MATCH (Transition (8))

Let $Conf_{unisect}$ be the output configuration of Procedure SPLIT, where Cir is split into k uniform sectors $\{\Upsilon_i\}_{0 \leq i \leq k-1}$. Procedure SEQUENTIAL MATCH is executed starting from $Conf_{unisect}$ when the number of robots q in each uniform sector Υ_i (except for its boundaries) is less than 12. Remember that, at the end of Procedure SPLIT, each Υ_i contains a left and a right robot at U_1 and U_q , and possibly a regular robot at its boundaries. We assume all the robots that are not left-, right- or regular-colored set their color as unmatched. Now, the closest unmatched robot to the related U_2 of each uniform sector sets its color as pre_matched. After the setting of the pre_matched in each of the k uniform sectors, these robots reach the corresponding uniform position U_2 and set their color as matched. This routine is repeated until each

uniform position U_j for j = 2, ..., q - 1 is covered by a matched robot. Since the number of movements is upper-bounded by a constant, the whole procedure is performed in constant time. Eventually, all the robots change their color to regular, solving UCF.

See Appendix B.5 for the correctness proofs of Procedure SEQUENTIAL MATCH.

Lemma 7 (Sequential Match). Starting from $Conf_{unisect}$, $Conf_{regular}$ is reached in O(1) epochs using O(1) colors in the ASYNC setting, avoiding collisions, guaranteeing all robots perform within $SEC(Conf_{unisect})$. Each robot is colored regular.

7 Putting It All Together

Algorithm 2 summarizes the steps of our UCF algorithm. Starting from an arbitrary initial configuration $Conf_{init}$, robots arrange in $Conf_{convex}$ through the algorithm in [30] which guarantees to avoid collisions and to use O(1) epochs/colors (Transition 1). Moreover, no robot moves out from $SEC(Conf_{init})$ while reaching $SEC(Conf_{convex})$, thus not expanding the initial computational SEC. Afterward, robots achieve $Conf_{circle}$ by reaching the boundaries of $SEC(Conf_{convex})$ in O(1) epochs/colors, without colliding or moving out from $SEC(Conf_{convex})$ (Transition 2). Indeed, $SEC(Conf_{circle}) = SEC(Conf_{convex})$. Lemma 1 summarizes the results of Transitions 1-2.

If $Conf_{circle}$ is a biangular configuration, then robots arrange themselves in a regular *n*-gon through our strategy explained in Section 5 (Transition ③). Lemma 2 shows that this transition occurs without collisions, in O(1) epochs/colors, without expanding the computational SEC. Otherwise, if $Conf_{circle}$ is a periodic configuration, robots perform a sequence of procedures (corresponding to Transitions ④-⑧) to eventually form $Conf_{regular}$. Colors are adopted to synchronize robots and make them identify the exact procedure to be executed. Lemmas 3–7 show that such procedures are performed using O(1) epochs/colors, avoiding collisions and within $SEC(Conf_{circle})$. Combining all these results, we have the following theorem, our contribution.

Theorem 1 (Uniform Circle Formation). Given any $Conf_{init}$ of n robots on distinct points on a plane initially colored off, the robots reposition to $Conf_{regular}$ solving UCF in O(1) epochs using O(1) colors under ASYNC, avoiding collisions, always performing within $SEC(Conf_{init})$.

As a corollary, our UCF algorithm asymptotically optimizes the computational time (number of epochs) and the used light colors, and minimizes the computational SEC.

8 Concluding Remarks

In this paper, we have studied the UNIFORM CIRCLE FORMATION (UCF) problem, which is considered an important special case of the fundamental GEOMETRIC PATTERN FORMATION problem. Specifically, we have investigated UCF under the ASYNC scheduler in the *luminous-opaque* robot model and presented a O(1)-time O(1)-color deterministic algorithm, which is asymptotically optimal in both the fundamental metrics, time and color complexities. Additionally, it minimizes what we have called the *computational SEC*, i.e. the smallest circular area touched by the swarm during the execution of the algorithm. The state-of-the-art solution [27] was optimal in either time complexity or color complexity but not both (Table 1) and the computational SEC was not minimized.

Although our solution optimizes the *color complexity*, we have not focused on minimizing the *exact number* of colors used along the whole algorithm. Indeed, the size of our palette can be significantly reduced by reusing some colors in multiple steps along the algorithm. However, for the sake of clarity, instead of saving on the number of colors, we have used colors with specific, consistent, and meaningful names to help the reader understand their purposes and follow the algorithm steps. Moreover, minimizing the palette size would result in proving that no ambiguities, deadlocks, or wrong computations can ever happen along the algorithm. Trustingly, we leave this investigation for further work.

For other future work, it would be interesting to consider non-rigid movements of robots, so that a robot may not reach the computed destination but stop at some point along the Move trajectory. It would also be interesting to establish whether a O(1)-time solution can be obtained for UCF considering oblivious robots (i.e. without lights) with both rigid and non-rigid movements of robots.

References

- [1] Subhash Bhagat and Krishnendu Mukhopadhyaya. Optimum circle formation by autonomous robots. Advances in Intelligent Systems and Computing, 666:153 – 165, 2018.
- [2] Kaustav Bose, Ranendu Adhikary, Manash Kumar Kundu, and Buddhadeb Sau. Positional encoding by robots with non-rigid movements. In 26th International Colloquium on Structural Information and Communication Complexity, SIROCCO 2019, volume 11639 of Lecture Notes in Computer Science, pages 94–108. Springer, 2019.
- [3] Quentin Bramas, Anissa Lamani, and Sébastien Tixeuil. Stand up indulgent gathering. Theoretical Computer Science, 939:63–77, 2023.
- [4] Ioannis Chatzigiannakis, Michael Markou, and Sotiris E. Nikoletseas. Distributed circle formation for anonymous oblivious robots. In WEA, volume 3059 of Lecture Notes in Computer Science, pages 159– 174. Springer, 2004.
- [5] Jared Ray Coleman, Evangelos Kranakis, Oscar Morales-Ponce, Jaroslav Opatrny, Jorge Urrutia, and Birgit Vogtenhuber. Minimizing the maximum distance traveled to form patterns with systems of mobile robots. In Proceedings of the 32nd Canadian Conference on Computational Geometry, CCCG 2020, August 5-7, 2020, University of Saskatchewan, Saskatoon, Saskatchewan, Canada, pages 73–79, 2020.
- [6] Andreas Cord-Landwehr, Bastian Degener, Matthias Fischer, Martina Hüllmann, Barbara Kempkes, Alexander Klaas, Peter Kling, Sven Kurras, Marcus Märtens, Friedhelm Meyer auf der Heide, Christoph Raupach, Kamil Swierkot, Daniel Warner, Christoph Weddemann, and Daniel Wonisch. A new approach for analyzing convergence algorithms for mobile robots. In *ICALP*, volume 6756 of *Lecture Notes in Computer Science*, pages 650–661. Springer, 2011.
- [7] Shantanu Das, Paola Flocchini, Giuseppe Prencipe, Nicola Santoro, and Masafumi Yamashita. Autonomous mobile robots with lights. *Theor. Comput. Sci.*, 609:171–184, 2016.
- [8] Suparno Datta, Ayan Dutta, Sruti Gan Chaudhuri, and Krishnendu Mukhopadhyaya. Circle formation by asynchronous transparent fat robots. In *Distributed Computing and Internet Technology*, volume 7753, pages 195–207, 02 2013.
- [9] Xavier Défago and Akihiko Konagaya. Circle formation for oblivious anonymous mobile robots with no common sense of orientation. In *POMC*, pages 97–104. ACM, 2002.
- [10] Xavier Défago and Samia Souissi. Non-uniform circle formation algorithm for oblivious mobile robots with convergence toward uniformity. *Theor. Comput. Sci.*, 396(1-3):97–112, 2008.
- [11] Giuseppe Antonio Di Luna, Paola Flocchini, Sruti Gan Chaudhuri, Nicola Santoro, and Giovanni Viglietta. Robots with lights: Overcoming obstructed visibility without colliding. In SSS, pages 150–164, 2014.
- [12] Yoann Dieudonne, Ouiddad Labbani-Igbida, and Franck Petit. Circle formation of weak mobile robots. ACM Transactions on Autonomous and Adaptive Systems, 3, 08 2006.
- [13] Yoann Dieudonné and Franck Petit. Swing words to make circle formation quiescent. In SIROCCO, volume 4474, pages 166–179, 2007.
- [14] Yoann Dieudonné and Franck Petit. Squaring the circle with weak mobile robots. In ISAAC, pages 354–365, 2008.
- [15] Caterina Feletti, Carlo Mereghetti, and Beatrice Palano. Uniform Circle Formation for Swarms of Opaque Robots with Lights. In SSS, pages 317–332, 2018.
- [16] Caterina Feletti, Carlo Mereghetti, and Beatrice Palano. O(log{n})-time uniform circle formation for asynchronous opaque luminous robots. In OPODIS, pages 5:1–5:21, 2023.

- [17] Caterina Feletti, Carlo Mereghetti, and Beatrice Palano. Uniform Circle Formation for Fully, Semi-, and Asynchronous Opaque Robots with Lights. *Applied Sciences*, 13(13):7991, January 2023.
- [18] Caterina Feletti, Carlo Mereghetti, Beatrice Palano, and Priscilla Raucci. Uniform circle formation for fully semi-, and asynchronous opaque robots with lights. In *ICTCS*, pages 207–221, 2022.
- [19] Paola Flocchini, Giuseppe Prencipe, and Nicola Santoro. Distributed computing by oblivious mobile robots. Synthesis Lectures on Distributed Computing Theory, 3(2):1–185, 2012.
- [20] Paola Flocchini, Giuseppe Prencipe, and Nicola Santoro, editors. Distributed Computing by Mobile Entities, Current Research in Moving and Computing, volume 11340 of Lecture Notes in Computer Science. Springer, 2019.
- [21] Paola Flocchini, Giuseppe Prencipe, Nicola Santoro, and Giovanni Viglietta. Distributed computing by mobile robots: uniform circle formation. *Distributed Comput.*, 30(6):413–457, 2017.
- [22] Branislav Katreniak. Biangular circle formation by asynchronous mobile robots. In SIROCCO, pages 185–199, 2005.
- [23] Giuseppe Antonio Di Luna, Paola Flocchini, Nicola Santoro, Giovanni Viglietta, and Masafumi Yamashita. Meeting in a polygon by anonymous oblivious robots. *Distributed Comput.*, 33(5):445–469, 2020.
- [24] Marcello Mamino and Giovanni Viglietta. Square formation by asynchronous oblivious robots. In CCCG, pages 1–6. Simon Fraser University, Vancouver, British Columbia, Canada, 2016.
- [25] Moumita Mondal and Sruti Gan Chaudhuri. Uniform circle formation by mobile robots. In ICDCN, pages 20:1–20:2. ACM, 2018.
- [26] Moumita Mondal and Sruti Gan Chaudhuri. Uniform circle formation by fat robots under non-uniform visibility ranges. In *ICDCN*, pages 58:1–58:5. ACM, 2020.
- [27] Debasish Pattanayak and Gokarna Sharma. Time-color tradeoff on uniform circle formation by asynchronous robots. In *IPDPS*, pages 1–11, 2024.
- [28] David Peleg. Distributed coordination algorithms for mobile robot swarms: New directions and challenges. In *IWDC*, pages 1–12, 2005.
- [29] Giuseppe Prencipe. Autonomous mobile robots: A distributed computing perspective. In ALGOSEN-SORS, pages 6–21, 2013.
- [30] Gokarna Sharma, Ramachandran Vaidyanathan, and Jerry L. Trahan. Constant-time complete visibility for asynchronous robots with lights. In SSS, volume 10616 of Lecture Notes in Computer Science, pages 265–281. Springer, 2017.
- [31] Ichiro Suzuki and Masafumi Yamashita. Distributed anonymous mobile robots: Formation of geometric patterns. SIAM J. Comput., 28(4):1347–1363, 1999.
- [32] Ramachandran Vaidyanathan, Gokarna Sharma, and Jerry L. Trahan. On fast pattern formation by autonomous robots. *Inf. Comput.*, 285(Part):104699, 2022.
- [33] Giovanni Viglietta. Uniform circle formation. Chapter 5 of [20], pages 83–108, 2019.

A Pseudo-code

Algorithm 2: UCF pseudocode

1 Complete Visibility
Input: Conf _{init} with n robots in distinct positions on \mathbb{R}^2
2 Use [30] to arrange robots into a convex pattern;
_ Output: Conf _{convex}
3 CIRCLE FORMATION
$\begin{array}{c} \text{Input: } Conj_{convex} \\ Circle & SEC(Conflex) \\ \end{array}$
4 $Cir \leftarrow SEC(Conf_{convex}),$ Make all robots more to Cir radially:
Output: Conf. :!.
Input: Configure
if Conficience is Confraendar then
Final Result: Conf _{regular}
s else if Conf _{circle} is Conf _{bingular} then
9 Robots slide along the edges of the exogenous polygon EP [Section 5];
Final Result: Conf _{regular}
10 else
11 Confercle IS Confperiodic;
12 Procedure Split [Section 0.1]
13 Split Cir into k uniform sectors $\Upsilon_0, \ldots, \Upsilon_{k-1}$:
14 Set the chirality of each Υ_i through the left and right robots;
Output: Conf _{unisect}
15 $q \leftarrow$ number of robots in each Υ_i ;
16 if $q \ge 12$ then
17 Procedure ODD BLOCK [Section 6.2]
Input: $Conf_{unisect}$
18 In each T_i form an odd-block with the <i>left</i> and <i>right</i> guards;
19 Use BDOP to make robots on 1_i migrate on the block chord \mathcal{L} ;
20 Procedure SMALL CIRCLE [Section 6.3]
In each odd-block, spot the inscribed small circle C :
Robots migrate from \mathcal{L} to \mathcal{C} :
Robots on \mathcal{C} equally distribute on the two halves \mathcal{C}_e and \mathcal{C}_w ;
Output: Conf _{smallcircle}
24 Procedure SLICE [Section 6.4]
Input: $Conf_{small circle}$
25 Robots on \mathcal{C}_w encode their rank;
Robots on C_e and C_w reach their target uniform positions;
Final Result: Conf _{regular}
27 else
28 Procedure SEQUENTIAL MATCH [Section 6.5]
Input: $Conf_{unisect}$
29 Robots in each 1 _i reach their target uniform position using a sequential scheme Final Result : Conf

B Correctness Proofs

B.1 Procedure Split

We show here all the correctness proofs for Procedure SPLIT (Section 6.1).

Lemma 8 ([17]). Let us consider a configuration where all n robots lay on the same circle Cir.

- For odd n, there exists a diameter passing through a robot and dividing Cir into two half-circles, each having $\frac{n-1}{2}$ robots.
- For even n, there exists a diameter dividing Cir into two halves such that (i) either the diameter passes

through just one robot and the half-circles have $\frac{n}{2}$ and $\frac{n}{2} - 1$ robots, or (ii) the diameter passes through two antipodal robots and the half-circles have $\frac{n}{2} - 1$ robots each.

Proof. Let A, B be two distinct points on Cir, and let D_A, D_B be the respective antipodal points on Cir. We define the overlap arcs of A and B as the two equal-length arcs AD_B and BD_A . Note that overlap arcs are null iff A, B are antipodal. Let us assume n is odd, and reason by induction on n. For n = 1, the property follows straightforwardly. Now, assume the property true for an odd n > 1, and let us prove the property for n + 2. Let us remove two robots, say r_1 and r_2 , having minimal overlap arcs θ and θ' , so that n robots are left on Cir. So, by the induction hypothesis, there exists a diameter d passing through a robot and dividing Cir into two halves, each having $\frac{n-1}{2}$ robots. Notice that the only way for d to leave r_1 and r_2 in the same half-Cir is to pass through the overlap arcs θ and θ' . Yet, since θ and θ' are minimal, no other robot can sit on these overlap arcs (except for r_1 and r_2). So, since d passes through a robot, it clearly cannot leave r_1 and r_2 on the same half-Cir. Thus, the result follows. For even n, the proof is similar.

Lemma 9. If $|\Phi| = 1$, then the configuration is either asymmetric or mirror-symmetric with just one symmetry axis.

Proof. If $|\Phi| = 1$, the smallest angular sequence $\hat{\mu}$ starts from a unique robot, say r. There can exist just two cases: either $\hat{\mu}$ can be read just in one orientation (e.g. the clockwise one) or $\hat{\mu}$ can be read in both the orientations. In the first case, the configuration is asymmetric. In the second case, r lies on a mirror-symmetry axis. Since $|\Phi| = 1$, no other axes exist in the configuration.

Lemma 10. If $|\Phi| = 1$, then we can split Cir into two uniform sectors Υ_0, Υ_1 .

Proof. By Lemma 9, the configuration is asymmetric or mirror-symmetric with just one symmetry axis. In the first case, we can use Lemma 8 to elect the leader robot and the diameter splitting the *Cir* into two uniform sectors Υ_0, Υ_1 . Indeed, such *Cir*-halves are asymmetric and so chiral. In the second case, the axis of symmetry splits *Cir* into two mirrored halves Υ_0, Υ_1 . Since there is just one axis of symmetry, the two halves are asymmetric, thus guaranteeing the two sectors are chiral.

Lemma 11. In Conf_{biperiodic}, leader robots (i.e. the robots from Φ) do not lay on the axes of symmetry.

Proof. By contradiction, let r be a **leader** robot lying on an axis of symmetry of the configuration. Since r belongs to Φ , the minimal angular sequence $\hat{\mu}$ starts from r, in both directions (being r on a mirror-symmetry axis). Let $\hat{\mu} = \mu_0 \mu_1 \mu_2 \ldots$, and let r' be the left (w.l.o.g.) adjacent robot to r, so that from r' starts the angular sequence $\dot{\mu} = \mu_0 \mu_0 \mu_1 \ldots$ in the clockwise direction. Let μ_i be the first angle in $\hat{\mu}$ which is different from μ_0 (since the configuration is not regular, such an angle always exists). So we can conclude that $\dot{\mu} = \mu_0 \mu_0 \ldots \mu_i \ldots$ is lexicographically smaller than $\hat{\mu} = \mu_0 \ldots \mu_i \ldots$, and so r does not belong to Φ . Contradiction.

Observation 2. Consider a circle configuration where the robots lay on the same circle Cir. If a robot r on position X has to reach a new position Y on Cir traveling along the chord \overline{XY} , then r can create a collinearity \overline{arb} with just two robots a, b at a given time during its movement. Indeed, a and b must lay on the two distinct arcs cut by the chord \overline{XY} , each on a different arc.

Lemma 12. In the case of a biperiodic configuration, a pre_left (pre_right, resp.) robot can always recover its destination point even if other to_left (to_right, resp.) robots are moving and hiding leader robots.

Proof. Let r be a **pre_left** robot on the uniform sector Υ_i , activated during the movement of a **to_left** robot (see Figure 15). Since no robot moves in Υ_i , r can see at least a **leader** and a **pre_right** robot. If the uniform sectors are also defined by **regular** robots (Figure 5d), then r can see all of them (in fact, no robot moves out from its original uniform sector, and so no robot hides **regular** robots from r). Thus, in presence of **regular** robots, r can determine the boundaries of the uniform sectors (i.e. the points where **regular** robots lay on and the middle points on Cir between any pair of consecutive **regular** robots) and the cardinality n of the swarm by multiplying the number of robots inside its sector Υ_i with the number of uniform sectors (note that r has complete visibility of Υ_i since no robot is moving within it).



(a) pre_left (here *light cyan*) and pre_right (here *light lime*) robots have to reach the uniform positions and thus to fix the uniform sectors.



(b) left (*cyan*) and right (*lime*) robots fix the uniform sectors.

Figure 15: Procedure SPLIT in a biperiodic configuration with $|\Phi| = 4$ uniform sectors to be fixed. The moving to_left robot hides the leader (here *lightgray*) robot from r. However, r can compute its target point even in the case of collinearities, thus fixing the uniform sectors in constant time.

If r cannot see any regular robots, then the configuration originally was biperiodic and no robots lay on the boundaries of the uniform sectors (Figure 5c). In this case, r can spot the pre_right and the leader robot belonging to Υ_i by simply selecting the closest pre_right and the closest leader robot to r (note that pre_right and leader robots lay on symmetrical positions in adjacent sectors). Following the leaderpre_right orientation of Υ_i , let us consider the adjacent uniform sector, say Υ_{i+1} . Let g be the closest leader or pre_right robot which r sees following this direction. Of course, g must belong to Υ_{i+1} . In fact, since within Υ_{i+1} at most one robot is moving, at least one {leader, pre_right}-colored robot cannot be hidden from r (by Observation 2). If g is pre_right, then r can determine the boundary between Υ_i and Υ_{i+1} as the middle point on Cir between g and the position of the pre_right robot belonging to Υ_i . Otherwise, it means that the pre_right robot of Υ_{i+1} is hidden by a moving robot which is visible to r. Thus, r can compute the exact position of the hidden pre_right robot and so determine the boundary between Υ_i and Υ_{i+1} . The same strategy is applied searching the leader robot in Υ_{i-1} . Being the uniform sectors equal in amplitude and number of robots, r can easily reconstruct the boundaries of all the other sectors and so the number of robots in the swarm.

The proof for the pre_right robots is similar.

B.2 Procedure ODD BLOCK

We show here all the correctness proofs for Procedure ODD BLOCK (Section 6.2).

Lemma 13. Consider a configuration $Conf_{unisect}$ with k uniform sectors. Let r be a **pre_x** robot (being $x \in \{mid, median, blockR\}$) lying on the arc of a sector Υ_i . Within Υ_i , no robot is moving. Then, r can always determine the boundaries of all the uniform sectors and the cardinality of the swarm n even if at most one robot to_x is moving within any other sector $\Upsilon_{j\neq i}$ to reach a new position on Cir.

Proof. The proof is similar to that of Lemma 12. Since no robot moves in Υ_i , r can see at least a left and a right robot. If $Conf_{unisect}$ is also defined by regular robots, then r can see all of them (in fact, no robot moves out from its original uniform sector, and so hides regular robots from r). According to the number of regular robots and the number of {left, right}-colored robots between two regular robots, r can determine if the configuration originally was uniperiodic (Figure 5b) or biperiodic (Figures 5a, 5c and 5d). If there are regular robots, r can determine n by the central angle $2\pi/n$ between the regular and the related left or right robot, and the positions of all the uniform sectors.

If r cannot see any regular robots, then the configuration originally was biperiodic and no robots lay on the boundaries of the uniform sectors (Figure 5d). In this case, r can spot the pair of left-right robots belonging to Υ_i . In fact, r selects the closest left-right pair which cuts a sector where no robot is moving. Following the left-right orientation of Υ_i , let us consider the adjacent uniform sector Υ_{i+1} , which is located on the right w.r.t. Υ_i . Let g be the closest left or right robot which r sees following the right direction. Of course, g must belong to Υ_{i+1} . In fact, since within Υ_{i+1} at most one to_x robot is moving, at least one {left, right}-colored robot cannot be hidden from r (by Observation 2). If g is right, then r can determine the boundary between Υ_i and Υ_{i+1} as the middle point on Cir between g and the position of the right robot belonging to Υ_i . Otherwise, it means that the right robot of Υ_{i+1} is hidden by a moving robot which is visible to r. Thus, r can compute the exact position of the hidden right robot and so determine the boundary between Υ_i and Υ_{i+1} . The same strategy is applied searching the left robot in Υ_{i-1} . Being the uniform sectors equal in amplitude and number of robots, r can easily reconstruct the boundaries of all the other sectors and so the number of robots in the swarm.

Corollary 1. In Procedure ODD BLOCK the setting of the block R, median, and mid takes O(1) epochs.

Proof. By Lemma 13, we know that each pre_x robot r (being $x \in \{\text{mid}, \text{median}, \text{blockR}\}$) computes its target position (where it will assume the color x once stopped there and reactivated) even if other to_x robots are moving to reach their target positions in the other uniform sectors. It follows that the time taken for setting the x robots is independent of the number of uniform sectors.

Lemma 14. Given an odd block built inside a uniform sector Υ_i , the midpoint M of the arc of Υ_i lies on the block arc Γ .

Proof. Let U_1 and U_{2l+1} be the uniform positions where the guards of the block lay on (i.e. they are the endpoints of Γ), and let B_i and B_{i+1} be the boundaries of Υ_i . To prove the statement, we need to prove that $\angle U_1 O U_{2l+1} \ge \frac{\angle B_i O B_{i+1}}{2}$ (where O is the center of Cir), i.e. the amplitude of the odd block is always not smaller than the amplitude of half Υ_i . By construction we know that $\angle B_i O U_1 \le \frac{2\pi}{n}$ (for the left guard), while $\angle U_{2l+1} O B_{i+1} \le \frac{2\pi}{n} + \frac{2\pi}{n}$ (for the right guard and for the padding robot). Thus, $\angle U_1 O U_{2l+1} \ge \angle B_i O B_{i+1} - \frac{6\pi}{n}$. To prove that $\angle U_1 O U_{2l+1} \ge \frac{\angle B_i O B_{i+1}}{2}$, it is sufficient to verify that

$$\angle B_i O B_{i+1} - \frac{6\pi}{n} \stackrel{?}{\ge} \frac{\angle B_i O B_{i+1}}{2}$$
$$\angle B_i O B_{i+1} \stackrel{?}{\ge} \frac{12\pi}{n} = 6 \cdot \frac{2\pi}{n}.$$

Since each Υ contains $q \ge 12$ robots (laying not on its boundaries), we know that $\angle B_i OB_{i+1} \ge 12 \cdot \frac{2\pi}{n}$, thus proving our statement.

Observation 3. Two chords of the same circle can (i) have no points in common, (ii) intersect in only one point, or (iii) be coincident.

Lemma 15. During Stage 2 of Procedure ODD BLOCK, all the out_chord robots can reach \mathcal{L} in O(1) epochs using BDCP.

Proof. We verify that all the input assumptions listed in Algorithm 1 hold to correctly implement BDCP in O(1) time.

- 1. \mathcal{L} is the target 2-curve;
- 2. 4 beacons are originally set to fix \mathcal{L} (the guards and the two *ad hoc* beacons);
- 3. the out_chord robots are the waiting robots which have to reach \mathcal{L} , so that
 - (a) they lay on the arcs $\widehat{B_iU_1}$ and $\widehat{U_{2l+1}B_{i+1}}$ (except for their endpoints), so they are external to \mathcal{L} , belonging to the same half-plane delimited by \mathcal{L} ;
 - (b) at the beginning of Stage 2, no robot is moving in Υ_i , and all robots of the uniform sector lay on the arc of Υ_i or on \mathcal{L} . So, any out_chord robot can see the 4 original beacons on \mathcal{L} .
 - (c) they have to reach \mathcal{L}

- by construction, the two internal beacons lay on \mathcal{L} so that the target points of each out_chord robots are located between them;
- each out_chord r robot must reach \mathcal{L} traveling along the trajectory \overline{rM} where M is the position of the mid robot. Of course, the trajectories do not intersect each other;
- such trajectories intersect \mathcal{L} in just one point (see Observation 3);
- by construction, the beacons have been placed on \mathcal{L} so that they do not create collinearities with the mid robot and the out_chord robots. This guarantees that any out_chord robot can see the mid robot at the beginning of Stage 2. Moreover, throughout the whole execution of BDCP, out_chord robots travel along distinct concurrent trajectories that are generated by the origin (the mid robot), they never create collinearities with the mid robot. As follows, any out_chord robot can reconstruct its path towards \mathcal{L} . For the same reason, the moving robots never collide since each out_chord trajectory does not intersect with any other trajectory.
- (d) each out_chord robot sets its color as chord once on \mathcal{L} , playing the role of a new beacon fixing the chord \mathcal{L} .

All these assumptions guarantee all out_chord robots reach \mathcal{L} in $O(\log 2) = O(1)$ epochs without colliding.

Lemma 16. During Phase 3 of Procedure ODD BLOCK, all the *in_chord* robots can reach \mathcal{L} in O(1) epochs using BDCP.

Proof. The proof is similar to the proof of Lemma 15, so we report just the differences. The presence of the original 4 beacons, plus the chord robots, fix the target curve \mathcal{L} . If no such beacons exist, then the robots closest to U_1 and U_{2l+1} move to the \mathcal{L} to act as beacons. By construction, the beacons have been set in order to be on the left and on the right of the target positions of the in_chord robots on \mathcal{L} . Let r be a in_chord which sees at least 2 robots on \mathcal{L} , and let F' be its projection on \mathcal{L} . Let Z be the position of the closest in_chord robot (still on Γ or in transit towards \mathcal{L}) and let Z' be its projection on \mathcal{L} . Then r always can compute its target position F'' on \mathcal{L} and so its path towards \mathcal{L} (F'' = F' if no robot lies on F', otherwise $|\overline{F'F''}| = |\overline{F'Z'}|/3$). According to this rule, two adjacent in_chord robots will always compute two paths without colliding. The other assumptions hold for the same reasons as in Lemma 15.

B.3 Procedure SMALL CIRCLE

We show here all the correctness proofs for each step in Procedure SMALL CIRCLE (Section 6.3).

Lemma 17. When all the robots have migrated from \mathcal{L} to \mathcal{C} , then they can always see the right guard (if they lay on \mathcal{C}_e) or the left guard (if they lay on \mathcal{C}_w).

Proof. Let l be the line passing through the median robot and the right guard. This line splits C_e into two arcs: the upper one (which we call the unsafe arc) and the lower one (which we call the safe arc). According to Stage 1 of Procedure SMALL CIRCLE, all the robots on C_e are located in the safe arc cut by line l (see Figure 11). Let l' be any other line passing through the right guard and a point of C_e (different from the median robot). If l' intersects the unsafe arc, then it intersects it into two points. Otherwise, l' intersects the safe arc into only one point. This means that no robot on C_e creates collinearity with another robot on C_e and the right guard. The same holds considering the left guard and C_w .

Lemma 18. During Stage 1 of Procedure SMALL CIRCLE, the following statements hold:

- 1. each chord robot on \mathcal{L} can see the scMedian robot even when other robots are moving to \mathcal{C} . Moreover, the movements at Stage 1 are collision-less.
- 2. If the right guard (resp. left guard) sets its color as scR_complete (resp. scL_complete), no chord or to_smallcircle robot exists in the right (resp. left) half-block.

- 1. At the beginning of Stage 1, all the robots (except for the scMedian one) are located on the block chord \mathcal{L} (and not inside the block), so no robot obstructs the visibility of the chord robot. Moreover, since the chord robots travel along distinct concurrent trajectories that are generated by the origin (the scMedian robot), they never create collinearities with the scMedian robot. For the same reason, the moving robots never collide.
- 2. Let us prove for C_e (the same holds for C_w). By Lemma 17, robots on C_e do not create collinearities with the right guard. Moreover, a to_smallcircle robot cannot be hidden by other robots on C_e from the right guard. So, if a to_smallcircle robot exists, the right guard can see it. At the same time, if at least a chord robot exists on \mathcal{L} , then the right guard can see.

Lemma 19. During Stage 2 of Procedure SMALL CIRCLE, the following statements hold:

- 1. Each smallcircle_complete robot on C can correctly detect if it belongs on C_e or C_w and so set its color as smallcircle_east or smallcircle_west, respectively.
- 2. The position shift of the smallcircle_west robots can be executed without colliding and in O(1) time.
- 3. The smallcircle_west robots migrate from C_w to C_e in O(1) using BDCP.

- 1. By Lemma 17, all the smallcircle_complete robots on C_e (resp. C_w) see the related guard. Thus, they can detect if they belong to the right/left side of C, and update their color properly.
- 2. The new positions of smallcircle_west robots can be easily computed so that each robot shifts on \mathcal{C}_w of a little distance downward so that it neither collides with nor goes beyond the adjacent robot. Such movements always guarantee complete visibility among the robots within \mathcal{C} . Note that a smallcircle_west robot can always recompute correctly \mathcal{C} even when the other robots are shifting; in fact, there are always at least three robots still on \mathcal{C} : the robot itself, the median robot, and at least one smallcircle_east robot on \mathcal{C}_e (otherwise, no shift is needed).
- 3. We verify that all the input assumptions listed in Algorithm 1 hold to correctly implement BDCP in O(1) time.
 - (a) C_e is the target 3-curve;
 - (b) 6 robots (selected among the smallcircle_east or smallcircle_west robots) can be set on C_e so that they play the role of the left and right beacons (using a proper color). This setting can be achieved in constant time;
 - (c) the smallcircle_west robots are the waiting robots which have to reach C_e . We can guarantee that:
 - i. being on \mathcal{C}_w , they are external to \mathcal{C}_e , and they lay on the convex region delimited by \mathcal{C}_e ;
 - ii. at the beginning of this step, no robot is moving within C, so the waiting robot on C_w can see all the robots on C_e ;
 - iii. they have to reach C_e
 - to their projections on C_e . Being the beacons originally the "leftmost" and the "rightmost" robots on C_e , the robots on C_w will migrate between the two groups of beacons;
 - being parallel, the robots' trajectories do not intersect each other;
 - such trajectories are chords connecting C_w to C_e , thus they intersect C_e in just one point;
 - if a smallcircle_west robot on C_w can reconstruct C, then it can reconstruct its trajectory (looking at the left guard, a smallcircle_west robot can detect the position of ρ and so its trajectory towards C_e);
 - iv. each smallcircle_west robot becomes a new beacon (setting its color as smallcircle_east) once on C_e .

All these assumptions guarantee all smallcircle_west robots reach C_e in $O(\log 3) = O(1)$ epochs without colliding.

Lemma 20. During Stage 3 of Procedure SMALL CIRCLE, the following statements hold:

- 1. Each west robot on C_e correctly detects its upper-adjacent east robot, even if other robots are moving.
- 2. Each west robot on C_e correctly and safely reaches its target position on C_w .

Proof. We prove each statement:

- 1. Let w be a west robot on C_e . Thanks to the presence of the right guard (always visible to w), w understands it has to migrate on the other side. Moreover, w can always see its two adjacent east robots even when other robots are migrating to C_w (the first robot on C_e has an east robot and the median robot as adjacent). So w recomputes C. Now, let us suppose the median robot is hidden from w. Thus, w must detect which of its two east adjacent robots is the upper-adjacent one. From the right guard, two chords can be elected as \mathcal{L} . However, by the presence of other robots of other blocks, w can always detect which is the correct block chord, and so it can establish the upper-down orientation of the block.
- 2. Again, let w be a west robot on C_e . As proved above, w computes C by the presence of at least three robots on it, and ρ by the presence of the right guard. Once obtained C_w and once selected its upper-adjacent robot u, w heads to the projection of u on C_w . All the trajectories are disjoint and so no collision can occur.

B.4 Procedure SLICE

We show here all the correctness proofs for each step in Procedure SLICE (Section 6.4).

Lemma 21. During Stage 1 of Procedure SLICE, the following statements hold:

- 1. At the beginning of Stage 1, each slice arc on C_w contains at most two robots: in the case of exactly two robots, both of them must lay on the endpoints of the slice arc;
- 2. Each slice is chosen by at most one west robot where it will encode its rank;
- 3. During the movements in Stage 1, each west robot w_j will move to a new point w'_j which is strictly contained in its original slice;
- 4. At the end of Stage 1, each slice arc of C_w contains at most one robot, except for the slice η_0 which contains two robots (the *sliceMedian* robot and the *angle* one) on its endpoints.
- 5. Movements at Stage 1 never create collisions or collinearities among robots on C.

- 1. By construction, each slice has an amplitude of δ , where δ is the minimum angle between any two robots on the circle C_w . Let η be a δ -slice of C_w . If three robots lay on the arc of η , then they define a smaller angle than δ (contradiction). The same contradiction results in the case of two robots where one of them does not lay on the endpoint of the η arc. Note that the remaining slice of amplitude $< \delta$ which can exist between the last δ -slice and the lower endpoint of C_w does not contain any robot (otherwise δ would not be the minimum angle).
- 2. If a slice does not contain any robots, then it will be chosen by no robots. If a slice contains just one west robot, then it will choose its slice to encode its rank. If a slice η_k contain two west robots, say w_j, w_{j+1} , one per each arc endpoint, then w_j chooses η_{k-1} whereas w_{j+1} chooses η_k . Since η_{k-1} contains either just w_j or both w_{j-1} and w_j (by Item 1), η_{k-1} will be chosen just by w_j (in fact, if w_{j-1} is not angle, then it will choose η_{k-2}).

- 3. Let η_k be the chosen slice for the rank encoding of w_j (i.e. the slice where w_j lays on, possibly on one of its endpoints). Since w_j reaches a new point w'_j such that $\angle w_0 Ow'_j = k\delta + \frac{j\delta}{m+1}$, it is sufficient to prove that w'_j belongs to η_k (endpoints excluded). Such a property is easily proved since $\frac{j\delta}{m+1} < \delta$ (in fact, j < m+1) and since $j \neq 0$ (west robots have rank j = 2, ..., m).
- 4. By Item 1, each west robot travels in a new position which is strictly contained in its chosen slice. By Item 2, each slice is chosen by at most one robot. These two results ensure each slice arc of C_w contains at most one robot. To conclude, η_0 is the only slice in C_w containing two robots at the end of Stage 1.
- 5. Movements of west robots are performed in separated slices, thus never creating collisions with the other robots. Let w_j be a west robot which has to travel in the slice η_k to reach the point w'_j . This robot creates collinearity with another robot on C only if both the arcs cut by the trajectory $\overline{w_j w'_j}$ contain at least a robot. However, since in the minor arc $\widehat{w_j w'_j}$ (i.e. the arc strictly contained in η_k) no robots are contained except for w_j itself, no collinearities can occur.

Lemma 22. During Stage 2, the following statements hold:

- 1. [Step 1] The migration of the east robots $\{e_j\}_{4 \le j \le m}$ on ρ is always possible in one epoch without collisions.
- 2. [Step 1] The beacons e_1, e_2 and e_3 correctly and safely migrate on the safe arc \widehat{uv} .
- 3. [Step 2] An east_diameter robot on ρ can recompute the slices on C_e and C_w .
- 4. [Step 2] The rank j computed by an east_diameter robot on ρ coincides with its original rank on C_e , for $2 \le j \le m$.
- 5. [Step 2] Every east_diameter robot on ρ can see the three beacons.
- 6. [Step 2] An east_diameter robot e on ρ can instantly recompute its uniform position U_i on Γ_e .
- 7. [Step 2] Beacons e_1, e_2 and e_3 on Γ_w safely reach their target positions on Γ_e in constant time.

- 1. Let e be an east robot on C_e at the beginning of Stage 2 (after the setting of the beacons on C_e). At most m 4 to_east_diameter robots are moving to ρ , thus possibly obstructing the visibility of e. However, since each moving robot can hide only one other robot on C from e, and since there are at least m + 5 robots on C (included e), then e can always reconstruct C. By Lemma 17, e can see sliceR and so it can recompute the supporting line of *chord*, and so ρ . Thus, e directly travels perpendicularly towards ρ , without waiting. Since all the trajectories are perpendicular to the same line, the migration of the east robots is accomplished without colliding.
- 2. Let b be a beacon robot on C_e which sees all the east_diameter robots on ρ . Thanks to the presence of the west robots, e can recompute C, and so it can establish whether a beacon is still moving or if the configuration is static. For the sake of simplicity, we make our beacons reach Γ_w following a sequential scheme: thus, firstly e_3 reaches a deterministic point on \widehat{uv} , while e_1 is the last beacon to move. As soon as b sees a static configuration (within its block) and understands it is its turn, it can easily compute the safe arc \widehat{uv} and move to a deterministic position on \widehat{uv} , thus avoiding collisions with the other robots. Since the number of beacons for a block is constant, their migration takes O(1)time.
- 3. Since at Stage 2 no robot moves within the west half-circle given by C_w , an east_diameter robot e on ρ can always see all the west robots and the angle one, thus allowing it to determine C and the angle δ . Moreover, e can easily recompute ρ by the presence of the adjacent east_diameter or sliceMedian robot. So, e can split C_w and C_e in δ -slices and determine the slice η'_k and η_k which contain its projection on C.

- 4. Thanks to Lemma 21, each west robot w_j (except for w_1 which became the angle robot) has moved in its own original slice during Stage 1, thus maintaining the one-to-one rank association with the east side.
- 5. See Figure 13a. The beacons lay on the safe arc \widehat{uv} , which was defined by the two lines: the first one which connects the initial position of e_1 and w_1 (the **angle** robot), and the second one which connects the position of e_m and w_2 . Let ρ' be the segment of ρ cut by such lines. By construction, all the **east_diameter** lay on ρ' (e_m lay on its lower endpoint). Let x be an internal point of the safe arc \widehat{uv} and let y be a point of ρ' . Then, the line connecting x with y crosses the arc $\widehat{w_1w_2}$ (endpoints excluded). Since no robot lays within the arc $\widehat{w_1w_2}$, any robot on \widehat{uv} can see any robot on ρ' .
- 6. The robot e can always recompute its rank j (according to the previous Items), the circle C, and the diameter ρ . Thanks to Item 5, e can see the three beacons on \widehat{uv} and so it can reconstruct Γ_e . Since e has complete visibility of C_w , it counts the m west robots and so it can define the positions of all the uniform positions on Γ_e . Thus, it computes its target position U_j .
- 7. See Figure 13b. Let b ∈ {e₁, e₂, e₃} be a beacon robot on Γ_w that sees no east_diameter robots or moving robots within the block. Note that, in this situation, b has complete visibility of Γ_e except for at most one robot which can be hidden by the angle robot. So, following a sequential scheme (b = e₃, e₂, e₁), b recomputes Γ_e, and the angle of each uniform arc U_jU_{j+1} and so its target position. Thus, b reaches its target uniform position and sets its color as regular. In particular, if angle lays on the trajectory between b and its target position U_j, then b reaches U_j in two moves: firstly, it stops in a position on ρ which is visible to the other beacon on Γ_w, secondly, it reaches U_j. Note that at most one beacon has to split its trajectories into two steps (in fact, angle can be collinear with just one e_j and the related U_j). So, this task is accomplished in constant time.

Lemma 23. During Stage 3, the following statements hold:

- 1. [Step 1] Robots w_1 and w_2 can safely and correctly travel to C_e fixing the angle δ and the cardinality m.
- 2. [Step 1] If a west robot on C_w sees a west_diameter or a sliceMedian robot, then it is always able to determine whether such robots belong to its block or not.
- 3. [Step 1] The west robots w_3, w_{m-1}, w_m migrate to ρ in constant time in order to play the role of the beacons (together with w_0 , the median robot) for the other west robots;
- 4. [Step 2] A west_diameter robot w on ρ can correctly and instantly compute C_e and C_w and its original slice η_k . So, it correctly decodes its rank j.
- 5. [Step 2] A west-diameter robot w on ρ can correctly spot Γ_w and its target uniform position U'_i .
- 6. [Step 2] The angle and anglem robots reach U'_1 and U'_2 without colliding.

- 1. The angle robot (w_1) can detect Stage 2 has ended since it can see all the uniform positions on Γ_e are covered by regular robots. So, it can safely migrate on its projection on \mathcal{C}_e , maintaining the angle δ . Once w_1 has switched half-circle, w_2 enjoys complete visibility of all the m + 1 robots on \mathcal{C} and so it can correctly migrate on \mathcal{C}_w to fix the angle $\frac{\delta}{m}$.
- 2. Let us suppose that a west robot w on C_w sees some robots (west_diameter or sliceMedian) of another median diameter ρ' , and it cannot see the robots on its ρ (due to the movements of the other robots). This situation never creates ambiguous snapshots since w can always understand ρ' does not belong to its block. In fact, the moving robots in the block of w can never hide all the regular robots on Γ_e : the visibility of w can be obstructed by at most m-6 robots which are moving inside C (where the 6 still robots are: w itself, the angle and anglem robots, and the three beacons w_3, w_{m-1}, w_m). So w can see at least 6 regular robots on its block. Such regular robots are sufficient to prevent wfrom selecting the wrong median diameter.

- 3. Before this step, w_0 (the median robot) is the only robot on ρ . Robots w_3 (as the "left" beacon) and w_{m-1}, w_m (as "right" beacons) can easily and safely elect themselves and reach their projections on ρ , by following a sequential scheme (i.e. in constant time). Traveling along parallel trajectories, they do not collide.
- 4. Let w be a west_diameter robot on ρ . It can always recompute the supporting line of ρ (w can always see another west_diameter robot or the sliceMedian robot). Moreover, it can always see the robots angle and anglem. Thus, w can recompute C (the center of C is the intersection point between the bisector of angle-anglem and the supporting line of ρ) and its projection w' on C_w . Then, w splits C_e and C_w in δ -slices (δ being fixed by the angle robot) and computes the slice η_k where w' lays on (i.e. where w originally laid before the migration on ρ).

After having recomputed η_k , w obtains its original rank j by inverting the formula $\angle w_0 Ow' = k\delta + \frac{j\delta}{m+1}$, where m is fixed by angle and anglem.

- 5. See Figure 14. Thanks to Item 4, we know that w can compute C_e , C_w , and its rank j, even when other robots are moving to reach their uniform positions on Γ_w . Moreover, w can see at least three robots on Γ_e (one of them is **sliceR**) and so it recomputes Γ_w . The presence of the **angle** and **anglem** robots allows w to recompute m and so the positions of each uniform position. Thus, it can easily spot the position of its target U'_i .
- 6. For the sake of simplicity, we make angle and anglem move sequentially. Let a be the angle or anglem robot. When a sees no west_diameter robots, a easily recomputes the (possible) missing uniform positions U'₁ or U'₂ (by the presence of the sliceMedian robot and the robots on Γ_{e,w}). Then, it heads to its U'_j without colliding with any other robots (due to the absence of robots on ρ and C_w, except for the sliceMedian robot).

Lemma 24. During Stage 3 of Procedure SLICE, all the west robots on C_w can reach ρ in O(1) epochs by implementing BDCP.

Proof. We verify that all the input assumptions listed in Algorithm 1 hold to correctly implement BDCP in O(1) time.

- 1. ρ is the target 2-curve;
- 2. 4 beacons $(w_3, w_{m-1}, w_m \text{ together with the median robot } w_0)$ are originally set to fix ρ (see Lemma 23, Item 3);
- 3. the west robots are the waiting robots which have to reach ρ , so that
 - (a) since they start from C_w (excluded its endpoints), they are external to ρ , belonging to the same half-plane delimited by ρ ;
 - (b) at the beginning of this step, no robot is moving within C, so each west robot can see all the robots on ρ ;
 - (c) they have to reach ρ
 - to their projections on ρ . Being the beacons originally the "leftmost" and the "rightmost" west robots on C_w , the west robots will migrate between the two groups of beacons;
 - being parallel, the west robots' trajectories do not intersect each other;
 - such trajectories are perpendicular to ρ , so they intersect each other in just one point;
 - if a west robot on C_w can see its target line ρ , then it can reconstruct its trajectory (the projection on ρ);
 - (d) each west robot sets its color as west_diameter once on ρ , playing the role of a new beacon fixing the chord ρ .

All these assumptions guarantee all west robots reach ρ in $O(\log 2) = O(1)$ epochs without colliding.

B.5 Procedure SEQUENTIAL MATCH

We show here all the correctness proofs for Procedure SEQUENTIAL MATCH (Section 6.5).

Lemma 25. Given $Conf_{unisect}$ with q < 12 robots in each uniform sector (boundaries excluded), a pre_matched robot can compute and reach its target uniform position U_j even if other to_matched robots are moving and hiding right or left robots.

Proof. The proof is similar to the one for Lemmas 12 and 13. In particular, a pre_matched robot can always spot the left and right robots of its uniform sector Υ_i . Using the same strategy as Lemmas 12 and 13, it recomputes the boundaries of the uniform sectors and the central angle $2\pi/n$ formed by two consecutive uniform positions (occupied by left, right or regular robots). Since a pre_matched robot has complete visibility of its uniform sector (in fact, no robot is moving within it), it counts the matched robots in Υ_i and, so, it recomputes the current index j of the uniform position to be matched. Thus, it heads to the uniform position U_j of Υ_i and sets its color as matched.