Better Algorithms for Constructing Minimum Cost Markov Chains and AIFV Codes

Mordecai J. Golin University of Massachusetts, Amherst Email: mgolin@umass.edu Reza Hosseini Dolatabadi and Arian Zamani Department of Computer Engineering Sharif University of Technology, Tehran, Iran Emails: {reza.dolatabadi256}, {arian.zamani243}@sharif.edu

Abstract—Almost Instantaneous Fixed to Variable (AIFV) coding is a relatively new method of lossless coding that, unlike Huffman coding, uses more than one coding tree. The problem of constructing optimal AIFV codes is a special case of that of constructing minimum cost Markov Chains. This paper provides the first complete proof of correctness for the previously known iterative algorithm for constructing such Markov chains.

A recent work describes how to efficiently solve the Markov Chain problem by first constructing a *Markov Chain Polytope* and then running the Ellipsoid algorithm for linear programming on it. This paper's second result is that, in the AIFV case, a special property of the polytope instead permits solving the corresponding linear program using simple binary search.

I. INTRODUCTION

In what follows m, n are positive integers, $[m] = \{0, 1, \dots, m-1\}$ and $\langle n \rangle = \{1, 2, \dots, n\}$.

Consider a stationary memoryless source with alphabet $\Sigma = \{\sigma_1, \sigma_2, \dots, \sigma_n\}$ in which symbol σ_i is generated with probability p_i . Binary Huffman codes encode each σ_i as a binary string. Huffman codes are usually represented as a tree, with the codewords being leaves of the tree.

m-ary Almost Instantaneous Fixed to Variable (AIFV-*m*) coding [1, 2, 3, 10, 12, 14, 15] is a relatively new method of lossless coding that encodes using *m* different coding trees (switching between the trees using a complicated rule). Minimum cost AIFV-*m* codes are interesting because they can approach Shannon Entropy closer than Huffman coding.

The initial method for constructing minimum cost AIFV-m codes was an iterative ("fastest descent") one developed in [1, 2, 14, 15]. As noted in [2], this algorithm actually solved the more general problem of constructing a minimum-cost m-state Markov chain. This algorithm was therefore also able to be used to solve the problem of finding better parsing dictionaries using multiple parse trees [13] as well as better lossless codes for finite channel coding [11], two other problems that fit into the minimum-cost Markov Chain framework.

The sequel is framed in terms of the general Markov Chain problem and not the specific AIFV one. (For completeness, the appendix provides a complete description of the motivating AIFV problem.)

The iterative algorithm referenced above ran in exponential time. [5] described a binary-search algorithm running in $O(n^3b)$ time for solving the AIFV-2 coding problem; this corresponded to constructing a minimun cost 2-state Markov chain. Recall that n is the size of the source alphabet. b was the maximum number of bits required to represent any of the p_i . [8] recently showed how to transform the general mstate Markov chain problem into a problem on corresponding *Markov Chain Polytope (MCP)* in which the highest point on the MCP corresponds somehow to a minimum-cost Markov Chain. This transforms the problem into a linear programming one which, even though the MCP has exponential size, can be efficiently solved using the Ellipsoid algorithm [9]. If the MCP has a polynomial time separation oracle, which the AIFV MCP does, the problem could then be solved in polynomial time. A major weakness of this last result is that it is purely theoretical, since the Ellipsoid algorithm is not very efficient in practice. This paper contains two separate results.

The first proves the correctness of the iterative algorithm given in [1, 2, 14, 15] and rewritten as Algorithm 1 below. The existing proofs only showed that if the algorithm terminates, it terminates at a correct (min-cost) solution. That still left open the possibility that the algorithm might infinitely loop. We show that the algorithm always terminates for any instance of a Minimum Cost Markov Chain problem.

The second result is a much simpler algorithm for solving the AIFV-*m* problem. As intermediate steps in its analysis, [8] derived an additional property of the specific MCP associated with the AIFV-*m* problem (Lemma 4 below). We show that this implies that linear programming on this polytope can be solved using easily implementable simple binary search rather than requiring the more complicated Ellipsoid algorithm.

A. The Minimum Cost Markov Chain Problem

Recall that a Markov Chain $\mathbf{S} = (S_0, \ldots, S_{m-1})$ is specified by knowing the *transition probabilities* $\{q_j(S_k)\}_{j \in [m]}$ for each $k \in [m]$. These satisfy $\forall j \in [m], q_j(S_k) \ge 0$ and $\sum_{j \in [m]} q_j(S_k) = 1$. If the Markov chain is *ergodic*, \mathbf{S} has a unique stationary distribution $\pi(\mathbf{S}) = (\pi_0(\mathbf{S}), \ldots, \pi_{m-1}(\mathbf{S}))$.

Our problem is on Markov Chains with *rewards*. That is, each state S_k has a real nonnegative *reward* or *cost* $\ell(S_k)$.

If $\pi(\mathbf{S})$ exists, e.g., if **S** is ergodic then its gain [4] or (average steady state) cost is $cost(\mathbf{S}) = \sum_{k \in [m]} \ell(S_k) \cdot \pi_k(\mathbf{S})$.

Our problem is to find the chain S with minimum cost among a specifically defined set of permissible Markov Chains. More explicitly:

Definition 1. Fix m > 1.

- 1) $\forall k \in [m]$, let \mathbb{S}_k be some finite given set of "permissible state k's", satisfying that $\forall S_k \in \mathbb{S}_k$, $q_0(S_k) > 0$.
- 2) A Markov Chain $\mathbf{S} = (S_0, \dots, S_{m-1})$ is permissible if $\forall k \in [m], S_k \in \mathbb{S}_k$.
- 3) the set of permissible Markov chains is $\mathbb{S} = \bigotimes_{k=0}^{m-1} \mathbb{S}_k = \{(S_0, \dots, S_{m-1}) \mid \forall k \in [m], S_k \in \mathbb{S}_k\}$

The Minimum Cost Markov Chain (MCMC) Problem is to find $a \mathbf{S} \in \mathbb{S}$ satisfying $\text{cost}(\mathbf{S}) = \min_{\mathbf{S}' \in \mathbb{S}} \text{cost}(\mathbf{S}')$.

The specific structure of the S_k is different from problem to problem. For intuition, in the original motivating example of AIFV-*m* coding, AIFV-*m* codes were *m*-tuples of coding trees. The *k*'th tree in such a code could be any permissible type-*k* tree (independent of the other trees in the tuple). The $q_j(S_k)$ were the probabilities of encoding a source symbol with a type-*j* tree immediately after encoding the previous source symbol with a specific type-*k* tree. The average number of bits used to encode a source symbol turned out to be exactly the cost of the associated Markov Chain. For more information on this correspondence please see the appendix.

We also note that condition (1) in the definition implies that $\mathbf{S} = (S_0, \ldots, S_{m-1})$ is an ergodic *unichain*, with one aperiodic recurrent class (containing S_0) and, possibly, some transient states. **S** therefore has a unique stationary distribution $\pi(\mathbf{S})$ so $\operatorname{cost}(\mathbf{S})$ is well defined for all $\mathbf{S} \in \mathbb{S}$.

B. The Markov Chain Polytope

The next set of definitions are from [8] which showed how to transform the MCMC problem into a linear programming one by first transforming permissible states into mdimensional hyperplanes and then working with the polytope defined by their lower envelope.

Definition 2. Let $k \in [m]$. In what follows, \mathbf{x} will always satisfy $\mathbf{x} = [x_1, x_2 \dots, x_{m-1}]^T \in \mathbb{R}^{m-1}$.

• Define $f_k : \mathbb{R}^{m-1} \times \mathbb{S}_k \to \mathbb{R}$ as follows:

$$f_0(\mathbf{x}, S_0) = \ell(S_0) + \sum_{j=1}^{m-1} q_j(S_0) x_j$$

$$\forall k > 0 : f_k(\mathbf{x}, S_k) = \ell(S_k) + \sum_{j=1}^{m-1} q_j(S_k) x_j - x_k$$

• Define $g_k : \mathbb{R}^{m-1} \to \mathbb{R}$ as follows:

$$g_{k} \left(\mathbf{x} \right) = \min_{S_{k} \in \mathbb{S}_{k}} f_{k} \left(\mathbf{x}, S_{k} \right)$$
$$S_{k} \left(\mathbf{x} \right) = \arg \min_{S_{k} \in \mathbb{S}_{k}} f_{k} \left(\mathbf{x}, S_{k} \right)$$
$$\mathbf{S} \left(\mathbf{x} \right) = \left(S_{0} \left(\mathbf{x} \right), \dots, S_{m-1} \left(\mathbf{x} \right) \right)$$

We call $g_k(x)$ the lower-envelope of type k.

• Define $h : \mathbb{R}^{m-1} \to \mathbb{R}$ as

$$h\left(\mathbf{x}\right) = \min_{k} g_{k}\left(\mathbf{x}\right)$$

The Markov Chain Polytope corresponding to S is

$$\mathbb{H} = \{ (\mathbf{x}, y) \in \mathbb{R}^m \mid 0 \le y \le h(\mathbf{x}) \}$$

The height of \mathbb{H} is height(\mathbb{H}) = max_{(**x**,y)\in\mathbb{H}} y.

[8] described the relationship of this polytope to the MCMC problem.

Proposition 1 (Lemma 3.1 in [8]). Let $\mathbf{S} = (S_0, \ldots, S_{m-1})$ be any permissible Markov chain and $f_k(\mathbf{x}, S_i), k \in [m]$, its associated hyperplanes. Then these *m* hyperplanes intersect at a unique point $(\mathbf{x}, y) \in \mathbb{R}^m$. Furthermore, $y \ge \text{height}(\mathbb{H})$.

Such a point (\mathbf{x}, y) will be called the multi-typed intersection corresponding to S.

Note that the proposition implies that if (\mathbf{x}, y) is the multityped intersection corresponding to $\mathbf{S} = (S_0, \dots, S_{m-1})$,

$$\operatorname{cost}(\mathbf{S}) = f_0(\mathbf{x}, S_0) = f_1(\mathbf{x}, S_1) = \dots = f_{m-1}(\mathbf{x}, S_{m-1}).$$

It also immediately implies that the lowest (y-coordinate) multi-typed intersection point corresponds to the cheapest Markov chain and its height is at least height(\mathbb{H}). Thus

Corollary 1. If some $(\mathbf{x}, y) \in \mathbb{H}$ is a multi-typed intersection point (\mathbf{x}, y) , then (\mathbf{x}, y) is a highest point on \mathbb{H} , i.e., $y = \text{height}(\mathbb{H})$. Furthermore, $\mathbf{S}(\mathbf{x})$ is a min cost Markov chain.

According to the above statements, it is sufficient to prove that H contains a multi-typed intersection point. Then finding the cheapest Markov chain will be equivalent to finding the highest point of the polytope H. We will use this fact later.

II. THE ITERATIVE ALGORITHM

[1, 2, 14, 15] introduced the following iterative algorithm for solving the AIFV-*m* problem. As noted by [2], it actually solves the generic MCMC Problem.

Algorithr	n 1 Iterative	Algorithm	to Find Th	e Optimal	$\mathcal{T}\in\mathbb{S}$
Require:	\mathbb{S} and $\mathbf{S}(\mathbf{x})$	defined in	Section I		

Initialization: Let $\mathbf{p}_0 \in \mathbb{R}^{m-1}$ be the projection of any arbitrary multi-typed intersection point.

1: while $\mathbf{p}_i \neq \mathbf{p}_{i-1}$ do

- 2: $i \leftarrow i+1$
- 3: $\mathbf{p}_i \leftarrow$ the projection of the multi-typed intersection point corresponding to $\mathbf{S}(\mathbf{p}_{i-1})$.
- 4: end while
- 5: return $\mathbf{S}(\mathbf{p}_i)$

In the algorithm, the projection of $\mathbf{x}' = [x_1, x_2, \dots, x_m]^T \in \mathbb{R}^m$ on \mathbb{R}^{m-1} is $\mathbf{x} = [x_1, x_2, \dots, x_{m-1}]^T \in \mathbb{R}^{m-1}$.

The algorithm starts by choosing any arbitrary $\mathbf{S} = (S_0, \ldots, S_{m-1}) \in \mathbb{S}$, setting $\mathbf{x}'_0 = (\mathbf{x}_0, y_0)$ to be the multityped intersection point corresponding to S and the starting point as $\mathbf{p}_0 = \mathbf{x}_0$, i.e., the projection of \mathbf{x}'_0 on \mathbb{R}^{m-1} .

Note that the algorithm strongly depends upon Proposition 1 to ensure that a unique multi-typed intersection point corresponding to any $\mathbf{S} \in \mathbb{S}$ always exists.

The discussions in [1, 2, 14, 15] don't actually prove that the algorithm is always correct. They rather prove that if it terminates, then it outputs a correct solution. They did not prove though, that it always terminates. It could end up looping infinitely. Our first new result will be a proof of termination and correctness in all cases.

The next section proves the correctness of Algorithm 1. For completeness, we note that Algorithm 1 as presented is actually not the iterative algorithm presented in [1, 2, 14, 15]. But, it is shown in [8] that Algorithm 1 is identical to the earlier one(s) after a change of variables. This change of variables vastly simplifies the proof of correctness

III. PROOF OF CORRECTNESS OF ALGORITHM 1

Let

$$\mathbf{u} = [u_1, u_2, \dots, u_n]^T, \mathbf{v} = [v_1, v_2, \dots, v_n]^T \in \mathbb{R}^n$$

be two vectors. Define $\mathbf{u} \leq \mathbf{v}$ if $\forall i \in \langle n \rangle : u_i \leq v_i$. The proof requires partitioning \mathbb{R}^{m-1} into *m* cones.

Definition 3. Let $k \in [m]$. Define:

$$C_0 = \left\{ \boldsymbol{u} \in \mathbb{R}^{m-1} \mid \boldsymbol{u} \preceq 0 \right\},\$$

$$\forall k > 0 : C_k = \Big\{ \boldsymbol{u} \in \mathbb{R}^{m-1} \mid u_k > 0 \text{ and } \forall j : u_k \ge u_j \Big\}.$$

Lemma 1. Fix $i \in [m]$ and let $S_i \in \mathbf{S}_i$. Let $\boldsymbol{u}, \boldsymbol{v} \in \mathbb{R}^{m-1}$ with $\boldsymbol{u} \neq \boldsymbol{v}$ and $\boldsymbol{v} - \boldsymbol{u} \in C_i$. Then

$$f_i(\mathbf{v}, S_i) \leq f_i(\mathbf{u}, S_i)$$

Moreover, if $i \neq 0$, $f_i(\mathbf{v}, S_i) < f_i(\mathbf{u}, S_i)$.

Proof. We first analyze the case i = 0, i.e., $\mathbf{v} - \mathbf{u} \in C_0$, or, equivalently, $\mathbf{v} \leq \mathbf{u}$. By Definition 2:

$$f_0 (\mathbf{u}, S_0) = \ell (S_0) + \sum_{j=1}^{m-1} q_j (S_0) u_j$$
$$f_0 (\mathbf{v}, S_0) = \ell (S_0) + \sum_{j=1}^{m-1} q_j (S_0) v_j$$

Therefore,

$$f_0(\mathbf{v}, S_0) - f_0(\mathbf{u}, S_0) = \sum_{j=1}^{m-1} q_j(S_0)(v_j - u_j)$$
(1)

By assumption, $\mathbf{v} \leq \mathbf{u}$, so for all $1 \leq j < m$, $v_j - u_j \leq 0$. Hence, by Equation (1),

$$f_0(\mathbf{v}, S_0) - f_0(\mathbf{u}, S_0) \le 0$$

We now analyze the cases in which $i \neq 0$, i.e., $\mathbf{v} - \mathbf{u} \in C_i$ for $i \in \langle m - 1 \rangle$. Define the set of indices $I \subseteq \langle m - 1 \rangle$ as

$$I = \{ j \in [m-1] \mid v_j > u_j \}.$$
 (2)

By assumption $i \in I$, so $I \neq \emptyset$. By Definition 2,

$$f_i(\mathbf{u}, S_i) - f_i(\mathbf{v}, S_i) = \sum_{j \neq i} q_j(S_i) (u_j - v_j) + (q_i(S_i) - 1) (u_i - v_j)$$

From Equation (2),

$$f_{i} (\mathbf{u}, S_{i}) - f_{i} (\mathbf{v}, S_{i}) = \sum_{j \in I \setminus \{i\}} q_{j} (S_{i}) (u_{j} - v_{j}) + \sum_{k \notin I} q_{k} (S_{i}) (u_{k} - v_{k}) + (q_{i} (S_{i}) - 1) (u_{i} - v_{i})$$
(3)

By the definition of C_i ,

$$\sum_{j \in I \setminus \{i\}} q_j \left(S_i\right) \left(u_j - v_j\right) \ge \left(\sum_{j \in I \setminus \{i\}} q_j \left(S_i\right)\right) \left(u_i - v_i\right) \quad (4)$$

and by the definition of I

$$\sum_{k \notin I} q_k \left(S_i \right) \left(u_k - v_k \right) \ge 0.$$
(5)

Since

$$1 - q_i\left(S_i\right) = \left(\sum_{j \in \langle m-1 \rangle \setminus \{i\}} q_j\left(S_i\right)\right) + q_0\left(S_i\right)$$

by Equations (3), (4) and (5) we can conclude:

$$f_{i}\left(\mathbf{u}, S_{i}\right) - f_{i}\left(\mathbf{v}, S_{i}\right) \geq \left(\sum_{j \in I \setminus \{i\}} q_{j}\left(S_{i}\right)\right)\left(u_{i} - v_{i}\right) + 0$$
$$- \left(\left(\sum_{j \in \langle m-1 \rangle \setminus \{i\}} q_{j}\left(S_{i}\right)\right) + q_{0}\left(S_{i}\right)\right)\left(u_{i} - v_{i}\right).$$

Hence

$$f_{i}\left(\mathbf{u}, S_{i}\right) - f_{i}\left(\mathbf{v}, S_{i}\right)$$

$$\geq \left(\left(\sum_{j \in \langle m-1 \rangle \setminus I} q_{j}\left(S_{i}\right)\right) + q_{0}\left(S_{i}\right)\right)\left(v_{i} - u_{i}\right)$$

$$\geq q_{0}\left(S_{i}\right)\left(v_{i} - u_{i}\right) > 0$$

completing the proof.

Theorem 1. Algorithm 1 always terminates in finite time. Furthermore, at termination, $\mathbf{S}(\mathbf{p}_i)$ is a minimum cost Markov Chain and the multi-typed intersection point associated with $\mathbf{S}(\mathbf{p}_i)$ is in \mathbb{H} .

Proof. Since the set S of permissible Markov Chains is finite the set $\{\mathbf{p}_0, \mathbf{p}_1, \ldots\}$ is finite.

Now set $c_0 = y_0$. For i > 0, define $c_i = \text{cost} (\mathbf{S} (\mathbf{p}_{i-1}))$. From Proposition 1 and the definition of the \mathbf{p}_i

$$c_{i} = f_{0} \left(\mathbf{p}_{i}, S_{0} \left(\mathbf{p}_{i-1} \right) \right) = f_{1} \left(\mathbf{p}_{i}, S_{1} \left(\mathbf{p}_{i-1} \right) \right)$$

= \dots = f_{m-1} \left(\mathbf{p}_{i}, S_{m-1} \left(\mathbf{p}_{i-1} \right) \right)

We claim that for all i > 1, (i) $c_i \le c_{i-1}$. Furthermore, (ii) if $c_i = c_{i-1}$, $\mathbf{p}_i \le \mathbf{p}_{i-1}$.

The C_j partition \mathbb{R}^{m-1} so there exists some j such that $\mathbf{p}_i - \mathbf{p}_{i-1} \in C_j$. From Lemma 1, v_i).

$$f_j\left(\mathbf{p}_{i-1}, S_j\left(\mathbf{p}_{i-1}\right)\right) \ge f_j\left(\mathbf{p}_i, S_j\left(\mathbf{p}_{i-1}\right)\right) = c_i.$$
(6)

From the definition of $S_i(x)$ (via $\arg \min$) in Definition 2,

$$c_{i-1} = f_j \left(\mathbf{p}_{i-1}, S_j \left(\mathbf{p}_{i-2} \right) \right) \ge f_j \left(\mathbf{p}_{i-1}, S_j \left(\mathbf{p}_{i-1} \right) \right)$$

Combining with inequality (6), yields (i),

$$\forall i > 0, \quad c_i \le c_{i-1}. \tag{7}$$

Moreover, by Lemma 1 we know if j > 0, the inequality in (6) is strict; thus, inequality (7) is also strict. So, if $c_i = c_{i-1}$, then j = 0 so $\mathbf{p}_i \leq \mathbf{p}_{i-1}$ and (ii) is proved.

Since the set $\{\mathbf{p}_0, \mathbf{p}_1, \ldots\}$ is finite, $\{c_0, c_1, \ldots\}$ is also finite. Inequality (7) thus implies that the c_i converge in finite time, i.e., there exists $N \in \mathbb{N}$ s.t. for all i > N, $c_i = c_{i-1}$.

Claim (ii) then implies that for all i > N, $\mathbf{p}_i \leq \mathbf{p}_{i-1}$. The finiteness of the set $\{\mathbf{p}_0, \mathbf{p}_1, \ldots\}$, then immediately implies that, for all sufficiently large $n \in \mathbb{N}$, $\mathbf{p}_n = \mathbf{p}_{n+1}$, i.e., the algorithm terminates.

Note that if
$$\mathbf{p}_n = \mathbf{p}_{n+1}$$
, then $c_n = c_{n+1}$ so, $\forall k \in [m]$,
 $c_n = c_{n+1} = f_k \left(\mathbf{p}_{n+1}, S_k \left(\mathbf{p}_n \right) \right) = f_k \left(\mathbf{p}_n, S_k \left(\mathbf{p}_n \right) \right) = g_k \left(\mathbf{p}_n \right)$.

Thus
$$c_n = h(\mathbf{p}_n)$$
, so $(\mathbf{p}_n, c_n) \in \mathbb{H}$ is a multi-typed intersection point. Corollary 1 then implies that $\mathbf{S}(\mathbf{p}_n)$ is a minimum cost Markov Chain.

Lemma 1 also provides more information about the structure of \mathbb{H} . This will be useful later.

Theorem 2. The multi-typed intersection point found by Algorithm 1 is the unique multi-typed intersection point in \mathbb{H} . Furthermore, it is a vertex of \mathbb{H} .

Proof. To prove the uniqueness, assume $Q = (\mathbf{x}, h)$ and $Q' = (\mathbf{x}', h) (Q, Q' \in \mathbb{R}^m \text{ and } \mathbf{x}, \mathbf{x}' \in \mathbb{R}^{m-1})$ are multi-typed intersection points in \mathbb{H} . Note that from Corollary 1 $h = h' = h(\mathbf{x}) = h(\mathbf{x}') = \text{height}(\mathbb{H})$.

It is sufficient to show that Q = Q'. Assume $Q \preceq Q'$ doesn't hold. By Lemma 1, there exists an index $i \in (m - 1)$ s.t.

$$\forall S_i \in \mathbb{S}_i, \quad f_i(\mathbf{x}, S_i) > f_i(\mathbf{x}', S_i).$$
(8)

Let $f_i(\bar{\mathbf{x}}, S_i)$ denote the hyperplane associated with state S_i . Let $S_i \in \mathbb{S}_i$ be such that Q lies on $f_i(\bar{\mathbf{x}}, S_i)$. Then

$$f_i(\mathbf{x}, S_i) = h = h(\mathbf{x}') \le f_i(\mathbf{x}', S_i),$$

contradicting (8). Hence $Q \leq Q'$. We can symmetrically prove that $Q' \leq Q$. Thus, Q = Q', and the uniqueness follows.

If Q is not a vertex of \mathbb{H} , since it is a highest point of \mathbb{H} , there exist two other points highest points Q_1, Q_2 on \mathbb{H} s.t.

$$Q = \frac{1}{2} \left(Q_1 + Q_2 \right)$$

It is clear that at least for one $i \in \{1, 2\}$, $\mathbf{x}_i - \mathbf{x} \notin C_0$; thus, by Lemma 1, there exists $j \in \langle m - 1 \rangle$ s.t. for all $S_j \in \mathbb{S}_j$, $f_j(\mathbf{x}_i, S_j) < f_j(\mathbf{x}, S_j)$ and thus, $g_j(\mathbf{x}_i) < g_j(\mathbf{x})$ which is a contradiction. Thus Q must be a vertex of \mathbb{H} . \Box

Corollary 2. There exists a unique $\mathbf{x}^* \in \mathbb{R}^m$ satisfying

$$g_0(\mathbf{x}^*) = g_1(\mathbf{x}^*) = \ldots = g_{m-1}(\mathbf{x}^*).$$

Furthermore, $\mathbf{S}(\mathbf{x}^*)$ *is a solution to the MCMC problem.*

Proof. In the appendix.

IV. A NEW WEAKLY POLYNOMIAL TIME ALGORITHM FOR AIFV-3-CODING

The previous section proved the correctness of Algorithm 1 in solving any MCMC problem. The running time of the algorithm depends upon two factors. The first is how quickly $\mathbf{S}(\mathbf{x})$ can be calculated. This is very dependent upon how the states S_i are defined. In the special case of AIFV-*m* coding of *n* source-code words, $\mathbf{S}(\mathbf{x})$ was first solved using integer linear programming [15] requiring time exponential in *n*.

When $\mathbf{x} \in [0, 1]^{m-1}$ this was improved to polynomial time by using dynamic programs. More specifically, for m = 2, [12] developed a $O(n^5)$ DP, improved to $O(n^3)$ by [6]; for m > 2, [14] solved it in $O(n^{2m+1})$ time, improved to $O(n^{m+2})$ by [7].

The second factor determining running time is the number of iterative steps performed by the algorithm. It might have to iterate through ALL permissible Markov Chains in which case, at least for AIFV coding, it requires exponential time.

[8] recently showed how to transform a MCMC problem into an equivalent Linear Programming one of finding a highest point in the associated Markov Chain Polytope \mathbb{H} . Although \mathbb{H} might be defined by an exponential number of constraints this linear program can be solved using the Ellipsoid method. In the specific case of AIFV-*m* coding this yielded a polynomial (in *n* and *b*) time algorithm.

Unfortunately, this result was purely theoretical, since the Ellipsoid method is known to be extremely difficult to practically implement.

In this section we derive further special properties of the Markov Chain Polytope for the specific case of the AIFV-3 problem. These will permit replacing the Ellipsoid method by simple binary search and yielding a $O(n^5b^2)$ time algorithm.

Due to space considerations we restrict the discussion to the specific case of AIFV-3 coding. We claim, though, that this technique works for all AIFV-m coding, for m > 3 as well.

Recall that for each $i \in \{0, 1, 2\}$ and every $S_i \in \mathbb{S}_i$ there exists a type-*i* hyperplane $f_i(\mathbf{x}, S_i)$ that ranges over all $\mathbf{x} = (x_1, x_2) \in \mathbb{R}^2$. Let $\lambda \in \mathbb{R}$ be fixed. For $j \in \{0, 1\}$ let $h_{j,\lambda}$ denote the hyperplane in \mathbb{R}^3 defined by setting $x_j = \lambda$. Now consider the intersection of type-0 and type-2 hyperplanes with $h_{1,\lambda}$:

$$f_0((\lambda, x_2), S_0) = \ell(S_0) + q_1(S_0) \cdot \lambda + q_2(S_0) \cdot x_2,$$

$$f_2((\lambda, x_2), S_2) = \ell(S_2) + q_1(S_2) \cdot \lambda + q_2(S_2) \cdot x_2 - x_2$$

$$= \ell(S_2) + q_1(S_2) \cdot \lambda + (q_2(S_2) - 1) \cdot x_2$$

These are both lines in x_2 . The intersection of each f_0 hyperplane with $h_{1,\lambda}$ corresponds to a line with a non-negative slope; since $q_2(S_i) = 1 - q_0(S_i) - q_1(S_i) < 1$, because $q_0(S_i)$ is always positive, the intersection of each f_2 hyperplane with $h_{1,\lambda}$ corresponds to a line with a negative slope. Thus the intersection of g_0 and with $h_{1,\lambda}$ is the lower-envelope of non-

negative slope lines and the intersection of q_2 and with $h_{1,\lambda}$ is the lower-envelope of negative slope lines. Thus

Lemma 2. For any fixed $\lambda \in \mathbb{R}$, g_0 and g_2 intersect exactly once on the $h_{1,\lambda}$ hyperplane.

Note that this means that, for any $x_1 \in \mathbb{R}$ there exists a unique x_2 such that $g_0(x_1, x_2) = g_2(x_1, x_2)$. This permits defining the function $E_1: [0,1] \to \mathbb{R}^3$ to be a function that takes $x_1 \in [0, 1]$ as an input and outputs the unique intersection point of g_0 and g_2 on h_{1,x_1} .

Lemma 3. E_1 is a piecewise linear continuous function.

Proof. Included in the appendix.

Everything up to this point would be correct for any Minimum Cost Markov Chain problem. We now use the following known facts that are specific to the AIFV coding case, i.e., when the states are AIFV coding trees.

Lemma 4 ([8], Lemma 7.2). Let the states S_i be as defined by the AIFV coding trees. Let m be fixed, $n \ge 2^m - 1$, $\mathbf{x} \in \mathbb{R}^{m-1}$ and $k \in \{1, 2, ..., m - 1\}$. Then

- If $x_k = 0$, $g_0(\mathbf{x}) g_k(\mathbf{x}) \le 0$. If $x_k = 1$, $g_k(\mathbf{x}) g_0(\mathbf{x}) \le 0$.

This lets us prove

Lemma 5. Let $x_1 \in [0,1]$ and $E(x_1) = (x_1, x_2, y)$ be the unique intersection of g_0 and g_2 on the h_{1,x_1} hyperplane. Then $x_2 \in [0, 1].$

Proof. From Lemma 4, $g_0(x_1, 0) - g_2(x_1, 0) \leq 0$ and $g_0(x_1,1) - g_2(x_1,1) \ge 0$. Since $g_0(x_1,x_2) - g_2(x_1,x_2)$ is continuous in x_2 for fixed x_1 , the unique intersection of g_0 and g_2 with the h_{1,x_1} hyperplane must occur when $x_2 \in [0,1]$.

Lemma 6. If $\lambda \in [0, 1]$ can be written using at most O(b) bits when represented in binary, then $E_1(\lambda)$ can be calculated in $O(n^5 \cdot b)$ time.

Proof. We use a halving method similar to one used in [5] for solving the AIFV-2 problem.

Note that, for any $(x_1, x_2) \in [0, 1]^2$ the DP algorithm from [7] mentioned earlier can calculate $g_0(x_1, x_2)$ and $g_2(x_1, x_2)$ in $O(n^5)$ time. Thus it can determine in $O(n^5)$ time whether or not $g_0(x_1, x_2) - g_2(x_1, x_2) \le 0$.

From Lemma 5, finding $E_1(\lambda)$ is equivalent to finding the unique $x_2^*(\lambda) \in [0,1]$ satisfying $g_0(\lambda, x_2^*(\lambda)) = g_2(\lambda, x_2^*(\lambda))$.

From Lemma 4, $g_0(x_1, 0) - g_2(x_1, 0) \le 0$ and $g_0(x_1, 1) - g_2(x_1, 0) \le 0$ $g_2(x_1,1) \ge 0$. Set $\ell = 0$ and r = 1. We can then simply do a halving search, after s steps always maintaining an interval $[\ell, r]$ where $x_2^*(\lambda) \in [\ell, r]$ satisfying $\ell = t2^{-s}$ and $r = (t + \ell)^{-s}$ $1)2^{-s}$ for some $t \in [2^s]$. This requires $O(n^5s)$ time in total.

We now note that, again using an argument similar to the one used in [5], in the AIFV case we know that the $q_i(S_i)$ and $\ell(S_i)$ are all integer multiples of 2^{-b} .

This lower bounds the absolute values of the non-zero slopes and y-intercepts of all lines $f_i((\lambda, x_2), S_i)$ to be $2^{-O(b)}$. This in turn implies (see [5] for more details) that after O(b) steps

the interval $[\ell, r]$ will be small enough that $(\lambda, x_2^*(\lambda))$ will lie on one of the four lines, $f_i((\lambda, x_2), S_i^d)$ where $i \in \{0, 2\}$, $d \in \{\ell, r\}$ and $S_i^d = S_i(\lambda, d)$. The S_i^d can be found in $O(n^5)$ time using the DP procedure. Since there are only 4 lines, $x_2^*(\lambda)$ itself can be found in only a further O(1) time.

Set $E'_1: [0,1] \to \mathbb{R}^2$ to be the function that takes $\lambda \in [0,1]$ as input and outputs the first two elements of $E_1(\lambda)$. That is if $E_1(\lambda) = (\lambda, x_2, y)$ then $E'_1 = (\lambda, x_2)$.

Algorithm 2 Finds x'_1 satisfying $ x_1^* - x'_1 \le 2^{-b'}$.				
Require: $\{p_1,, p_n\}$ and b'.				
Initialization: $l, r \leftarrow 0, 1$ and $\epsilon_0 = 2^{-b'}$.				
1: repeat				
2: mid $\leftarrow \frac{l+r}{2}$;				
3: Calculate $p = E'_1(\text{mid})$.				
4: $e_0 = g_0(p); e_1 = g_1(p)$				
5: if $e_0 < e_1$ then				
6: $l = \operatorname{mid}$				
7: else				
8: $r = \operatorname{mid}$				
9: end if				
10: until $r - l = \epsilon_0$				
11: return l				

Let $\mathbf{x}^* = (x_1^*, x_2^*, y^*)$ be the unique intersection of g_0, g_1 and g_2 . We will now construct an algorithm that helps us find a point $\mathbf{x}' = (x'_1, x'_2, y')$ that is close to \mathbf{x}^* . More specifically, we will prove the following lemma:

Lemma 7. Let b' be an integer such that b' = O(b), Algorithm 2 can find x'_1 satisfying $|x^*_1 - x'_1| \le 2^{-b'}$ in $O(n^5 \cdot b^2)$ time. Furthermore we can modify this algorithm to find $|x_2^* - x_2'| \leq$ $2^{-b'}$ in the same time complexity.

Proof. Included in the appendix.

Let $b' = 14 \cdot b + 18$ and T'_0 , T'_1 and T'_2 be the trees corresponding to $g_0(x_1', x_2'), g_1(x_1', x_2')$ and $g_2(x_1', x_2')$ respectively. From Proposition 1, the hyperplanes corresponding to T'_0 , T'_1 and T'_2 intersect at exactly one point. This means that if \mathbf{x}^* also lies on all three of these hyperplanes, then their intersection is \mathbf{x}^* and therefore, from Corollary 2, (T'_0, T'_1, T'_2) forms an optimal answer to the AIFV-3 problem and we are done.

Lemma 8. \mathbf{x}^* lies on $f_0(\mathbf{x}, T'_0)$, $f_1(\mathbf{x}, T'_1)$ and $f_2(\mathbf{x}, T'_2)$.

Proof. Included in the appendix

To recap, Lemma 7 shows us how to find appropriate (x'_1, x'_2) in $O(n^5b^2)$ time. The associated T'_0, T'_1, T'_2 can be found in $O(n^5)$ further time using the known DP algorithm. Lemma 8 then ensures that this is a correct solution to the AIFV-3 problem. Although a polynomial time solution for the AIFV-3 problem was previously presented in [8], that required using the Ellipsoid algorithm while the approach here only needed simple binary searches.

ACKNOWLEDGMENT

Work of all authors partially supported by RGC CERG Grant 16212021.

REFERENCES

- R. Fujita, K.-I. Iwata, and H. Yamamoto. An optimality proof of the iterative algorithm for AIFV-m codes. In 2018 IEEE International Symposium on Information Theory (ISIT), pages 2187–2191, 2018. doi: 10.1109/ISIT.2018.8437861.
- [2] R. Fujita, K.-I. Iwata, and H. Yamamoto. An iterative algorithm to optimize the average performance of markov chains with finite states. In 2019 IEEE International Symposium on Information Theory (ISIT), pages 1902– 1906, 2019. doi: 10.1109/ISIT.2019.8849856.
- [3] R. Fujita, K.-I. Iwata, and H. Yamamoto. On a redundancy of AIFV-m codes for m =3,5. In 2020 IEEE International Symposium on Information Theory (ISIT), pages 2355–2359, 2020. doi: 10.1109/ISIT44484.2020. 9174219.
- [4] R. G. Gallager. Discrete stochastic processes. Open-CourseWare: Massachusetts Institute of Technology, 2011.
- [5] M. Golin and E. Harb. A polynomial time algorithm for constructing optimal binary aifv-2 codes. *IEEE Transactions on Information Theory*, 69(10):6269–6278, 2023. doi: 10.1109/TIT.2023.3287587.
- [6] M. J. Golin and E. Harb. Speeding up the AIFV-2 dynamic programs by two orders of magnitude using range minimum queries. *Theor. Comput. Science.*, 865: 99–118, 2021. doi: 10.1016/j.tcs.2021.02.040.
- [7] M. J. Golin and A. J. L. Patupat. Speeding up AIFVm dynamic programs by m - 1 orders of magnitude. In 2022 IEEE International Symposium on Information Theory (ISIT), pages 246–251.
- [8] M. J. Golin and A. J. L. Patupat. The markov-chain polytope with applications. arXiv:2401.11622, 2024.
- [9] M. Grötschel, L. Lovász, and A. Schrijver. The ellipsoid method and its consequences in combinatorial optimization. *Combinatorica*, 1(2):169–197, Jun 1981. ISSN 1439-6912. doi: 10.1007/BF02579273.
- [10] W. Hu, H. Yamamoto, and J. Honda. Worst-case redundancy of optimal binary AIFV codes and their extended codes. *IEEE Transactions on Information Theory*, 63(8): 5074–5086, 2017. doi: 10.1109/TIT.2017.2694017.
- [11] K.-I. Iwata and H. Yamamoto. Joint coding for discrete sources and finite-state noiseless channels. In 2022 IEEE International Symposium on Information Theory (ISIT), pages 3327–3332.
- [12] K.-I. Iwata and H. Yamamoto. A dynamic programming algorithm to construct optimal code trees of AIFV codes. In 2016 International Symposium on Information Theory and Its Applications (ISITA), pages 641–645, 2016.
- [13] K.-I. Iwata and H. Yamamoto. Aivf codes based on iterative algorithm and dynamic programming. In 2021

IEEE International Symposium on Information Theory (*ISIT*), pages 2018–2023, 2021.

- [14] H. Yamamoto and K.-I. Iwata. An iterative algorithm to construct optimal binary AIFV-m codes. In 2017 IEEE Information Theory Workshop (ITW), pages 519– 523, 2017. doi: 10.1109/ITW.2017.8277992.
- [15] H. Yamamoto, M. Tsuchihashi, and J. Honda. Almost instantaneous fixed-to-variable length codes. *IEEE Transactions on Information Theory*, 61(12):6432–6443, 2015. doi: 10.1109/TIT.2015.2492961.



Fig. 1: Node types in a binary AIFV-3 code tree: complete node (*C*), intermediate-0 and intermediate-1 nodes (I_0 , I_1), master nodes of degrees 0, 1, 2 (M_0 , M_1 , M_2), (M_0 is a leaf)and non-intermediate-0 nodes ($\neg I_0$). The $\neg I_0$ nodes can be complete, master, or intermediate-1 nodes, depending upon their location in the tree.

APPENDIX

AIFV-m code definition

[Note: This 2 page subsection with its definitions and accompanying examples and diagrams has been copied, with permission, from [8].]

A binary AIFV-m code will be a sequence $(T_0, T_1, \dots, T_{m-1})$ of m binary code trees satisfying Definitions 4 and 5 below. Each T_i contains n codewords. Unlike in Huffman codes, codewords can be internal nodes.

Definition 4. (Node Types in a Binary AIFV-m Code [10]). Figure 1. Edges in an AIFV-m code tree are labelled as 0edges or 1-edges. If node v is connected to its child node u via a 0-edge (1-edge) then u is v's 0-child (1-child). We will often identify a node interchangeably with its associated (code)word. For example 0^210 is the node reached by following the edges 0, 0, 1, 0 down from the root. Following [10], the nodes in AIFV-m code trees can be classified as being exactly one of 3 different types:

- Complete Nodes. A complete node has two children: a 0-child and a 1-child. A complete node has no source symbol assigned to it.
- Intermediate Nodes. A intermediate node has no source symbol assigned to it and has exactly one child. A intermediate node with a 0-child is called a intermediate-0 node; with a 1-child is called a intermediate-1 node
- Master Nodes. A master node has an assigned source symbol and at most one child node. Master nodes have associated degrees:
 - a master node of degree k = 0 is a leaf.
 - a master node v of degree $k \ge 1$ is connected to its unique child by a 0-edge. Furthermore it has exactly k consecutive intermediate 0 nodes as its direct descendants, i.e., $v0^t$ for $0 < t \le k$ are intermediate-0 nodes while $v0^{k+1}$ is not a intermediate-0 node.

Binary AIFV-m codes are now defined as follows:

Definition 5. (Binary AIFV-m Codes [10]). See Figure 2. Let $m \ge 2$ be a positive integer. A binary AIFV-m code is an



Fig. 2: Example binary AIFV-3 code for source alphabet $\{a, b, c, d\}$. The small nodes are either complete or intermediate nodes, while the large nodes are master nodes with their assigned source symbols. Note that T_2 encodes \hat{a} , which is at its root, with an empty string!

ordered m-tuple of m code trees $(T_0, T_1, \dots, T_{m-1})$ satisfying the following conditions:

- 1) Every node in each code tree is either a complete node, a intermediate node, or a master node of degree k where $0 \le k < m$.
- For k ≥ 1, the code tree T_k has a intermediate-1 node connected to the root by exactly k 0-edges, i.e., the node 0^k is a intermediate-1 node.

Consequences of the Definitions:

- a) Every leaf of a code tree must be a master node of degree 0. In particular, this implies that every code tree contains at least one master node of degree 0.
- b) Definition 5, and in particular Condition (2), result in unique decodability (proven in [10]).
- c) For $k \neq 1$, the root of a T_k tree is permitted to be a master node. If a root is a master node, the associated codeword is the empty string (Figure 3)! The root of a T_1 tree cannot be a master node.
- d) The root of a T_k tree may be a intermediate-0 node.
- e) For k > 0, every T_k tree must contain at least one intermediate-1 node, the node 0^k . A T_0 tree might not contain any intermediate-1 node. For k > 0, the root of a T_k tree cannot be a intermediate-1 node. The root of a T_0 tree is permitted to be a intermediate-1 node.

We now describe the encoding and decoding procedures. These are illustrated in Figures 3 and 4 which demonstrate the unique decodability property of binary AIFV-m codes.

Procedure 1(Encoding of a Binary AIFV-m Code). A source sequence $\alpha_1, \alpha_2 \cdots$ is encoded as follows: Set $T = T_0$ and i = 1.

- 1) Encode α_i using T
- 2) Let k be the index such that α_i is encoded using a degree-k master node in T
- 3) Set $T = T_k$; i = i + 1
- 4) Goto line 1

Procedure 2 (Decoding of a Binary AIFV-m Code). Let β be a binary string that is the encoded message. Set $T = T_0$ and i = 1.



Fig. 3: Encoding *cbab* using the binary AIFV-3 code in Figure 2. The first *c* is encoded using a degree-0 master node (leaf) in T_0 so the first *b* is encoded using T_0 . This *b* is encoded using a degree-2 master node, so *a* is encoded using T_2 . *a* is encoded using a degree-1 master node, so the second *b* is encoded using T_1

- 1) Let β_i be longest prefix of β that corresponds to a path from the root of T to some master node M in T
- 2) Let k be the degree of M (as a master node) in T
- 3) Set α_i to be the source symbol assigned to β_i in T
- 4) Remove β_i from the start of β
- 5) Set $T = T_k$; i = i + 1
- 6) Goto line 1



Fig. 4: Decoding 0001010 using the binary AIFV-3 code in Figure 2.

Theorem 3. ([10], Theorem 3). Binary AIFV-m codes are uniquely decodable with delay at most m.

The cost of AIFV-m codes

Definition 6. Let $\mathcal{T}_k(m, n)$ denote the set of all possible typek trees that can appear in a binary AIFV-m code on n source symbols. T_k will be used to denote a tree $T_k \in \mathcal{T}_k(m, n)$. Set $\mathcal{T}(m, n) = \bigotimes_{i=0}^{m-1} \mathcal{T}_k(m, n)$.

 $\mathbf{T} = (T_0, ..., T_{m-1}) \in \mathcal{T}(m, n)$ will be a binary AIFV-m code.

Definition 7. Let $T_k \in \mathcal{T}_k(m, n)$ and σ_i be a source symbol.

- $\ell(T_k, \sigma_i)$ denotes the length of the codeword in T_k for σ_i .
- d(T_k, σ_i) denotes the degree of the master node in T_k assigned to σ_i.
- $\ell(T_k)$ denotes the average length of a codeword in T_k , *i.e.*,

$$\ell(T_k) = \sum_{i=1}^n \ell(T_k, \sigma_i) \cdot p_i$$

 M_j(T_k) = {i ∈ {1, 2, · · · , n} : d(T_k, σ_i) = j} is the set of indices of source nodes that are assigned master nodes of degree j in T_k. Set

$$q(T_k) = (q_0(T_k), \cdots, q_{m-1}(T_k))$$
 where



Fig. 5: Markov chain corresponding to AIFV-3 code in Figure 2. Note that T_1 contains no degree 1 master node, so there is no edge from T_1 to T_1 . Similarly, T_2 contains no degree 2 master node, so there is no edge from T_2 to T_2 .

$$\forall j \in [m], q_j(T_k) = \sum_{i \in M_j(T_k)} pi.$$

 $\sum_{j \in m} q_j(T_k) = 1$, so $q(T_k)$ is a probability distribution. If a source symbol is encoded using a degree-j master node in T_k , then the next source symbol will be encoded using code tree T_j . Since the source is memoryless, the transition probability of encoding using code tree T_j immediately after encoding using code tree T_k is $q_j(T_k)$.

This permits viewing the process as a Markov chain whose states are the code trees. Figure 5 provides an example. From Consequence (a) following Definition 5, $\forall k \in [m]$, every $T_k \in \mathcal{T}_k(m, n)$ contains at least one leaf, so $q_0(T_k) > 0$. Thus, as described in Section I-A this implies that the associated Markov chain is a unichain whose unique recurrence class contains T_0 and whose associated transition matrix Q has a unique stationary distribution π .

Definition 8. Let $T = (T_0, \dots, T_{m-1}) \in \mathcal{T}(m, n)$ be some AIFV-m code, Q(T) be the transition matrix of the associated Markov chain and

$$\boldsymbol{\pi}(\boldsymbol{T}) = (\pi_0(\boldsymbol{T}), \cdots, \pi_{m-1}(\boldsymbol{T}))$$

be Q(T)'s associated unique stationary distribution. Then the average cost of the code is the average length of an encoded symbol in the limit, i.e.,

$$cost(\mathbf{T}) = \sum_{k=0}^{m-1} \ell(T_k) \cdot \pi_k(\mathbf{T}).$$

Definition 9. (The Binary AIFV-m Code problem). Construct a binary AIFV-m code $T \in T(m, n)$ with minimum cost(T), *i.e.*,

$$cost(\mathbf{T}) = \min_{\mathbf{T}' \in \mathcal{T}(m,n)} cost(\mathbf{T}').$$

This problem is exactly the minimum-cost Markov Chain problem introduced in section Section I-A with $\mathbb{S}_k = \mathcal{T}_k(m, n)$.

Proofs of Lemmas and Corollaries

Proof of Corollary 2. With the exception of the uniqueness the proof follows almost directly from the definitions. The details are provided in Corollary 3.3. in [8]. Uniqueness follows from our Theorem 2. \Box

Proof of Lemma 3. First define set

$$g_1' = \left\{ \mathbf{x} = (x_1, x_2, y) \in \mathbb{R}^3 \mid x_1 \in [0, 1] \\ \text{and } y = g_0((x_1, x_2)) = g_2((x_1, x_2)) \right\}$$

By definition,

$$g_1' = \{ E_1(x_1) \mid x_1 \in [0, 1] \}.$$
(9)

Since we know that g_0 and g_2 are piecewise linear, g'_1 is a compact set.

The proof that E_1 is continuous will be by contradiction. Suppose E_1 is not a continuous function. Then there exists $x_1 \in [0, 1]$ and $\epsilon \in \mathbb{R}^+$ along with a sequence of numbers $Z = \{z_1, z_2, ...\} \subset [0, 1]$ satisfying the following properties. The z_i converge to x_1 but $d(E_1(x_1), E_1(z_i)) \ge \epsilon$ for all $z_i \in Z$ where $d(E_1(x_1), E_1(z_i))$ denotes the euclidean distance between $E_1(x_1)$ and $E_1(z_i)$.

Since g'_1 is compact there must exist a subsequence of $\{E_1(z_1), E_1(z_2), ...\}$ that converges to a point in g'_1 . Since the points in Z converge to x_1 this subsequence must converge to a point in g'_1 whose first coordinate is x_1 and the only point in g_1 that satisfies this property is $E_1(x_1)$. But this contradicts the fact that $d(E_1(x_1), E_1(z_i)) \ge \epsilon$ for all $z_i \in Z$. Thus E_1 is continuous.

 $g_0(x_1, x_2)$ and $g_2(x_1, x_2)$ are both piecewise linear functions. This immediately implies that g'_1 is composed of pairwise linear pieces and thus $E_1(x_1)$ is a piecewise linear function.

Proof of Lemma 7. We will first show how to find x'_1 and then explain how finding x'_2 can be done using a similar procedure.

Suppose l < r, $g_0(E'_1(l)) \leq g_1(E'_1(l))$, and $g_0(E'_1(r)) \geq g_1(E'_1(r))$. Since g_0 , g_1 are continuous, there exists $x_1 \in [l, r]$ such that $g_0(E'_1(x_1)) = g_1(E'_1(x_1))$. Recall that from the definition of $E(x_1) g_0(E'_1(x_1)) = g_2(E'_1(x_1))$. Thus

$$g_0(E'_1(x_1)) = g_1(E'_1(x_1)) = g_2(E'_1(x_1))$$

so $E'(x_1) = (x_1^*, x_2^*)$ and, in particular, $x_1 = x_1^*$.

From Lemma 4 we know that $g_0(E'_1(0)) \leq g_1(E'_1(0))$ and $g_0(E'_1(1)) \geq g_1(E'_1(1))$. Thus, after initializing l = 0 and r = 1, a binary halving search finds x'_1 as close as needed to x^* . This is illustrated in Algorithm 2.

The algorithm stops after b' iterations with $r - l = 2^{-b'}$ and $x_1^* \in [l, r]$ so $|x_1^* - x_1'| \le 2^{-b'}$. Setting $l = x_1'$ yields the desired x_1' .

Since Algorithm 2 runs for b' iterations and in each iteration calculating $E'_1(\text{mid})$ needs $O(n^5 \cdot b)$ operations from Lemma 6, the algorithm 2 has total running time of $O(n^5 \cdot b \cdot b') = O(n^5 \cdot b^2)$. Note that Lemma 6 can always be applied because "mid" can always be written using b' bits.

We now see that we can similarly find x'_2 satisfying $|x^*_2 - x'_2| \le 2^{-b'}$. The argument is almost exactly the same as for x'_1 .

Let $\lambda \in [0,1]$ be fixed. Now consider the intersection of a type-0 and type-1 hyperplanes with $h_{2,\lambda}$:

$$f_{0}((x_{1},\lambda),S_{0}) = \ell(S_{0}) + q_{1}(S_{0}) \cdot x_{1} + q_{2}(S_{0}) \cdot \lambda$$

$$f_{1}((x_{1},\lambda),S_{1}) = \ell(S_{1}) + q_{1}(S_{1}) \cdot x_{1} + q_{2}(S_{1}) \cdot \lambda - x_{1}$$

$$= \ell(S_{1}) + (q_{1}(S_{1}) - 1) + q_{2}(S_{1}) \cdot \lambda$$

$$= \ell(S_{1}) - (q_{0}(S_{1}) + q_{2}(S_{1})) \cdot x_{1}$$

$$+ q_{2}(S_{1}) \cdot \lambda$$
(10)

Thus the intersection of each type-0 hyperplane with $h_{2,\lambda}$ corresponds to a line with a non-negative slope and the intersection of each type-1 hyperplane with $h_{2,\lambda}$ corresponds to a line with a negative slope (because we know $q_0(S_i)$ is always positive). Thus the intersection of g_0 and with $h_{2,\lambda}$ is the lower-envelope of non-negative slope lines and the intersection of g_1 and with $h_{2,\lambda}$ is the lower-envelope of negative slope lines.

From this the argument follows exactly the same as for x_1 . and we can also find x'_2 satisfying $|x_2^* - x'_2| \le 2^{-b'}$ in $O(n^5 \cdot b^2)$.

Proof of Lemma 8. Set T_0^* , T_1^* and T_2^* be the trees associated with $\mathbf{x}^* = (x_1^*, x_2^*, y^*)$, the unique intersection of g_0 , g_1 and g_2 .

Following Definition 2, the hyperplanes associated with T_0^* , T_1^* and T_2^* have the formulas

$$y = \ell(T_0^*) + q_1(T_0^*) \cdot x_1 + q_2(T_0^*) \cdot x_2 \tag{11}$$

$$q = \ell(T_1^*) - (q_0(T_1^*) + q_2(T_1)) \cdot x_1 + q_2(T_1^*) \cdot x_2$$
 (12)

$$y = \ell(T_2^*) + q_1(T_2^*) \cdot x_1 - (q_0(T_2^*) + q_1(T_2^*)) \cdot x_2 \quad (13)$$

This can be rewritten as

z

$$-\begin{bmatrix} \ell(T_0^*)\\ \ell(T_1^*)\\ \ell(T_2^*) \end{bmatrix} = \begin{bmatrix} 1 & q_1(T_0^*) & q_2(T_0^*)\\ 1 & q_1(T_1^*) - 1 & q_2(T_1^*)\\ 1 & q_1(T_2^*) & q_2(T_2^*) - 1 \end{bmatrix} \cdot \begin{bmatrix} -y^*\\ x_1^*\\ x_2^* \end{bmatrix}$$
(14)

We denote the matrix used in equation 14 by M. [8] proves that M is invertible. We therefore have:

$$-M^{-1} \begin{bmatrix} \ell(T_0^*) \\ \ell(T_1^*) \\ \ell(T_2^*) \end{bmatrix} = \begin{bmatrix} -y^* \\ x_1^* \\ x_2^* \end{bmatrix}$$
(15)

We also have that:

$$M = \begin{bmatrix} 1 & q_1(T_0^*) & q_2(T_0^*) \\ 1 & q_1(T_1^*) - 1 & q_2(T_1^*) \\ 1 & q_1(T_2^*) & q_2(T_2^*) - 1 \end{bmatrix}$$
$$= \begin{bmatrix} 1 & q_1(T_0^*) & q_2(T_0^*) \\ 1 & -q_0(T_1^*) - q_2(T_1^*) & q_2(T_1^*) \\ 1 & q_1(T_2^*) & -q_0(T_2^*) - q_1(T_2^*) \end{bmatrix}$$

We know that $M^{-1} = \frac{adjM}{detM}$. We also know that each element in M can be written in the format of $k \cdot 2^{-b}$ where $|k| \le 2^{b}$. Using the Leibniz formula for determinants we see that detM can be written as $2^{-2b} \cdot k$ where k is an integer and $|k| \le 6 \cdot 2^{2b}$. Now consider the fact that each element in adjM is ± 1 times the determinant of a 2×2 sub matrix of M. We can use this fact to show that each element in adjM can be written as $2^{-2b} \cdot k'$ where k' is an integer. Finally using $M^{-1} = \frac{adjM}{detM}$, we can show that each element of M^{-1} can be written as $\frac{k'}{k}$ where k and k' are integers and $|k| \le 6 \cdot 2^{2b}$. Therefore x_1^* and x_2^* can be written as

$$\frac{k'_0}{k_0} \cdot \ell(T_0^*) + \frac{k'_1}{k_1} \cdot \ell(T_1^*) + \frac{k'_2}{k_2} \cdot \ell(T_2^*)$$
(16)

where k'_0 , k'_1 , k'_2 , k_0 , k_1 , k_2 are integers and $|k_0|, |k_1|, |k_2| \le 6 \cdot 2^{2b}$ and we know that we can write $\ell(T_i^*)$ as $\ell_i^* \cdot 2^{-b}$ where ℓ_i^* is an integer. We can now write x_1^* and x_2^* in the following format:

$$\frac{k'_0 \cdot \ell^*_0}{k_0 \cdot 2^b} + \frac{k'_1 \cdot \ell^*_1}{k_1 \cdot 2^b} + \frac{k'_2 \cdot \ell^*_2}{k_2 \cdot 2^b}$$
(17)

This means x_1^* and x_2^* can be written as $\frac{a_1}{b_1 \cdot 2^b}$ and $\frac{a_2}{b_2 \cdot 2^b}$ where b_1 , $b_2 \leq 6^3 \cdot 2^{6b} \leq 2^{6b+8}$. This is because all of the terms used for x_i^* have a common denominator of $2^b \cdot k_0 \cdot k_1 \cdot k_2$.

We will now show by contradiction that \mathbf{x}^* lies on the hyperplane associated to T'_0 . If \mathbf{x}^* doesn't lie on the hyperplane associated to T'_0 then we know that the hyperplane associated to T'_0 must be higher than the hyperplane associated to T^*_0 at (x_1^*, x_2^*) . We therefore have:

$$\ell(T'_0) + q_1(T'_0)x_1^* + q_2(T'_0)x_2^* > \\ \ell(T^*_0) + q_1(T^*_0)x_1^* + q_2(T^*_0)x_2^*.$$

Thus,

$$\ell(T'_0) - \ell(T^*_0) + (q_1(T'_0) - q_1(T^*_0))x_1^* + (q_2(T'_0) - q_2(T^*_0))x_2^* > 0$$

Therefore,

$$\ell(T'_0) - \ell(T^*_0) + (q_1(T'_0) - q_1(T^*_0))\frac{a_1}{b_1}2^{-b} + (q_2(T'_0) - q_2(T^*_0))\frac{a_2}{b_2}2^{-b} > 0.$$
(18)

Hence,

$$\ell(T'_0) - \ell(T^*_0) + (q_1(T'_0) - q_1(T^*_0)) \cdot x^*_1 + (q_2(T'_0) - q_2(T^*_0)) \cdot x^*_2 \ge 2^{-(14b+16)}$$

The last inequality comes from the fact that all the terms in equation (18) have a common denominator of $2^{2b} \cdot b1 \cdot b2$ which is at most $2^{(14b+16)}$.

Since T_0' is the lowest type-0 hyperplane at (x_1', x_2') we have:

$$\ell(T'_{0}) + q_{1}(T'_{0}) \cdot x'_{1} + q_{2}(T'_{0}) \cdot x'_{2} \leq \ell(T^{*}_{0}) + q_{1}(T^{*}_{0}) \cdot x'_{1} + q_{2}(T^{*}_{0}) \cdot x'_{2}.$$
(19)

Thus,

$$\ell(T'_0) - \ell(T^*_0) + (q_1(T'_0) - q_1(T^*_0))x'_1 + (q_2(T'_0) - q_2(T^*_0))x'_2 \le 0.$$

Therefore,

$$\ell(T'_{0}) - \ell(T^{*}_{0}) + (q_{1}(T'_{0}) - q_{1}(T^{*}_{0}))x^{*}_{1} + (q_{2}(T'_{0}) - q_{2}(T^{*}_{0}))x^{*}_{2}$$

$$\leq (q_{1}(T'_{0}) - q_{1}(T^{*}_{0}))(x^{*}_{1} - x'_{1}) + (q_{2}(T'_{0}) - q_{2}(T^{*}_{0}))(x^{*}_{2} - x'_{2})$$

$$\Longrightarrow 2^{-(14b+16)} \leq (q_{1}(T'_{0}) - q_{1}(T^{*}_{0})) \cdot (x^{*}_{1} - x'_{1}) + (q_{2}(T'_{0}) - q_{2}(T^{*}_{0})) \cdot (x^{*}_{2} - x'_{2})$$

$$\leq |x^{*}_{1} - x'_{1}| + |x^{*}_{2} - x'_{2}|$$

$$\leq 2 \cdot 2^{-(14b+18)} = 2^{-(14b+17)}$$
(20)

This contradiction shows that \mathbf{x}^* must lie on on the hyperplane associated to T'_0 . We can similarly show the same is true for T'_1 and T'_2 .