Foreground separation methods for satellite observations of the cosmic microwave background

M.P. Hobson¹, A.W. Jones¹, A.N. Lasenby¹ and F.R. Bouchet²

¹Mullard Radio Astronomy Observatory, Cavendish Laboratory, Madingley Road, Cambridge CB3 OHE, UK ²Institut d'Astrophysique de Paris, CNRS, 98 bis Boulevard Arago, F-75014 Paris, France

Accepted ???. Received ???; in original form 7 April 2018

ABSTRACT

A maximum entropy method (MEM) is presented for separating the emission due to different foreground components from simulated satellite observations of the cosmic microwave background radiation (CMBR). In particular, the method is applied to simulated observations by the proposed Planck Surveyor satellite. The simulations, performed by Bouchet and Gispert (1998), include emission from the CMBR, the kinetic and thermal Sunyaev-Zel'dovich (SZ) effects from galaxy clusters, as well as Galactic dust, free-free and synchrotron emission. We find that the MEM technique performs well and produces faithful reconstructions of the main input components. The method is also compared with traditional Wiener filtering and is shown to produce consistently better results, particularly in the recovery of the thermal SZ effect.

Key words: methods: data analysis – techniques: image processing – cosmic microwave background.

I INTRODUCTION

The importance of making accurate measurements of the fluctuations in the CMBR is now widely appreciated. Indeed, by making maps of these fluctuations and by measuring their power spectrum, it is hoped that tight constraints may be placed on fundamental cosmological parameters and that we may distinguish between competing theories of structure formation in the early Universe such as inflation and topological defects.

Several ground-based and balloon-borne experiments are planned over the next few years, and these should provide accurate images of the CMBR fluctuations and lead to a significant improvement in the measurement of the CMBR power spectrum. Nevertheless, these experiments are unlikely to be able to achieve the accuracy required to resolve numerous degeneracies that exist in the parameter set of, for example, the standard inflationary CDM model. As a result, a new generation of CMBR satellites are currently in the final stages of design, and it is hoped that these experiments will provide definitive measurements of the CMBR power spectrum as well as detailed all-sky maps of the fluctuations.

According to current estimates, the NASA MAP satellite is due to be launched in 2000, followed by the ESA Planck Surveyor mission in 2005. Both experiments aim to make high-resolution, low-noise maps of the whole sky at several observing frequencies. As with any CMBR experiment, however, the maps produced will contain contribu-

© 1998 RAS

tions from various foreground components. The main foreground components are expected to be Galactic dust, freefree and synchrotron emission as well as the kinetic and thermal SZ effects from galaxy clusters. In addition, significant contamination from extragalactic points sources is also likely.

It is clear that in order to obtain maps of the CMBR fluctuations alone it is necessary to separate the emission due to these various components. The removal of point sources from the satellite observations is perhaps the most troublesome aspect of this separation, since our knowledge of the various populations of sources is incomplete. Nevertheless, at observing frequencies in the range 10–100 GHz, we expect the point sources to be mainly radio-loud AGN. including flat-spectrum radiogalaxies and QSOs, blazars and possibly some inverted-spectrum radiosources. At higher observing frequencies in the range 300–900 GHz, the dominant point sources should be infrared luminous galaxies, radioquiet AGN and smaller numbers of high-redshift galaxies and QSOs. However, since the frequency spectra of many of these extragalactic objects are, in general, rather complicated, any extrapolation of their emission over a wide frequency interval must be performed with caution.

For small fields, a straightforward and effective technique for removing point sources is to make high-resolution, high-flux-sensitivity observations of each field, at frequencies close to those of the CMBR experiment. The point sources can then be identified and accurately subtracted from the maps (O'Sullivan et al. 1995). For multifrequency all-sky satellite observations, however, such a procedure is infeasible. Nevertheless, for the Planck Surveyor, it is expected that a significant fraction of point sources may be identified and removed using the satellite observations themselves, together perhaps with pre-existing surveys. Based on the estimated sensitivity of the Planck Surveyor to point sources, De Zotti et al. (1997) find that it is straightforward, at each observing frequency independently, to subtract all sources brighter than 1 Jy and that it may be possible to subtract all sources brighter than 100 mJy at intermediate frequencies where the CMBR emission peaks. Careful modelling of the likely point source contamination also suggests that the number of pixels affected at each frequency should only be a small percentage of the total number. Moreover, De Zotti et al. find the level of fluctuations due to unsubtracted sources to be very low. Similar conclusions follow from the model of Guiderdoni et al. (1997, 1998). Using simulated maps of point sources (Toffolatti et al. 1998), a full investigation of their effects on Planck Surveyor observations will be presented in a forthcoming paper (Hobson et al, in preparation).

Aside from extragalactic point sources, the other physical components mentioned above have reasonably well defined spectral characteristics, and we may use this information, together with multifrequency observations, to distinguish between the various foregrounds. Several linear methods have been suggested to perform this separation, many of which are based on Wiener filtering (e.g. Bouchet, Gispert & Puget 1996; Tegmark & Efstathiou 1996; Bouchet et al. 1997). In this paper, however, we investigate the use of a non-linear maximum entropy method (MEM) for separating out the emission due to different physical components and compare its performance with the Wiener filter approach. We apply these methods to simulated observations from the Planck surveyor satellite but, of course, the same algorithms can be used to analyse data from the MAP satellite. The application of the MEM technique to simulated interferometer observations of the CMBR is discussed in Maisinger, Hobson & Lasenby (1997) and the method has also been applied to the analysis of ground-based switched-beam observations by Jones et al. (1997).

2 SIMULATED PLANCK SURVEYOR OBSERVATIONS

In order to create simulated Planck Surveyor observations, we must first build a realistic model of the sky at each of the proposed observing frequencies. As mentioned above, dust, free-free and synchrotron emission from our own Galaxy, extragalactic radiosources and infrared galaxies, and the kinetic and thermal SZ effect from clusters of galaxies all contribute to sky emission at least at some frequencies and angular resolutions of interest. We assume that point sources may be removed as described above, and that the residual background of unsubtracted sources is negligible. Thus the simulations presented here include emission from the three Galactic components, the two SZ effects and the primordial CMBR fluctuations.

Simulated maps of these six components are constructed on 10×10 -degree fields with 1.5 arcmin pixels; thus each map consists of 400×400 pixels. A detailed discussion of these simulations is given by Bouchet et al. (1997), Gispert & Bouchet (1997) and Bouchet & Gispert (1998). The primary CMBR fluctuations are a realisation of a COBE-normalised standard CDM model with critical density and a Hubble parameter $H_0 = 50$ km s⁻¹ Mpc⁻¹ (using a program kindly provided by J.R. Bond). Realisations of the kinetic and thermal SZ effects are generated using the Press-Schechter formalism, as discussed in Aghanim et al. (1997), which yields the number density of clusters per unit redshift, solid angle and flux density interval. The gas profiles of individual clusters are taken as King models, and their peculiar radial velocities are drawn at random from an assumed Gaussian velocity distribution with a standard deviation at z = 0 of 400 km s⁻¹.

For the Galactic dust and free-free emission, $100-\mu m$ IRAS maps are used as spatial templates. Comparison of dust, free-free and 21cm HI emission suggests the existence of a spatial correlation between these components (Kogut et al. 1996; Boulanger et al. 1996). In order to take account of these correlations, the simulations assume the existence of an HI-correlated component that accounts for 50 per cent of the free-free emission and 95 per cent of the dust emission. The remaining free-free and dust emission is assumed to come from a second, HI-uncorrelated component. For any particular simulation, a given $100-\mu m$ IRAS map is used as a spatial template for the HI-correlated component and a contiguous map is used for the HI-uncorrelated component. The dust spectral behaviour is modelled as a single temperature component at 18 K with dust emissivity $\propto \nu^2$; the rms level of fluctuations at any given frequency is scaled accordingly from the 100- μ m IRAS map. The IRAS map used here has an rms level approximately equal to the median level for such maps, i.e. about one-half of IRAS $100-\mu m$ maps of this size have a lower rms, and half have a higher rms when scales between 1 and 3 degrees are included (see Bouchet et al. 1996 for details). The free-free intensity is assumed to vary as $I \propto \nu^{-0.16}$, and is normalised to give an rms temperature fluctuation of 6.2 μ K at 53 GHz.

No spatial template is available for the synchrotron emission at a sufficiently high angular resolution, so the simulations of this component are performed using the 408 MHz radio maps of Haslam et al. (1982), which have a resolution of 0.85 degrees, and adding to them (Gaussian) small scale structure that follows a $C_{\ell} \propto \ell^{-3}$ power spectrum. The synchrotron intensity is assumed vary as $I \propto \nu^{-0.9}$ and its normalisation taken directly from the 408 MHz maps.

For primary CMBR fluctuations it is usual to work in terms of temperature rather than intensity. A temperature difference on the sky $\Delta T_{\rm cmb}(\hat{x})$ leads to a fluctuation in the intensity given by

$$\Delta I_{\rm cmb}(\hat{\boldsymbol{x}},\nu) \approx \left. \frac{\partial B(\nu,T)}{\partial T} \right|_{T=T_0} \Delta T_{\rm cmb}(\hat{\boldsymbol{x}}),$$

where $B(\nu, T)$ is the Planck function and $T_0 = 2.726$ K is the mean temperature of the CMBR (Mather et al. 1994). The conversion factor can be approximated by

$$\left. \frac{\partial B(\nu,T)}{\partial T} \right|_{T=T_0} \approx 24.8 \left[\frac{x^2}{\sinh(x/2)} \right]^2 \text{ Jy sr}^{-1} \ (\mu \text{K})^{-1}$$

where $x \approx \nu/56.8$ GHz. In order to compare the relative level of fluctuations in each physical component we shall



Figure 1. The 10×10 -degree realisations of the six input components used to make simulated Planck Surveyor observations: (a) primary CMBR fluctuations; (b) kinetic SZ effect; (c) thermal SZ effect; (d) Galactic dust; (e) Galactic free-free; (f) Galactic synchrotron emission. Each component is plotted at 300 GHz and has been convolved with a Gaussian beam of FWHM equal to 4.5 arcmin, the maximum angular resolution proposed for the Planck Surveyor. The map units are equivalent thermodynamic temperature in μK .

adopt the convention of Tegmark & Efstathiou (1996) and also define the equivalent thermodynamic temperature fluctuation for the other components by

$$\Delta T_p(\hat{\boldsymbol{x}}, \nu) \approx \frac{\Delta I_p(\hat{\boldsymbol{x}}, \nu)}{\partial B(\nu, T_0)/\partial T}$$

where p denotes the relevant physical foreground component. We note that, in general, the 'temperature' fluctuations of these other components will be frequency dependent, unlike those of the CMBR. For the remainder of this paper, fluctuations will be quoted in temperature units measured in μ K.

The realisations of the six input components used to make simulated observations are shown in Fig. 1. Each component is plotted at 300 GHz and, for illustration purposes, has been convolved with a Gaussian beam of FWHM equal to 4.5 arcmin, which is the highest angular resolution proposed for the Planck Surveyor. For convenience, we have also set the mean of each map to zero, in order to highlight the relative level of fluctuations due to each component.

From Fig. 1 we see that, as expected, the emission due to primordial CMBR fluctuations appears Gaussian in nature. This is, of course, a direct consequence of using a standard inflationary CDM model to create this realisation. If the CMBR realisation were instead created assuming an alternative theory of structure formation such as topological defects, for example, then the CMBR fluctuations are not required to be Gaussian, but may exhibit sharp edges or highly non-Gaussian localised hot spots (Bouchet, Bennett & Stebbins 1988, Turok 1996). The emission due to the kinetic and thermal SZ effects is clearly highly non-Gaussian, being dominated by resolved and unresolved clusters that appears as sharp peaks of emission. As we would expect, although an obvious correlation exists between the positions of the kinetic and thermal SZ effects, the signs and magnitudes of the kinetic effect are not correlated with those of the thermal effect. We also note that the IRAS $100-\mu m$ maps used as templates for the Galactic dust and free-free emission also appear quite non-Gaussian; the imposed correlation between the dust and free-free emission is also clearly seen. Finally, the synchrotron emission seems quite Gaussian, although this appearance is due mainly to the addition to the Haslam 408 MHz map of Gaussian small scale structure, following a $C_{\ell} \propto \ell^{-3}$ power law, on angular scales below 0.85 degrees.

The azimuthally-averaged power spectra of the input maps are shown in Fig. 2. At lower multipoles, all three Galactic components have power spectra which vary roughly as $C_{\ell} \propto \ell^{-3}$ (for the synchrotron component small scale structure with this power spectrum was added artificial for $\ell \gtrsim 250$). For the kinetic and thermal SZ effects, however, the power spectra are quite different and are better approximated by a white-noise power spectrum $C_{\ell} \propto \text{constant}$, as expected for Poisson-distributed processes.

Using the realisations for each physical component shown in Fig. 1, it is straightforward to simulate Planck Surveyor observations. The satellite is made up of two mains parts: the Low Frequency Instrument (LFI), which uses HEMT radio receivers, and the High Frequency Instrument (HFI), which contains bolometer arrays. Since the final design of the satellite is still undecided, the precise values of observational parameters for the LFI and HFI are subject



Figure 2. The azimuthally-averaged power spectra of the input maps at 300 GHz.

to revision. Nevertheless, recent proposed changes to both instruments may significantly improve the sensitivity of the satellite, as compared to the design outlined in the ESA phase A study (Bersanelli et al. 1996). Therefore, although these modifications are not yet finalised, we have incorporated the latest design specifications into our simulations. The parameters used in making the simulated observations are given in Table 2.

The simulated observations are produced by integrating the emission due to each physical component across each waveband, assuming the transmission is uniform across the band. At each observing frequency, the total sky emission is convolved with a Gaussian beam of the appropriate FWHM. Finally, isotropic noise is added to the maps, assuming a spatial sampling rate of FWHM/2.4 at each frequency (thus the noise rms of the maps is about 2.4 times *higher* than the instrumental sensitivity per FWHM quoted in Table 2). We note, however, that the assumption of isotropic noise is not required by the separation algorithms discussed in Section 3. We have also assumed that any striping due to the scanning strategy and 1/f noise has been removed to sufficient accuracy that any residuals are negligible.

Fig. 3 shows the rms temperature fluctuations at each observing frequency due to each physical component, after convolution with the appropriate beam. The rms noise per pixel at each frequency channel is also plotted. We see from the figure that, as expected, the rms temperature fluctuation of the CMBR is almost constant across the frequency channels; the only variation being due to the convolution with beams of different sizes. Furthermore, for all channels up to 217 GHz, the CMBR signal is several times the level of the instrumental noise even for a pixelisation at FWHM/2.4(which boosts by 2.4 the noise level per FWHM). At higher frequencies, the noise level exceeds the CMBR signal but is itself dominated by Galactic dust emission. We also see a sharp dip in the rms level of the thermal SZ effect at 217 GHz, since the emission from this component is close to zero at this frequency. At any given frequency, the rms level of the thermal SZ effect is at least an order of magnitude below that of the dominant component. The kinetic SZ effect has the same spectral characteristics as the CMBR, but the effect of convolution with beams of different sizes has a sig-

 Table 1. Proposed observational parameters for the Planck Surveyor satellite (Efstathiou, private communication). Angular resolution is quoted as FWHM for a Gaussian beam. Sensitivities are quoted per FWHM for 12 months of observation.

	Low Frequency Instrument				High Frequency Instrument					
Central frequency (GHz):	30	44	70	100	100	143	217	353	545	857
Fractional bandwidth $(\Delta \nu / \nu)$:	0.2	0.2	0.2	0.2	0.37	0.37	0.37	0.37	0.37	0.37
Transmission:	1.0	1.0	1.0	1.0	0.3	0.3	0.3	0.3	0.3	0.3
Angular resolution (arcmin):	33	23	14	10	10.6	7.4	4.9	4.5	4.5	4.5
ΔT sensitivity (μK):	4.4	6.5	9.8	11.7	4.9	5.7	12.5	40.9	392	12621



Figure 3. The rms thermodynamic temperature fluctuations at each Planck Surveyor observing frequency due to each physical component, after convolution with the appropriate beam and using a sampling rate of FWHM/2.4. The rms noise per pixel at each frequency channel is also plotted.

nificant effect on the point-like emission and leads to a more pronounced variation in the observed rms level than for the CMBR (since then most of the power is at small scales). The observed rms level of the kinetic SZ is at least two orders of magnitude below the dominant component at any given frequency. In a similar manner, the Galactic free-free and synchrotron emission are also completely dominated by either CMBR or dust emission at all observing frequencies.

The observed maps at each of the ten Planck Surveyor frequencies are shown in Fig. 4 in units of equivalent thermodynamic temperature measured in μ K. The coarser pixelisation at the lower observing frequencies is due to the FWHM/2.4 sampling rate. Moreover, at these lower frequencies, the effect of convolution with the relatively large beam is also easily seen. As the observing frequency increases, the beam size becomes smaller, leading to a corresponding increase in the sampling rate. Consequently, the observed maps more closely resemble the input map of the dominant physical component at each frequency. As may have been anticipated from Fig. 3, the emission in the lowest seven channels is dominated by the CMBR, whereas dust emission dominates in the highest three channels. Indeed, the main reason for the inclusion of the highest frequency channels is to obtain an accurate dust model, in order that it may be subtracted from lower frequency channels with some confidence. Perhaps the most notable feature of the ten channels maps is that, at least by eye, it is not possible to discern features due to physical components other than the CMBR or dust.

3 COMPONENT SEPARATION METHODS

As a first step in discussing component separation methods, let us consider in more detail how the simulated data are made. At any given frequency ν the total rms temperature fluctuation on the sky in a direction \hat{x} is given by the superposition of n_c physical components ($n_c = 6$ in our simulations). It is convenient to factorise the contribution of each process into a spatial template $s_p(\hat{x})$ at a reference frequency ν_0 and a frequency dependence $f_p(\nu)$, so that

$$\Delta T(\hat{\boldsymbol{x}},\nu) = \sum_{p=1}^{n_c} \Delta T_p(\hat{\boldsymbol{x}},\nu) = \sum_{p=1}^{n_c} f_p(\nu) s_p(\hat{\boldsymbol{x}})$$

In this paper we take the reference frequency $\nu_0 = 300$ GHz and normalise the frequency dependencies such that $f_p(\nu_0) = 1$.

If we observe the sky at n_f observing frequencies then, in any given direction \hat{x} , we obtain a n_f -component data vector that contains the observed temperature fluctuation in this direction at each observing frequency plus instrumental noise. In order to relate this data vector to the emission from each physical component it is useful to introduce the $n_f \times n_c$ frequency response matrix with components defined by

$$F_{\nu p} = \int_0^\infty t_{\nu}(\nu') f_p(\nu') \,\mathrm{d}\nu'$$
 (1)

where $t_{\nu}(\nu')$ is the frequency response (or transmission) of the ν th frequency channel. Assuming that the satellite observing beam in each channel is spatially invariant, we may write the beam-smoothing as a convolution and, in discretised form, the ν th component of the data vector in the direction \hat{x} is then given by

$$d_{\nu}(\hat{x}) = \sum_{j=1}^{N_p} P_{\nu}(|\hat{x} - \hat{x}_j|) \sum_{p=1}^{n_c} F_{\nu p} s_p(\hat{x}_j) + \epsilon_{\nu}(\hat{x})$$
(2)

where $P_{\nu}(\hat{x})$ is the beam profile for the ν th frequency channel, and the index j labels the N_p pixels in each of the simulated input maps shown in Fig. 1; the $\epsilon_{\nu}(\hat{x})$ term represents the instrumental noise in the ν th channel in the direction \hat{x} .

In each channel the beam profile is assumed spatially invariant and the noise statistically homogeneous (which are both reasonable assumptions for small fields), and it is more convenient to work in Fourier space, since the convolution in (2) becomes a simple multiplication and we obtain



Figure 4. The 10 × 10-degree maps observed at each of the ten Planck Surveyor frequencies listed in Table 2. At each frequency we assume a Gaussian beam with the appropriate FWHM and a sampling rate of FWHM/2.4. Isotropic noise with the relevant rms has been added to each map. The map units are equivalent thermodynamic temperature in μ K.

$$\widetilde{d}_{\nu}(\boldsymbol{k}) = \sum_{p=1}^{n_c} R_{\nu p}(\boldsymbol{k}) \widetilde{s}_p(\boldsymbol{k}) + \widetilde{\epsilon}_{\nu}(\boldsymbol{k}), \qquad (3)$$

where $R_{\nu p}(\mathbf{k}) = P_{\nu}(\mathbf{k})F_{\nu p}$ are the components of the *response matrix* for the observations. It is important to note that (3) is satisfied at each Fourier mode \mathbf{k} independently. Thus, in matrix notation, at each mode we have

$$\mathbf{d} = \mathbf{R}\mathbf{s} + \boldsymbol{\epsilon} \tag{4}$$

where **d**, **s** and ϵ are column vectors containing n_f , n_c and n_f complex components respectively, and the response matrix **R** has dimensions $n_f \times n_c$. Although the column vectors in (4) refer to quantities defined in the Fourier domain, it should be noted that for later convenience they are not written with a tilde.

The significant simplification that results from working in the Fourier domain is clear, since the dimensions of the matrices in (4) are rather small $(n_c = 6 \text{ and } n_f = 10 \text{ in})$ our simulations). Thus, the situation reduces to the solving a small-scale linear inversion problem at each Fourier mode separately. Once this inversion has been performed for all the measured modes, the spatial templates for the sky emission due to each physical component at the reference frequency ν_0 are then obtained by an inverse Fourier transformation. Owing to the presence of instrumental noise, however, it is clear that the inverse, \mathbf{R}^{-1} , of the response matrix at each Fourier mode does not exist and that the linear inversion problem in each case is degenerate. The approximate inversion of (4) must therefore be performed using a statistical technique in which the inversion is regularised in some way. This naturally leads us to consider a Bayesian approach.

3.1 Bayes' theorem

Bayes' theorem states that, given a hypothesis H and some data D the posterior probability $\Pr(H|D)$ is the product of the likelihood $\Pr(D|H)$ and the prior probability $\Pr(H)$, normalised by the evidence $\Pr(D)$,

$$\Pr(H|D) = \frac{\Pr(H)\Pr(D|H)}{\Pr(D)}$$

In our application, we consider each Fourier mode k separately and, from (4), we see that the data consist of the n_f complex numbers in the data vector \mathbf{d} , and we take the 'hypothesis' to consist of the n_c complex numbers in the signal vector \mathbf{s} . We then choose as our estimator $\hat{\mathbf{s}}$ of the signal vector that which maximises the posterior probability $\Pr(\mathbf{s}|\mathbf{d})$. Since the evidence in Bayes' theorem is merely a normalisation constant we must therefore maximise with respect to \mathbf{s} the quantity

$$\Pr(\mathbf{s}|\mathbf{d}) \propto \Pr(\mathbf{d}|\mathbf{s}) \Pr(\mathbf{s})$$
 (5)

which is the product of the likelihood $\Pr(d|s)$ and the prior $\Pr(s)$.

Let us first consider the form of the likelihood. If the instrumental noise on each frequency channel is Gaussiandistributed, then at each Fourier mode the probability distribution of the n_f -component noise vector $\boldsymbol{\epsilon}$ is described by an n_f -dimensional multivariate Gaussian. Assuming the expectation value of the noise to be zero at each observing frequency, the likelihood is therefore given by

$$\Pr(\mathbf{d}|\mathbf{s}) \propto \exp\left(-\epsilon^{\dagger}\mathbf{N}^{-1}\epsilon\right)$$
$$\propto \exp\left[-(\mathbf{d}-\mathbf{Rs})^{\dagger}\mathbf{N}^{-1}(\mathbf{d}-\mathbf{Rs})\right], \tag{6}$$

where the dagger denotes the Hermitian conjugate and in the second line we have used (4). We note that no factor of 1/2 appears in the exponent in (6) since it refers to the multivariate Gaussian distribution of a set of complex random variables. The *noise covariance matrix* **N** has dimensions $n_f \times n_f$ and at any given Fourier mode **k** it is defined by

$$\mathbf{N}(\boldsymbol{k}) = \langle \boldsymbol{\epsilon}(\boldsymbol{k}) \boldsymbol{\epsilon}^{\dagger}(\boldsymbol{k}) \rangle, \tag{7}$$

i.e. its elements are given by $N_{\nu\nu'}(\mathbf{k}) = \langle \tilde{\epsilon}_{\nu}(\mathbf{k}) \tilde{\epsilon}_{\nu'}(\mathbf{k}) \rangle$, where the asterisk denotes complex conjugation. Thus, at a given Fourier mode, the ν th diagonal element of **N** contains the value at that mode of the ensemble-averaged power spectra of the instrumental noise on the ν th frequency channel. If the noise is uncorrelated between channels then the off-diagonal elements are zero for all \mathbf{k} .

We note that the expression in square brackets in (6) is simply the χ^2 misfit statistic. Since, for a given set of observations, the data vector **d**, the response matrix **R** and the noise covariance matrix **N** are all fixed, we may consider the misfit statistic as a function only of the signal vector **s**,

$$\chi^{2}(\mathbf{s}) = (\mathbf{d} - \mathbf{R}\mathbf{s})^{\dagger} \mathbf{N}^{-1} (\mathbf{d} - \mathbf{R}\mathbf{s}), \tag{8}$$

so that the likelihood can be written as

$$\Pr(\mathbf{d}|\mathbf{s}) \propto \exp[-\chi^2(\mathbf{s})]. \tag{9}$$

Having calculated the form of the likelihood we must now turn our attention to the form of the prior probability $Pr(\mathbf{s})$.

3.2 The Gaussian prior

If we assume that the emission due to each of the physical components shown in Fig. 1 is well approximated by a Gaussian random field, then it is straightforward to derive an appropriate form for the prior $Pr(\mathbf{s})$. In this case, the probability distribution of the sky emission is described by a multivariate Gaussian distribution, characterised by a given sky covariance matrix. Thus, at each mode \mathbf{k} in Fourier space, the probability distribution of the signal vector \mathbf{s} is also described by a multivariate Gaussian of dimension n_c , where n_c is the number of distinct physical components ($n_c = 6$ in our simulations). The prior therefore has the form

$$\Pr(\mathbf{s}) \propto \exp\left(-\mathbf{s}^{\dagger} \mathbf{C}^{-1} \mathbf{s}\right),$$
(10)

where the signal covariance matrix \mathbf{C} is real with dimensions $n_c \times n_c$ and is given by

$$C(k) = \langle \mathbf{s}(k) \mathbf{s}^{\dagger}(k) \rangle, \qquad (11)$$

i.e. it has elements $C_{pp'}(\mathbf{k}) = \langle \tilde{s}_p(\mathbf{k}) \tilde{s}_{p'}^*(\mathbf{k}) \rangle$. Thus, at each Fourier mode, the *p*th diagonal element of **C** contains the value of the ensemble-averaged power spectrum of the *p*th physical component at the reference frequency ν_0 ; the off-diagonal terms describe cross-power spectra between the components.

Strictly speaking, the use of this prior requires advance knowledge of the full covariance structure of the processes that we are trying to reconstruct. Nevertheless, it is anticipated that some information concerning the power spectra of the various components, and correlations between them, will be available either from pre-existing observations or by performing an initial approximate separation using, for example, the singular value decomposition (SVD) algorithm (see Bouchet et al. 1997, Bouchet & Gispert 1998). A discussion of the SVD solution, in the context of Bayes' theorem, is given in Appendix C. This information can then be used to construct an approximate signal covariance matrix for use in $\Pr(\mathbf{s})$.

Substituting (9) and (10) into (5), the posterior probability is then given by

$$\Pr(\mathbf{s}|\mathbf{d}) \propto \exp\left[-\chi^2(\mathbf{s}) - \mathbf{s}^{\dagger} \mathbf{C}^{-1} \mathbf{s}\right].$$
(12)

where $\chi^2(\mathbf{s})$ is given by (8). Completing the square for \mathbf{s} in the exponential (see Zaroubi et al. 1995), it is straightforward to show that the posterior probability is also a multivariate Gaussian of the form

$$\Pr(\mathbf{s}|\mathbf{d}) \propto \exp\left[-(\mathbf{s}-\hat{\mathbf{s}})^{\dagger}\mathbf{E}^{-1}(\mathbf{s}-\hat{\mathbf{s}})\right].$$
(13)

which has its maximum value at the estimate \hat{s} of the signal vector and where **E** is the covariance matrix of the reconstruction errors.

The estimate $\hat{\mathbf{s}}$ of the signal vector is found to be

$$\hat{\mathbf{s}} = \left(\mathbf{C}^{-1} + \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R}\right)^{-1} \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{d} \equiv \mathbf{W} \mathbf{d},\tag{14}$$

where we have identified the Wiener matrix \mathbf{W} . Thus, we find that by assuming a Gaussian prior of the form (10) in Bayes' theorem, we recover the standard Wiener filter. This optimal linear filter is usually derived by choosing the elements of \mathbf{W} such that they minimise the variances of the resulting reconstruction errors. From (14) we see that at a given Fourier mode, we may calculate the estimator $\hat{\mathbf{s}}$ that maximises the posterior probability simply by multiplying the data vector \mathbf{d} by the Wiener matrix \mathbf{W} . Equation (14) can also be derived straightforwardly by differentiating (12) with respect \mathbf{s} and equating the result to zero (see Appendix A).

As is well-known, the assignment of errors on the Wiener filter reconstruction is straightforward and the covariance matrix of the reconstruction errors \mathbf{E} in (14) is given by

$$\mathbf{E} \equiv \langle (\mathbf{s} - \hat{\mathbf{s}}) (\mathbf{s} - \hat{\mathbf{s}})^{\dagger} \rangle = \left(\mathbf{C}^{-1} + \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R} \right)^{-1}$$
(15)

Since the posterior probability (13) is Gaussian, this matrix is simply the inverse Hessian or curvature matrix of (minus) the exponent in (13), evaluated at \hat{s} (see Appendix A).

It should be noted that the linear nature of the Wiener filter and the simple propagation of errors are both direct consequences of assuming that the spatial templates we wish to reconstruct are well-described by Gaussian random fields with a known covariance structure. Several applications are given in Bouchet et al. (1997).

3.3 The entropic prior

It is clear from Fig. 1 that the emission due to several of the underlying physical processes is far from Gaussian. This is particularly pronounced for the kinetic and thermal SZ effects, but the Galactic dust and free-free emissions also appear quite non-Gaussian. Ideally, one might like to assign priors for the various physical components by measuring empirically the probability distribution of temperature fluctuations from numerous realisations of each component. This is not feasible in practice, however, and instead we consider here the use of the entropic prior, which is based on information-theoretic considerations alone.

Let us consider a discretised image h_j consisting of L cells, so that j = 1, ..., L; we may consider the h_j as the components of an image vector **h**. Using very general notions of subset independence, coordinate invariance and system independence, it may be shown (Skilling 1989) that the prior probability assigned to the values of the components in this vector should take form

$\Pr(\mathbf{h}) \propto \exp[\alpha S(\mathbf{h}, \mathbf{m})],$

where the dimensional constant α depends on the scaling of the problem and may be considered as a regularising parameter, and **m** is a model vector to which **h** defaults in the absence of any data. The function $S(\mathbf{h}, \mathbf{m})$ is the *cross entropy* of **h** and **m**. In standard applications of the maximum entropy method, the image **h** is taken to be a positive additive distribution (PAD). Nevertheless, the MEM approach can be extended to images that take both positive and negative values by considering them to be the difference of two PADS, so that

 $\mathbf{h} = \mathbf{u} - \mathbf{v}.$

where **u** and **v** are the positive and negative parts of **h** respectively. In this case, the cross entropy is given by (Gull & Skilling 1990; Hobson & Lasenby 1998)

$$S(\mathbf{h}, \mathbf{m}_{u}, \mathbf{m}_{v}) = \sum_{j=1}^{L} \left\{ \psi_{j} - m_{uj} - m_{vj} - h_{j} \ln \left[\frac{\psi_{j} + h_{j}}{2m_{uj}} \right] \right\}, (16)$$

where $\psi_j = [h_j^2 + 4m_{uj}m_{vj}]^{1/2}$ and \mathbf{m}_u and \mathbf{m}_v are separate models for each PAD. The global maximum of the cross entropy occurs at $\mathbf{h} = \mathbf{m}_u - \mathbf{m}_v$.

In our application, we might initially suppose that at each Fourier mode we should take the 'image' to be the n_c components of the signal vector **s**. However, this results in two additional complications. First, the components of signal vector are, in general, complex, but the cross entropy given in (16) is defined only if the image \mathbf{h} is real. Nevertheless, the MEM technique can be straightforwardly extended to the reconstruction of a complex image by making a slight modification to the above discussion. If the image \mathbf{h} is complex, then models \mathbf{m}_u and \mathbf{m}_v are also taken to be complex. In this case, the real and imaginary parts of \mathbf{m}_u are the models for the positive portions of the real and imaginary parts of h respectively. Similarly, the real and imaginary parts of \mathbf{m}_v are the models for the negative portions of the real and imaginary parts of the image. The total cross entropy is then obtained by evaluating the sum (16) using first the real parts and then the imaginary parts of **h**, \mathbf{m}_u and \mathbf{m}_v , and adding the results. Thus the total cross entropy for the complex image **h** is given by

$$S(\Re(\mathbf{h}), \Re(\mathbf{m}_u), \Re(\mathbf{m}_v)) + S(\Im(\mathbf{h}), \Im(\mathbf{m}_u), \Im(\mathbf{m}_v)),$$
(17)

where \Re and \Im denote the real and imaginary parts of each vector. For simplicity we denote the sum (17) by $S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v)$ where the subscript *c* indicates that it is the entropy of a complex image.

The second complication mentioned above is more subtle and results from the fact that one of the fundamental axioms of the MEM is that it should not itself introduce correlations between individual elements of the image. However, as discussed in previous subsection, the elements of the signal vector **s** at each Fourier mode may well be correlated, this correlation being described by the signal covariance matrix **C** defined in (11). Moreover, if prior information is available concerning these correlations, we would wish to include it in our analysis. We are therefore lead to consider the introduction of an intrinsic correlation function (ICF) into the MEM framework (Gull & Skilling 1990).

The inclusion of an ICF is most easily achieved by assuming that, at each Fourier mode, the 'image' does not consist of the components of the signal vector \mathbf{s} , but that instead \mathbf{h} consists of the components of a vector of hidden variables that are related to the signal vector by

$$\mathbf{s} = \mathbf{L}\mathbf{h},\tag{18}$$

The $n_c \times n_c$ lower triangular matrix **L** in (18) is that obtained by performing a Cholesky decomposition of the signal covariance matrix, i.e. $\mathbf{C} = \mathbf{L}\mathbf{L}^{\mathrm{T}}$. We note that since **C** is real then so is **L**. Thus, if the components of **h** are apriori uncorrelated (thereby satisfying the MEM axiom) and of unit variance, so that $\langle h_p h_{p'}^* \rangle = \delta_{pp'}$, we find that, as required, the *a priori* covariance structure of the signal vector is given by

$$\langle ss^{\dagger} \rangle = \langle Lhh^{\dagger}L^{\mathrm{T}} \rangle = L \langle hh^{\dagger} \rangle L^{\mathrm{T}} = LL^{\mathrm{T}} = C$$

Moreover, using this construction the expected rms level for the real or imaginary part of each element of **h** is simply equal to $1/\sqrt{2}$. Therefore, at each Fourier mode, we assign the real and imaginary parts of every component in the model vectors \mathbf{m}_u and \mathbf{m}_v to be equal to $m = 1/\sqrt{2}$.

Substituting (18) into (8), χ^2 can also be written in terms of **h** and is given by

$$\chi^{2}(\mathbf{h}) = (\mathbf{d} - \mathbf{R}\mathbf{L}\mathbf{h})^{\dagger}\mathbf{N}^{-1}(\mathbf{d} - \mathbf{R}\mathbf{L}\mathbf{h}).$$
(19)

Thus, using an entropic prior, the posterior probability becomes

$$\Pr(\mathbf{h}|\mathbf{d}) \propto \exp\left[-\chi^2(\mathbf{h}) + \alpha S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v)\right].$$
(20)

where the cross entropy $S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v)$ is given by (17) and (16).

3.4 Maximising the posterior probability

As discussed in Section 3.1, we choose our estimate $\hat{\mathbf{s}}$ of the signal vector at each Fourier mode, as that which maximises the posterior probability $\Pr(\mathbf{s}|\mathbf{d})$ with respect to \mathbf{s} .

For the Gaussian prior, we found in subsection 3.2 that the posterior probability is also a Gaussian and that the estimate $\hat{\mathbf{s}}$ is given directly by the linear relation (14). Nevertheless, we also note that, in terms of **h** defined in (18), the quadratic form in the exponent of the Gaussian prior (10) has the particularly simple form

$$\mathbf{s}^{\dagger}\mathbf{C}^{-1}\mathbf{s} = \mathbf{h}^{\dagger}\mathbf{L}^{\mathrm{T}}(\mathbf{L}\mathbf{L}^{\mathrm{T}})^{-1}\mathbf{L}\mathbf{h} = \mathbf{h}^{\dagger}\mathbf{L}^{\mathrm{T}}(\mathbf{L}^{\mathrm{T}})^{-1}\mathbf{L}^{-1}\mathbf{L}\mathbf{h} = \mathbf{h}^{\dagger}\mathbf{h},$$

i.e. it is equal to the inner product of \boldsymbol{h} with itself. Thus, using a Gaussian prior, the posterior probability can be written in terms of \boldsymbol{h} as

$$\Pr(\mathbf{h}|\mathbf{d}) \propto \exp\left[-\chi^2(\mathbf{h}) - \mathbf{h}^{\dagger}\mathbf{h}\right].$$
(21)

where $\chi^2(\mathbf{h})$ is given by (19) Therefore, in addition to using the linear relation (14), the Wiener filter estimate $\hat{\mathbf{s}}$ can also be found by first minimising the function

$$\Phi_{\rm WF}(\mathbf{h}) = \chi^2(\mathbf{h}) + \mathbf{h}^{\dagger} \mathbf{h}, \tag{22}$$

to obtain the estimate $\hat{\mathbf{h}}$ of the corresponding hidden vector, and then using (18) to give $\hat{\mathbf{s}} = \mathbf{L}\hat{\mathbf{h}}$.

We have developed an algorithm (which will be presented in a forthcoming paper) for minimising the function $\Phi_{\rm WF}$ with respect to **h**. Indeed, this algorithm calculates the reconstruction $\hat{\mathbf{h}}$ in slightly less CPU time than the matrix inversions and multiplications required to evaluate the linear relation (14). The minimiser requires only the first derivatives of the function and these are given in Appendix A.

Let us now consider the MEM solution. From (20), we see that maximising the posterior probability when assuming an entropic prior is equivalent to minimising the function

$$\Phi_{\text{MEM}}(\mathbf{h}) = \chi^2(\mathbf{h}) - \alpha S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v), \qquad (23)$$

The minimisation of this $2n_c$ -dimensional functions may also performed using the minimisation algorithm mentioned above, and the required first derivatives in this case are also given in Appendix A.

It is important to note that, since we are using the same minimiser to obtain both the Wiener filter (WF) and MEM reconstructions, and the evaluation of each function and its derivatives requires similar amounts of computation, the two methods require approximately the *same* CPU time. Thus, at least in this application, any criticism of MEM that is based on its greater computational complexity, as compared to the WF, is no longer valid. For both the WF and the MEM, the reconstruction of the six 400×400 maps of the input components requires about two minutes on a Sparc Ultra workstation.

3.5 The small fluctuation limit

Despite the formal differences between (22) and (23), the WF and MEM approaches are closely related. Indeed the WF can be viewed as a quadratic approximation to MEM, and is commonly referred to as such in the literature. This approximation is most easily verified by considering the small fluctuation limit, in which the real and imaginary parts of **h** are small compared to the corresponding models.

Following the discussion at the end of Section 3.3, we begin by setting the real and imaginary parts of all the components of the models vectors \mathbf{m}_u and \mathbf{m}_v equal to m. Then, expanding the sum in (16) as a power series in h_j and using (17), we find that for small h_j the total cross entropy is approximated by

$$S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v) \approx -\sum_{j=1}^{n_c} \frac{\Re(h_j)^2 + \Im(h_j)^2}{4m} = -\frac{\mathbf{h}^{\dagger} \mathbf{h}}{4m}.$$
 (24)

Thus, in the small fluctuation limit, the posterior probability assuming an entropic prior becomes Gaussian and is given

$$\Pr(\mathbf{h}|\mathbf{d}) \propto \exp\left[-\chi^2(\mathbf{h}) - \alpha \frac{\mathbf{h}^{\dagger} \mathbf{h}}{4m}\right].$$
 (25)

In fact, this approximation is reasonably accurate provided

the magnitudes of the real and imaginary parts of each element of **h** are less than about 3m. Since m is set equal to the expected rms level of these parameters, we would therefore expect that for a Gaussian process this approximation should remain valid. In this case, the posterior probability (25) becomes identical to that for the WF solution, provided we set $\alpha = 4m$.

We note, however, that for highly non-Gaussian processes, the magnitudes of the real and imaginary parts of the elements of \mathbf{h} can easily exceed 3m and in this case the shapes of the posterior probability for the WF and MEM approaches become increasingly different.

3.6 The regularisation constant α

A common criticism of MEM has been the arbitrary choice of regularisation constant α , which is often considered merely as a Lagrange multiplier. In early applications of MEM, α was chosen so that the misfit statistic χ^2 equalled its expectation value, i.e. the number of data points to be fitted. This choice is usually referred to as historic MEM.

In the reconstruction of Fourier modes presented here, the situation is eased somewhat since the choice $\alpha = 4m$ is at least guaranteed to reproduce the results of the Wiener filter when applied to Gaussian processes. In fact, when applied to the simulations presented in Section 2, this choice of α does indeed bring χ^2 into its expected statistical range $n_f \pm \sqrt{2n_f}$, where n_f is the number of (complex) values in the data vector **d** at each Fourier mode.

Nevertheless, it is possible to determine the appropriate value for α in a fully Bayesian manner (Skilling 1989; Gull & Skilling 1990) by simply treating it as another parameter in our hypothesis space. It may be shown (see Appendix B) that α must be a solution of

$$-\alpha S_c(\hat{\mathbf{h}}, \mathbf{m}_u, \mathbf{m}_v) = n_c - \alpha \mathrm{Tr}(\mathbf{M}^{-1}), \qquad (26)$$

where $\hat{\mathbf{h}}$ is the hidden vector that maximises the posterior probability for this value of α . The $n_c \times n_c$ matrix \mathbf{M} is given by

$$\mathbf{M} = \mathbf{G}^{-1/2} \mathbf{H}_{\mathrm{MEM}} \mathbf{G}^{-1/2},$$

where $\mathbf{H}_{\mathrm{MEM}}$ is the Hessian matrix of the function Φ_{MEM} at the point $\hat{\mathbf{h}}$ and \mathbf{G} is the metric on image-space at this point.

It should be noted that both the reconstruction \mathbf{h} and the matrix \mathbf{M} depend on α and so (26) must be solved numerically using an iterative technique such as linear interpolation or the Newton-Raphson method. We take $\alpha = 4m$ as our initial estimate in order to coincide with the Wiener filter in the small fluctuation limit. For any particular value of α , the corresponding reconstruction $\hat{\mathbf{h}}(\alpha)$ is obtained by minimising Φ_{MEM} as given in (23), and the Hessian of the posterior probability at this point is then calculated (see Appendix A). This in turn allows the evaluation of $S_c(\hat{\mathbf{h}}, \mathbf{m}_u, \mathbf{m}_v)$ and $\text{Tr}(\mathbf{M}^{-1})$ respectively. Typically, fewer than ten iterations are needed in order to converge on a solution $\hat{\alpha}$ that satisfies (26).

3.7 Updating the ICF and models

In the MEM approach, after the Bayesian value $\hat{\alpha}$ for the regularisation constant has been found, the corresponding

posterior probability distribution is maximised to obtain the reconstruction $\hat{\mathbf{h}}(\hat{\alpha})$, from which the estimate of the signal vector $\hat{\mathbf{s}}$ may be straightforwardly derived. Once this has been performed for each Fourier mode, the reconstruction of the sky emission due to each physical component is then found by performing an inverse Fourier transform.

We could, of course, end our analysis at this point and use the maps obtained as our final reconstructions. However, we find that the results can be further improved by using the current reconstruction to update the ICF matrix \mathbf{L} and the models \mathbf{m}_u and \mathbf{m}_v , and then repeating the entire MEM analysis discussed above. At each Fourier mode, the updated models are taken directly from the current reconstruction and the updated ICF matrix is obtained by calculating a new signal covariance matrix \mathbf{C} from the current reconstruction and performing a Cholesky decomposition. These quantities are then used in the next iteration of the MEM and the process is repeated until it converges on a final reconstruction. Usually, fewer than ten such iterations are required in order to achieve convergence.

We might expect that a similar method may be used in the WF case, by repeatedly calculating an updated signal covariance matrix from the current reconstruction and using it in the subsequent iteration of the WF analysis. It is wellknown, however, that, since the WF tends to suppress power at higher Fourier modes, the solution gradually tends to zero as more iterations are performed. One would thus first have to correct the derived component power spectra in order to obtain an unbiased estimator of the real spectrum (since one knows by how much power has been suppressed, see the discussion in 5.1) before performing the next iteration. This could somewhat improve the determination of the dominant processes (but in that case the exact input spectra is of little impact) but it would not help with the spectrum determination of the weak processes (since WF essentially sets their power spectra level at the input level). In fact WF should rather be thought of as the last 'polishing' step of a component separation, once a first determination of the power spectra has been achieved by other means (e.g. by singular value decomposition). Bouchet & Gispert (1998) have assessed the reachable accuracy level for the Planck Surveyor in that case. In the following, we shall restrict our discussion to the two extreme cases of exact prior knowledge of the covariance matrix or the prior knowledge of the rms levels only (the power spectra being all assumed to be white noise). Of course, WF makes much more sense if the assumed prior is not far from the truth, since it is designed to take advantage of that information.

3.8 Estimating errors on the reconstruction

Once the final reconstruction has been obtained, it is important to be able to characterise the errors associated with it. In the case of the Wiener filter, the reconstructed signal vector $\hat{\mathbf{s}}$ at each Fourier mode may be obtained in a linear manner from the observed data vector using (14). Thus the propagation of errors is straightforward and the covariance matrix of the reconstruction errors at each Fourier mode is given by (15).

As mentioned in Section 3.2, however, this simple propagation of errors is entirely a result of the assumption of a Gaussian prior, which, together with the assumption of Gaussian noise, leads to a Gaussian posterior probability distribution. In terms of the vector of hidden variables \mathbf{h} the posterior probability for the WF is given by

$$\Pr(\mathbf{h}|\mathbf{d}) \propto \exp\left[-\Phi_{\rm WF}(\mathbf{h})\right] = \exp\left[-(\mathbf{h} - \hat{\mathbf{h}})^{\dagger}\mathbf{H}_{\rm WF}(\mathbf{h} - \hat{\mathbf{h}})\right]$$

where the Hessian matrix \mathbf{H}_{WF} is given by $\mathbf{H}_{WF} = \nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} \Phi_{WF}$ evaluated at the peak $\hat{\mathbf{h}}$ of the distribution, and the function Φ_{WF} is given by (22). Thus, the covariance matrix of the errors on the reconstructed hidden vector is then given *exactly* by the inverse of this matrix, i.e

$$\langle (\mathbf{h} - \hat{\mathbf{h}})(\mathbf{h} - \hat{\mathbf{h}})^{\dagger} \rangle = \mathbf{H}_{WF}^{-1}.$$

From (18), the error covariance matrix for the reconstructed signal vector is then given by

$$\langle (\mathbf{s} - \hat{\mathbf{s}})(\mathbf{s} - \hat{\mathbf{s}})^{\dagger} \rangle = \langle \mathbf{L}(\mathbf{h} - \hat{\mathbf{h}})(\mathbf{h} - \hat{\mathbf{h}})^{\dagger} \mathbf{L}^{\mathrm{T}} \rangle = \mathbf{L} \mathbf{H}_{\mathrm{WF}}^{-1} \mathbf{L}^{\mathrm{T}}.$$
 (27)

Using the expression for the Hessian matrix given in (A7), and remembering that $\mathbf{s} = \mathbf{L}\mathbf{h}$ and $\mathbf{C} = \mathbf{L}\mathbf{L}^{\mathrm{T}}$, the expression (27) is easily shown to be identical to the result (15).

For the entropic prior, the posterior probability distribution is not strictly Gaussian in shape. Nevertheless, we may still approximate the shape of this distribution by a Gaussian at its maximum and, recalling the discussion of subsection 3.5, we might expect this approximation to be reasonably accurate, particularly in the reconstruction of Gaussian processes. Thus, near the point $\hat{\mathbf{h}}$, we make the approximation

$$\Pr(\mathbf{h}|\mathbf{d}) \propto \exp\left[-\Phi_{\mathrm{MEM}}(\mathbf{h})\right] \approx \exp\left[-(\mathbf{h}-\hat{\mathbf{h}})^{\dagger}\mathbf{H}_{\mathrm{MEM}}(\mathbf{h}-\hat{\mathbf{h}})\right],$$

where $\mathbf{H}_{\text{MEM}} = \nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} \Phi_{\text{MEM}}$ evaluated at $\hat{\mathbf{h}}$, and Φ_{MEM} is given by (23). The covariance matrix of the errors on the reconstructed hidden vector is then given *approximately* by the inverse of this matrix, and so

$$\langle (\mathbf{s} - \hat{\mathbf{s}}) (\mathbf{s} - \hat{\mathbf{s}})^{\dagger} \rangle \approx \mathbf{L} \mathbf{H}_{\mathrm{MEM}}^{-1} \mathbf{L}^{\mathrm{T}}.$$

In both the WF and MEM cases, the reconstructed maps of the sky emission due to each physical component is obtained by inverse Fourier transformation of the signal vectors at each Fourier mode. Since this operation is linear, the errors on these maps may therefore be deduced straightforwardly from the above error covariance matrices.

4 APPLICATION TO SIMULATED OBSERVATIONS

We now apply the MEM and WF analyses outlined above to the simulated Planck Surveyor data discussed in Section 2. Clearly, both techniques rely to some extent on our prior knowledge of the input components we are trying to reconstruct. Information concerning the spectral behaviour of each component is contained in the frequency response matrix **F** defined in (1), whereas the assumed covariance structure of the components is contained in the signal covariance matrix \mathbf{C} given in (11). Since we are in fact performing the reconstruction in the Fourier domain, the latter matrix contains the power spectrum of each component as its diagonal entries and the cross power spectra between components as its off-diagonal entries. Strictly speaking, since we reconstruct the vector of hidden variables \mathbf{h} , rather than the signal vector **s**, this power spectrum information actually resides in the ICF matrix L.

For the reconstructions presented in this section, we assume that the spectral behaviour of the components is accurately known. This is certainly true for the CMBR emission and the kinetic and thermal SZ effects, but it is perhaps optimistic to assume that this would be the case for the three Galactic components. In reality the spectral indices of the free-free and synchrotron emission are uncertain to within about 20 per cent and the dust temperature and emissivity will also not be known in advance. We have investigated the effect of varying these parameters in the reconstruction algorithms and have found both the MEM and WF separations to be quite robust. This is discussed further in Section 5 (see also Gispert & Bouchet 1997).

Our prior knowledge of the covariance structure or power spectra of the various emission components is certainly poorer than our knowledge of their spectral behaviour. Nevertheless, we are not entirely ignorant of the shapes of these power spectra and we would obviously wish to include any such information in our analysis. In order to investigate how the quality of the reconstructions depends on our knowledge of the power spectra, we have chosen to model two extreme cases. First, we assume knowledge of the azimuthally-averaged power spectra of all six input components, as shown in Fig. 2, together with the azimuthallyaveraged cross power spectra between components; these contain cross-correlation information in Fourier space, so that the ICF matrix **L** is fully specified. In the second case, however, we take the opposite view and assume that almost no power spectrum information is available. This corresponds to assuming a flat (white-noise) power spectrum for each component out to the highest measured Fourier mode. The levels of the flat power spectra are chosen so that the total power in each component is approximately that observed in the input maps in Fig. 1.

It is likely, in practice, that the quality of prior information concerning the component power spectra will lie somewhere between these two extreme cases. Therefore, by presenting the results for each case, we aim to provide some idea of the best- and worst-case limits on the quality of component separation that can be achieved for the Planck Surveyor mission. In addition, we hope to illustrate the different behaviour of the MEM and WF techniques in the two extreme régimes. The reconstructions with full ICF information are intended to display that the main advantage of the MEM technique in this case is its superiority in reconstructing weak non-Gaussian processes. In the absence of ICF information, we wish to illustrate that the iterative formulation of MEM presented above allows the component separation to be nearly as efficient without prior knowledge as it is when the ICF matrix is fully specified. On the other hand, we anticipate much larger differences between the two régimes for the WF reconstructions, since this method amounts to designing optimal linear filters by using prior knowledge of the component power spectra. Nevertheless, although WF makes more sense as a method when the assumed prior information is close to truth, it is of interest to investigate the robustness the reconstructions of the various components in the absence of such information. Indeed, if the CMB is well reconstructed with essentially no prior information given to the WF, then its estimate is truly very robust.

4.1 Reconstructions with full ICF information

We first consider the case in which power spectrum and cross-correlation information are assumed, so that the ICF matrix **L** is fully specified. In this case, the Bayesian value of the regularising parameter α that satisfies (26) is found to be $\alpha = 0.8$.

4.1.1 The reconstructed maps

The corresponding MEM and WF reconstructions of the six input components shown are shown in Figs 5 and 6 respectively, convolved with a 4.5 arcmin FWHM Gaussian beam. The grey scales in these figures are chosen to coincide with those in Fig. 1 in order to enable a more straightforward comparison with the input maps.

We see that the main input components are faithfully reconstructed. Perhaps most importantly, the CMBR has been reproduced extremely accurately, and at least by eye both the MEM and WF reconstructions are virtually indistinguishable from the true input map. As we might expect the dust emission is also accurately recovered, since it dominates the high frequency channels. The free-free emission, which is highly correlated with the dust, has also been reconstructed well, with both the MEM and WF reconstructions containing most of the main features present in the true input map. The recovery of the synchrotron emission is also reasonable, although the MEM algorithm is more successful in recovering the brightest regions.

The MEM and WF reconstructions of the kinetic and thermal SZ effects are worth some comment. Both techniques have produced reasonable reconstructions of the thermal SZ effect for those clusters in which the effect is very strong. However, it is clear that the MEM has successfully reconstructed the SZ effect in a greater number of clusters. Moreover, the magnitudes of the SZ effects in the MEM reconstruction are closer to the true values than those obtained with the WF. Thus, as anticipated, the assumption of Gaussian random fields that is central to the WF approach leads to poorer reconstructions of highly non-Gaussian fields as compared with MEM. A more detailed discussion of the recovery of thermal SZ profiles is given in Section 4.1.3. For the kinetic SZ effect, however, neither method has reconstructed any features in the input map with their true magnitudes. In fact, both methods have reconstructed fields with very low-level fluctuations that coincide with the brightest features in the thermal SZ map. The inability of either method to make very accurate reconstructions of the kinetic SZ effect is not surprising since, as mentioned in Section 2, this emission due to this component is at least two orders of magnitude below the dominant emission component or the noise at all of the Planck Surveyor observing frequencies. Moreover, this component has the same frequency dependence as the primordial CMBR fluctuations, and so we cannot distinguish them by their spectral behaviour. Nevertheless, it is still possible to distinguish between the CMBR and kinetic SZ emission on the basis of their different power spectra, and we do indeed obtain marginal detections of the kinetic SZ effect in some clusters; this is also discussed in Section 4.1.3.

While a visual inspection of the reconstructed maps is a useful method of assessing how well the algorithms are per-

Table 2. The rms residuals per 4.5 arcmin FHWM Gaussian beam (in μ K) for the MEM and WF reconstructions shown in Figs 5 and 6, which assume full ICF information.

Component	$e_{\rm rms}^{\rm MEM}$	$e_{\rm rms}^{\rm WF}$
CMBR	5.90	6.00
Kinetic SZ	0.85	0.85
Thermal SZ	3.90	4.10
Dust	1.60	1.90
Free-Free	0.30	0.37
Synchrotron	0.05	0.06

forming, a more quantitative analysis of the reconstruction errors is required if we are to make any meaningful comparison between the MEM and WF approaches. The most straightforward means of comparison is to calculate the rms of the residuals for each set of reconstructions. For any particular physical component, this is given by

$$e_{\mathrm{rms}} = \left[rac{1}{N}\sum_{i=1}^{N}\left(T_{\mathrm{rec}}(\boldsymbol{x}_i) - T_{\mathrm{true}}(\boldsymbol{x}_i)
ight)^2
ight]^{1/2},$$

where $T_{\rm rec}(\boldsymbol{x}_i)$ and $T_{\rm true}(\boldsymbol{x}_i)$ are respectively the reconstructed and true temperatures in the ith pixel; N is the total number of pixels in the map. The values of $e_{\rm rms}$ for each physical component in the MEM and WF reconstructions are shown in Table 4.1.1. Since, for comparison purposes, both the input and reconstructed maps have been convolved with a 4.5 arcmin FHWM Gaussian, the $e_{\rm rms}$ values quoted should interpreted as the rms residual per beam of this size. We see from the table that, in terms of the rms of the reconstruction errors, the two methods are nearly equivalent. In particular, we note that the CMBR has been reconstructed to an accuracy of about $6\mu K$, which is the desired value quoted for the Planck Surveyor mission (Bersanelli et al. 1996). We note, however, that the rms error for MEM reconstruction is slightly smaller than for the WF. The rms errors for the other components are also similar for the MEM and WF reconstructions, but are always lower for the MEM algorithm. This is particularly true for the reconstructions of the thermal SZ effect, dust and free-free emission and is due in part to the non-Gaussian nature of these components.

Simply quoting the rms of the residuals is, however, a rather crude method of quantifying the accuracy of the reconstructions. A more useful approach is to characterise the reconstruction errors on a given component by plotting the amplitudes of the temperature fluctuations for each pixel of the reconstructed map against those in the true map. Usually such plots consist of a collection of points, one for each pixel in the true/reconstructed map. We shall, however, adopt a slightly different approach For each component, the temperature range of the true map is divided into 100 bins. Three contours are then plotted which correspond to the 68, 95 and 99 per cent points of the distribution of corresponding reconstructed temperatures in each bin. If the reconstruction is particularly good, then only the 95 and 99 per cent contours are plotted. Clearly, a perfect reconstruction would be represented by a single diagonal box of width equal to the bin size used. Figs 7 and 8 show the comparison plots for the WF and MEM reconstructions respectively



Figure 5. MEM reconstruction of the 10×10 -degree maps of the six input components shown in Fig. 1, using full ICF information (see text). The components are: (a) primary CMBR fluctuations; (b) kinetic SZ effect; (c) thermal SZ effect; (d) Galactic dust; (e) Galactic free-free; (f) Galactic synchrotron emission. Each component is plotted at 300 GHz and has been convolved with a Gaussian beam of FWHM equal to 4.5 arcmin. The map units are equivalent thermodynamic temperature in μK .



Figure 6. Wiener filter reconstruction of the 10×10 -degree maps of the six input components shown in Fig. 5, using full ICF information (see text).



Figure 7. Comparison of the input maps with the maps reconstructed using the MEM algorithm with full ICF information. The horizontal axes show the input map amplitude within a pixel and the vertical axes show the reconstructed amplitude. The contours contain 50 and 99 per cent of the pixels respectively.



Figure 8. As for Fig. 7 but for the Wiener filter reconstruction with full ICF information.

and Table 4.1.1 gives the gradient of the best-fit straight line through the origin for each component.

Panel (a) in each figure shows the confidence limits for the reconstruction of the CMBR, and it is clear that both reconstructions are very accurate. In each case, for those points in the true CMBR map with temperatures lying in the range $-200 \ \mu K$ to 200 μK , the 68 per cent limits of the reconstructed temperatures lie approximately $5\mu K$ on either side of the true value. This agrees with the values for $e_{\rm rms}$ for each reconstruction, given in Table 4.1.1. For points in the true map having very large positive or negative values, both the MEM and WF reconstructions become slightly less accurate, but the errors are still in the range 5–10 μ K. Comparing the performance of the MEM and WF approaches, there is some evidence in that the MEM reconstruction is slightly more accurate for points having large positive temperatures, and it is these points that make the largest contribution to difference in the values of $e_{\rm rms}$ given in Table. 4.1.1.

Panels (b) and (c) in Figs 7 and 8 show the confidence limits for the reconstruction of the kinetic and thermal SZ respectively. As we would anticipate from the maps of the kinetic SZ reconstructions in Figs 5(b) and 6(b), for both the MEM and WF techniques, the distribution of the reconstructed temperatures centres around zero for all values of the temperature in the input map. For the thermal SZ, however, we see that the reconstructions are considerable better. Nevertheless, for both reconstructions, the best-fit straight line through the origin has a slope that is significantly smaller than unity, indicating that magnitudes of the thermal SZ effects are generally underestimated. It is clear from the plots that this effect is more pronounced in the WF reconstruction, since the corresponding best-fit line has a markedly lower slope than for the MEM reconstruction. About the corresponding best-fit line the range in the values of the reconstructed temperatures is slightly smaller for the WF reconstruction than for MEM. However, the bias in the best-fit line and the relatively low dispersion in the WF case are both due to its signal-to-noise weighting to reach minimum variance estimates. This tends to reduce the reconstructed values for weak processes like the thermal SZ. Accounting for the bias (see Section 5 for further discussion) would boost the recovered mode values and decrease the bias while keeping constant the signal-to-noise, i.e. it would result in more noise in the recovered maps without changing the significance level of the detections. We have not done performed this correction and have instead kept the standard minimum-variance WF procedure. In this case, the standard deviation of the reconstructed temperatures about the true temperature is lower for MEM, as indicated by the relatives values of $e_{\rm rms}$ for this component given in Table 4.1.1. The tendency for both methods to underestimate the magnitude of the thermal SZ effects is due to the fact that the emission in this component is dominated by dust emission and pixel noise at the observing frequencies with the highest angular resolutions. Thus information concerning the higher Fourier modes of the thermal SZ map is not present in the data and so very sharp features are unavoidably smoothed in the reconstructions.

The confidence limits for the reconstructions of the Galactic components are shown in panels (d), (e) and (f) of Figs 7 and 8; these correspond to dust, free-free and

Table 3. The gradients of the best-fit straight line through the origin for the comparison plots shown in Figs 7 and 8 for the MEM and WF reconstructions, which assume full ICF information.

Component	MEM gradient	WF gradient
CMBR	1.00	1.00
Kinetic SZ	0.06	0.05
Thermal SZ	0.55	0.27
Dust	1.00	1.00
Free-Free	0.48	0.37
Synchrotron	0.62	0.44

synchrotron emission respectively. The confidence contours for the MEM and WF reconstructions of the dust component are indistinguishable and clearly show that the dust is the most accurately reconstructed component. The 99 per cent limits of the reconstructed temperature distributions are approximately constant for all values of the true input temperature and correspond to 3σ error in the reconstruction of about $5\mu K$. From panels (e) and (f) it is clear that the reconstructions of the free-free and synchrotron emission are considerable less accurate. By comparing these plots for the MEM and WF reconstructions, we again notice (for the same reasons as noted above) that the best-fit straight line through the origin has a slope that is closer to unity for MEM than for the WF and the standard deviation of the reconstructed temperatures about these lines is also smaller for MEM, as indicated by the smaller corresponding values of $e_{\rm rms}$ in each case . The relative large spread of reconstructed temperatures for the free-free and synchrotron components is due partially to the fact that the reconstructions have low effective resolution, since the Planck Surveyor has relatively large beam sizes at the lower observing frequencies where the free-free and synchrotron emission is highest. If the input maps are instead convolved to a lower resolution. such as 20 arcmin, which is more typical of the beam sizes at the lower observing frequencies, then the spread in the reconstruction values is considerably reduced. In fact for WF alone, one should rather convolve the input map with the effective beam of the reconstruction as determined from the WF method itself (see Bouchet et al. 1997 for examples of such beams), but this would prevent a straight comparison with MEM.

4.1.2 The reconstructed power spectra

Since both the MEM and WF reconstructions are performed in the Fourier domain, it is particularly straightforward to compute the reconstructed power spectra of the physical components. Both techniques reconstruct the signal vector $\hat{\mathbf{s}}(\mathbf{k})$ at all measured Fourier modes. These Fourier modes lie on a square 400 × 400 grid with a grid spacing $\Delta k = 36$ wavenumbers. At a given value of k, the estimator $\hat{C}_p(k)$ of the azimuthally averaged power spectrum for the *p*th physical component is obtained simply by calculating the average value of $|\hat{s}_p(\mathbf{k})|^2$ over those modes for which $|\mathbf{k}| = k$, i.e.

$$\hat{C}_{p}(k) = \frac{1}{N(k)} \sum_{|\mathbf{k}_{i}|=k} \hat{s}_{p}(\mathbf{k}_{i}) \hat{s}_{p}^{*}(\mathbf{k}_{i}), \qquad (28)$$



Figure 9. The power spectra of the input maps (bold line) compared to to the power spectra of the maps reconstructed using MEM with full ICF information (faint line). The dotted lines show one sigma confidence limits on the reconstructed power spectra.



Figure 10. As for Fig 9, but for the WF reconstruction with full ICF information.

where N(k) is the number of measured Fourier modes satisfying $|\mathbf{k}_i| = k$. We note that for $k \geq 36$ it is a reasonable approximation to identify the flat two-dimensional wavenumber k with the spherical harmonic multipole index ℓ . The errors on the reconstructed power spectrum are also easily estimated from the errors on the reconstructed signal vectors at each Fourier mode. It is straightforward to show that

$$\begin{aligned} \operatorname{Var}[\hat{C}_{p}(k)] &\approx 2\sum_{|\boldsymbol{k}_{i}|=k} \frac{\partial \hat{C}_{p}(k)}{\partial \hat{s}_{p}(\boldsymbol{k}_{i})} \frac{\partial \hat{C}_{p}(k)}{\partial \hat{s}_{p}^{*}(\boldsymbol{k}_{i})} \operatorname{Var}[\hat{s}_{p}(\boldsymbol{k}_{i})] \\ &\approx \frac{2}{N^{2}(k)} \sum_{|\boldsymbol{k}_{i}|=k} \hat{s}_{p}(\boldsymbol{k}_{i}) \hat{s}_{p}^{*}(\boldsymbol{k}_{i}) \operatorname{Var}[\hat{s}_{p}(\boldsymbol{k}_{i})]. \end{aligned}$$

For a WF reconstruction, it is well known that $\hat{C}_p(k)$ is a biased estimator of the underlying power spectrum (see e.g. Bouchet et al. 1997). Nevertheless, this is not necessarily the case for the MEM reconstruction and, for comparison purposes, it is instructive to use the same power spectrum estimator for both the MEM and WF reconstructions. Moreover, in this section we are interested simply in the power spectra of the reconstructed maps, rather than in developing optimal methods to recover the input power spectrum from a given reconstruction. In Section 5, we discuss in more detail the biased nature of this simple power spectrum estimate, and consider several variants of the standard Wiener filter that may be used to circumvent this problem. At this point, however, it is sufficient to note that where the underlying power spectrum of the *p*th process is poorly determined by the observations, the estimator $\hat{C}_p(k)$ can be shown to underestimate the true power spectrum.

Figs. 9 and 10 show the power spectra of the MEM and WF reconstructions respectively, together with the 68 per cent error bars. In each panel the faint line is the power spectrum of the reconstructed map and the bold line is the power spectrum of the relevant input map as shown in Fig. 2 (for the power spectrum comparison the maps are *not* convolved by a 4.5 arcmin FHWM Gaussian beam). We see that the 68 per cent confidence intervals always contain the true power spectrum, which indicates that our estimate of the errors on the reconstructed power spectrum are quite robust.

The power spectrum of the reconstructed CMBR maps are shown in panel (a) of each figure, and we see that both techniques have faithfully reproduced the true power spectrum for $\ell \lesssim 1500$, at which point the WF reconstructed map begins visibly to underestimate the true spectrum. The MEM reconstruction, however, remains indistinguishable from the true power spectrum up to $\ell \approx 2000$, where it too begins to underestimate the true spectrum.

The power spectra of MEM and WF reconstructions of the kinetic SZ map are shown in panel (b) of each figure and are predictably poor, with both reconstructed power spectra underestimating the true one over almost the entire range of measured multipoles. For the thermal SZ component shown in panel (c), both methods produce maps with power spectra that lie close to the true spectrum for at lower multipoles. However, we again find that the MEM reconstruction remains faithful out to larger multipoles ($\ell \approx 1000$) as compared to the WF reconstruction ($\ell \approx 300$).

Panels (d), (e) and (f) in Fig. 9 and 10 show the power spectra of the MEM and WF reconstructions of the Galac-

tic dust, free-free and synchrotron. As expected, for the dust component both methods produce reconstructions with power spectra that are very close to the power spectrum of the true map over a large range of multipoles. The power spectrum of the MEM reconstruction is indistinguishable from that of the true map up to $\ell \approx 3000$, whereas the WF reconstruction becomes inaccurate at $\ell \approx 2000$. For the free-free component, both MEM and WF produce reconstructions with power spectra that slightly underestimate the true spectrum over the entire range of measured multipoles. Finally, the power spectra of the synchrotron reconstructions show the MEM technique reproduces the true power spectrum to moderate accuracy for $\ell \lesssim 400$, whereas the WF reconstruction underestimates the true power spectrum for all multipoles.

4.1.3 The reconstructed kinetic and thermal SZ effects

As discussed in Section 3.2, a central assumption of the Wiener filter method is that the fields to be reconstructed are well described by Gaussian statistics. This is clearly not a valid assumption for either the kinetic or thermal SZ effects for which the emission consists of sharp peaks. Thus we would expect that it is in the reconstruction of this component especially that the difference between the MEM and WF approaches would be most apparent.

Unfortunately, the small magnitude of the kinetic SZ, together with a frequency spectrum identical to that of the primary CMBR fluctuations, means that neither of the methods is capable of reconstructing this component very accurately. Nevertheless, the both methods do make marginal detections of the kinetic SZ effect in some clusters. Fig. 11 shows the MEM reconstruction of the kinetic SZ map compared to the true map convolved to the lowest Planck Surveyor resolution of 33 arcmin; it is in this lowest frequency channel that the relative contribution of the kinetic SZ effect to the total emission is highest. From the figure, we see that the MEM algorithm has recovered the kinetic SZ effect at this lowest resolution, but only in a few clusters. By comparing these maps with the MEM thermal SZ reconstruction in Figs 5(c), we see that these clusters are those with the largest thermal SZ effects. Conversely, the largest kinetic SZ effect in the true map is not recovered with any accuracy, since by chance it corresponds to a cluster with a small thermal SZ effect.

For the thermal SZ, we see from Figs 5(c) and 6(c) that both the MEM and WF algorithms reproduce the main features present in the input map, but that MEM reconstructs the thermal SZ effect in many more clusters than the WF and that the magnitude of the reconstructed effects using MEM are closer to those in the input map. This observation is confirmed by investigating the errors on the reconstructed maps and by comparing the power spectra of the input map and the reconstructions.

It is hoped that Planck Surveyor observations of the thermal SZ effect, together with follow-up X-ray observations of the relevant galaxy clusters, will provide a large catalogue of H_0 determinations to supplement the value of H_0 obtained from the accurate measurement of the primordial CMBR power spectrum. In order for this to be possible, however, the density profile of the clusters must be known. Furthermore, an accurate determination of the density pro-



Figure 11. (a) The input kinetic SZ map convolved to the lowest Planck Surveyor angular resolution of 33 arcmin. (b) The MEM reconstruction of the kinetic SZ effect. The map units are equivalent thermodynamic temperature in μ K at 300 GHz.

file of a cluster enables the construction of optimal filters, tuned to the individual cluster characteristics, that may enable the magnitude of the kinetic SZ to be recovered more accurately and hence allow its peculiar radial velocity to be measured to greater precision (Haehnelt & Tegmark 1996). Clearly, a large catalogue of radial cluster velocities measured across the whole sky would be an invaluable resource for the investigation of large-scale motions in the Universe.

Fig. 12 shows the MEM and WF reconstructions of the thermal SZ profiles for a few typical clusters. These profiles are plotted as dashed lines and dotted lines respectively and are produced by making cuts through the reconstructed maps shown in Figs 5(c) and 6(c). The reconstructions are compared with the true cluster profiles convolved with a Gaussian beam of FWHM 10', which are plotted as solid lines. Such a convolution is necessary in order to make a meaningful comparison since, as we see from Fig. 3, the thermal SZ effect is severely dominated by dust emission and pixel noise in the frequency channels above 100 GHz, which have the highest angular resolutions. Thus the Planck Surveyor observations contain very little information on the thermal SZ effect at angular resolutions above about 10 arcmin.

From Fig. 12 we see that the MEM reconstruction of both the peak magnitude of the SZ effect and the cluster profile are closer to the true maps than those produced by the WF. We note that, as expected, the WF underestimates the magnitude of the effect and reconstructs profiles that are far less peaked. By allowing for the bias inherent in the WF method, it is possible to increase the heights of the main peaks in the reconstruction, but only at the cost of increasing the overall rms residuals significantly, since the signal-to-noise ratio for a given WF reconstruction is fixed.

At first sight, it appears that the MEM reconstructions contain several spurious features as compared to the input profiles. This appears to have occurred most dramatically in the top panel of the figure, on the right-hand side of the central cluster profile. In fact, this phenomenon illustrates the care that must taken in interpreting plots of this type, since this feature is in fact present in the true map, but has been smoothed out by convolving the image to 10 arcmin resolution. The reason it is present in the MEM reconstruction is that the effective resolution of the MEM (and WF) reconstructions can vary across the map, depending on the level of the recovered process compared to the other processes and the pixel noise. Thus, in some regions, some super-resolution is possible which leads to the reconstruction of features that are considerable smoothed by the convolution with the 10 arcmin beam. In different regions, however, where the other physical components happen to have high levels of emission, or the level of pixel noise is greater, than this super-resolution does not occur.

4.2 Reconstructions with no ICF information

Throughout subsection 4.1, the reconstructions were made assuming full ICF information, which consists of a knowledge of the azimuthally-averaged power spectrum of each input map, together with cross-correlation information. In this subsection, we consider the opposite extreme and obtain MEM and WF reconstructions assuming virtually no ICF information. In this case we assume no cross-correlations between components (so that the ICF matrix L is diagonal) and initially we assume the power spectrum of each component to be constant for all measured Fourier modes and normalised to give approximately the observed rms fluctuation in the corresponding map.

In this case, it is no longer possible in principle to distinguish between the primordial CMBR fluctuations and the kinetic SZ effect, since they have the same frequency characteristics, and initially the same power spectrum (to within a normalisation constant). Nevertheless, we find that by attempting to reconstruct the kinetic SZ effect in this case, the reconstructions of the other components are not noticeably affected. Thus, in this section, we still attempt to reconstruct all six components. For the MEM solution the reconstruction process is iterated, as discussed in Section 3.7, but this



Figure 12. The cluster profiles of some SZ effect reconstructions compared to the input profiles convolved with a 10' beam (solid line). The full MEM with full ICF information was used to reconstruct the dashed line whereas the quadratic approximation to this was used to reconstruct the dotted line.

is not possible for the WF technique since the solution in this case tends to zero. Hence, for the WF only the original solution is presented. For the MEM reconstruction, the Bayesian value of the regularising parameter α that satisfies (26) is found to be $\alpha = 2.9$.

4.2.1 The reconstructed maps

Figs 13 and 14 show respectively the MEM and WF reconstructions of the six input components. Once again, for comparison purposes, the grey scales in these figures are chosen to coincide with those in Fig. 1 and both sets of maps have beem convolved with a 4.5 arcmin FWHM Gaussian beam. Comparing these figures with the input maps, we see that by assuming no ICF information, the overall quality of the reconstructed maps has been somewhat reduced, in particular for the WF.

It is encouraging to note that both the MEM and WF reconstructions of the CMBR, shown in panel (a) of each

Table 4. The rms residuals per 4.5 arcmin FWHM Gaussian beam (in μ K) for the MEM and WF reconstructions shown in Figs 13 and 14, which assume no ICF information.

Component	$e_{\rm rms}^{\rm MEM}$	$e^{WF}_{\rm rms}$	$e_{\mathrm{rms}}^{\mathrm{MEM}}$ (1 iter.)
CMBR	6.10	7.50	7.10
Kinetic SZ	0.85	0.85	0.85
Thermal SZ	4.35	4.61	4.42
Dust	1.90	2.10	2.07
Free-Free	0.44	0.50	0.48
Synchrotron	0.07	0.08	0.07

figure, still closely resemble the true input map. This is also true for the reconstructions of the dust emission shown in panel (d) of each figure. As mentioned in section 2, it is possible, by simple visual inspection of the data maps at each observing frequency, to distinguish the CMBR and dust contributions quite clearly, and so we would indeed hope that any reasonable separation algorithm would be able to reconstruct these components with some accuracy.

The quality of both the MEM and WF reconstructions of the free-free and synchrotron components has been significantly reduced by assuming no ICF information. We do see, however, that both reconstructions of the free-free component contain the main features of the input map, but smoothed to a much lower resolution, but that MEM reconstruction contains slightly more detail. For the synchrotron component, shown in panel (f), the WF algorithm has again produced a very low-level, smoothed reconstruction of the input map, whereas the MEM reconstruction has been more successful in recovering the brightest regions.

As expected, the quality of the MEM and WF reconstructions differs most for the thermal SZ effect, shown in panel (c) of each figure. Although the MEM reconstruction is not as accurate as that obtained assuming full ICF information, it still provides a reasonable representation of the main features of the input map. This is certainly not true for the WF reconstruction which contains only very low-level features at the positions of the few largest peaks.

The rms of the residuals for each set of reconstructions are given in Table 4.2.1. We see from the table that the MEM reconstruction of the CMBR has a significantly lower rms error than the WF reconstruction and is only marginally less accurate than that obtained assuming full ICF information. Indeed, once again, the rms error of the MEM reconstructions of the other components are again consistently lower than the corresponding WF reconstructions.

As mentioned above, the MEM technique is iterated until the reconstructions coverged, but this is not directly possible for the WF. In is therefore of some interest to investigate how much the MEM solution is improved by this iterative process. Therefore, in Table 4.2.1, we also quote the rms residuals for the MEM reconstruction after just one iteration. As we might expect, the initial rms errors are slightly better than those found using the WF, but we also see that iterating the MEM technique clearly reduces the residuals, most notably for the CMBR reconstruction.

Figs 15 and 16 show the distribution of pixel temperatures in the MEM and WF reconstructions as compared to the pixel temperatures in the corresponding input maps.



Figure 13. MEM reconstruction of the 10×10 -degree maps of the input components shown in Fig. 1, using no power spectrum information (see text). The components are: (a) primary CMBR fluctuations; (b) kinetic SZ effect; (c) thermal SZ effect; (d) Galactic dust; (e) Galactic free-free; (f) Galactic synchrotron emission. Each component is plotted at 300 GHz and has been convolved with a Gaussian beam of FWHM equal to 4.5 arcmin. The map units are equivalent thermodynamic temperature in μK .



Figure 14. Wiener filter reconstruction of the 10×10 -degree maps of the six input components shown in Fig. 9, using no power spectrum information (see text).



Figure 15. Comparison of the input maps with the maps reconstructed using the MEM algorithm with no ICF information. The horizontal axes show the input map amplitudes and the vertical axes show the corresponding reconstructed amplitudes. The contours contain 68, 95 and 99 per cent of the pixels respectively.



Figure 16. As for Fig. 15, but for the Wiener filter reconstruction with no ICF information.

Table 5. The gradients of the best-fit straight line through the origin for the comparison plots shown in Figs 15 and 16 for the MEM and WF reconstructions, which assume no ICF information.

Component	MEM gradient	WF gradient
CMBR	1.00	0.97
Kinetic SZ	0.00	0.00
Thermal SZ	0.50	0.24
Dust	1.00	1.00
Free-Free	0.60	0.22
Synchrotron	0.47	0.13

Table 4.2.1 gives the gradient of the best-fit straight line through the origin for each component.

The confidence limits for pixel temperatures in the reconstructed CMBR maps are shown in panel (a) in each figure. We see that for most input temperatures the confidence contours are somewhat narrower for the MEM reconstruction than for the WF, and this is reflected in its lower $e_{\rm rms}$ value. At high input temperatures, however, the 95 and 99 per cent limits become slightly wider for the MEM reconstruction. From Table 4.2.1 we also notice that the best-fit straight line through the origin has a slope of approximately 0.96 for the WF as compared to a value of 1.0 for the MEM reconstruction. Thus in the absence of ICF information the WF reconstruction slightly underestimates the true temperature in each pixel of the CMBR map.

Panel (c) in Figs 15 and 16 shows the confidence limits for the reconstructions of the thermal SZ. We see for the MEM algorithm that the confidence contours are slightly wider than those in Fig. 7(c), obtained assuming full ICF information. The best-fit straight line through the origin again has a slope significantly smaller than unity, indicating that magnitudes of the thermal SZ effects are underestimated, but its slope is close to that obtained with full ICF information. For the WF reconstruction, however, the best-fit line now has a slope very close to zero.

The confidence contours for the WF and MEM reconstructions of the dust component, shown in panel (d) of each figure, are again indistinguishable and clearly show that the dust is once more the most accurately reconstructed component. Finally, from panels (e) and (f) in Fig. 16, we see that the slope of the confidence contours is much closer to unity for the MEM reconstructions than for the WF (see Table 4.2.1). We note, however, that about the best-fit line the spread of values in the WF reconstructions is smaller than for MEM. Nevertheless, the spread of reconstructed temperatures about the *true* values is still smaller for MEM, as seen by the relative values of $e_{\rm rms}$ given in Table 4.2.1.

4.2.2 The reconstructed power spectra

For the reconstruction presented in this section the assumed power spectra of the input components were constant for all measured Fourier modes. It is therefore of particular interest to investigate the power spectra of the reconstructed maps in this case.

The reconstructed power spectra are calculated in the same manner as that outlined in subsection 4.1, as are the errors bars. The resulting power spectra are plotted in Figs 17 and 18 for the MEM and WF reconstructions respectively.

The power spectrum of the reconstructed CMBR maps are shown in panel (a) of each figure, and we see that the MEM and WF techniques produce noticeably different results. For the MEM reconstruction the power spectrum closely follows the true spectrum out to $\ell \approx 1500$, at which point it drops rapidly to zero. For the WF reconstruction, however, the features in the power spectrum match those in the true spectrum for $\ell \lesssim 1000$, and then slightly underestimate the true power for $\ell \approx 1000-1500$. At higher multipoles, the power spectrum of the WF reconstruction contains a spurious hump, which results in an overestimate of the true power spectrum for $\ell \approx 2000-5000$, before the power spectrum finally tends to zero.

For MEM and WF reconstructions of the thermal SZ map, the corresponding power spectra are shown in panel (c) of each figure. We see that the power spectrum of the MEM reconstruction is reasonably accurate out to $\ell \approx 1000$, but does overestimate the power slightly over this range. At higher multipoles, we again find that the MEM power spectrum drops rapidly to zero. The power spectrum of the WF reconstruction underestimates to true power at high multipoles and is only reasonably accurate for $\ell \lesssim 200$.

Panels (d), (e) and (f) in Fig. 17 and 18 show the power spectra of the MEM and WF reconstructions of the Galactic dust, free-free and synchrotron. For the dust component, we see that the power spectrum of the MEM component follows the true power spectrum up to $\ell \approx 2000$, before dropping rapidly to zero. For the WF reconstruction, however, the recovered power spectrum is accurate up to $\ell \approx 3000$, but then exhibits a spurious hump which results in the overestimation of the true power at all higher multipoles. The power spectra of the reconstructed free-free maps are shown in panel (e) of each figure. We see that the MEM reconstruction is accurate for $\ell \gtrsim 100$, but then underestimates the true power at higher multipoles, whereas the WF reconstructions underestimates the true power at all multipoles. For the synchrotron component, the WF reconstructions underestimate the true power at all multipoles, whereas the MEM solution oscillates widely about the true power spectrum for $\ell \lesssim 300$, before dropping to zero.

4.2.3 The reconstructed thermal SZ profiles

From Figs 13 and 14 we see that assuming no ICF information leads to a substantial difference in the quality of the MEM and WF reconstructions of the thermal SZ effect. We find that the MEM reconstruction is only marginally less accurate than that obtained assuming full ICF information, but the WF reconstruction is considerably poorer in this case.

Fig. 19 shows cuts through the MEM and WF reconstructions that coincide with several typical clusters. The reconstructed MEM and WF cluster profiles are plotted as dashed lines and dotted lines respectively and are again compared with the true cluster profiles convolved with a Gaussian beam of FWHM 10' (solid line). From the figure we see that there is indeed a considerable difference between the MEM and WF reconstructions. The cluster profiles in the MEM reconstruction are reasonable approximations to the input profiles, although the reconstructed peak values

Figure 17. The power spectra of the input maps (bold line) compared to to the power spectra of the maps reconstructed using MEM with no ICF information (faint line). The dotted lines show one sigma confidence limits on the reconstructed power spectra.

Figure 18. As for Fig 17, but for the WF reconstruction with no ICF information.

Figure 19. The cluster profiles of some SZ effect reconstructions compared to the input profiles convolved with a 10' beam (solid line). The full MEM with full ICF information was used to reconstruct the dashed line whereas the quadratic approximation to this was used to reconstruct the dotted line.

are slightly lower in most cases. For the WF reconstruction, however, the cluster profiles are very poorly approximated indeed, with the peak value often underestimated by an order of magnitude. Of course, this simply reflects that it would be extremely ill-advised to use WF for determining weak processes in the absence of the power spectrum information of which WF is meant to take advantage.

5 DISCUSSION AND CONCLUSIONS

In this paper we adopt a Bayesian approach to the separation of foreground components from CMBR emission for satellite observations. In particular, we use simulated Planck Surveyor observations of a 10×10 degree patch of sky at ten different observing frequencies performed by Gispert & Bouchet (1997) and Bouchet & Gispert (1998) . The sky emission includes contributions from primary CMBR fluctuations, kinetic and thermal Sunyaev-Zel'dovich effects from

clusters and dust, free-free and synchrotron emission from the Galaxy.

We find that by assuming a suitable Gaussian prior in Bayes' theorem for the sky emission, we recover the standard Wiener filter (WF) approach. Alternatively, we may assume an entropic prior, based on information-theoretic considerations alone, from which we derive a maximum entropy method (MEM). We apply these two methods to the problem of separating the different physical components of sky emission.

The reconstructions presented in Section 4 show that, in the absence of severe point source contamination, the Planck Surveyor observations enable the recovery of the CMBR fluctuations with an absolute accuracy of about 6 μ K. Moreover, depending on assumed knowledge of the power spectra of the various components, we find that it is possible to reconstruct the emission due to other components with varying degrees of accuracy. In particular, the Galactic dust emission may be reconstructed with an accuracy of about 2 μ K. The main features of Galactic free-free and synchrotron are also reconstructed. We find that both the magnitude and radial profile of the thermal SZ effect may be recovered for rich clusters, but the reconstruction of the kinetic SZ effect is only possible in clusters which also have a large thermal SZ effect. Given the cluster gas profile derived from the thermal SZ effect, however, it may be possible to recover the kinetic effect more successfully by using optimal filtering methods tailored to individual cluster shapes (Haehnelt & Tegmark 1996, Aghanim et al. 1997). We also find that the power spectra of the input components are well-recovered. Irrespective of the amount of prior information assumed, we find that the CMBR power spectrum is faithfully reproduced up to $\ell \approx 2000$, where as the recovered dust and thermal SZ power spectra are accurate up to $\ell \approx 3000$ and $\ell \approx 1000$ respectively.

In nearly all cases, we find that the MEM algorithm produces equally or more accurate reconstructed maps and power spectra of the various components than the WF, and this is particularly true for reconstructions of the thermal SZ effect. This difference is most likely a result of the assumption in the WF method that the fields to be reconstructed are well-described by Gaussian random fields. This is clearly not the case for the SZ effect, and other foreground components such as Galactic dust also appear quite non-Gaussian in nature. In the case of Galactic dust, however, the information provided by the three highest Planck Surveyor observing frequencies allows the WF also to recover this process very accurately. The superiority of MEM is most apparent for processes which are both weak and non-Gaussian.

5.1 Variations on standard Wiener filtering

By assuming a Gaussian prior in Bayes' theorem, we derived the standard form of the Wiener filter. This approach is optimal in the sense that it is the linear filter for which the variance of the reconstruction residuals is minimised. This is true both in the Fourier domain and the map domain. Nevertheless, as mentioned in section 4.1, it is straightforward to show that this algorithm leads to maps with power spectra that are biased compared to the true spectra, and this leads us to consider variants of the standard Wiener filter. The bias in the power spectrum of the standard WF map reconstruction may be quantified by introducing, for each physical component, a *quality factor* $Q_p(\mathbf{k})$ at each Fourier mode \mathbf{k} (Bouchet et al. 1997). This factor is given by

$$Q_p(\boldsymbol{k}) = \sum_{\nu} W_{p\nu}(\boldsymbol{k}) R_{\nu p}(\boldsymbol{k}),$$

where $\mathbf{R}(\mathbf{k})$ is the response matrix of the observations at the Fourier mode \mathbf{k} , as defined in equation (3), and $\mathbf{W}(\mathbf{k})$ is the corresponding Wiener matrix given in equation (14). The quality factor varies between unity (in the absence of noise) and zero. If $\hat{s}_p(\mathbf{k})$ is the WF estimate of the *p*th component of the signal vector at \mathbf{k} and $s_p(\mathbf{k})$ is the actual value, then it is straightforward to show that

$$\langle |\hat{s}_p(m{k})|^2
angle = Q_p(m{k}) \langle |s_p(m{k})|^2
angle.$$

Thus, in similar way, the expectation value of the naive power spectrum estimator defined in (28) is given by $\langle \hat{C}_p(k) \rangle = Q_p(k) \langle C_p(k) \rangle$, where $Q_p(k)$ is the average of the quality factors at each Fourier mode satisfying $|\mathbf{k}| = k$; thus the estimator in equation (28) is biased and should be replaced by $\hat{C}_p(k)/Q_p(k)$. In addition, Q_p may be considered as the effective ℓ -space window of the experiment for the process p.

It is clearly unsatisfactory, however, to produce reconstructed maps with biased power spectra and, from the above discussion, we might consider using the matrix with elements $W_{p\nu}/Q_p^{1/2}$ to perform the reconstructions. Bouchet et al. (1997) shows that this leads to reconstructed maps that do indeed possess unbiased power spectra and, moreover, the method is less sensitive to the assumed input power spectra. However, one finds in this case that the variance of the reconstruction residuals is increase by a factor $2(1-Q_p^{1/2})/(1-Q_p)$ compared to those obtained with the standard WF and so the reconstructed maps appear somewhat noisier.

Another variant of the Wiener filter technique has been proposed by Tegmark & Efstathiou (1996), and uses the matrix $W_{p\nu}/Q_p$ to perform the reconstructions. This approach has the advantage that the reconstruction of the *p*th physical component is independent of its assumed input power spectrum. Nevertheless, Bouchet et al. (1997) show that the variance of the reconstruction residuals for this technique is then increased by the factor $(1/Q_p - 1)/(1 - Q_p)$ as compared to the standard WF, which results in even noisier reconstructed maps.

As a final variant, Tegmark (1997) suggests the inclusion into the WF algorithm of a parameter η that scales the assumed input power spectra of the components, This parameter can be included in all of the versions of the WF discussed above and is equivalent to assuming in Bayes' theorem a Gaussian prior of the form

$$\Pr(\mathbf{s}) \propto \exp\left(-\eta \mathbf{s}^{\dagger} \mathbf{C}^{-1} \mathbf{s}\right).$$

In the use of this variant for the analysis of real data, η is varied in order to obtain some desired signal-to-noise ratio in the reconstructed maps by artificially suppressing or enhancing the assumed power in the physical components as compared to the noise. Clearly, η plays a similar role in the WF analysis to the parameter α in the MEM. Thus, by making the appropriate changes to the calculation of the Bayesian value of α in Appendix B, we may obtain an analogous expression to (26) that defines a Bayesian value for η . Indeed, with the inclusion of the parameter η , the WF method is simply the quadratic approximation to the MEM, as discussed in Section 3.5. However, even with the inclusion of the η factor, we find that the corresponding reconstructions of non-Gaussian components are still somewhat poorer than for MEM.

5.2 Uncertainties in spectral behaviour

In creating the reconstructions presented in the is paper, we have throughout assumed that the frequency dependence of all the components are known *a priori*. This is a reasonable for the CMBR emission, as well as the kinetic and thermal SZ effects, but it is unlikely to be the case for the three Galactic components. For real observations, the spectral indices of the free-free and synchrotron emission will be uncertain to within about 20 per cent. Moreover, the dust temperature and emissivity may be known to even poorer accuracy.

If we assume for the moment that the frequency dependence of each component is the same across the entire 10×10 degree field, then we find that reasonable uncertainties in the parameters describing the Galactic components do not significantly affect our reconstructions. In fact, we find that the dust temperature and emissivity may be *determined* to within 1 per cent accuracy from the data by including them as free parameters in either the MEM or WF algorithm. The resulting reconstructions of all the physical components are virtually indistinguishable from those obtained by assuming these parameters. Unfortunately, we find that it is not possible to determine either the free-free or synchrotron spectral index in this way. Nevertheless, if in the algorithm we assume a spectral index for either component that is in error by within 20 per cent, we find that the reconstructions of the remaining components are virtually unaffected. The resulting reconstructions of the free-free and synchrotron components are, however, slightly poorer in this case.

It is clear that for real observations we may not assume that the frequency dependence of the emission in each component is the same across the field. In this case, the method must be modified slightly, as discussed by Tegmark & Efstathiou (1996) and Maisinger et al. (1997), by the introduction of additional channels in the reconstruction. For instance, if we assume that the frequency dependence of the synchrotron emission is of the form $I \propto \nu^{-\beta}$, with $\beta = -0.7 \pm 0.2$, we simply include two synchrotron channels, one with $\beta = -0.5$ and one with $\beta = -0.9$, or even with intermediate values, and afterwards sum over these channels to obtain the reconstructed synchrotron map. Alternatively, one could consider deviations from the mean spectrum as just another template to be recovered with a modified spectral behaviour as obtained by linearising the frequency dependence of the intensity with theses deviations (Bouchet et al. 1996).

5.3 Future improvements and modifications

In this paper, the simulated Planck Surveyor observations were somewhat idealised in that it was assumed that the

beam at each observing frequency was a simple Gaussian. For the real observations, however, it is unavoidable that the beam will in fact possess sidelobes at some level, and care must be taken to include any such features into the analysis, in particular if these sidelobes contain emission from any strong sources.

The simulated observations presented here also assume that any striping due to the scan strategy has been removed to a sufficient level so that it may be considered negligible. In fact, it may be possible to use MEM to perform the destriping of the maps and the component separation simultaneously. Indeed the simultaneous reconstruction of a deconvolved CMBR maps and the removal of scan baselines has already been performed using MEM in the analysis of Tenerife data (Jones et al. 1997).

In terms of computational speed, however, the most important assumption made in our simulations were that the beam at each frequency does not change shape with position on the sky This assumption is not unreasonable in the analysis of small patches of sky considered here, but may be questionable for all-sky maps. The importance of this assumption lies in the fact that the beam-smoothing may be written as a convolution and therefore allows us to analyse the observations entirely in the Fourier domain, where each mode may be considered independently. As discussed in Section 3, this means that the analysis is reduced to a large number $(400 \times 400 \times 6)$ of small-scale linear inversion problems and so is computationally very fast.

If the beam is spatially varying, however, the beamsmoothing cannot be written as a simple convolution. In this case the analysis should properly be performed in the sky plane, and requires the use of sparse matrix techniques to compute the beam-smoothing at each point on the sky as opposed to Fast Fourier Transforms (FFTs). In addition, the matrices involved in the linear problem are then very large indeed, since we are attempting simultaneously to determine $400 \times 400 \times 6$ parameters by the minimisation of a function of corresponding dimensionality. The large dimensionality of the problem also complicates the inclusion of power spectrum information and the determination of Bayesian values for α in the MEM algorithm and η in the WF. Nevertheless, the authors have investigated the use of MEM and the WF in this case and find that reconstructions similar to those presented here can be performed in about 12 hours of CPU on a SPARC 20 workstation. For both MEM and WF, however, the calculation of errors cannot be performed by inverting the Hessian matrix of the posterior probability, since this matrix has dimensions $(400 \times 400 \times 6)^2$. Although this matrix is in fact reasonable sparse, the inversion is still not feasible. Instead, the errors on the reconstructions must be estimated by performing several hundred Monte-Carlo simulations for different noise realisations (see Maisinger et al. 1997). A full discussion of the performance of sky-plane MEM and WF algorithms, when applied to simulated Planck Surveyor observations, will be presented in a forthcoming paper.

Finally, perhaps the most important improvement on the simulations and reconstructions presented here is the inclusion of a realistic population of point sources. Using the point source simulations of Toffolatti et al (1998), a full investigation of the effects on the reconstruction of the CMBR and other components is given by Hobson et al. (in preparation).

ACKNOWLEDGEMENTS

MPH and AWJ acknowledge Trinity Hall and King's College, Cambridge, respectively, for support in the form of Research Fellowships. FRB thanks R. Gispert for permission to use some of their unpublished results.

REFERENCES

- Aghanim N., De Luca A., Bouchet F.R., Gispert R., Puget J.-L., 1997, A&A, 325, 9.
- Bersanelli M. et al., 1996, Report on Phase A Study for CO-BRAS/SAMBA, European Space Agency.
- Bouchet F.R., Bennett D.P., Stebbins A., 1988, Nat, 335, 410
- Bouchet F.R., Gispert R., 1998, in preparation
- Bouchet F.R., Gispert R., Puget J.L., 1996, in Dwek E., ed., Proc. AIP Conf. 348, The mm/sub-mm foregrounds and future CMB space missions. AIP Press, New York, p. 255
- Bouchet F.R., Gispert R., Boulanger F., Puget J.L., 1997, in Bouchet F.R., Gispert R., Guideroni B., Tran Thanh Van J., eds, Proc. 16th Moriond Astrophysics Meeting, Microwave Anisotropies. Editions Frontière, Gif-sur-Yvette, p. 481
- Boulanger F., Abergel A., Bernard J.P., Burton W.B., Desert F.X., Hartmann D., Lagache G., Puget J.L., 1996, A&A, 312, 256
- De Zotti L., Toffolatti F., Argüeso Gómez F., Franceschini A., Mazzei P., Danese L., Burigana C., 1997, in Bouchet F.R., Gispert R., Guideroni B., Tran Thanh Van J., eds, Proc. 16th Moriond Astrophysics Meeting, Microwave Anisotropies. Editions Frontière, Gif-sur-Yvette, p. 437
- Gispert R., Bouchet F.R., 1997, in Bouchet F.R., Gispert R., Guideroni B., Tran Thanh Van J.,eds, Proc. 16th Moriond Astrophysics Meeting, Microwave Anisotropies. Editions Frontière, Gif-sur-Yvette, p. 503
- Guiderdoni B., Bouchet F.R., Puget J.-L., Lagache G., Hivon E., 1997, Nat, 390, 257
- Guiderdoni B., Hivon E., Bouchet F.R., Maffeï B., 1998, MNRAS, in press
- Gull S. F., 1989, in Skilling J., ed., Maximum Entropy and Bayesian Methods. Kluwer, Dordrecht, p. 53
- Gull S. F., Skilling J., 1990, The MEMSYS5 User's Manual. Maximum Entropy Data Consultants Ltd. Royston
- Haehnelt M., Tegmark M., 1996, MNRAS, 279, 545
- Haslam C. G. T et al., 1982, A&AS, 47, 1
- Hobson M.P., Lasenby A.N., 1998, MNRAS, in press
- Jones A. W., Hancock S., Lasenby A. N., Davies R. D., Gutiérrez C. M., Rocha G., Watson R. A., Rebolo R., 1998, MNRAS, 294, 582
- Kogut A., Banday A.J., Bennett C.L., Gorski K.M., Hinshaw G., Smoot G.F., Wright E.I., 1996, ApJ, 464, L5
- Maisinger K., Hobson M.P., Lasenby A.N., 1997, MNRAS, 290, 313
- Mather et al., 1994, ApJ, 420, 439
- O'Sullivan C. et al., 1995, MNRAS, 274, 861
- Press P. H., Teukolsky S. A., Vettering W. T., Flannery B. P., 1994, Numerical Recipes. Cambridge Univ. Press, Cambridge
- Skilling J., 1989, in Skilling J., ed., Maximum Entropy and Bayesian Methods. Kluwer, Dordrecht, p. 45
- Tegmark M., 1997, ApJ, 480, L87
- Tegmark M., Efstathiou G., 1996, MNRAS, 281, 1297
- Toffolatti L., Argüeso Gómez F., De Zotti G., Mazzei P., Francheschini A., Danese L., Burigana C., 1998, MNRAS, submitted Turok N., 1996, ApJ, 473, L5
- Zaroubi S., Hoffman Y., Fisher K. B., Lahav O., 1995, ApJ, 449, 446

As discussed in Section 3.4, maximising the posterior probability for the WF and MEM cases is equivalent to minimising respectively the functions Φ_{WF} and Φ_{MEM} , which are given by (22) and (23) as

$$\Phi_{\rm WF}(\mathbf{h}) = \chi^2(\mathbf{h}) + \mathbf{h}^{\dagger}\mathbf{h}, \qquad (A1)$$

$$\Phi_{\text{MEM}}(\mathbf{h}) = \chi^2(\mathbf{h}) - \alpha S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v).$$
 (A2)

From (19), in each case the standard χ^2 misfit statistic may be written in terms of the hidden vector $\mathbf{h} = \mathbf{L}^{-1} \mathbf{s}$ as

$$\chi^{2}(\mathbf{h}) = (\mathbf{d} - \mathbf{R}\mathbf{L}\mathbf{h})^{\dagger}\mathbf{N}^{-1}(\mathbf{d} - \mathbf{R}\mathbf{L}\mathbf{h}).$$
(A3)

The cross entropy $S_c(\mathbf{h}, \mathbf{m}_u, \mathbf{m}_v)$ for this complex image is given by (16) and (17).

Since **h** is a complex vector we may consider Φ_{WF} and Φ_{MEM} to be functions of the real and imaginary parts of the elements of **h**. Alternatively, we may consider these functions to depend upon the complex elements of **h**, together with their complex conjugates. While it is clear that the former approach is required in order to use standard numerical minimisers, a simpler mathematical derivation is provided by adopting the latter approach. In any case, derivatives with respect to the real and imaginary parts of **h** may be easily found using the relations

$$\begin{split} \nabla_{\Re(\mathbf{h})} &\equiv \nabla_{\mathbf{h}} + \nabla_{\mathbf{h}^*}, \\ \nabla_{\Im(\mathbf{h})} &\equiv i \left(\nabla_{\mathbf{h}} - \nabla_{\mathbf{h}^*} \right). \end{split}$$

Differentiating (A3) with respect to **h** and **h**^{*}, we find the gradient of χ^2 is given by

$$\nabla_{\mathbf{h}^*} \chi^2 = \left[\nabla_{\mathbf{h}} \chi^2 \right]^* = -\mathbf{L}^{\mathrm{T}} \mathbf{R}^{\dagger} \mathbf{N}^{-1} (\mathbf{d} - \mathbf{R} \mathbf{L} \mathbf{h}), \tag{A4}$$

and upon differentiating once more we find the Hessian (curvature) matrix of χ^2 has the form

$$\nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} \chi^2 = \mathbf{L}^{\mathrm{T}} \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R} \mathbf{L}.$$
 (A5)

Using (A4) and (A5), the gradient of Φ_{WF} in (A1) is simply given by

$$\nabla_{\mathbf{h}^*} \Phi_{\mathrm{WF}} = [\nabla_{\mathbf{h}} \Phi_{\mathrm{WF}}]^* = -\mathbf{L}^{\mathrm{T}} \mathbf{R}^{\dagger} \mathbf{N}^{-1} (\mathbf{d} - \mathbf{R} \mathbf{L} \mathbf{h}) + \mathbf{h}, \qquad (A6)$$

and its Hessian matrix reads

$$\mathbf{H}_{\mathrm{WF}} = \nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} \Phi_{\mathrm{WF}} = \mathbf{L}^{\mathrm{T}} \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R} \mathbf{L} + \mathbf{I}, \qquad (A7)$$

where I is the unit matrix of appropriate dimensions. We note that the Hessian matrix for Φ_{WF} is independent of h.

By setting the right-hand side of (A6) equal to zero, and remembering that $\mathbf{s} = \mathbf{L}\mathbf{h}$ and $\mathbf{C} = \mathbf{L}\mathbf{L}^{\mathrm{T}}$, it is straightforward to obtain the linear relation (14) for the WF solution. Moreover, from (27), the error covariance matrix for the reconstructed signal vector is given by $\mathbf{E} = \mathbf{L}\mathbf{H}^{-1}\mathbf{L}^{\mathrm{T}}$, and using (A7) this is easily shown to be identical to the result (15).

In a similar way, we may calculate the derivatives of Φ_{MEM} defined in (A2). Unfortunately, the form of the cross entropy given in (16) precludes us from writing its gradient or curvature as a simple matrix multiplication, and we must instead express them in component form. From (16) and (17), we find the components of the gradient vector of the cross entropy are given by

$$\frac{\partial S_c}{\partial h_j} = \left(\frac{\partial S_c}{\partial h_j^*}\right)^*$$

$$= -\frac{1}{2}\ln\left[\frac{\Re(\psi_j + h_j)}{2\Re(m_{u_j})}\right] - \frac{1}{2}i\ln\left[\frac{\Im(\psi_j + h_j)}{2\Im(m_{u_j})}\right], (A8)$$

where $\Re(\psi_j) = [\Re(h_j) + 4\Re(m_{uj})\Re(m_{vj})]^{1/2}$ and a similar expression exists for $\Im(\psi_j)$. Differentiating once more we find the components of the Hessian of the cross entropy to be given by

$$\frac{\partial^2 S_c}{\partial h_j \partial h_k^*} = -\frac{1}{4} \left[\frac{1}{\Re(\psi_j)} + \frac{1}{\Im(\psi_j)} \right] \quad \text{if } j = k \tag{A9}$$

and equals zero otherwise. We note that these components may be used to define the (diagonal) metric on the space of images, which is given simply by $\mathbf{G}(\mathbf{h}) = -\nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} S_c$ (Skilling 1989; Hobson & Lasenby 1998).

Using (A8) and (A9) the gradient and Hessian of Φ_{MEM} are then easily calculated. In particular, we find that the Hessian matrix is given by

$$\mathbf{H}_{\text{MEM}} = \nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} (\chi^2 - \alpha S_c) = \mathbf{L}^{\text{T}} \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R} \mathbf{L} + \alpha \mathbf{G}$$
(A10)

where **G** is the image space metric and we have used the expression for the curvature of χ^2 given in (A5). In contrast to (A7), we see that the Hessian matrix of Φ_{MEM} depends on **h** through the metric **G**.

APPENDIX B: BAYESIAN VALUE FOR α

A Bayesian value for α may be found simply by treating it as another parameter in our hypothesis space. This procedure is outlined for the case of real images in Skilling (1989) and Gull & Skilling (1990), and we modify their treatment here in order to accommodate complex images **h**.

After including α into our hypothesis space, the full joint probability distribution can be expanded as

$$Pr(\mathbf{h}, \mathbf{d}, \alpha) = Pr(\alpha) Pr(\mathbf{h}|\alpha) Pr(\mathbf{d}|\mathbf{h}, \alpha)$$
$$= Pr(\alpha) Pr(\mathbf{h}|\alpha) Pr(\mathbf{d}|\mathbf{h})$$
(B1)

where in the last factor we can drop the conditioning on α since it is **h** alone that induces the data **d**. We then recognise this as the likelihood. Furthermore, the second factor $\Pr(\mathbf{h}|\alpha)$ can be identified as the entropic prior and so (B1) becomes

$$\Pr(\mathbf{h}, \mathbf{d}, \alpha) = \Pr(\alpha) \frac{e^{\alpha S_c(\mathbf{h})}}{Z_S(\alpha)} \frac{e^{-\chi^2(\mathbf{h})}}{Z_L}$$
$$= \Pr(\alpha) \frac{e^{\alpha S_c(\mathbf{h}) - \chi^2(\mathbf{h})}}{Z_S(\alpha) Z_L},$$
(B2)

where $Z_S(\alpha)$ and Z_L are respectively the normalisation constants for the entropic prior and the likelihood such that the total probability density function in each case integrates to unity. For convenience we have dropped the explicit dependence of the cross entropy S_c on the models \mathbf{m}_u and \mathbf{m}_v .

Since we have assumed the instrumental noise on the data to be Gaussian, the likelihood function is also Gaussian and so the normalisation factor Z_L is easily found. Evaluating the appropriate Gaussian integral gives

$$Z_L = \pi^{n_f} |\mathbf{N}|$$

where n_f is the dimension of the complex data vector **d** and is equal to the number of observing frequencies that make up the Planck Surveyor data set; $|\mathbf{N}|$ is the determinant of the noise covariance matrix defined in (7).

30 M.P. Hobson et al.

The normalisation factor $Z_S(\alpha)$ for the entropic prior is more difficult to calculate since this prior is not Gaussian in shape. Nevertheless, we find that a reasonable approximation to $Z_S(\alpha)$ for all α may be obtained by making a Gaussian approximation to the prior at its maximum, which occurs at $\mathbf{h}_m = \mathbf{m}_u - \mathbf{m}_v$. As discussed in Appendix A, the Hessian matrix of the entropy at this point is given by $\nabla_{\mathbf{h}} \nabla_{\mathbf{h}^*} S_c = -\mathbf{G}$, where **G** is the metric on image space evaluated at the maximum of the prior \mathbf{h}_m ; the metric matrix is real and diagonal. Remembering that $S_c(\mathbf{h}_m) = 0$ and using the Gaussian approximation, $Z_S(\alpha)$ is then given by

$$Z_{S}(\alpha) = \int_{\infty} e^{\alpha S_{c}(\mathbf{h})} |\mathbf{G}| d^{n_{c}} \mathbf{h} d^{n_{c}} \mathbf{h}^{*}$$

$$\approx \int_{\infty} e^{-\alpha (\mathbf{h} - \mathbf{h}_{m})^{\dagger} \mathbf{G}(\mathbf{h} - \mathbf{h}_{m})} |\mathbf{G}| d^{n_{c}} \mathbf{h} d^{n_{c}} \mathbf{h}^{*}$$

$$\approx \pi^{n_{c}} |\alpha \mathbf{I}|^{-1} = (\pi/\alpha)^{n_{c}}, \qquad (B3)$$

where n_c is the dimension of the complex (hidden) image vector **h** and is equal to the number of physical components present in the simulations.

Now, returning to (B2), in order to investigate more closely the role of α , we begin by considering the joint probability distribution $Pr(\mathbf{d}, \alpha)$, which may be obtained by integrating out **h** in (B2):

$$Pr(\mathbf{d}, \alpha) = \int_{\infty} Pr(\mathbf{h}, \mathbf{d}, \alpha) |\mathbf{G}| d^{n_c} \mathbf{h} d^{n_c} \mathbf{h}^*$$
$$= \frac{Pr(\alpha)}{Z_S(\alpha) Z_L} \int_{\infty} e^{\alpha S_c(\mathbf{h}) - \chi^2(\mathbf{h})} |\mathbf{G}| d^{n_c} \mathbf{h} d^{n_c} \mathbf{h}^*$$
$$\equiv Pr(\alpha) \frac{Z_{\Phi}(\alpha)}{Z_S(\alpha) Z_L}$$
(B4)

where we have defined the normalisation integral $Z_{\Phi}(\alpha)$. In order to calculate $Z_{\Phi}(\alpha)$, we follow a similar approach to that use to calculate $Z_S(\alpha)$ and make a Gaussian approximation to $\exp[\alpha S_c(\mathbf{h}) - \chi^2(\mathbf{h})]$ about its maximum at $\hat{\mathbf{h}}$. The required Hessian matrix \mathbf{H}_{MEM} is given by (A10) evaluated at $\hat{\mathbf{h}}$. Let us, however, define a new matrix \mathbf{M} that is given by

$$\mathbf{M} \equiv \mathbf{G}^{-1/2} \mathbf{H}_{\text{MEM}} \mathbf{G}^{-1/2} = \mathbf{G}^{-1/2} \mathbf{L}^{\text{T}} \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R} \mathbf{L} \mathbf{G}^{-1/2} + \alpha \mathbf{I}.(\text{B5})$$

The integral $Z_{\Phi}(\alpha)$ is then approximated by

$$Z_{\Phi}(\alpha) \approx e^{\alpha S_{c}(\hat{\mathbf{h}}) - \chi^{2}(\hat{\mathbf{h}})} \int_{\infty}^{\infty} e^{-(\mathbf{h} - \hat{\mathbf{h}})^{\dagger} \mathbf{H}_{\mathrm{MEM}}(\mathbf{h} - \hat{\mathbf{h}})} |\mathbf{G}| \, \mathrm{d}^{n_{c}} \mathbf{h} \, \mathrm{d}^{n_{c}} \mathbf{h}^{*}$$
$$\approx e^{\alpha S_{c}(\hat{\mathbf{h}}) - \chi^{2}(\hat{\mathbf{h}})} \int_{\infty}^{\infty} e^{-(\mathbf{h} - \hat{\mathbf{h}})^{\dagger} \mathbf{G}^{1/2} \mathbf{M} \mathbf{G}^{1/2}(\mathbf{h} - \hat{\mathbf{h}})} |\mathbf{G}| \, \mathrm{d}^{n_{c}} \mathbf{h} \, \mathrm{d}^{n_{c}} \mathbf{h}$$
$$\approx e^{\alpha S_{c}(\hat{\mathbf{h}}) - \chi^{2}(\hat{\mathbf{h}})} \pi^{n_{c}} |\mathbf{M}|^{-1}. \qquad (B)$$

Thus, substituting into (B4) the expressions for $Z_S(\alpha)$ and $Z_{\Phi}(\alpha)$ given by (B3) and (B6) respectively, we find that in the Gaussian approximation the joint probability distribution $\Pr(\mathbf{d}, \alpha)$ has the form

$$\begin{aligned} \Pr(\mathbf{d}, \alpha) &= \Pr(\alpha) \Pr(\mathbf{d}|\alpha) \\ &\approx \Pr(\alpha) Z_L^{-1} e^{\alpha S_c(\hat{\mathbf{h}}) - \chi^2(\hat{\mathbf{h}})} \alpha^{n_c} |\mathbf{M}|^{-1}. \end{aligned}$$

Now, in order to obtain a Bayesian estimate for α , we should choose an appropriate form for the prior $\Pr(\alpha)$. Nevertheless, for realistically large data sets, the distribution $\Pr(\mathbf{d}|\alpha)$ is so strongly peaked that it overwhelms any reasonable prior on α , and so we assign the Bayesian value $\hat{\alpha}$

of the regularisation constant to be that which maximises $\Pr(\mathbf{d}|\alpha)$. Taking logarithms we obtain

$$\ln \Pr(\mathbf{d}|\alpha) = \text{constant} + \alpha S_c(\hat{\mathbf{h}}) - \chi^2(\hat{\mathbf{h}}) + n_c \ln \alpha - \ln |\mathbf{M}|.$$

Differentiating with respect to α , and noting that the $\hat{\mathbf{h}}$ -derivatives cancel, we find

$$\frac{\mathrm{d}}{\mathrm{d}\alpha}\ln\Pr(\mathbf{d}|\alpha) = S_c(\hat{\mathbf{h}}) + \frac{n_c}{\alpha} - \operatorname{Tr}\left(\mathbf{M}^{-1}\frac{\mathrm{d}\mathbf{M}}{\mathrm{d}\alpha}\right),\tag{B7}$$

where we have used the identity

$$\frac{\mathrm{d}}{\mathrm{d}\alpha}\ln|\mathbf{M}| \equiv \mathrm{Tr}\left(\mathbf{M}^{-1}\frac{\mathrm{d}\mathbf{M}}{\mathrm{d}\alpha}\right)$$

which is valid for any non-singular matrix $\mathbf{M}(\alpha)$. From (B5), however, we see that $d\mathbf{M}/d\alpha = \mathbf{I}$. Substituting this relation into (B7) and equating to the result to zero, we find that in order to maximise $\Pr(\mathbf{d}|\alpha)$, the parameter α must satisfy

$$-\alpha S_c(\hat{\mathbf{h}}) = n_c - \alpha \mathrm{Tr}(\mathbf{M}^{-1}).$$
(B8)

APPENDIX C: SINGULAR VALUE DECOMPOSITION IN A BAYESIAN CONTEXT

As outlined by Bouchet et al. (1997) and Bouchet & Gispert (1998), a straightforward initial approach to the component separation problem is to perform a singular value decomposition (SVD) at each Fourier mode separately. A full description of the SVD technique is given by Press et al. (1994). Generalising their discussion slightly to include complex matrices, the SVD of the $n_f \times n_c$ response matrix **R** is given by

$$\mathbf{R} = \mathbf{U}\mathbf{W}\mathbf{V}^{\dagger},\tag{C1}$$

where **U** and **V** are unitary matrices with dimensions $n_f \times n_c$ and $n_c \times n_c$ respectively, and **W** is a $n_c \times n_c$ diagonal matrix.

From (4), at each Fourier mode, we have $\mathbf{d} = \mathbf{Rs} + \boldsymbol{\epsilon}$, and the SVD estimator of the signal vector is given by

$$\hat{\mathbf{s}} = \mathbf{V}\mathbf{W}^{-1}\mathbf{U}^{\dagger}\mathbf{d}.$$
 (C2)

It is straightforward to show that this estimator minimises the residual $|\mathbf{d} - \mathbf{Rs}|$ (Press et al. 1994). Thus, from (8), we see that the SVD solution minimises $\chi^2(\mathbf{s})$ provided the noise covariance matrix **N** is equal to the identity matrix. Therefore, in the context of Bayes' theorem (5), the SVD solution is equivalent to assuming a uniform prior and *independent* Gaussian noise with *unit variance*.

h* We can make the connection between the SVD and modified minimum chi-squared solutions more explicit by 6)rewriting the SVD solution solely in terms of the response matrix R. Using the unitary properties of the matrices U and V, it is easy to show that the SVD solution (C2) can be rewritten as

$$\hat{\mathbf{s}} = \left(\mathbf{R}^{\dagger}\mathbf{R}\right)^{-1}\mathbf{R}^{\dagger}\mathbf{d}.\tag{C3}$$

Alternatively, we find from (A4) that the gradient of $\chi^2(\mathbf{s})$ with respect to \mathbf{s} is given by

$$\nabla_{\mathbf{s}^*} \chi^2 = \left[\nabla_{\mathbf{s}} \chi^2 \right]^* = -\mathbf{R}^{\dagger} \mathbf{N}^{-1} (\mathbf{d} - \mathbf{R} \mathbf{s}), \tag{C4}$$

Equating this expression for the gradient to zero, we quickly obtain the minimum chi-squared estimator

$$\hat{\mathbf{s}} = \left(\mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{R}\right)^{-1} \mathbf{R}^{\dagger} \mathbf{N}^{-1} \mathbf{d}, \tag{C5}$$

which, on setting \mathbf{N} equal to the identity matrix, is identical to the SVD solution (C3).

This paper has been produced using the Royal Astronomical Society/Blackwell Science ${\rm IAT}_{\rm E}{\rm X}$ style file.